

FCC ID: 2BEEE-S7

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot \sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2.4GWIFI:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
802.11b	2.412	9.047	8.03	8.5±1	9.50	8.91	<5	2.76834	3.00	YES
	2.437	9.014	7.97	8.5±1	9.50	8.91	<5	2.78264	3.00	YES
	2.462	9.402	8.71	8.5±1	9.50	8.91	<5	2.79688	3.00	YES
802.11g	2.412	8.709	7.43	8±1	9.00	7.94	<5	2.46728	3.00	YES
	2.437	8.546	7.15	8±1	9.00	7.94	<5	2.48003	3.00	YES
	2.462	8.625	7.29	8±1	9.00	7.94	<5	2.49272	3.00	YES
802.11n(HT20)	2.412	8.619	7.28	8±1	9.00	7.94	<5	2.46728	3.00	YES
	2.437	7.626	5.79	7±1	8.00	6.31	<5	1.96996	3.00	YES
	2.462	8.092	6.44	8±1	9.00	7.94	<5	2.49272	3.00	YES
802.11n(HT40)	2.422	6.986	5.00	6±1	7.00	5.01	<6	1.55997	3.00	YES
	2.437	7.385	5.48	7±1	8.00	6.31	<7	1.96996	3.00	YES
	2.452	8.375	6.88	8±1	9.00	7.94	<8	2.48766	3.00	YES

Conclusion:

supported simultaneous transmission: $2.79688 \leq 3$, So passed.