

RF EXPOSURE EVALUATION

FCC ID: 2BEHS-LV-M9PRO

According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b):

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0 \text{ for } 1\text{-g SAR} \text{ and } \leq 7.5 \text{ for } 10\text{-g extremity SAR,}^{16} \text{ where}$

- f_(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- · The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by §2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Channel (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)		Max Tune Up Power (dBm)	71.	Calculation results	Anbotel Limit ^{of}	Operating Mode
2402		3.06	±,1	4.060	5	0.789	otel ^k 3	Aupor
2441	3.4	3.4	±1	4.400	5 Ani	0.861	3K	GFSK
2480	3.51	3.51	±1	4.510	otek 5	0.890	3 tel	Anboren
2402	3.84	3.84	±1	4.840	abot 5	0.945	3	lek Aupore
2441	4.18	4.18	±1	5.180	5	1.030	3	π/4-DQPSK
2480	4.23	4.23	ore¥1	5.230	5 note	1.050	3	loc sek
2402	4.26	4.26	也也	5.260	5	1.041	3	Augo.
2441	4.59	4.59	±1	5.590	5 Ame	1.132	10013	8DPSK
2480	4.65	4.65	±1	5.650	5	1.157	3 tek	Anbore

Result: No Standalone SAR test is required.

