

Shenzhen Chenda zhike electronics co., Itd

Address:Room 1011A15, Building A, Xinghe Century, No. 3069 Caitian Road, Gangxia Community, Futian District, Shenzhen TEL: 86-0755-26788713 FAX: 86-0755-86095342

CDT458-2 User manual

1. Product model: CDT458-2

2. Operating voltage: DC6V(2 CR2016 batteries)

3. Working current: ≤8MA

4. Operating temperature: -20—+65°C

5. Modulation mode: ASK

6. Operating frequency: 433.92MHz

7. Transmission rate: 50-60khz

8. Coding type: Learning Code (EV1527)9. Appearance size: 61mm*29mm*12mm

10. Working current: ≤8mA

FCC Caution:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.