

# FCC Test Report

**Applicant** : **Equity Sales & Marketing.Inc.**

---

**Address** : **2203 Promenade Blvd,Suite 5230 Rogers  
Arkansas USA**

---

**Product Name** : **300W Portable Power Station for Diehard**

---

**Report Date** : **Apr. 22, 2024**

---

**Shenzhen Anbotek Compliance Laboratory Limited**



**Shenzhen Anbotek Compliance Laboratory Limited**

Address:1/F.,Building D,Sogood Science and Technology Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.  
Tel:(86) 0755-26066440 Fax:(86) 0755-26014772 Email:service@anbotek.com

Code:AB-RF-05-b

 Hotline  
400-003-0500  
www.anbotek.com.cn



# Contents

1. General Information.....	5
1.1. Client Information.....	5
1.2. Description of Device (EUT).....	5
1.3. Auxiliary Equipment Used During Test.....	6
1.4. Test Equipment List.....	6
1.5. Measurement Uncertainty.....	6
1.6. Description of Test Facility.....	7
1.7. Disclaimer.....	7
2. Measurement and Result.....	8
2.1. Requirements.....	8
2.2. Test Setup.....	9
2.3. Test Procedure.....	10
2.4. Test Result.....	10
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	12
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	12
APPENDIX III -- INTERNAL PHOTOGRAPH.....	12



# TEST REPORT

Applicant : Equity Sales & Marketing.Inc.  
Manufacturer : Huizhou Intelligent Energy Co., Ltd.  
Product Name : 300W Portable Power Station for Diehard  
Test Model No. : DH-20001-01  
Reference Model No. : N/A  
Trade Mark : N/A  
Rating(s) : Please refer to page 6  
**Test Standard(s) : FCC Part 1.1310, 1.1307(b)**  
**Test Method(s) : KDB 680106 D01 Wireless Power Transfer v04**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 1.1307 & KDB680106 D01 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Feb. 27, 2024

Date of Test

Dec. 27, 2023~Mar. 07, 2024

Prepared By



(Ella Liang)

Approved &amp; Authorized Signer



(Edward Pan)





### Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Apr. 22, 2024



## 1. General Information

### 1.1. Client Information

Applicant	:	Equity Sales & Marketing.Inc.
Address	:	2203 Promenade Blvd,Suite 5230 Rogers Arkansas USA
Manufacturer	:	Huizhou Intelligent Energy Co., Ltd.
Address	:	8-9/F,Bldg.E2,Qunyi Industrial Park,Sanhe Avenue, Tonghu Town, Zhongkai High-tech Zone, HuiZhou, 516039, China
Factory	:	Huizhou Intelligent Energy Co., Ltd.
Address	:	8-9/F,Bldg.E2,Qunyi Industrial Park,Sanhe Avenue, Tonghu Town, Zhongkai High-tech Zone, HuiZhou, 516039, China

### 1.2. Description of Device (EUT)

Product Name	:	300W Portable Power Station for Diehard
Test Model No.	:	DH-20001-01
Reference Model No.	:	N/A
Trade Mark	:	N/A
Test Power Supply	:	DC 22.2V battery inside
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	Model No.: A653-1504000D Input: 100-240~50/60Hz 1.5A Output: 15.0V= 4.0A 60.0W

#### RF Specification

Operation Frequency	:	110.1~205kHz
Modulation Type	:	ASK
Antenna Type	:	Inductive loop coil Antenna
Antenna Gain(Peak)	:	0 dBi

**Remark:** 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



Rating(s):



**300 WATT PORTABLE POWER STATION**

MODEL: DH-20001-01  
SERIAL: \_\_\_\_\_

DH20001-01  
3.05.04.0693

- Battery Capacity: 22.2V, 13Ah/288.6Wh
- DC/PC Input: 12V-26V, 5.5W Max
- AC Output: Pure Sine Wave, 110V-60Hz, 300W
- DC Output: x2: 12V=5A (Each)
- Cigarette Lighter Socket Output: 12V=10A
- USB-A Output: x3: 5V=3A, 9V=2A, 12V=1.5A, 18W Max
- USB-C Output: 5V/9V/12V/15V/20V=3A, 60W Max
- Wireless Charge: 5W
- Operating Temp: 14 to 104°F (-10 to 40°C)
- Charging Temp: 32 to 104°F (0 to 40°C)

**READ USER MANUAL BEFORE USE**

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. FCC ID: 2BEP7DH-20001MV1000

DieHard name and logo are used under license by Equity Sales & Marketing, Inc., Rogers, AR 72756  
Customer Service Email: support@diehardpowerstations.com  
[www.diehardpowerstations.com](http://www.diehardpowerstations.com)





Made in China

- ⚠ WARNING!**
- Do not short-circuit the power station. To avoid short-circuiting, keep the power station away from all metal objects (e.g. coins, hair-pins, keys, etc.).
  - Do not heat the power station, or dispose of it in fire, water or other liquids. Keep away from high temperatures.
  - Do not expose the power station to direct sunlight. Keep away from high humidity, dusty places.
  - Do not disassemble or reassemble this power station.
  - Do not drop and place heavy objects on, or allow strong impact to this power station.
  - Do not use the power station in or near water. Do not allow rain or other moisture to fall on the power station.
  - This power station is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the power station by a person responsible for their safety.
  - Children should be supervised to ensure that they do not play with the power station or any device connected to it.
  - The power station may become hot when charging. This is normal. Be careful when handling.
  - Use the power station properly to avoid electronic shock.
  - The power station is only used for emergency power station; it can not replace the standard DC or AC power of household appliances or digital products.
  - Do not overcharge the internal battery. See Instruction Manual.
- ⚠ AVERTISSEMENT!**
- Ne court-circuitez pas l'appareil. Pour éviter tout court-circuit, éloignez l'appareil de tout objet métallique (pièces de monnaie, épingles, cheveux, clés, etc.).
  - Ne chauffez pas l'appareil et ne le jetez pas dans le feu, l'eau ou d'autres liquides. Tenir l'écart des températures élevées. N'exposez pas l'appareil à la pluie ou au soleil.
  - Ne pas exposer la station d'alimentation à la lumière directe du soleil, tenir à l'écart des endroits très humides et poussiéreux.
  - Ne pas utiliser la station d'alimentation dans l'eau ou à proximité de l'eau. Ne pas laisser la pluie ou d'autres formes d'humidité tomber sur la station d'alimentation.
  - Ne démontez pas et ne réassemblez pas cet appareil.
  - Ne laissez pas tomber, ne placez pas d'objets lourds dessus et ne laissez pas de chocs violents sur cet appareil.
  - Cet appareil n'est pas destiné à être utilisé par des personnes (y compris des enfants) ayant des capacités physiques, sensorielles ou mentales réduites, ou un manque d'expérience et de connaissances, moins qu'elles n'aient reçu une supervision ou des instructions concernant.
  - L'utilisation de l'appareil par une personne responsable de leur sécurité.
  - Les enfants doivent être surveillés pour s'assurer qu'ils ne jouent pas avec l'appareil.
  - L'appareil peut devenir chaud pendant la charge. C'est normal. Soyez prudent lors de la manipulation.
  - Utilisez l'appareil correctement pour éviter les chocs électroniques. Le produit n'est utilisé que pour le contrôle électronique de secours. Il ne peut pas remplacer l'alimentation DC ou CA standard des appareils ménagers ou des produits numériques.
  - Ne pas surcharger la batterie interne. Consultez le manuel d'utilisation.

### 1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
Wireless charging load	Shenzhen Oju Technology Co., Ltd.	CD2577	/

### 1.4. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Electric and Magnetic field Analyzer	NARDA	EHP-200A	180ZX10202	Oct. 16, 2023	1 Year

### 1.5. Measurement Uncertainty

Magnetic Field Reading(A/m) : +/-0.04282(A/m)
Electric Field Reading(V/m) : +/-0.03679(V/m)
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.





## 1.6. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### FCC-Registration No.: 434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

### ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

### Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

## 1.7. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



## 2. Measurement and Result

### 2.1. Requirements

According to the item 5.b) of KDB 680106 D01v04:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

- (1) The power transfer frequency is below 1 MHz.
- (2) The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.
- (3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)
- (4) Only § 2.1091-Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions).
- (5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.
- (6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested.






Limits For Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz  
 \*=Plane-wave equivalent power density  
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

## 2.2. Test Setup



Note: Measurements should be made at 20 cm surrounding the EUT and 20cm above the top surface of the EUT.



### 2.3. Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at required test distance which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points  
(A, B, C, D, E) were completed.(A is the right, B is the back, C is the left, D is the front, and E is the top.)
- 4) The EUT was measured according to the dictates of KDB 680106 D01 v04.

Remark; The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

### 2.4. Test Result

#### 2.4.1. Equipment Approval Considerations item 5.b of KDB 680106 D01 v04.

- (1) The power transfer frequency is below 1 MHz.
  - The device operate in the frequency range 110.1-205kHz.
- (2) The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.
  - The maximum output power of the primary coil is 5W.
- (3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)
  - The surfaces of the transmitter and client device enclosures is in physical contact.
- (4) Only § 2.1091-Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions).
  - The EUT is a Mobile exposure conditions
- (5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.
  - Conducted the measurement with the required distance and the test results please refer to the section 2.4.





(6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested.

- The EUT is one radiating structure.

2.4.2. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

Temperature:	22.5°C	Relative Humidity:	49 %
Pressure:	101 kPa	Test Voltage:	DC 22.2V battery inside

E-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT

Battery power	Frequency Range (kHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (V/m)	Limits Test (V/m)
1%	110.1-205	0.336	0.426	0.376	0.386	0.506	307	614
50%	110.1-205	1.387	1.827	1.317	1.447	1.617	307	614
99%	110.1-205	2.407	2.807	2.417	2.367	2.827	307	614
Stand-by	110.1-205	0.443	0.593	0.433	0.423	0.563	307	614

H-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT

Battery power	Frequency Range (kHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
1%	110.1-205	0.030	0.052	0.058	0.042	0.052	0.815	1.63
50%	110.1-205	0.294	0.384	0.284	0.284	0.454	0.815	1.63
99%	110.1-205	0.443	0.623	0.513	0.333	0.323	0.815	1.63
Stand-by	110.1-205	0.539	0.359	0.459	0.579	0.439	0.815	1.63

Note: All the situation(full load, half load and empty load) has been tested,only the worst situation (full load 5W) was recorded in the report.



## APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph\_MPE

## APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

## APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

