

FCC ID: 2BEPH-DYMOVEIEW

# **RF Exposure Evaluation**

#### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0	614	1.63	*(100)				
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6			
30–300	61.4	0.163	1.0	6			
300–1500			f/300	6			
1500–100,000			5	6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34 614		1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30			
30–300	27.5	0.073	0.2	30			
300–1500			f/1500	30			
1500–100,000			1.0	30			

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

### Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### **Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



## **Test Result of RF Exposure Evaluation**

## **BLE**

Channel	Max output power (dBm)	Output power (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm²)	Result
2480MHz	6	3.98	0.0017	1.0	PASS

Remark: antenna gain=3.43dBi

## **WIFI 2.4G**

	Channel	Max output power (dBm)	Output power (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm²)	Result
75 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	2462MHz 802.11n(HT20)	14.84	30.48	0.0134	1.0	PASS

Remark: antenna gain=3.43dBi

## WIFI 5G

Channel	Max output power (dBm)	Output power (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm²)	Result
5230MHz 802.11n (HT40)	14.85	30.55	0.0139	1.0	PASS


Remark: antenna gain=3.58dBi

## **WIFI 5.8G**

Channel	Max output power (dBm)	Output power (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm²)	Result
5795MHz 802.11n (HT40)	14.53	28.38	0.0129	1.0	PASS

Remark: antenna gain=3.59dBi

BT and WIFI Simultaneous Transmission:



 $\mathsf{BT} + \mathsf{WIFI}\ 2.4\mathsf{G} + \mathsf{WIFI}\ 5\mathsf{G} = (0.0017/1) + (\ 0.0134/1) + (0.0139/1) = 0.0017 + 0.0134 + 0.0139 = 0.029 < 1.0017 + 0.0134 + 0.0139 = 0.029 < 1.0017 + 0.0134 + 0.0139 = 0.0017 + 0.0134 + 0.0139 + 0.0017 + 0.0134 + 0.0139 + 0.0017 + 0.0134 + 0.0139 + 0.0017 + 0.0134 + 0.0139 + 0.0017 + 0.0134 + 0.0139 + 0.0017 + 0.0134 + 0.0017 +$ 

The max power density is less than MPE exempt limit, so it is compliance.