



# FCC RF Test Report

**APPLICANT** : FCNT LLC.  
**EQUIPMENT** : Mobile cellular phone  
**BRAND NAME** : arrows We2  
**MODEL NAME** : F-52E  
**FCC ID** : 2BEPUFMP195  
**STANDARD** : FCC Part 15 Subpart E §15.407  
**CLASSIFICATION** : (NII) Unlicensed National Information Infrastructure  
**TEST DATE(S)** : Feb. 19, 2024 ~ Apr. 04, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



**Sporton International Inc. (Kunshan)**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant ..... 5

    1.2 Manufacturer..... 5

    1.3 Product Feature of Equipment Under Test..... 5

    1.4 Product Specification of Equipment Under Test..... 6

    1.5 Modification of EUT ..... 7

    1.6 Testing Location ..... 8

    1.7 Test Software..... 8

    1.8 Applicable Standards..... 8

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 9**

    2.1 Carrier Frequency and Channel ..... 9

    2.2 Test Mode..... 11

    2.3 Connection Diagram of Test System..... 12

    2.4 Support Unit used in test configuration and system ..... 13

    2.5 EUT Operation Test Setup ..... 13

    2.6 Measurement Results Explanation Example..... 13

**3 TEST RESULT..... 14**

    3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement ..... 14

    3.2 Maximum Conducted Output Power Measurement ..... 16

    3.3 Power Spectral Density Measurement ..... 18

    3.4 Unwanted Emissions Measurement ..... 21

    3.5 AC Conducted Emission Measurement..... 26

    3.6 Antenna Requirements ..... 28

**4 LIST OF MEASURING EQUIPMENT ..... 29**

**5 MEASUREMENT UNCERTAINTY ..... 30**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. AC CONDUCTED EMISSION TEST RESULT**

**APPENDIX C. RADIATED SPURIOUS EMISSION**

**APPENDIX D. DUTY CYCLE PLOTS**

**APPENDIX E. SETUP PHOTOGRAPHS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1/2A/2C	Limit for U-NII-3	Result	Remark
3.1	2.1049 & 15.403(i)	6dB, 26dB & 99% Bandwidth	-	6dB Bandwidth > 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm/MHz	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 7.84 dB at 5350.01 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	15.207(a)	Pass	Under limit 15.56 dB at 0.518 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	15.203 & 15.407(a)	15.203 & 15.407(a)	Pass	-

**Conformity Assessment Condition:**

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



# 1 General Description

## 1.1 Applicant

FCNT LLC.

Sanki Yamato Bldg. 3F, 7-10-1, Chuorinkan, Yamato-shi, Kanagawa, 242-0007, Japan

## 1.2 Manufacturer

FCNT LLC.

Sanki Yamato Bldg. 3F, 7-10-1, Chuorinkan, Yamato-shi, Kanagawa, 242-0007, Japan

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile cellular phone
Brand Name	arrows We2
Model Name	F-52E
FCC ID	2BEPUFMP195
IMEI Code	Conducted: 354214220026404/354214220026412 Conduction: 354214220043946/354214220043953 Radiation: 354214220043508/354214220043516
HW Version	V4
SW Version	FAC_V006
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Frequency Range</b>	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz
<b>Maximum Output Power to Antenna</b>	<p><b>&lt;5180 MHz ~ 5240 MHz&gt;</b>  802.11a : 10.73 dBm / 0.0118 W  802.11n HT20 : 10.54 dBm / 0.0113 W  802.11n HT40 : 10.71 dBm / 0.0118 W  802.11ac VHT20: 10.60 dBm / 0.0115 W  802.11ac VHT40: 10.74 dBm / 0.0119 W  802.11ac VHT80: 10.28 dBm / 0.0107 W</p> <p><b>&lt;5260 MHz ~ 5320 MHz&gt;</b>  802.11a : 10.74 dBm / 0.0119 W  802.11n HT20 : 10.57 dBm / 0.0114 W  802.11n HT40 : 10.73 dBm / 0.0118 W  802.11ac VHT20: 10.64 dBm / 0.0116 W  802.11ac VHT40: 10.75 dBm / 0.0119 W  802.11ac VHT80: 10.31 dBm / 0.0107 W</p> <p><b>&lt;5500 MHz ~ 5720 MHz &gt;</b>  802.11a : 10.78 dBm / 0.0120 W  802.11n HT20 : 10.60 dBm / 0.0115 W  802.11n HT40 : 10.84 dBm / 0.0121 W  802.11ac VHT20: 10.69 dBm / 0.0117 W  802.11ac VHT40: 10.86 dBm / 0.0122 W  802.11ac VHT80: 10.35 dBm / 0.0108 W</p> <p><b>&lt;5745 MHz ~ 5825 MHz&gt;</b>  802.11a : 10.67 dBm / 0.0117 W  802.11n HT20 : 10.58 dBm / 0.0114 W  802.11n HT40 : 10.74 dBm / 0.0119 W  802.11ac VHT20: 10.63 dBm / 0.0116 W  802.11ac VHT40: 10.78 dBm / 0.0120 W  802.11ac VHT80: 10.22 dBm / 0.0105 W</p>



<p><b>99% Occupied Bandwidth</b></p>	<p><b>&lt;5180 MHz ~ 5240 MHz&gt;</b>  802.11a : 17.343 MHz  802.11n HT20 : 18.142 MHz  802.11n HT40 : 36.523 MHz  802.11ac VHT80 : 75.445 MHz</p> <p><b>&lt;5260 MHz ~ 5320 MHz&gt;</b>  802.11a : 17.303 MHz  802.11n HT20 : 18.182 MHz  802.11n HT40 : 36.603 MHz  802.11ac VHT80 : 75.445 MHz</p> <p><b>&lt;5500 MHz ~ 5720 MHz&gt;</b>  802.11a : 17.383 MHz  802.11n HT20 : 18.222 MHz  802.11n HT40 : 36.683 MHz  802.11ac VHT80 : 75.445 MHz</p> <p><b>&lt;5745 MHz ~ 5825 MHz&gt;</b>  802.11a : 17.423 MHz  802.11n HT20 : 18.262 MHz  802.11n HT40 : 36.603 MHz  802.11ac VHT80 : 75.604 MHz</p>
<p><b>Antenna Type / Gain</b></p>	<p><b>&lt;Ant.8&gt;</b></p> <p><b>&lt;5180 MHz ~ 5240 MHz&gt;</b>  LOOP Antenna type with gain -2.09 dBi</p> <p><b>&lt;5260 MHz ~ 5320 MHz&gt;</b>  LOOP Antenna type with gain -1.52 dBi</p> <p><b>&lt;5500 MHz ~ 5720 MHz&gt;</b>  LOOP Antenna type with gain -1.53 dBi</p> <p><b>&lt;5745 MHz ~ 5825 MHz&gt;</b>  LOOP Antenna type with gain -1.59 dBi</p>
<p><b>Type of Modulation</b></p>	<p>802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)  802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)</p>

**Note:** For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing has assessed only 802.11ac VHT20/ VHT40 by referring to their higher conducted power.

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH06-KS TH01-KS	CN1257	314309

### 1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH06-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

### 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.





## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 <sup>#</sup>	5210	-	-

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 <sup>#</sup>	5290	-	-

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5500-5720MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 <sup>#</sup>	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 <sup>#</sup>	5775	165	5825



Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122 <sup>#</sup>	5610	128	5640
	-	-	-	-

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138 <sup>#</sup>	5690	144	5720
	142*	5710	-	-

**Note:**

1. The above Frequency and Channel in "\*" are 40MHz bandwidth.
2. The above Frequency and Channel in "<sup>#</sup>" are 80MHz bandwidth.



## 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0

<b>AC Conducted Emission</b>	Mode 1 : GSM850 Idle + BT Link + WLAN Link(5G) + USB Cable (Charging From Adaptor)
<b>Remark:</b> For Radiated Test Cases, the tests were performance with Adapter and USB Cable.	


Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		20M BW	20M BW	20M BW	20M BW
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		40M BW	40M BW	40M BW	40M BW
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159
Straddle		-	-	142	-


Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		80M BW	80M BW	80M BW	80M BW
L	Low	-	-	106	-
M	Middle	42	58	-	155
H	High	-	-	-	-
Straddle		-	-	138	-

## 2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:





### 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
2.	LTE Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	WLAN AP	ASUS	GT-AXE11000	N/A	N/A	N/A
5.	SD Card	Kingston	8GB	N/A	N/A	N/A
6.	Earphone	N/A	N/A	N/A	N/A	N/A

### 2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

### 2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

Following shows an offset computation example with cable loss 4.28 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.28 + 10 = 14.28 \text{ (dB)} \end{aligned}$$



### 3 Test Result

#### 3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

##### 3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

##### 3.1.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

- The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

<input checked="" type="checkbox"/>	Section C) Bandwidth Measurement 1. Emission Bandwidth (EBW) and 99% OBW
	<ol style="list-style-type: none"> <li>Set RBW = approximately 1% of the emission bandwidth.</li> <li>Set the VBW &gt; RBW.</li> <li>Detector = Peak.</li> <li>Trace mode = max hold</li> <li>Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.</li> <li>For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set to 1%~5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW.</li> <li>Measure and record the results in the test report.</li> </ol>
<input checked="" type="checkbox"/>	Section C) Bandwidth Measurement 2. Minimum Emission Bandwidth for the band 5.725 - 5.85 GHz
	<ol style="list-style-type: none"> <li>Set RBW = 100kHz.</li> <li>Set the VBW ≥ 3 x RBW.</li> <li>Detector = Peak.</li> <li>Trace mode = max hold</li> <li>Measure the maximum width of the emission that is 6 dB down from the peak of the emission.</li> <li>Measure and record the results in the test report.</li> </ol>

### 3.1.4 Test Setup



### 3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



## 3.2 Maximum Conducted Output Power Measurement

### 3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log_{10} B$ , where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



### 3.2.3 Test Procedures


The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor,  $10 \log(1/x)$ , where  $x$  is the duty cycle.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



### 3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section F) Maximum power spectral density.

#### For devices operating in the bands UNII-1/2A/2C

##### # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW  $\geq$  3 MHz.
- Number of points in sweep  $\geq$  2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add  $10 \log(1/x)$ , where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add  $10 \log(1/0.25) = 6$  dB if the duty cycle is 25 percent.

#### For devices operating in the band UNII-3


##### # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500KHz (or 300 kHz if the SA can't set RBW=500KHz).
- Set VBW  $\geq$  1 MHz.
- Number of points in sweep  $\geq$  2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- If the SA can't set RBW=500KHz, then add  $10 \log(500\text{kHz}/\text{RBW})$  to the test result.
- Add  $10 \log(1/x)$ , where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add  $10 \log(1/0.25) = 6$  dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



### 3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

#### 3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of  $-27$  dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of  $-27$  dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of  $-27$  dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725 MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725 MHz band shall not exceed an EIRP of  $-27$  dBm/MHz.

- (2) For transmitters operating in the 5.725-5.85 GHz band:  
15.407(b)(4)(i) All emissions shall be limited to a level of  $-27$  dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to  $10$  dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of  $15.6$  dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of  $27$  dBm/MHz at the band edge.



(3) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

(4) EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log (d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E<sub>Meas</sub> is the field strength of the emission at the measurement distance, in dBµV/m

d<sub>Meas</sub> is the measurement distance, in m

### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### 3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section G) Unwanted emissions measurement.
  - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
    - RBW = 120 kHz
    - VBW = 300 kHz
    - Detector = Peak
    - Trace mode = max hold
  - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
    - RBW = 1 MHz
    - VBW  $\geq$  3 MHz
    - Detector = Peak
    - Sweep time = auto
    - Trace mode = max hold
  - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
    - RBW = 1 MHz
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq$  1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

### 3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz







### **3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### **3.4.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix C.

### **3.4.7 Duty Cycle**

Please refer to Appendix D.

### **3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)**

Please refer to Appendix C.



### 3.5 AC Conducted Emission Measurement

#### 3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.5.4 Test Setup



### 3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.6 Antenna Requirements**

### **3.6.1 Standard Applicable**

According to FCC 47 CFR Section 15.407(a)(1)(2), if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **3.6.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.6.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Ma x 30dBm	Oct. 10, 2023	Apr. 02, 2024	Oct. 09, 2024	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz-44GHz	Oct. 10, 2023	Apr. 02, 2024	Oct. 09, 2024	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	Apr. 02, 2024	Oct. 09, 2024	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz-1GHz	Apr. 09, 2023	Apr. 02, 2024	Apr. 08, 2024	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 06, 2023	Apr. 02, 2024	Apr. 05, 2024	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 05, 2024	Apr. 02, 2024	Jan. 04, 2025	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	380827	9KHz ~1GHZ	Jul. 06, 2023	Apr. 02, 2024	Jul. 05, 2024	Radiation (03CH06-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 04, 2024	Apr. 02, 2024	Jan. 03, 2025	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2082395	1Ghz-18Ghz	Jan. 04, 2024	Apr. 02, 2024	Jan. 03, 2025	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270319	500MHz~26.5G Hz	Oct. 10, 2023	Apr. 02, 2024	Oct. 09, 2024	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Apr. 02, 2024	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Apr. 02, 2024	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Apr. 02, 2024	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 16, 2023	Apr. 04, 2024	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 11, 2023	Apr. 04, 2024	Oct. 10, 2024	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Apr. 04, 2024	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 11, 2023	Apr. 04, 2024	Oct. 10, 2024	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Feb. 19, 2024~ Mar. 13, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2024	Feb. 19, 2024~ Mar. 13, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024	Feb. 19, 2024~ Mar. 13, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H201401144 0	-40~+150°C 20%~95%RH	Jul. 06, 2023	Feb. 19, 2024~ Mar. 13, 2024	Jul. 05, 2024	Conducted (TH01-KS)

NCR: No Calibration Required



## 5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.46 dB
Conducted Power Spectral Density	±0.88 dB
Frequency	±0.4 Hz

### Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84 dB
---	---------

### Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.32 dB
---	---------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.26 dB
---	---------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.02 dB
---	---------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.26 dB
---	---------

----- THE END -----



## **Appendix A. Conducted Test Results**

### A1. Conducted Test Results

Test Engineer:	Long Wu	Temperature:	21~25	°C
Test Date:	2024.2.27	Relative Humidity:	51~54	%



**TEST RESULTS DATA**  
**Average Power Table**

<5180 MHz ~ 5240 MHz>										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
					Ant 8	Ant 8	Ant 8	Ant 8		
11a	6Mbps	1	36	5180	0.11	10.65	24.00	-2.09		Pass
11a	6Mbps	1	44	5220	0.11	10.69	24.00	-2.09		Pass
11a	6Mbps	1	48	5240	0.11	10.73	24.00	-2.09		Pass
HT20	MCS0	1	36	5180	0.12	10.44	24.00	-2.09		Pass
HT20	MCS0	1	44	5220	0.12	10.54	24.00	-2.09		Pass
HT20	MCS0	1	48	5240	0.12	10.51	24.00	-2.09		Pass
HT40	MCS0	1	38	5190	0.22	10.64	24.00	-2.09		Pass
HT40	MCS0	1	46	5230	0.22	10.71	24.00	-2.09		Pass
VHT20	MCS0	1	36	5180	0.12	10.51	24.00	-2.09		Pass
VHT20	MCS0	1	44	5220	0.12	10.60	24.00	-2.09		Pass
VHT20	MCS0	1	48	5240	0.12	10.56	24.00	-2.09		Pass
VHT40	MCS0	1	38	5190	0.22	10.69	24.00	-2.09		Pass
VHT40	MCS0	1	46	5230	0.22	10.74	24.00	-2.09		Pass
VHT80	MCS0	1	42	5210	0.63	10.28	24.00	-2.09		Pass

**TEST RESULTS DATA**  
**Average Power Table**

<5260 MHz ~ 5320 MHz>										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
					Ant 8	Ant 8	Ant 8	Ant 8		
11a	6Mbps	1	52	5260	0.11	10.69	23.98	-1.52	26.99	Pass
11a	6Mbps	1	60	5300	0.11	10.74	23.97	-1.52	26.99	Pass
11a	6Mbps	1	64	5320	0.11	10.66	23.98	-1.52	26.99	Pass
HT20	MCS0	1	52	5260	0.12	10.57	23.98	-1.52	26.99	Pass
HT20	MCS0	1	60	5300	0.12	10.56	23.98	-1.52	26.99	Pass
HT20	MCS0	1	64	5320	0.12	10.48	23.98	-1.52	26.99	Pass
HT40	MCS0	1	54	5270	0.22	10.73	23.98	-1.52	26.99	Pass
HT40	MCS0	1	62	5310	0.22	10.71	23.98	-1.52	26.99	Pass
VHT20	MCS0	1	52	5260	0.12	10.64	23.98	-1.52	26.99	Pass
VHT20	MCS0	1	60	5300	0.12	10.60	23.98	-1.52	26.99	Pass
VHT20	MCS0	1	64	5320	0.12	10.50	23.98	-1.52	26.99	Pass
VHT40	MCS0	1	54	5270	0.22	10.75	23.98	-1.52	26.99	Pass
VHT40	MCS0	1	62	5310	0.22	10.74	23.98	-1.52	26.99	Pass
VHT80	MCS0	1	58	5290	0.63	10.31	23.98	-1.52	26.99	Pass

**TEST RESULTS DATA**  
**Average Power Table**

<5500 MHz ~ 5720 MHz>										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
					Ant 8	Ant 8	Ant 8	Ant 8		
11a	6Mbps	1	100	5500	0.11	10.59	23.98	-1.53	26.99	Pass
11a	6Mbps	1	116	5580	0.11	10.47	23.98	-1.53	26.99	Pass
11a	6Mbps	1	140	5700	0.11	10.78	23.98	-1.53	26.99	Pass
HT20	MCS0	1	100	5500	0.12	10.49	23.98	-1.53	26.99	Pass
HT20	MCS0	1	116	5580	0.12	10.45	23.98	-1.53	26.99	Pass
HT20	MCS0	1	140	5700	0.12	10.60	23.98	-1.53	26.99	Pass
HT40	MCS0	1	102	5510	0.22	10.63	23.98	-1.53	26.99	Pass
HT40	MCS0	1	110	5550	0.22	10.64	23.98	-1.53	26.99	Pass
HT40	MCS0	1	134	5670	0.22	10.84	23.98	-1.53	26.99	Pass
VHT20	MCS0	1	100	5500	0.12	10.55	23.98	-1.53	26.99	Pass
VHT20	MCS0	1	116	5580	0.12	10.48	23.98	-1.53	26.99	Pass
VHT20	MCS0	1	140	5700	0.12	10.69	23.98	-1.53	26.99	Pass
VHT40	MCS0	1	102	5510	0.22	10.65	23.98	-1.53	26.99	Pass
VHT40	MCS0	1	110	5550	0.22	10.68	23.98	-1.53	26.99	Pass
VHT40	MCS0	1	134	5670	0.22	10.86	23.98	-1.53	26.99	Pass
VHT80	MCS0	1	106	5530	0.63	10.26	23.98	-1.53	26.99	Pass
VHT80	MCS0	1	122	5610	0.63	10.27	23.98	-1.53	26.99	Pass

<5500 MHz ~ 5720 MHz>straddle channel										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
					Ant 8	Ant 8	Ant 8	Ant 8		
11a	6Mbps	1	144	5720	0.11	10.75	23.98	-1.53	26.99	Pass
HT20	MCS0	1	144	5720	0.12	10.54	23.98	-1.53	26.99	Pass
HT40	MCS0	1	142	5710	0.22	10.79	23.98	-1.53	26.99	Pass
VHT20	MCS0	1	144	5720	0.12	10.59	23.98	-1.53	26.99	Pass
VHT40	MCS0	1	142	5710	0.22	10.80	23.98	-1.53	26.99	Pass
VHT80	MCS0	1	138	5690	0.63	10.35	23.98	-1.53	26.99	Pass

**TEST RESULTS DATA**  
**Average Power Table**

<5745 MHz ~ 5825 MHz>									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	Pass/Fail
					Ant 8	Ant 8	Ant 8	Ant 8	
11a	6Mbps	1	149	5745	0.11	10.67	30.00	-1.59	Pass
11a	6Mbps	1	157	5785	0.11	10.66	30.00	-1.59	Pass
11a	6Mbps	1	165	5825	0.11	10.63	30.00	-1.59	Pass
HT20	MCS0	1	149	5745	0.12	10.58	30.00	-1.59	Pass
HT20	MCS0	1	157	5785	0.12	10.47	30.00	-1.59	Pass
HT20	MCS0	1	165	5825	0.12	10.51	30.00	-1.59	Pass
HT40	MCS0	1	151	5755	0.22	10.74	30.00	-1.59	Pass
HT40	MCS0	1	159	5795	0.22	10.64	30.00	-1.59	Pass
VHT20	MCS0	1	149	5745	0.12	10.63	30.00	-1.59	Pass
VHT20	MCS0	1	157	5785	0.12	10.56	30.00	-1.59	Pass
VHT20	MCS0	1	165	5825	0.12	10.54	30.00	-1.59	Pass
VHT40	MCS0	1	151	5755	0.22	10.78	30.00	-1.59	Pass
VHT40	MCS0	1	159	5795	0.22	10.66	30.00	-1.59	Pass
VHT80	MCS0	1	155	5775	0.63	10.22	30.00	-1.59	Pass




## Emission Bandwidth


### Test Result


TestMode	Antenna	Freq(MHz)	26dB EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant8	5180	20.20	5169.90	5190.10	---	---
		5220	19.70	5210.20	5229.90	---	---
		5240	20.90	5229.50	5250.40	---	---
		5260	22.00	5249.90	5271.90	---	---
		5300	19.80	5290.10	5309.90	---	---
		5320	19.90	5310.10	5330.00	---	---
		5500	20.40	5490.10	5510.50	---	---
		5580	21.00	5569.10	5590.10	---	---
		5700	24.40	5687.20	5711.60	---	---
		5720	21.00	5709.70	5730.70	---	---
		5745	22.10	5733.70	5755.80	---	---
5785	21.00	5774.90	5795.90	---	---		
5825	22.50	5813.80	5836.30	---	---		
11N20SISO	Ant8	5180	20.10	5170.00	5190.10	---	---
		5220	20.20	5209.90	5230.10	---	---
		5240	20.20	5229.90	5250.10	---	---
		5260	20.10	5250.00	5270.10	---	---
		5300	20.20	5290.00	5310.20	---	---
		5320	20.10	5310.00	5330.10	---	---
		5500	20.30	5489.90	5510.20	---	---
		5580	20.30	5569.90	5590.20	---	---
		5700	20.30	5689.90	5710.20	---	---
		5720	20.40	5709.80	5730.20	---	---
		5745	20.40	5734.80	5755.20	---	---
5785	20.30	5774.90	5795.20	---	---		
5825	20.20	5814.90	5835.10	---	---		
11N40SISO	Ant8	5190	40.80	5169.80	5210.60	---	---
		5230	40.60	5209.80	5250.40	---	---
		5270	41.00	5249.80	5290.80	---	---
		5310	40.60	5289.80	5330.40	---	---
		5510	40.40	5490.00	5530.40	---	---
		5550	40.20	5530.00	5570.20	---	---
		5670	40.60	5649.80	5690.40	---	---
		5710	40.80	5689.60	5730.40	---	---
		5755	40.80	5734.60	5775.40	---	---
5795	50.40	5766.00	5816.40	---	---		
11AC80SISO	Ant8	5210	81.20	5169.60	5250.80	---	---
		5290	81.20	5249.60	5330.80	---	---
		5530	81.20	5489.60	5570.80	---	---
		5610	81.20	5569.60	5650.80	---	---
		5690	80.80	5650.00	5730.80	---	---
		5775	81.20	5734.60	5815.80	---	---




### Test Graphs




































































### Occupied channel bandwidth

#### Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant8	5180	17.343	5171.3287	5188.6713	---	---
		5220	17.263	5211.3686	5228.6314	---	---
		5240	17.303	5231.3686	5248.6713	---	---
		5260	17.183	5251.3686	5268.5514	---	---
		5300	17.263	5291.3686	5308.6314	---	---
		5320	17.303	5311.3686	5328.6713	---	---
		5500	17.303	5491.3686	5508.6713	---	---
		5580	17.303	5571.3686	5588.6713	---	---
		5700	17.383	5691.2887	5708.6713	---	---
		5720	17.343	5711.3287	5728.6713	---	---
		5745	17.343	5736.3287	5753.6713	---	---
		5785	17.423	5776.2887	5793.7113	---	---
11N20SISO	Ant8	5180	18.142	5170.9690	5189.1109	---	---
		5220	18.102	5210.9291	5229.0310	---	---
		5240	18.142	5230.9291	5249.0709	---	---
		5260	18.102	5250.9291	5269.0310	---	---
		5300	18.142	5290.9291	5309.0709	---	---
		5320	18.182	5310.9291	5329.1109	---	---
		5500	18.182	5490.8891	5509.0709	---	---
		5580	18.142	5570.9291	5589.0709	---	---
		5700	18.222	5690.8492	5709.0709	---	---
		5720	18.222	5710.8891	5729.1109	---	---
		5745	18.142	5735.9291	5754.0709	---	---
		5785	18.182	5775.9291	5794.1109	---	---
11N40SISO	Ant8	5190	36.523	5171.7782	5208.3017	---	---
		5230	36.444	5211.8581	5248.3017	---	---
		5270	36.444	5251.7782	5288.2218	---	---
		5310	36.603	5291.6983	5328.3017	---	---
		5510	36.444	5491.7782	5528.2218	---	---
		5550	36.364	5531.8581	5568.2218	---	---
		5670	36.523	5651.7782	5688.3017	---	---
		5710	36.683	5691.6184	5728.3017	---	---
		5755	36.603	5736.6983	5773.3017	---	---
11AC80SISO	Ant8	5210	75.445	5172.2777	5247.7223	---	---
		5290	75.445	5252.2777	5327.7223	---	---
		5530	75.445	5492.2777	5567.7223	---	---
		5610	75.285	5572.2777	5647.5624	---	---
		5690	75.285	5652.2777	5727.5624	---	---
		5775	75.604	5737.2777	5812.8821	---	---



### Test Graphs

