

**CFR 47 FCC PART 15 SUBPART C**

**TEST REPORT**

*For*

**Smart deadbolt lock**

**MODEL NUMBER: H2 C20, H1 C20**

**REPORT NUMBER: E04A24080413F00103**

**ISSUE DATE: September 25, 2024**

**FCC ID: 2BEW6-H1C20**

*Prepared for*

**Shenzhen Fenda Smart Home Co., Ltd.**

**Floors 7-9, Building 2, Phase II, Fenda Industrial Park, Baoyuan Community, Shiyan Street, Bao'an District, Shenzhen, China**

*Prepared by*

**Guangdong Global Testing Technology Co., Ltd.**

**Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808**

**This report shall not be reproduced, except in full, without the written approval of Guangdong Global Testing Technology Co., Ltd.**

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	September 25, 2024	Initial Issue	

### Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.11 & Clause 11.12	FCC Part 15.247 (d) FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

\*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

\*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C> when <Accuracy Method> decision rule is applied.

## CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>5</b>
<b>2. TEST METHODOLOGY.....</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>7</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION.....</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>8</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>8</i>
5.2. <i>CHANNEL LIST .....</i>	<i>9</i>
5.3. <i>MAXIMUM PEAK Conducted OUTPUT POWER .....</i>	<i>9</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>9</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>10</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>11</i>
5.7. <i>SUPPORT UNITS FOR SYSTEM TEST .....</i>	<i>11</i>
5.8. <i>SETUP DIAGRAM .....</i>	<i>12</i>
<b>6. MEASURING EQUIPMENT AND SOFTWARE USED.....</b>	<b>13</b>
<b>7. ANTENNA PORT TEST RESULTS .....</b>	<b>14</b>
7.1. <i>Conducted Output Power.....</i>	<i>14</i>
7.2. <i>6dB Bandwidth Occupied Bandwidth .....</i>	<i>16</i>
7.3. <i>Power Spectral Density.....</i>	<i>18</i>
7.4. <i>Conducted Band edge and spurious emission .....</i>	<i>20</i>
7.5. <i>Duty Cycle .....</i>	<i>22</i>
<b>8. RADIATED TEST RESULTS .....</b>	<b>23</b>
<b>9. ANTENNA REQUIREMENT .....</b>	<b>41</b>
<b>10. AC POWER LINE CONDUCTED EMISSION .....</b>	<b>42</b>
<b>11. TEST DATA - Appendix C.....</b>	<b>45</b>
<b>APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION .....</b>	<b>87</b>
<b>APPENDIX: PHOTOGRAPHS OF THE EUT .....</b>	<b>88</b>

# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: Shenzhen Fenda Smart Home Co., Ltd.  
 Address: Floors 7-9, Building 2, Phase II, Fenda Industrial Park, Baoyuan Community, Shiyan Street, Bao'an District, Shenzhen, China

## Manufacturer Information

Company Name: Shenzhen Fenda Smart Home Co., Ltd.  
 Address: Floors 7-9, Building 2, Phase II, Fenda Industrial Park, Baoyuan Community, Shiyan Street, Bao'an District, Shenzhen, China

## EUT Information

Product Description: Smart deadbolt lock  
 Model: H1 C20  
 Serial Model: H2 C20  
 Brand: N/A  
 Sample Received Date: August 20, 2024  
 Sample Status: Normal  
 Sample ID: A24080413 001  
 Date of Tested: August 28, 2024 to September 11, 2024

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	Pass

Prepared By:

*Win Huang*

Win Huang  
 Project Engineer

Checked By:

*Alan He*

Alan He  
 Laboratory Leader

Approved By:

*Shawn Wen*

Shawn Wen  
 Laboratory Manager



## 2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C(DTS)

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 6947.01)</b> Guangdong Global Testing Technology Co., Ltd. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1343)</b> Guangdong Global Testing Technology Co., Ltd. has been recognized to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification rules</p> <p><b>ISED (Company No.: 30714)</b> Guangdong Global Testing Technology Co., Ltd. has been registered and fully described in a report filed with ISED. The Company Number is 30714 and the test lab Conformity Assessment Body Identifier (CABID) is CN0148.</p>
---------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Items	k	Uncertainty
DTS Bandwidth	1.96	±9.2 PPM
20dB Emission Bandwidth	1.96	±9.2 PPM
Carrier Frequency Separation	1.96	±9.2 PPM
Time of Occupancy	1.96	±0.57%
Conducted Output Power	1.96	±1.5 dB
Power Spectral Density Level	1.96	±1.9 dB
Conducted Spurious Emission	1.96	9 kHz-30 MHz: ± 0.95 dB 30 MHz-1 GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.8 dB 12.75 GHz-26.5 GHz: ± 2.1dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports (AMN)	150 kHz ~ 30 MHz	2	3.37
Radiated emissions	9 kHz ~ 30 MHz	2	4.16
Radiated emissions	30 MHz ~ 1 GHz	2	3.79
Radiated emissions	1 GHz ~ 18 GHz	2	5.62
Radiated emissions	18 GHz ~ 40 GHz	2	5.54

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name		Smart deadbolt lock
Model		H1 C20
Series Model		H2 C20
Hardware Version		V1.1
Software Version		2.0.4
Ratings		Battery 7.4V
Power Supply	AC	120V/60Hz From Adapter
	DC	Battery 7.4V

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n: Up to MCS7
Number of Channels:	IEEE 802.11b/g/n-HT20: 11
Maximum Peak Power:	IEEE 802.11b: 8.44 dBm IEEE 802.11g: 7.86 dBm IEEE 802.11n-HT20: 6.38 dBm
Antenna Type:	Internal antenna
Antenna Gain:	4.32dBi
Normal Test Voltage:	5 Vdc
EUT Test software:	FCC_assist_v1.1.5



## 5.2. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

## 5.3. MAXIMUM PEAK CONDUCTED OUTPUT POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted Peak Output Power (dBm)
b	2412 ~ 2462	1-11[11]	8.44
g	2412 ~ 2462	1-11[11]	7.86
n HT20	2412 ~ 2462	1-11[11]	6.38

## 5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz

## 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		FCC_assist_v1.1.5					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	20	20	20			
802.11g	1	18	18	18			
802.11n HT20	1	17	17	17			

## WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps

802.11g mode: 6 Mbps

802.11n HT20 mode: MCS0

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Conducted output power, power spectral density tests separately on each port with all supported SISO & MIMO port combinations.

Conducted bandedge and spurious emissions tests were performed with SISO mode, as this port was found to have the worst case in terms of power settings amongst all supported possible SISO & MIMO port combinations.

Radiated emissions tests were performed with the MIMO modes. These were found to be the worst modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest conducted output power level, it was deemed to be the worst case.

The EUT support Cyclic Shift Diversity(CDD), Space Time Coding(STBC), Spatial Division Multiplexing(SDM) modes. They use the same conducted power per chain in any given mode, so we only chose the worst case mode CDD for final testing.

## 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	Internal antenna	4.32

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.

Note: The value of the antenna gain was declared by customer.


## 5.7. SUPPORT UNITS FOR SYSTEM TEST

The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	PC	Lenovo	B4650-D002	M90601U3	GTG Support
E-2	Adapter	Xiaomi	MDY-11-EX	N/A	GTG Support

### 5.8. SETUP DIAGRAM

#### AC conducted emission



#### Radiated Emission:



#### RF conducted:



## 6. MEASURING EQUIPMENT AND SOFTWARE USED

Test Equipment of Conducted RF					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40	102257	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51285127	2023/09/18	2024/09/17
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61253075	2023/09/18	2024/09/17
Vector Signal Generator	Rohde & Schwarz	SMM100A	101899	2023/09/18	2024/09/17
RF Control box	MWRF-test	MW100-RFCB	MW220926GTG	2023/09/18	2024/09/17
Wideband Radio Communication Tester	Rohde & Schwarz	CMW270	102792	2023/09/18	2024/09/17
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	103235	2023/09/18	2024/09/17
temperature humidity chamber	Espec	SH-241	SH-241-2014	2023/09/18	2024/09/17
RF Test Software	MWRF-test	MTS8310E (Ver. V2/0)	N/A	N/A	N/A

Test Equipment of Radiated emissions below 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2146	2022/08/30	2025/08/29
EMI Test Receiver	Rohde & Schwarz	ESCI3	101409	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2023/09/18	2024/09/17
Pre-Amplifier	HzEMC	HPA-9K0130	HYP A21001	2023/09/18	2024/09/17
Biconilog Antenna	Schwarzbeck	VULB 9168	01315	2022/10/10	2025/10/09
Biconilog Antenna	ETS	3142E	00243646	2022/03/23	2025/03/22
Loop Antenna	ETS	6502	243668	2022/03/30	2025/03/29
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE)	N/A	N/A	N/A

Test Equipment of Radiated emissions above 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2149	2022/08/30	2025/08/29
Spectrum Analyzer	Rohde & Schwarz	FSV40	101413	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2023/09/18	2024/09/17
Pre-Amplifier	A-INFO	HPA-1G1850	HYP A21003	2023/09/18	2024/09/17
Horn antenna	A-INFO	3117	246069	2022/03/11	2025/03/10
Pre-Amplifier	ZKJC	HPA-184057	HYP A21004	2023/09/18	2024/09/17
Horn antenna	ZKJC	3116C	246265	2022/03/29	2025/03/28
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE+)	N/A	N/A	N/A

Test Equipment of Conducted emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Shielded Room	CHENG YU	8m*5m*4m	N/A	2022/10/29	2025/10/28
EMI Test Receiver	Rohde & Schwarz	ESR3	102647	2023/09/18	2024/09/17
LISN/AMN	Rohde & Schwarz	ENV216	102843	2023/09/18	2024/09/17
NNLK 8129 RC	Schwarzbeck	NNLK 8129 RC	5046	2023/09/18	2024/09/17
Test Software	Farad	EZ-EMC (Ver. EMC-con-3A1 1+)	N/A	N/A	N/A

## 7. ANTENNA PORT TEST RESULTS

### 7.1. CONDUCTED OUTPUT POWER

#### LIMITS


CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5

#### TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

**TEST SETUP**



**TEST ENVIRONMENT**

Temperature	24°C	Relative Humidity	55%
Atmosphere Pressure	101kPa		

**TEST RESULTS**

Please refer to section "Test Data" - Appendix C

## 7.2. 6DB BANDWIDTH OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5

### TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz
VBW	For 6 dB Bandwidth: ≥3 × RBW
Trace	Max hold
Sweep	Auto couple

a) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	24°C	Relative Humidity	55%
Atmosphere Pressure	101kPa		



**TEST RESULTS**

Please refer to section "Test Data" - Appendix C

### 7.3. POWER SPECTRAL DENSITY

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

#### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	PEAK
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	24°C	Relative Humidity	55%
Atmosphere Pressure	101kPa		

**TEST RESULTS**

Please refer to section "Test Data" - Appendix C

## 7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

**TEST SETUP**



**TEST ENVIRONMENT**

Temperature	24°C	Relative Humidity	55%
Atmosphere Pressure	101kPa		

**TEST RESULTS**

Please refer to section "Test Data" - Appendix C

## 7.5. DUTY CYCLE


### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	24°C	Relative Humidity	55%
Atmosphere Pressure	101kPa		

### TEST RESULTS

Please refer to section "Test Data" - Appendix C

## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

- Note:1. Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.  
 2. Above 38.6c

**TEST PROCEDURE**

Below 30 MHz

The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.



7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377\Omega$ . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1G

The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold



1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.


X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

### TEST SETUP






**TEST ENVIRONMENT**

Temperature	24.1°C	Relative Humidity	53%
Atmosphere Pressure	101kPa		

**TEST RESULTS**

The worst data of the mode (802.11b 2412MHz) are recorded in the following pages.


Mode:	11B 2412
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3°C/52% /101Kpa



### Critical\_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	159.980	36.68	-21.82	14.86	43.50	28.64	PK+	H
2	271.530	37.30	-18.64	18.66	46.00	27.34	PK+	H
3	369.500	35.32	-15.46	19.86	46.00	26.14	PK+	H
4	540.220	31.23	-10.25	20.98	46.00	25.02	PK+	H
5	780.780	31.90	-6.88	25.02	46.00	20.98	PK+	H
6	944.710	31.77	-3.33	28.44	46.00	17.56	PK+	H

Mode:	11B 2412
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3°C/52%/101Kpa




### Critical\_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	132.820	42.46	-24.06	18.40	43.50	25.10	PK+	V
2	228.850	37.67	-20.38	17.29	46.00	28.71	PK+	V
3	360.770	33.08	-15.79	17.29	46.00	28.71	PK+	V
4	540.220	31.22	-10.25	20.97	46.00	25.03	PK+	V
5	709.970	31.34	-7.09	24.25	46.00	21.75	PK+	V
6	944.710	30.99	-3.33	27.66	46.00	18.34	PK+	V

Above 1GHz  
The worst result as bellow:


Mode:	11B 2412
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3°C/52% /101Kpa



**Critical\_Freqs**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2498.000	55.95	-8.41	47.54	74.00	26.46	PK+	H
2	4996.500	57.77	-	46.59	74.00	27.41	PK+	H
3	6000.000	52.35	-8.87	43.48	74.00	30.52	PK+	H
4	10830.000	49.39	-5.13	44.26	74.00	29.74	PK+	H
5	16419.000	46.58	-1.32	45.26	74.00	28.74	PK+	H
6	17715.000	46.15	-0.14	46.01	74.00	27.99	PK+	H

Mode:	11B 2412
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3□/52%/101Kpa




**Critical\_Freqs**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2094.000	54.69	-9.37	45.32	74.00	28.68	PK+	V
2	4999.500	57.83	-11.18	46.65	74.00	27.35	PK+	V
3	7200.000	51.84	-8.06	43.78	74.00	30.22	PK+	V
4	8199.000	52.15	-7.86	44.29	74.00	29.71	PK+	V
5	12501.000	48.27	-4.36	43.91	74.00	30.09	PK+	V
6	17697.000	46.35	0.2	46.55	74.00	27.45	PK+	V




Mode:	11B 2437
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3□/52%/101Kpa



**Critical\_Freqs**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2194.000	55.91	-9.2	46.71	74.00	27.29	PK+	V
2	3399.000	63.40	-14.36	49.04	74.00	24.96	PK+	V
3	6199.500	58.58	-8.45	50.13	74.00	23.87	PK+	V
4	7198.500	52.61	-8.08	44.53	74.00	29.47	PK+	V
5	9000.000	52.93	-7.87	45.06	74.00	28.94	PK+	V
6	17698.500	46.17	0.19	46.36	74.00	27.64	PK+	V


Mode:	11B 2437
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3□/52%/101Kpa



**Critical\_Freqs**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2498.000	56.39	-8.41	47.98	74.00	26.02	PK+	H
2	3771.000	55.12	-13.44	41.68	74.00	32.32	PK+	H
3	4981.500	58.24	-11.17	47.07	74.00	26.93	PK+	H
4	5875.500	53.96	-9.01	44.95	74.00	29.05	PK+	H
5	11410.500	48.05	-4.45	43.60	74.00	30.40	PK+	H
6	16738.500	46.38	-1.02	45.36	74.00	28.64	PK+	H
7	17704.500	46.41	0.08	46.49	74.00	27.51	PK+	H


Mode:	11B 2462
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3□/52%/101Kpa



**Critical\_Freqs**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2500.000	56.21	-8.41	47.80	74.00	26.20	PK+	H
2	3766.500	56.04	-13.45	42.59	74.00	31.41	PK+	H
3	4981.500	58.15	-11.17	46.98	74.00	27.02	PK+	H
4	10791.000	49.17	-4.93	44.24	74.00	29.76	PK+	H
5	16737.000	47.34	-1.03	46.31	74.00	27.69	PK+	H
6	17692.500	45.95	0.22	46.17	74.00	27.83	PK+	H

Mode:	11B 2462
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3□/52%/101Kpa



**Critical\_Freqs**


No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2198.000	57.29	-9.23	48.06	74.00	25.94	PK+	V
2	3309.000	58.38	-14.4	43.98	74.00	30.02	PK+	V
3	4980.000	58.22	-11.18	47.04	74.00	26.96	PK+	V
4	8992.500	54.38	-7.93	46.45	74.00	27.55	PK+	V
5	15018.000	48.00	-2.83	45.17	74.00	28.83	PK+	V
6	17704.500	46.15	0.08	46.23	74.00	27.77	PK+	V

No others harmonics emissions are higher than 20 dB below the limits of 47 CFR Part 15.247.

- Note:** (1) All Readings are Peak Value.  
 (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.  
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.  
 (4) Measuring frequencies from 1GHz to 25GHz.

Band Edge  
 The worst result as bellow:


Mode:	11B 2412
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3°C/52% /101Kpa



**Critical\_Freqs**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2387.870	30.53	22.68	53.21	74.00	20.79	PK+	H
2	2390.000	29.95	22.72	52.67	74.00	21.33	PK+	H

Mode:	11B 2412
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3□/52%/101Kpa




**Critical\_Freqs**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2389.170	32.90	22.7	55.60	74.00	18.40	PK+	V
2	2390.080	33.22	22.72	55.94	74.00	18.06	PK+	V

**Final\_Result**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.	Verdict
1	2389.170	27.90	22.7	50.60	53.90	3.30	AVG	V	PASS
2	2390.080	27.82	22.72	50.54	53.90	3.36	AVG	V	PASS

Mode:	11B 2462
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3□/52%/101Kpa




**Critical\_Freqs**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2483.500	31.58	23.15	54.73	74.00	19.27	PK+	H
2	2484.160	33.86	23.15	57.01	74.00	16.99	PK+	H

**Final\_Result**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.	Verdict
1	2483.500	25.58	23.15	48.73	53.90	5.17	AVG	H	PASS
2	2483.612	26.61	23.15	49.76	53.90	4.14	AVG	H	PASS

Mode:	11B 2462
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3□/52%/101Kpa



**Critical\_Freqs**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2483.500	31.74	23.15	54.89	74.00	19.11	PK+	V
2	2485.120	32.23	23.14	55.37	74.00	18.63	PK+	V

**Final\_Result**

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.	Verdict
1	2483.500	24.74	23.15	47.89	53.90	6.01	AVG	V	PASS
2	2485.120	25.23	23.14	48.37	53.90	5.53	AVG	V	PASS

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



## 9. ANTENNA REQUIREMENT

### **REQUIREMENT**

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### **DESCRIPTION**

The EUT's antenna, permanent attached antenna, used Internal antenna and integrated on PCB, The antenna's gain is 4.32dBi and meets the requirement.

## 10. AC POWER LINE CONDUCTED EMISSION

### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.


### TEST SETUP



### TEST ENVIRONMENT


Temperature	26°C	Relative Humidity	54%
Atmosphere Pressure	101kPa		

**TEST RESULTS**



Phase: N	Mode: 802.11b 2412MHz
----------	-----------------------

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1905	19.32	9.88	29.20	64.01	-34.81	QP
2	0.1905	-0.27	9.88	9.61	54.01	-44.40	AVG
3	0.2354	17.53	9.86	27.39	62.26	-34.87	QP
4	0.2354	0.90	9.86	10.76	52.26	-41.50	AVG
5	5.5904	23.68	10.07	33.75	60.00	-26.25	QP
6	5.5904	1.83	10.07	11.90	50.00	-38.10	AVG
7	7.8270	20.42	10.54	30.96	60.00	-29.04	QP
8	7.8270	-1.38	10.54	9.16	50.00	-40.84	AVG
9	11.7285	17.14	11.59	28.73	60.00	-31.27	QP
10	11.7285	-2.16	11.59	9.43	50.00	-40.57	AVG
11	20.1930	12.74	11.82	24.56	60.00	-35.44	QP
12	20.1930	-3.97	11.82	7.85	50.00	-42.15	AVG



Phase: L1	Mode: 802.11b 2412MHz
-----------	-----------------------

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1770	20.08	9.81	29.89	64.63	-34.74	QP
2	0.1770	0.59	9.81	10.40	54.63	-44.23	AVG
3	0.2175	17.35	9.81	27.16	62.91	-35.75	QP
4	0.2175	-1.25	9.81	8.56	52.91	-44.35	AVG
5	4.6860	14.58	9.81	24.39	56.00	-31.61	QP
6	4.6860	-2.56	9.81	7.25	46.00	-38.75	AVG
7	7.2330	21.70	9.77	31.47	60.00	-28.53	QP
8	7.2330	-0.59	9.77	9.18	50.00	-40.82	AVG
9	12.4035	22.40	9.89	32.29	60.00	-27.71	QP
10	12.4035	2.98	9.89	12.87	50.00	-37.13	AVG
11	28.1760	13.47	10.00	23.47	60.00	-36.53	QP
12	28.1760	-4.61	10.00	5.39	50.00	-44.61	AVG

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).


4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.


## 11. TEST DATA - Appendix C

### Duty Cycle



Condition	Mode	Frequency (MHz)	Antenna	On Time (ms)	Period (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	Ant1	8.19	10.7	76.54	1.16	0.12
NVNT	b	2437	Ant1	8.19	10.69	76.61	1.16	0.12
NVNT	b	2462	Ant1	8.19	10.69	76.61	1.16	0.12
NVNT	g	2412	Ant1	1.36	3.86	35.23	4.53	0.74
NVNT	g	2437	Ant1	1.36	3.86	35.23	4.53	0.73
NVNT	g	2462	Ant1	1.36	3.86	35.23	4.53	0.73
NVNT	n20	2412	Ant1	1.27	3.77	33.69	4.72	0.79
NVNT	n20	2437	Ant1	1.27	3.77	33.69	4.72	0.79
NVNT	n20	2462	Ant1	1.27	3.77	33.69	4.72	0.79





Date: 31.MAY.2024 12:53:08






Date: 31.MAY.2024 12:55:51












## Maximum Conducted Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	8.44	30	Pass
NVNT	b	2437	Ant1	8.42	30	Pass
NVNT	b	2462	Ant1	8.39	30	Pass
NVNT	g	2412	Ant1	7.53	30	Pass
NVNT	g	2437	Ant1	7.86	30	Pass
NVNT	g	2462	Ant1	7.31	30	Pass
NVNT	n20	2412	Ant1	5.07	30	Pass
NVNT	n20	2437	Ant1	6.38	30	Pass
NVNT	n20	2462	Ant1	5.86	30	Pass

**-6dB Bandwidth**



Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	10.1	0.5	Pass
NVNT	b	2437	Ant1	10.1	0.5	Pass
NVNT	b	2462	Ant1	10.08	0.5	Pass
NVNT	g	2412	Ant1	16.29	0.5	Pass
NVNT	g	2437	Ant1	16.28	0.5	Pass
NVNT	g	2462	Ant1	16.3	0.5	Pass
NVNT	n20	2412	Ant1	17.52	0.5	Pass
NVNT	n20	2437	Ant1	16.88	0.5	Pass
NVNT	n20	2462	Ant1	16.92	0.5	Pass







Date: 31.MAY.2024 12:54:22




Date: 31.MAY.2024 12:57:08



















## Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	b	2412	Ant1	14.897
NVNT	b	2437	Ant1	14.903
NVNT	b	2462	Ant1	14.903
NVNT	g	2412	Ant1	16.33
NVNT	g	2437	Ant1	16.342
NVNT	g	2462	Ant1	16.336
NVNT	n20	2412	Ant1	17.524
NVNT	n20	2437	Ant1	17.512
NVNT	n20	2462	Ant1	17.524

















## Maximum Power Spectral Density Level



Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	Ant1	-18.67	8	Pass
NVNT	b	2437	Ant1	-19.1	8	Pass
NVNT	b	2462	Ant1	-19.56	8	Pass
NVNT	g	2412	Ant1	-28.09	8	Pass
NVNT	g	2437	Ant1	-27.15	8	Pass
NVNT	g	2462	Ant1	-27.56	8	Pass
NVNT	n20	2412	Ant1	-30.08	8	Pass
NVNT	n20	2437	Ant1	-26.24	8	Pass
NVNT	n20	2462	Ant1	-29.27	8	Pass
















## Band Edge



Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-48.08	-20	Pass
NVNT	b	2462	Ant1	-49.9	-20	Pass
NVNT	g	2412	Ant1	-42.56	-20	Pass
NVNT	g	2462	Ant1	-42.09	-20	Pass
NVNT	n20	2412	Ant1	-40.71	-20	Pass
NVNT	n20	2462	Ant1	-42.57	-20	Pass





Date: 31.MAY.2024 12:54:43







Date: 31.MAY.2024 12:54:46















Date: 31.MAY.2024 14:00:44




**Marker**

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.45824 GHz	-13.02 dBm		
M2		1	2.4835 GHz	-59.07 dBm		
M3		1	2.4988 GHz	-55.40 dBm		


Date: 31.MAY.2024 14:00:47

## Conducted RF Spurious Emission



Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-44.73	-20	Pass
NVNT	b	2437	Ant1	-44.18	-20	Pass
NVNT	b	2462	Ant1	-42.83	-20	Pass
NVNT	g	2412	Ant1	-37.96	-20	Pass
NVNT	g	2437	Ant1	-35.38	-20	Pass
NVNT	g	2462	Ant1	-35.92	-20	Pass
NVNT	n20	2412	Ant1	-35.45	-20	Pass
NVNT	n20	2437	Ant1	-35.68	-20	Pass
NVNT	n20	2462	Ant1	-35.49	-20	Pass





Date: 31.MAY.2024 12:54:53







Date: 31.MAY.2024 12:55:09



























## **APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION**

Please refer to the report : E04A24080413F00101.

## **APPENDIX: PHOTOGRAPHS OF THE EUT**

Please refer to the report : E04A24080413F00101.

**END OF REPORT**