



MPE ESTIMATION

FCC ID: 2BEXO-AQBEAM

1, Per FCC Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices, the limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

Mode	Frequency (MHz)	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
BLE	2480	3.8	3±1(4)	2.51	1.9	1.55	0.000774

$$Pd = \frac{Pout * G}{4\pi r^2}$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2402010680-E**, antenna gain=1.9dBi,

When the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.000774 mW/cm² which is < 1.0mW/cm², RF Exposure testing is not required.

-----The End-----