

Report No.: SUCR240800031403

Rev.: 01 1 of 12 Page:

TEST REPORT

Application No.: SUCR2408000314MO

Applicant: NETPRISMA INC.

Address of Applicant: 1301 6TH AVE, SEATTLE, WA, 98101-2304, UNITED STATES

Manufacturer: NETPRISMA INC.

Address of Manufacturer: 1301 6TH AVE, SEATTLE, WA, 98101-2304, UNITED STATES

EUT Description: 5G Sub-6 GHz M.2 Module

Model No.: FCUN69-WWD

Trade Mark: Vrileg

FCC ID: 2BEY3FCUN69T Standards: 47 CFR Part 2.1091

FCC KDB 447498 D01 v06

April 10, 2024 (for report SUCR240400008903) Date of Receipt:

September 27, 2024 (for report SUCR240800031403)

Date of Issue: September 27, 2024

Test Result: PASS*

In the configuration tested, the EUT complied with the standards specified above.

Prepared by : Nature Shen / Project

Nature Shen

Manager

Approved by : Cloud Peng /

Technical Manager

Cloud Peng

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Ferms-e-Documents.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



Report No.: SUCR240800031403

Rev.: 01 2 of 12 Page:

Version

Revision Record								
Version	Version Chapter Date Modifier Remai							
01		September 27, 2024		Original				

Remark:

This test report (Report No.: SUCR240800031403 issue on 2024/09/27) is based on the original test report (Report No.: SUCR240400008903 issue on 2024/07/12).

Review this report and original report, this report just changing the parts according to the declaration letter from client.

Therefore in this report all items do not need to recalculated and all test data in this report are based on the previous report with report number SUCR240400008903 issue on 2024/07/12.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



Report No.: SUCR240800031403

Rev.: 01 3 of 12 Page:

Contents

1	Ver	sion	2
		neral Information	
		Client Information Test Facility	
		General Description of EUT	
3	RF	Exposure Evaluation	8
	3.1	RF Exposure Compliance Requirement	8
	3.1.	.1 Limits	8
	3.1.	.2 Test Procedure	9
	3.1.	.3 EUT RF Exposure Evaluation	9
		4 Exposure calculations for multiple sources	

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



Report No.: SUCR240800031403

Rev.: 01 4 of 12 Page:

General Information

2.1 Client Information

Applicant:	NETPRISMA INC.
Address of Applicant:	1301 6TH AVE, SEATTLE, WA, 98101-2304, UNITED STATES
Manufacturer:	NETPRISMA INC.
Address of Manufacturer:	1301 6TH AVE, SEATTLE, WA, 98101-2304, UNITED STATES

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 6336.01)

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

• Innovation, Science and Economic Development Canada

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

• FCC -Designation Number: CN1312

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an

accredited testing laboratory. Designation Number: CN1312.

Test Firm Registration Number: 717327

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



Report No.: SUCR240800031403

Rev.: 01 5 of 12 Page:

2.3 General Description of EUT

EUT Description:	5G Sub-6 GHz M.2	2 Module											
Model No.:	FCUN69-WWD												
Trade Mark:	Vrileg												
Hardware Version:	R1.0												
Software Version:	FCUN69WWDBL0	CUN69WWDBL0302											
Power Supply:	3.7V	7V											
Antenna Type:	PIFA Antenna	FA Antenna											
Feature:	UL 2*2 MIMO:												
reature.	NR Band n38; NR	R Band n38; NR Band n41; NR Band n48; NR Band n77; NR Band n78 ass 2: LTE Band 41:LTE UL CA 41C: NR Band n41: NR Band n77: NR Band n78											
Power Class:	Class 2: LTE Band	ass 2: LTE Band 41;LTE UL CA_41C; NR Band n41; NR Band n77; NR Band n78											
	WCDMA Band II:	3.87dBi(NPANT001)	WCDMA Band IV:	3.91dBi(NPANT001)									
	WCDMA Band V:	3.32dBi(NPANT002)											
	LTE Band 2:	3.87dBi(NPANT001)	LTE Band 4:	3.91dBi(NPANT001)									
	LTE Band 5:	3.32dBi(NPANT002)	LTE Band 7:	3.16dBi(NPANT002)									
	LTE Band 12:	3.19dBi(NPANT004)	LTE Band 13:	3.28dBi(NPANT002)									
	LTE Band 14:	3.25dBi(NPANT002)	LTE Band 17:	3.19dBi(NPANT004)									
	LTE Band 25:	3.87dBi(NPANT001)	LTE Band 26:	3.32dBi(NPANT002)									
	LTE Band 30:	0.98dBi(NPANT003)	LTE Band 38:	3.07dBi(NPANT002)									
	LTE Band 41:	3.16dBi(NPANT002)	LTE Band 42:	2.35dBi(NPANT004)									
	LTE Band 43:	1.94dBi(NPANT004)	LTE Band 48:	1dBi(NPANT003)									
Antenna Gain:	LTE Band 66:	3.91dBi(NPANT001)	LTE Band 71:	3.07dBi(NPANT001)									
	LTE CA_2C:	3.87dBi(NPANT001)	LTE CA_5B:	3.32dBi(NPANT002)									
	LTE CA_7C:	3.16dBi(NPANT002)	LTE CA_38C:	3.07dBi(NPANT002)									
	LTE CA_41C:	3.16dBi(NPANT002)	LTE CA_42C:	2.35dBi(NPANT004)									
	LTE CA_43C:	1.94dBi(NPANT004)	LTE CA_48C:	1dBi(NPANT003)									
	LTE CA_66C:	3.91dBi(NPANT001)	LTE CA_66B:	3.91dBi(NPANT001)									
	NR Band n2:	3.87dBi(NPANT001)	NR Band n5:	3.32dBi(NPANT002)									
	NR Band n7:	3.16dBi(NPANT002)	NR Band n12:	3.19dBi(NPANT004)									
	NR Band n13:	3.28dBi(NPANT002)	NR Band n14:	3.25dBi(NPANT002)									
	NR Band n25:	3.87dBi(NPANT001)	NR Band n26:	3.32dBi(NPANT002)									
	NR Band n30:	0.98dBi(NPANT003)	NR Band n38:	3.07dBi(NPANT002)									

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. Wireless Laborator

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 t (86-512) 62992980



SUCR240800031403 Report No.:

Rev.: 01

		Page: 6	of 12
NR Band n41:	3.16dBi(NPANT002)	NR Band n48:	1dBi(NPANT003)
NR Band n66:	3.91dBi(NPANT001)	NR Band n71:	3.07dBi(NPANT001)
NR Band n77(3450)-3550): 2.35dBi(NPAN	T004)	
NR Band n77(3700)-3980): 1.94dBi(NPAN	T004)	
NR Band n78(3450)-3550): 2.35dBi(NPAN	T004)	
NR Band n78(3700)-3800): 1.94dBi(NPAN	T004)	
LTE UL CA:			
CA_2C, CA_5B, C	A_7C, CA_38C, CA_41	IC, CA_42C, CA_43	BC, CA_66B,
CA_66C, CA_48C;			
UL CA_2A-4A; UL	CA_2A-5A; UL CA_2A	-7A; UL CA_2A-12 <i>A</i>	\ ;
UL CA_2A-13A; UI	L CA_2A-30A; UL CA_2	2A-66A; UL CA_4A	-5A;
UL CA_4A-7A; UL	CA_4A-12A; UL CA_4	A-13A; UL CA_4A-3	80A;
UL CA_5A-7A; UL	CA_5A-30A; UL CA_5A	A-66A; UL CA_12A-	-30A;
UL CA_12A-66A; U ENDC:	JL CA_13A-66A; UL CA	A_14A-30A;	
DC_13A_n66A;DC	_5A_n2A;DC_14A_n2A	A;DC_30A_n2A;DC	_2A_n5A;
DC_30A_n5A;DC_	66A_n5A;DC_2A_n12A	A;DC_66A_n12A;D0	C_2A_n66A;
DC_5A_n66A;DC_	_12A_n66A;DC_14A_n6	66A;DC_30A_n66A	;DC_12A_n2A;
DC_66A_n2A;DC_	.71A_n2A;DC_12A_n41	1A;DC_71A_n66A;[DC_2A_n71A;
DC_66A_n71A;DC	=_66A_n25A;DC_25A_r	n41A;DC_12A_n78 <i>i</i>	A;DC_13A_n78A;
DC_25A_n78A;DC	_12A_n77A;DC_13A_r	n77A;DC_14A_n77	A;DC_26A_n78A;
DC_2A_n78A;DC_	26A_n41A;DC_2A_n41	1A;DC_7A_n5A;DC	_38A_n78A;
DC_7A_n71A;DC_	41A_n78A;DC_5A_n7A	A;DC_12A_n7A;DC	_66A_n7A;
	7A_n66A;DC_2A_n48 <i>A</i>		
DC_66A_n48A;DC	_4A_n78A;DC_20A_n7	77A;DC_5A_n78A;[DC_4A_n41A;
	_2A_n38A;DC_12A_n3		
DC_66A_n78A;DC	_12A_n25A;DC_25A_r	n77A;DC_2A_n77A;	;DC_71A_n78A;
DC_71A_n38A;DC	_13A_n7A;DC_5A_n41	1A;DC_66A_n41A;[DC_2A_n7A;
DC_7A_n2A;DC_3	0A_n77A;DC_41A_n77	7A;DC_7A_n78A;	
DC_71A_n41A;DC	_28A_n66A;DC_30A_r	n12A;DC_2A_n14A;	;DC_30A_n14A;
DC_66A_n14A;DC	_2A_n30A;DC_5A_n30	DA;DC_12A_n30A;	
DC_14A_n30A;DC	_66A_n30A;DC_71A_r	n7A;DC_7A_n12A;[DC_5A_n77A;

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. Wireless Laboratory

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 t (86-512) 62992980

DC_66A_n77A;DC_71A_n77A;DC_4A_n2A;DC_7A_n25A;DC_71A_n25A;



Report No.: SUCR240800031403

Rev.: 01 7 of 12 Page:

DC_5A_n25A;DC_26A_n25A;DC_4A_n7A;DC_13A_n25A;DC_7A_n77A; DC_48A_n5A; DC_48A_n66A; DC_48A_n25A; DC_48A_n71A; DC_48A_n12A; Note: The antenna gain are derived from the gain information report provided by the manufacturer.

Remark:

As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



Report No.: SUCR240800031403

Rev.: 01 8 of 12 Page:

3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	ectric field strength (V/m) Magnetic field strength (A/m) Power density (mW/cm2)			
	(A) Limits for Occup	oational/Controlled Expo	sures		
0.3-3.0	614	1.63	*(100)	6	
3.0-30	1842/f	4.89/f	*(900/f2)	6	
30-300	61.4	0.163	1.0	6	
300-1500	1	1	f/300	6	
1500-100,000	/	1	5	6	
(B) Limits for General P	opulation/Uncontrolled	Exposure		
0.3-1.34	614	1.63	*(100)	30	
1.34-30	824/f	2.19/f	*(180/f2)	30	
30-300	27.5	0.073	0.2	30	
300-1500	/	1	f/1500	30	
1500-100,000	/	1	1.0	30	

F=frequency in MHz

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4* Pi * R2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 t (86-512) 62992980

^{*=}Plane-wave equivalent power density



Report No.: SUCR240800031403

Rev.: 01 9 of 12 Page:

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

3.1.3 EUT RF Exposure Evaluation

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	MIMO Directional gain	Max Conducted Power (dBm)	EIRP(ERP) (dBm)	EIRP(ERP) Limit (dBm)	Power Density at R = 20 cm (mW/cm2)	Limit (mW/cm2)	Gain according to EIRP(ERP) (dBi)	Gain according to Pd (dBi)	Max Gain Allowed (dBi)	conclusion
WCDMA Band II	1852.4	3.87	NA	25.00	28.87	33.00	0.1534	1.0000	8.00	12.01	8.00	Pass
WCDMA Band IV	1712.4	3.91	NA	25.00	28.91	30.00	0.1548	1.0000	5.00	12.01	5.00	Pass
WCDMA Band V	826.4	3.32	NA	25.00	26.17	38.45	0.1351	0.5509	15.60	9.42	9.42	Pass
LTE Band 2/LTE CA_2C	1850.7	3.87	NA	25.00	28.87	33.00	0.1534	1.0000	8.00	12.01	8.00	Pass
LTE Band 4	1710.7	3.91	NA	25.00	28.91	30.00	0.1548	1.0000	5.00	12.01	5.00	Pass
LTE Band 5/LTE CA_5B	824.7	3.32	NA	25.00	26.17	38.45	0.1351	0.5498	15.60	9.41	9.41	Pass
LTE Band 7/LTE CA_7C	2502.5	3.16	NA	25.00	28.16	33.00	0.1302	1.0000	8.00	12.01	8.00	Pass
LTE Band 12	699.7	3.19	NA	25.00	26.04	34.77	0.1311	0.4665	11.92	8.70	8.70	Pass
LTE Band 13	779.5	3.28	NA	25.00	26.13	34.77	0.1339	0.5197	11.92	9.16	9.16	Pass
LTE Band 14	790.5	3.25	NA	25.00	26.10	34.77	0.1330	0.5270	11.92	9.23	9.23	Pass
LTE Band 17	706.5	3.19	NA	25.00	26.04	34.77	0.1311	0.4710	11.92	8.74	8.74	Pass
LTE Band 25	1850.7	3.87	NA	25.00	28.87	33.00	0.1534	1.0000	8.00	12.01	8.00	Pass
LTE Band 26(814-824)	814.7	3.32	NA	25.00	26.17	NA	0.1351	0.5431	NA	9.36	9.36	Pass
LTE Band 26(824-849)	824.7	3.32	NA	25.00	26.17	38.45	0.1351	0.5498	15.60	9.41	9.41	Pass
LTE Band 30	2307.5	0.98	NA	23.00	23.98	23.98	0.0497	1.0000	0.98	14.01	0.98	Pass
LTE Band 38/LTE CA_38C	2572.5	3.07	NA	25.00	28.07	33.00	0.1276	1.0000	8.00	12.01	8.00	Pass
LTE Band 41/LTE CA_41C	2498.5	3.16	NA	27.00	30.16	33.00	0.2064	1.0000	6.00	10.01	6.00	Pass
LTE Band 42(3450-3550) LTE CA_42C	3452.5	2.35	NA	22.00	24.35	30.00	0.0542	1.0000	8.00	15.01	8.00	Pass
LTE Band 43(3700-3800)LTE CA_43C	3702.5	1.94	NA	22.00	23.94	30.00	0.0493	1.0000	8.00	15.01	8.00	Pass
LTE Band 48/LTE CA_48C	3552.5	1.00	NA	22.00	23.00	23.00	0.0397	1.0000	1.00	15.01	1.00	Pass
LTE Band 66/LTE CA_66B/LTE CA_66C	1710.7	3.91	NA	25.00	28.91	30.00	0.1548	1.0000	5.00	12.01	5.00	Pass
LTE Band 71	665.5	3.07	NA	25.00	25.92	34.77	0.1276	0.4437	11.92	8.48	8.48	Pass

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



Report No.: SUCR240800031403

Rev.: 01 10 of 12 Page:

Operating Band Frequency (MHz) Antenna Gain (dBi) MIMO Directional gain NR Band n2 1852.5 3.87 NA NR Band n5 826.5 3.32 NA NR Band n7 2502.5 3.16 NA NR Band n12 701.5 3.19 NA NR Band n13 779.5 3.28 NA NR Band n14 790.5 3.25 NA NR Band n25 1852.5 3.87 NA NR Band n26(814-824) 816.5 3.32 NA NR Band n26(824-849) 826.5 3.32 NA NR Band n38 (MIMO) 2507.5 0.98 NA NR Band n38 (MIMO) 2575.0 3.07 NA NR Band n41 (MIMO) 2501.0 3.16 3.16 NR Band n44 (MIMO) 2501.0 3.16 3.16 NR Band n48 (MIMO) 3555.0 1.00 NA NR Band n66 1712.5 3.91 NA NR Band n77 (3450-3550) 3.07 NA NR B						ge.			
NR Band n5 826.5 3.32 NA NR Band n7 2502.5 3.16 NA NR Band n12 701.5 3.19 NA NR Band n13 779.5 3.28 NA NR Band n14 790.5 3.25 NA NR Band n15 1852.5 3.87 NA NR Band n25 1852.5 3.87 NA NR Band n26 814-824) 816.5 3.32 NA NR Band n26 814-824) 816.5 3.32 NA NR Band n26 824-849) 826.5 3.32 NA NR Band n36 2307.5 0.98 NA NR Band n38 2575.0 3.07 NA NR Band n41 2501.0 3.16 3.16 NR Band n41 2501.0 3.16 3.16 NR Band n41 3555.0 1.00 NA NR Band n48 3555.0 1.00 NA NR Band n66 1712.5 3.91 NA NR Band n66 1712.5 3.91 NA NR Band n71 (365.5 3.07 NA NR Band n77 (3450-3550) 3455.0 2.35 NA NR Band n77 (3450-3550) NA NR Band n77 (3450-3550) NA NR Band n77 (3700-3980) MIMO) NR Band n77 (3700-3980) NR Band n77 (3700-3980) NR Band n78 (3450-3550) NA NR Band n78 (3450-3550) NA NR Band n78 (3450-3550) NA NR Band n78 (3450-3850) NA	Max Conducted Power (dBm)	EIRP(ERP) (dBm)	EIRP(ERP) Limit (dBm)	Power Density at R = 20 cm (mW/cm2)	Limit (mW/cm2)	Gain according to EIRP(ERP) (dBi)	Gain according to Pd (dBi)	Max Gain Allowed (dBi)	conclusion
NR Band n7 2502.5 3.16 NA NR Band n12 701.5 3.19 NA NR Band n13 779.5 3.28 NA NR Band n14 790.5 3.25 NA NR Band n25 1852.5 3.87 NA NR Band n25 1852.5 3.87 NA NR Band n26(814-824) 816.5 3.32 NA NR Band n26(824-849) 826.5 3.32 NA NR Band n30 2307.5 0.98 NA NR Band n30 2575.0 3.07 NA NR Band n31 2507.0 3.07 NA NR Band n38(MIMO) 2575.0 3.07 NA NR Band n38(MIMO) 2575.0 3.07 NA NR Band n41 2501.0 3.16 NA NR Band n41 2501.0 3.16 NA NR Band n41 2501.0 3.16 NA NR Band n41 6501.0 3.16 NA NR Band n41 665.5 1.00 NA NR Band n46 1712.5 3.91 NA NR Band n66 1712.5 3.91 NA NR Band n71 665.5 3.07 NA NR Band n77 (3450-3550) (MIMO) NR Band n77 (3450-3550) (MIMO) NR Band n77 (3700-3980)(MIMO) NR Band n77 (3700-3980)(MIMO) NR Band n78 (3450-3550) (MIMO) NR Band n78 (3450-3550)(MIMO) NR Band n78 (3500-3800)(MIMO)	25.00	25.00	33.00	0.1534	1.0000	8.00	12.01	8.00	Pass
NR Band n12 701.5 3.19 NA NR Band n13 779.5 3.28 NA NR Band n14 790.5 3.28 NA NR Band n14 790.5 3.25 NA NR Band n25 1852.5 3.87 NA NR Band n26(814-824) 816.5 3.32 NA NR Band n26(824-849) 826.5 3.32 NA NR Band n26(824-849) 826.5 3.32 NA NR Band n30 2307.5 0.98 NA NR Band n30 2307.5 0.98 NA NR Band n31 2575.0 3.07 NA NR Band n34 2575.0 3.07 NA NR Band n34 2501.0 3.16 NA NR Band n41 2501.0 3.16 NA NR Band n41 2501.0 3.16 NA NR Band n48 3555.0 1.00 NA NR Band n48 3555.0 1.00 NA NR Band n66 1712.5 3.91 NA NR Band n77 (3450-3550) MNA NR Band n77 (3450-3550) MNA NR Band n77 (3700-3980)(MIMO) NR Band n77 (3700-3980)(MIMO) NR Band n78 (3450-3550) 1.94 NA NR Band n77 (3700-3980)(MIMO) NR Band n78 (3450-3550) MNA NR Band n78 (3450-3550) MNA NR Band n78 (3450-3550) MNA NR Band n78 (3450-3550)(MIMO) NR Band n78 (3700-3800)(MIMO) NR Band n78 (3700-	25.00	26.17	38.45	0.1351	0.5510	15.60	9.42	9.42	Pass
NR Band n13 779.5 3.28 NA NR Band n14 790.5 3.25 NA NR Band n14 790.5 3.25 NA NR Band n25 1852.5 3.87 NA NR Band n26(814-824) 816.5 3.32 NA NR Band n26(824-849) 826.5 3.32 NA NR Band n30 2307.5 0.98 NA NR Band n38 2575.0 3.07 NA NR Band n41 2501.0 3.16 NA NR Band n44 (MIMO) 2501.0 3.16 NA NR Band n41 2501.0 3.16 3.16 NR Band n48 3555.0 1.00 NA NR Band n48 3555.0 1.00 NA NR Band n66 1712.5 3.91 NA NR Band n66 1712.5 3.91 NA NR Band n77 (3450-3550) NR Band n77 (3450-3550) (MIMO) NR Band n77 (3700-3980) MIMO) NR Band n77 (3700-3980) MIMO) NR Band n78 (3450-3550) NA NR Band n78 (3450-3550) NA NR Band n78 (3450-3550) (MIMO) NR Band n78 (3450-360) (MIMO)	25.00	25.00	33.00	0.1302	1.0000	8.00	12.01	8.00	Pass
NR Band n14 790.5 3.25 NA NR Band n25 1852.5 3.87 NA NR Band n26 (814-824) 816.5 3.32 NA NR Band n26 (824-849) 826.5 3.32 NA NR Band n36 (824-849) 826.5 3.32 NA NR Band n36 2307.5 0.98 NA NR Band n38 2575.0 3.07 NA NR Band n38 (MIMO) 2575.0 3.07 3.07 NR Band n38 (MIMO) 2501.0 3.16 NA NR Band n41 2501.0 3.16 NA NR Band n41 2501.0 3.16 NA NR Band n44 (MIMO) 3555.0 1.00 NA NR Band n48 3555.0 1.00 NA NR Band n66 1712.5 3.91 NA NR Band n66 1712.5 3.91 NA NR Band n77 (3450-3550) NA NR Band n77 (3450-3550) NA NR Band n77 (3700-3980) MIMO) NR Band n77 (3700-3980) MIMO) NR Band n77 (3700-3980) MIMO) NR Band n78 (3450-3550) NA NR Band n78 (3450-3560) NA NR Band n78 (3450-3560) NA NR Band n78 (3450-3800) NA NR Band n78 (3700-3800) NA	25.00	26.04	34.77	0.1311	0.4677	11.92	8.71	8.71	Pass
NR Band n25 1852.5 3.87 NA NR Band n26(814-824) 816.5 3.32 NA NR Band n26(824-849) 826.5 3.32 NA NR Band n36(824-849) 826.5 0.98 NA NR Band n30 2307.5 0.98 NA NR Band n30 2575.0 3.07 NA NR Band n38 2575.0 3.07 NA NR Band n38(MIMO) 2575.0 3.07 NA NR Band n41 2501.0 3.16 NA NR Band n41 2501.0 3.16 NA NR Band n41(MIMO) 2501.0 1.00 NA NR Band n48(MIMO) 3555.0 1.00 NA NR Band n48(MIMO) 3555.0 1.00 1.00 NR Band n66 1712.5 3.91 NA NR Band n71 665.5 3.07 NA NR Band n77 (3450-3550) 3455.0 2.35 NA NR Band n77 (3700-3980)(MIMO) NR Band n77 (3700-3980)(MIMO) NR Band n78 (3450-3550) 1.94 NA NR Band n78 (3450-3550) NA NR Band n78 (3450-3550)(MIMO) NR Band n78 (3450-3560)(MIMO) NR Band n78 (3450-3560)(MIMO) NR Band n78 (3450-3560)(MIMO) NR Band n78 (3700-3800)(MIMO) Bluetooth 2402.0 5.00 NA	25.00	26.13	34.77	0.1339	0.5197	11.92	9.16	9.16	Pass
NR Band n26(814-824) 816.5 3.32 NA NR Band n26(824-849) 826.5 3.32 NA NR Band n30 2307.5 0.98 NA NR Band n30 2307.5 0.98 NA NR Band n38 2575.0 3.07 NA NR Band n38 2575.0 3.07 3.07 NR Band n38 2575.0 3.07 3.07 NR Band n38 2575.0 3.07 3.07 NR Band n41 2501.0 3.16 NA NR Band n48 3555.0 1.00 NA NR Band n48 3555.0 1.00 1.00 NR Band n48 3555.0 3.07 NA NR Band n66 1712.5 3.91 NA NR Band n71 665.5 3.07 NA NR Band n77 3455.0 2.35 NA NR Band n77 3455.0 2.35 2.35 NR Band n77 3705.0 1.94 NA NR Band n77 3700.3980)(MIMO) NR Band n78 3455.0 2.35 NA NR Band n78 3455.0 2.35 2.35 NR Band n78 3705.0 1.94 NA NR Band n78 3705.0 1.94 1.94 NR Band n78 3705.0	25.00	26.10	34.77	0.1330	0.5270	11.92	9.23	9.23	Pass
NR Band n26(824-849) 826.5 3.32 NA NR Band n30 2307.5 0.98 NA NR Band n38 2575.0 3.07 NA NR Band n38(MIMO) 2575.0 3.07 NA NR Band n38(MIMO) 2575.0 3.07 3.07 NR Band n41 2501.0 3.16 NA NR Band n41(MIMO) 2501.0 3.16 3.16 NR Band n48 3555.0 1.00 NA NR Band n66 1712.5 3.91 NA NR Band n71 665.5 3.07 NA NR Band n77 3455.0 2.35 NA (3450-3550)(MIMO) 3455.0 2.35 2.35 NR Band n77 (3700-3980)(MIMO) 3705.0 1.94 NA NR Band n78 (3450-3550)(MIMO) 3455.0 2.35 NA NR Band n78 (3450-3550)(MIMO) 3455.0 2.35 NA NR Band n78 (3450-3550)(MIMO) 3455.0 2.35 NA NR Band n78	25.00	25.00	33.00	0.1534	1.0000	8.00	12.01	8.00	Pass
NR Band n30 2307.5 0.98 NA NR Band n38 2575.0 3.07 NA NR Band n38 2575.0 3.07 3.07 NR Band n38 2575.0 3.07 3.07 NR Band n38 2575.0 3.07 3.07 NR Band n40 2501.0 3.16 NA NR Band n41 2501.0 3.16 3.16 NR Band n48 3555.0 1.00 NA NR Band n48 3555.0 1.00 1.00 NR Band n66 1712.5 3.91 NA NR Band n71 666.5 3.07 NA NR Band n77 (3450-3550) NR Band n77 (3450-3550) NR Band n77 (3700-3980) NR Band n77 (3700-3980) 3705.0 1.94 NR Band n78 (3450-3550) NA NR Band n78 (3450-3800) NA NR Band n78 (3450-3800) NA NR Band n78 (3700-3800) NA	25.00	26.17	NA	0.1351	0.5443	NA	9.37	9.37	Pass
NR Band n38 2575.0 3.07 NA NR Band n38(MIMO) 2575.0 3.07 3.07 NR Band n38(MIMO) 2501.0 3.16 NA NR Band n41 2501.0 3.16 3.16 NR Band n48 3555.0 1.00 NA NR Band n48(MIMO) 3555.0 1.00 1.00 NR Band n66 1712.5 3.91 NA NR Band n71 665.5 3.07 NA NR Band n71 665.5 2.35 NA NR Band n77 (3450-3550) 3455.0 2.35 NA NR Band n77 (3450-3550) 1.94 NA NR Band n77 (3700-3980) 3705.0 1.94 NA NR Band n77 (3700-3980) 3455.0 2.35 NA NR Band n77 (3700-3980) MIMO) NR Band n77 (3700-3980) MIMO) NR Band n78 (3450-3550) 1.94 NA NR Band n78 (3450-3550) NA NR Band n78 (3450-3550) 1.94 NA NR Band n78 (3450-3550) NA NR Band n78 (3450-3550) 1.94 NA NR Band n78 (3700-3800) MIMO) NR Band n78 (3700-3800) NA	25.00	26.17	38.45	0.1351	0.5510	15.60	9.42	9.42	Pass
NR Band n38(MIMO) 2575.0 3.07 3.07 NR Band n41 2501.0 3.16 NA NR Band n41 2501.0 3.16 NA NR Band n41 3555.0 1.00 NA NR Band n48 3555.0 1.00 1.00 NR Band n66 1712.5 3.91 NA NR Band n71 665.5 3.07 NA NR Band n77 (3450-3550) 3455.0 2.35 NA (3450-3550) 3455.0 2.35 2.35 NA NR Band n77 (3700-3980) 3705.0 1.94 NA NR Band n77 (3700-3980) 3705.0 1.94 1.94 1.94 NR Band n78 (3450-3550) 3455.0 2.35 NA NR Band n78 (3450-3550) 3455.0 2.35 NA NR Band n78 (3450-3550) 3455.0 2.35 NA NR Band n78 (3450-3550) 3455.0 2.35 2.35 NA NR Band n78 (3450-3550) 3455.0 2.35 2.35 NA NR Band n78 (3700-3800) 3705.0 1.94 NA NR Band n78 (3700-3800) 3705.0 1.94 NA NA NR Band n78 (3700-3800) 3705.0 1.94 1.9	23.00	23.98	23.98	0.0497	1.0000	0.98	14.01	0.98	Pass
NR Band n41	25.00	28.07	33.00	0.1276	1.0000	8.00	12.01	8.00	Pass
NR Band n41(MIMO) 2501.0 3.16 3.16 NR Band n48 3555.0 1.00 NA NR Band n48(MIMO) 3555.0 1.00 1.00 NR Band n66 1712.5 3.91 NA NR Band n71 665.5 3.07 NA NR Band n77 (3450-3550) NR Band n77 (3450-3550) NR Band n77 (3450-3550) NR Band n77 (3700-3980) NR Band n77 (3700-3980) NR Band n78 (3450-3550) NR Band n78 (3450-3650) NR Band n78 (3450-3650) NR Band n78 (3450-360)	25.00	28.07	33.00	0.1276	1.0000	8.00	12.01	8.00	Pass
NR Band n48 3555.0 1.00 NA NR Band n48(MIMO) 3555.0 1.00 1.00 NR Band n66 1712.5 3.91 NA NR Band n71 665.5 3.07 NA NR Band n77 (3450-3550) 455.0 2.35 NA (3450-3550) NR Band n77 (3450-3550) 1.94 NA NR Band n77 (3700-3980) 3705.0 1.94 NA NR Band n77 (3700-3980)(MIMO) NR Band n77 (3700-3980)(MIMO) NR Band n78 (3450-3550) 455.0 2.35 NA NR Band n78 (3450-3550) NA NR Band n78 (3450-3550) NA NR Band n78 (3450-3550) NA NR Band n78 (3700-3800) 1.94 NA NR Band n78 (3700-3800) 1.94 NA NR Band n78 (3700-3800) 1.94 NA NR Band n78 (3700-3800)(MIMO) SIBUETOTH NA N	27.50	30.66	33.00	0.2316	1.0000	5.50	9.51	5.50	Pass
NR Band n48(MIMO) 3555.0 1.00 1.00 NR Band n66 1712.5 3.91 NA NR Band n71 665.5 3.07 NA NR Band n77 3455.0 2.35 NA NR Band n77 3455.0 2.35 2.35 NR Band n77 3455.0 2.35 2.35 NR Band n77 3455.0 2.35 2.35 NR Band n77 3705.0 1.94 NA NR Band n77 3705.0 1.94 1.94 NR Band n78 3455.0 2.35 NA NR Band n78 3455.0 2.35 2.35 NR Band n78 3455.0 2.35 2.35 NR Band n78 3455.0 2.35 2.35 NR Band n78 3705.0 1.94 NA NR Band n78 3705.0 1.94 1.94 NR Band n78 3705.0 1.94	27.50	30.66	33.00	0.2316	1.0000	5.50	9.51	5.50	Pass
NR Band n66 1712.5 3.91 NA NR Band n71 665.5 3.07 NA NR Band n77 3455.0 2.35 NA (3450-3550) MIMO) NR Band n77 3455.0 2.35 2.35 NR Band n77 3705.0 1.94 NA NR Band n77 3705.0 1.94 1.94 NR Band n78 (3450-3550) MIMO) NR Band n78 (3450-3550) 1.94 NA NR Band n78 (3700-3800) MIMO) Bluetooth 2402.0 5.00 NA	22.00	23.00	23.00	0.0397	1.0000	1.00	15.01	1.00	Pass
NR Band n71 665.5 3.07 NA NR Band n77 3455.0 2.35 NA NR Band n77 3455.0 2.35 NA NR Band n77 3455.0 2.35 2.35 NR Band n77 3705.0 1.94 NA NR Band n77 3705.0 1.94 1.94 NR Band n78 3455.0 2.35 NA NR Band n78 3705.0 1.94 1.94 NR BAND NA	22.00	23.00	23.00	0.0397	1.0000	1.00	15.01	1.00	Pass
NR Band n77 (3450-3550) NR Band n77 (3450-3550) NR Band n77 (3450-3550)(MIMO) NR Band n77 (3700-3980) NR Band n77 (3700-3980)(MIMO) NR Band n78 (3450-3550) NR Band n78 (3450-3550) NR Band n78 (3450-3550) NR Band n78 (3450-3550)(MIMO) NR Band n78 (3450-3550)(MIMO) NR Band n78 (3450-3550)(MIMO) NR Band n78 (3700-3800) NR Band n78 (3700-3800)(MIMO)	25.00	28.91	30.00	0.1548	1.0000	5.00	12.01	5.00	Pass
(3450-3550) 3455.0 2.35 NA NR Band n77 (3450-3550)(MIMO) NR Band n77 (3700-3980) 3705.0 1.94 NA NR Band n77 (3700-3980)(MIMO) NR Band n78 (3450-3550) 3455.0 2.35 NA (3450-3550) 3455.0 2.35 NA NR Band n78 (3450-3550)(MIMO) NR Band n78 (3700-3800) 3705.0 1.94 NA NR Band n78 (3700-3800)(MIMO)	25.00	25.92	34.77	0.1276	0.4437	11.92	8.48	8.48	Pass
(3450-3550)(MIMO) 3435.0 2.35 2.35 NR Band n77 (3700-3980) 3705.0 1.94 NA (3700-3980) MR Band n78 (3450-3550) NR Band n78 (3450-3550) Shadow 1.94 NA (3450-3550) NR Band n78 (3450-3550) NR Band n78 (3700-3800) MR Band n78 (3700-3800)(MIMO) NR Band n78 (3700-3800)(MIMO) NR Band n78 (3700-3800)(MIMO) Shuetooth 2402.0 5.00 NA WLANZ-4GHz 2412.0 5.00 NA	27.50	29.85	30.00	0.1922	1.0000	2.50	9.51	2.50	Pass
(3700-3980) 3705.0 1.94 NA NR Band n77 (3700-3980)(MIMO) 3705.0 1.94 1.94 NR Band n78 (3450-3550) 2.35 NA NR Band n78 (3450-3550)(MIMO) 3455.0 2.35 2.35 NR Band n78 (3700-3800) 3705.0 1.94 NA NR Band n78 (3700-3800)(MIMO) 1.94 1.94 NR Band n78 (3700-3800)(MIMO) 1.94 1.94 Bluetooth 2402.0 5.00 NA WLAN2.4GHz 2412.0 5.00 NA	27.50	29.85	30.00	0.1922	1.0000	2.50	9.51	2.50	Pass
(3700-3980)(MIMO) 3705.0 1.94 1.94 NR Band n78 (3450-3550) 3455.0 2.35 NA NR Band n78 (3450-3550)(MIMO) 3455.0 2.35 2.35 NR Band n78 (3700-3800) 3705.0 1.94 NA NR Band n78 (3700-3800)(MIMO) 3705.0 1.94 1.94 Bluetooth 2402.0 5.00 NA WLAN2.4GHz 2412.0 5.00 NA	27.50	29.44	30.00	0.1749	1.0000	2.50	9.51	2.50	Pass
(3450-3550) 3455.0 2.35 NA NR Band n78 (3450-3550)(MIMO) 3455.0 2.35 2.35 NR Band n78 (3700-3800) 3705.0 1.94 NA NR Band n78 (3700-3800)(MIMO) 3705.0 1.94 1.94 Bluetooth 2402.0 5.00 NA WLANZ-4GHz 2412.0 5.00 NA	27.50	29.44	30.00	0.1749	1.0000	2.50	9.51	2.50	Pass
(3450-3550)(MIMO) 3455.0 2.35 2.35 NR Band n78 (3700-3800) 3705.0 1.94 NA NR Band n78 (3700-3800)(MIMO) 3705.0 1.94 1.94 Bluetooth 2402.0 5.00 NA WLAN2.4GHz 2412.0 5.00 NA	27.50	29.85	30.00	0.1922	1.0000	2.50	9.51	2.50	Pass
(3700-3800) 3705.0 1.94 NA NR Band n78 (3700-3800)(MIMO) 1.94 1.94 Bluetooth 2402.0 5.00 NA WLAN2.4GHz 2412.0 5.00 NA	27.50	29.85	30.00	0.1922	1.0000	2.50	9.51	2.50	Pass
(3700-3800)(MIMO) 3705.0 1.94 1.94 Bluetooth 2402.0 5.00 NA WLAN2.4GHz 2412.0 5.00 NA	27.50	29.44	30.00	0.1749	1.0000	2.50	9.51	2.50	Pass
WLAN2.4GHz 2412.0 5.00 NA	27.50	29.44	30.00	0.1749	1.0000	2.50	9.51	2.50	Pass
	23.00	28.00	NA	0.1255	1.0000	NA	NA	NA	NA
	23.00	28.00	NA	0.1255	1.0000	NA	NA	NA	NA
WLAN5GHz 5180.0 5.00 NA	23.00	28.00	NA	0.1255	1.0000	NA	NA	NA	NA

Note:

- 1. This MPE analysis is applicable to any collocated transmitters with transmit power for WLAN is less than or equal to 28dBm and for Bluetooth is less than or equal to 28dBm.
- 2.A maximum antenna gain of 5dBi for WLAN/BT has been assumed for all collocated antennas.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions



Report No.: SUCR240800031403

Rev.: 01 11 of 12 Page:

$$\sum_{i=1}^{n} \frac{S_{E_{i}}(dutyfactor)}{MPE_{E_{i}}} < 1$$

Due to the EUT support NR ENDC and CA

Both LTE and NR/LTE band can transmit simultaneously, the formula of the calculated the MPE is: NOTE The corresponding MEs must be expressed in terms of power density in the above summation Therefore, the worst-case(DC 12A n30A situation is 0.2810+0.4970=0.7780, which is less than "1", this confirmed that the device comply with MPE limit.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 t (86-512) 62992980



SUCR240800031403 Report No.:

Rev.: 01 12 of 12 Page:

3.1.4 Exposure calculations for multiple sources

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^{n} \frac{S_i}{MPE_i} \le 1$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration			
1	WWAN + WiFi 2.4G + WiFi 5G + Bluetooth			

No.	Mode	Power Density (mW/cm²)	MPE Limit (mW/cm ²)	Result Ratio	Total Ratio	Limit	Result
	NR Band n71*	0.1276	0.4437	0.2876			
,	Bluetooth	0.1255	1.0000	0.1255	0.6641	1.0000	Pass
'	WiFi 2.4G	0.1255	1.0000	0.1255	0.0041	1.0000	Fd55
	WiFi 5G	0.1255	1.0000	0.1255			

Remark*: This WWAN Band was recalculated on worst Band.

Note: Considering the WWAN module collocation with the WLAN and Bluetooth transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 3 collocated transmitters is compliant.

---End of Report---

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Ferms-e-Documents.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 t (86-512) 62992980