

REM-EMIESS23G928ADK-01Av0

MPE test report

According to the standard: CFR 47 FCC PART 15

Equipment under test: NOVATERM TRAP

FCC ID: 2BEZD-NIGSV04

Company: BERKEM DEVELOPPEMENT

Distribution: Mr BOUTIN (Company: BERKEM DEVELOPPEMENT)

Number of pages: 5

Ed.	Date	Modified	Technical Verification and Quality Approval	
		Page(s)	Name and Function	Visa
0	4-Jul-24	Creation	M. DUMESNIL, Radio Laboratory Manager	

Duplication of this document is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above.

This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole manufactured

Information in italics are declared by the manufacturer/customer and are under his responsibility

products of the tested sample.



DESIGNATION OF PRODUCT: NOVATERM TRAP

Serial number (S/N): 22-2FF-223

Reference / model (P/N): TRAP-V0.4

Firmware version: 0.0.0

MANUFACTURER: EOLANE SAS

COMPANY CERTIFYING THE PRODUCT:

Company: BERKEM DEVELOPPEMENT

Address: 20, RUE JEAN DUVERT

33290

BLANQUEFORT

FRANCE

RESPONSIBLE: Mr BOUTIN

COMPANY SUBMITTING THE PRODUCT:

Company: ADKALIS SAS

Address: 20, RUE JEAN DUVERT

33290

BLANQUEFORT

FRANCE

Responsible: Mr BOUTIN

Person present during the tests: Mr KAMAL Ibrahim (Company: IKALOGIC) – (The first day)

DATES OF TEST: From 9-Jan-24 to 10-Jan-24

TESTING LOCATION: EMITECH ANGERS laboratory at JUIGNE SUR LOIRE (49) FRANCE

FCC Accredited under US-EU MRA Designation Number: FR0009

Test Firm Registration Number: 873677

TESTED BY: S. LOUIS VISA:

WRITTEN BY: S. LOUIS



CONTENTS

	TITLE	PAGE
1.	INTRODUCTION	4
2.	PRODUCT DESCRIPTION	4
3.	NORMATIVE REFERENCE	4
4.	RF EXPOSURE	5

REVISIONS HISTORY

Revision	Date	Modified	Modifications
		pages	
0	29-Jan-24	/	Creation



1. INTRODUCTION

This report presents the results of radio test carried out on the following radio equipment: **NOVATERM TRAP**, in accordance with normative reference.

The equipment under test integrates:

• SRD Monofrequency transceiver operational in the band (902MHz – 928MHz)

2. PRODUCT DESCRIPTION

Class: B

Utilization: Residential

Antenna type and gain: 0.01 dBi / integral antenna

Operating frequency range: From 902 MHz to 928 MHz

Frequency tested: 921MHz

Number of channels: 1

Channel spacing: Not concerned

Modulation: GFSK2

Power source: 3Vdc Lithium battery (CR2477X-HE / CR2477X-HO)

Power level, frequency range and channels characteristics are not user adjustable.

The details pictures of the product and the circuit boards are joined with this file.

3. NORMATIVE REFERENCE

The standards and testing methods related throughout this report are those listed below.

They are applied on the whole test report even though the extensions (version, date and amendment) are not repeated.

CFR 47 (2024) Radio Frequency Devices

ANSI C63.10 2013

Procedures for ComplianceTesting of Unlicensed Wireless Devices.

447498 D04 Interim General

RF Exposure Pocedures and Equipment Authorization Policies for Mobile and

RF Exposure Guidance v01 Portable Devices



4. RF EXPOSURE

In accordance with KDB 447498 D04 Interim General RF Exposure Guidance v01, paragraph 1.4.2:

Maximum Permissive Exemption according paragraph 1.1310(d)(2) of CFR 47 FCC Part 15

Maximum measured power = 90.1 dB μ V/m = 0.003334W at 921 MHz with P = (E×d)² / (30×Gp) with d = 10 m and Gp = 1.02

PSD= EIRP/ $(4*\pi*R^2)$

 \Rightarrow 3.334/(4* π *(20 cm)²)= 0.000663 mW/cm² (limit = 0.614 mW/cm²)

The equipment fulfils the requirements on power density for general population/uncontrolled exposure and therefore fulfils the requirements of 47 CFR §1.1310.