FCC §1.1307(b) & 2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (Minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	$*(180/f^2)$	30					
30-300	27.5	0.073	0.2	30					
300-1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \leq 1$$

Report No.: SZ1231225-78191E-RF

^{* =} Plane-wave equivalent power density

For worst case:

Mode	Frequency (MHz)	Antenna Gain#		Tune up conducted power#		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm ²)	(mW/cm ²)
BLE	2402-2480	2.45	1.76	1.0	1.26	20	0.0004	1
LTE Band 2(Only for FCC)	1850-1910	2.59	1.82	21.0	125.89	20	0.045	1
LTE Band 4	1710-1755	2.5	1.78	21.0	125.89	20	0.045	1
LTE Band 5	824-849	-1.72	0.67	21.5	141.25	20	0.019	0.549
LTE Band 12	699-716	-3.17	0.48	21.0	125.89	20	0.012	0.466

Report No.: SZ1231225-78191E-RF

Note: The tune-up power and antenna gain was declared by the applicant.

Simultaneous transmitting consideration (worst case):

The ratio=MPE_{BLE}/limit $_{BLE}$ + MPE_{LTE Band 2}/limit $_{LTE \ Band \ 2}$ = 0.0004/1+0.045 /1=0.045 < 1.0

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.