



## FCC RF EXPOSURE REPORT

<b>Applicant</b>	:	PERGOLUX LLC
<b>Address of Applicant</b>	:	407 Brookside Rd Waterbury, CT 06708, UNITED STATES
<b>Manufacturer</b>	:	Guangdong A-OK TechnologyGrand Development Co.,Ltd.
<b>Address of Manufacturer</b>	:	Hexing Road South Side Sanhe Economic Development Zone, Huiyang Huizhou, GuangdongPEOPLE'S REPUBLIC OF CHINA
<b>Equipment under Test</b>	:	RF Transmitter
<b>Model No.</b>	:	PX140-06C
<b>FCC ID</b>	:	2BEZT-PX140
<b>Test Standard(s)</b>	:	KDB447498 D01 General RF Exposure Guidance v06
<b>Report No.</b>	:	DDT-RE23102614-2E02
<b>Issue Date</b>	:	2024/11/06
<b>Issue By</b>	:	Guangdong Dongdian Testing Service Co., Ltd.
<b>Address of Laboratory</b>	:	Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

# REPORT

## Table of Contents

Test report declares.....	3
1. General Information .....	5
1.1. Description of equipment .....	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation for FCC .....	6

## Test Report Declare

<b>Applicant</b>	:	PERGOLUX LLC
<b>Address of Applicant</b>	:	407 Brookside Rd Waterbury, CT 06708, UNITED STATES
<b>Equipment under Test</b>	:	RF Transmitter
<b>Model No.</b>	:	PX140-06C
<b>Manufacturer</b>	:	Guangdong A-OK TechnologyGrand Development Co.,Ltd.
<b>Address of Manufacturer</b>	:	Hexing Road South Side Sanhe Economic Development Zone, Huiyang Huizhou, GuangdongPEOPLE'S REPUBLIC OF CHINA

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No.:</b>	DDT-RE23102614-2E02		
<b>Date of Receipt:</b>	2023/12/21	<b>Date of Test:</b>	2023/12/21 ~ 2024/11/06

**Prepared By:**



**Tiger Mo/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

**Note:** This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

## Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/11/06	

## 1. General Information

### 1.1. Description of equipment

EUT Name	:	RF Transmitter
Model Number	:	PX140-06C
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	DC 3V From Twist Button Battery
Operation Frequency	:	433.92MHz
Modulation	:	ASK
Antenna	:	PCB antenna, maximum PK gain: -13.51 dBi

### 1.2. Assess laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No.17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

### Manufacturing Tolerance

Mode	Antenna	Frequency [MHz]	Target (dBm)	Tolerance $\pm$ (dB)
ASK	Ant1	433.92	-12.7	1

PK Output Power=82.50dBuV/m@3m-95.2=-12.7dBm

Please refer to the test report "DDT-RE23102614-2E01"

### Estimation Result

Worse case is as below: [433.92 MHz, -11.7 dBm, (0.068 mW) output power]

$(0.068/5) \cdot [\sqrt{0.43392(\text{GHz})}] = 0.009 < 3.0 \text{ for 1-g SAR}$

Then SAR evaluation is not required.

### END OF REPORT