

CCSEM-TRF-001 Rev. 02 Sep 01, 2023 Report No.: KSCR240300045403

Page: 1 of 7

1 Cover Page

RF Exposure Evaluation Report

Application No.:KSCR2403000454ATFCC ID:2BF29GT573AG35E

Applicant: GOSUNCNWELINK TECHNOLOGY CO.,LTD.

Address of Applicant:

ROOM 606, TOWER A, GONGXIANG BUILDING, NO.78 NORTH KEYUAN ROAD, NANSHAN DISTRICT, SHENZHEN, CHINA

Manufacturer: Gosuncn Technology Group Co., Ltd.

Address of Manufacturer: 6F, No. 2819, KaiChuang Avenue, Science City, Huangpu District,

Guangzhou City, Guangdong Province, China

Factory: DBG TECHNOLOGY CO., LTD

Address of Factory:

No.5, Yongda Road, Xiang Shui River Industrial Area, Daya Bay,

Huizhou City, 516083 Guangdong, P. R. China

Equipment Under Test (EUT):

EUT Name: HARDWARE ASSY-TELEMATIC NODE

Model No.: GT573
Trade Mark: GOSUNCN

FCC Rules 47 CFR §2.1091

Standard(s): KDB 447498 D04 interim General RF Exposure Guidance v01

RSS-102 Issue 5 Amendment 1 (February 2, 2021)

Date of Receipt: 2024-03-18

Date of Test: 2024-03-28 to 2024-04-10

Date of Issue: 2024-04-12

Test Result: Pass*

* In the configuration tested, the EUT complied with the standards specified above.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240300045403

Page: 2 of 7

Revision Record						
Version	Description	Date	Remark			
00	Original	2024-04-12	/			

Authorized for issue by:		
Tested By	Maker_Qi /Project Engineer	
Approved By	Terry Hou /Reviewer	



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240300045403

Page: 3 of 7

2 Contents

			Page
1	Cov	er Page	1
2	Con	tents	3
3	Gen	eral Information	4
	3.1	General Description of E.U.T.	4
	3.2	Details of E.U.T.	4
	3.3	Test Location	5
	3.4	Test Facility	5
4	FCC	Radiofrequency radiation exposure limits	6
5	Mea	surement and Calculation	7
	5.1	Maximum transmit power	7
	5.2	MPE Calculation	7



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240300045403

Page: 4 of 7

3 General Information

3.1 General Description of E.U.T.

Power supply:	Voltage Range:9V~16V, Rating: 12V 0.6A
I OWEL SUDDIV.	I VOILAGE MAINGES V~ TO V. MAINING, TZ V O.OA

3.2 Details of E.U.T.

3**G**

	Operation Frequency:	Band 5:TX:824-849MHz RX:869-894MHz
	Modulation Type:	BPSK/QPSK/16QAM(16QAM uplink is not supported)
Antenna Type:		External Antenna
Antenna Gain:		-1dBi (Provided by the manufacturer)

4G

_4G	
	Band 5:Uplink:824-849MHz
Operation Frequency:	Band 7:Uplink:2500-2570MHz
	Band 38:Uplink:2570-2620MHz
Modulation Type:	QPSK/16QAM/64QAM(Downlink only)
Antenna Type:	External Antenna
	Band 5:-1dBi (Provided by the manufacturer)
Antenna Gain:	Band 7:1.5dBi (Provided by the manufacturer)
	Band 38:1.5dBi (Provided by the manufacturer)



CCSEM-TRF-001 Rev. 02 Sep 01, 2023 Report No.: KSCR240300045403

Page: 5 of 7

3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

- 1.SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc.) is provided by the applicant. (if applicable).
- 2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).
- 3. Sample source: sent by customer.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

A2LA

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

• FCC

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

• ISED

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 2324E

VCCI

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240300045403

Page: 6 of 7

4 FCC Radiofrequency radiation exposure limits

According to §1.1310, The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Frequency Electric field strength (MHz) (V/m)		Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)			
(i) Limits for Occupational/Controlled Exposure							
0.3-3.0	614	1.63	*(100)	≤6			
3.0-30	1842/f	4.89/f	*(900/f ²)	<6			
30-300	61.4	0.163	1.0	<6			
300-1,500			f/300	<6			
1,500- 100,000			5	<6			
(ii) Limits for General Population/Uncontrolled Exposure							
0.3-1.34	614	1.63	*(100)	<30			
1.34-30	824/f	2.19/f	*(180/f ²)	<30			
30-300	27.5	0.073	0.2	<30			
300-1,500			f/1500	<30			
1,500- 100,000			1.0	<30			



CCSEM-TRF-001 Rev. 02 Sep 01, 2023 Report No.: KSCR240300045403

Page: 7 of 7

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report FA950911

5.2 MPE Calculation

According to the formula S=P/4 π R², we can calculate S which is MPE. Note:

1) P (mW)

2) R = distance to the center of radiation of antenna (in centimeter)

For FCC

101100								
Test Mode	Max Average power (dBm)	Antenna Gain (dBi)	Max Tune up (dBm)	Max Tune up (W)	Operation Distance R(cm)	Power Density (mW/cm2)	Limit of Power Density S(mW/cm2) for FCC	Result
WCDMA B5	23.72	-1	24	0.25	20	0.050	0.55	Pass
LTE B5	23.07	-1	24	0.25	20	0.050	0.549	Pass
LTE B7	23.24	1.5	24	0.25	20	0.050	1	Pass
LTE B38	22.75	1.5	23	0.20	20	0.040	1	Pass

-- End of the Report--