

RF Exposure Compliance Requirement

Model no.: KJRH-120L2/BMWFNKDOU-E

1. Standard requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100000	--	--	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2. MPE Calculation Method

P= RF output Power (W)

G=EUT Antenna numeric gain (numeric)

d= Separation distance between radiator and human body (m)

The formula can be changed to

$P_d = (30 * P * G) / (377 * d^2)$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

3. Calculated Result and Limit

WIFI:

Output Power = 18.2 dBm(max.value declared by client), antenna gain =0.42 dBi

Frequency (MHz)	Antenna Gain (Numeric)	Output Power (dBm)	Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2412-2462	1.102	18.2	66.07	0.0145	1	Complies

MPE ratio:

$0.0145(\text{mW}/\text{cm}^2) / 1(\text{mW}/\text{cm}^2) = 0.0145$

Bluetooth:

Output Power = 7.65dBm(max.value declared by client), antenna gain = 0.42dBi

Frequency (MHz)	Antenna Gain (Numeric)	Output Power (dBm)	Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2402-2480	1.102	7.65	5.82	0.0013	1	Complies

MPE ratio:

$$0.0013(\text{mW}/\text{cm}^2)/1(\text{mW}/\text{cm}^2) = 0.0013$$

Sum of the MPE ratio for all simultaneously transmitting antennas:

$$0.0145+0.0013 = 0.0158 < 1$$

According to MPE test Exclusion condition in KDB 447498 (D01) General RF Exposure Guidance D01 v06, the MPE report is not required.

Test Location:

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

All tests were performed at:

Room102/104, No 203, KeZhu Road, Science City, GETDD Guangzhou, China