

TEST REPORT

Product : Floor Rising Screen Remote Control
Trade mark : AWOL VISION
Model/Type reference : FRSRC01
Serial Number : N/A
Report Number : EED32P80965801
FCC ID : 2BF6V-FRSRC01
Date of Issue : Jul. 25, 2024
Test Standards : 47 CFR Part 15 Subpart C
Test result : PASS

Prepared for:

Safe Space Scan Technology LLC
9169 W Atlantic Ave Suite 118, Delray Beach, FL 33446, USA.

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Frazer Li

Frazer Li

Reviewed by:

Tom Chen

Tom Chen

Approved by:

Aaron Ma

Aaron Ma

Date:

Jul. 25, 2024

Check No.: 7513280623



1 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203	ANSI C63.10:2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10:2013	N/A
Field Strength of the Fundamental Signal	47 CFR Part 15 Subpart C Section 15.231 (b)	ANSI C63.10:2013	PASS
Spurious Emissions	47 CFR Part 15 Subpart C Section 15.231 (b)/15.209	ANSI C63.10:2013	PASS
20dB Bandwidth	47 CFR Part 15 Subpart C Section 15.231 (c)	ANSI C63.10:2013	PASS
Dwell Time	47 CFR Part 15 Subpart C Section 15.231 (a)	ANSI C63.10:2013	PASS

Remark:

1.N/A:The product is powered by DC 3.0V Battery.

2.Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

2 Contents

1 TEST SUMMARY	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 TEST ENVIRONMENT AND MODE	5
3.4 DESCRIPTION OF SUPPORT UNITS	6
3.5 TEST LOCATION	6
3.6 DEVIATION FROM STANDARDS	6
3.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
3.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
3.9 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, $K=2$)	6
4 EQUIPMENT LIST	7
5 TEST RESULTS AND MEASUREMENT DATA	10
5.1 ANTENNA REQUIREMENT	10
5.2 SPURIOUS EMISSIONS	11
5.2.1 Duty Cycle	11
5.2.2 Spurious Emissions	13
5.3 20dB BANDWIDTH	18
5.4 DWELL TIME	19
APPENDIX 1 PHOTOGRAPHS OF TEST SETUP	21
APPENDIX 2 PHOTOGRAPHS OF EUT	23

3 General Information

3.1 Client Information

Applicant:	Safe Space Scan Technology LLC
Address of Applicant:	9169 W Atlantic Ave Suite 118, Delray Beach, FL 33446, USA.
Manufacturer:	Shenzhen WeProTalk Technology Co., Ltd.
Address of Manufacturer:	Yihua Financial Technology Building, Room 2501, 3939 Baishi Road, Binhai Community, Yuehai Street, Nanshan District, Shenzhen City.
Factory:	Shenzhen WeProTalk Technology Co., Ltd.
Address of Factory:	Yihua Financial Technology Building, Room 2501, 3939 Baishi Road, Binhai Community, Yuehai Street, Nanshan District, Shenzhen City.

3.2 General Description of EUT

Product Name:	Floor Rising Screen Remote Control		
Model No.(EUT):	FRSRC01		
Trade Mark:	AWOL VISION		
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location		
Power Supply:	Battery	DC 3.0V	
Frequency Range:	868.35MHz		
Modulation Type:	FSK		
Number of Channels:	1		
Antenna Type:	PCB antenna		
Test voltage:	DC 3.0V		
Sample Received Date:	Jun. 28, 2024		
Sample tested Date:	Jun. 28, 2024 to Jul. 12, 2024		

3.3 Test Environment and Mode

Operating Environment:	
Radiated Spurious Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
RF Conducted:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with modulation.

3.4 Description of Support Units

The EUT has been tested with associated equipment below.

1) support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
/	/	/	/	/

3.5 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.6 Deviation from Standards

None.

3.7 Abnormalities from Standard Conditions

None.

3.8 Other Information Requested by the Customer

None.

3.9 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-18GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.3dB (30MHz-1GHz)
		4.5dB (1GHz-12.75GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

4 Equipment List

RF test system					
Equipment	Manufacturer	Mode No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Spectrum Analyzer	R&S	FSV40	101200	07-25-2023	07-24-2024

3M Semi/full-anechoic Chamber(2#)					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	05-22-2022	05-21-2025
Receiver	R&S	ESC17	100938-003	09-22-2023	09-21-2024
Spectrum Analyzer	R&S	FSV40	101200	07-25-2023	07-24-2024
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04-16-2024	04-15-2025
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-618	05-18-2024	05-17-2025
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1869	04-16-2024	04-15-2025
Horn Antenna	A.H.SYSTEMS	SAS-574	374	07-02-2023	07-01-2026
Preamplifier	Agilent	11909A	12-1	03-22-2024	03-21-2025
Preamplifier	EMCI	EMC051845SE	980380	12-14-2023	12-13-2024
Preamplifier	CD	PAP-1840-60	6041.6042	06-19-2024	06-18-2025
Cable line	Fulai(7M)	SF106	5219/6A	---	---
Cable line	Fulai(6M)	SF106	5220/6A	---	---
Cable line	Fulai(3M)	SF106	5216/6A	---	---
Cable line	Fulai(3M)	SF106	5217/6A	---	---
Test software	Fara	EZ-EMC	EMEC-3A1-Pre	---	---

3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Fully Anechoic Chamber	TDK	FAC-3	---	01-09-2024	01-08-2027
Receiver	Keysight	N9038A	MY57290136	01-09-2024	01-08-2025
Spectrum Analyzer	Keysight	N9020B	MY57111112	01-29-2024	01-28-2025
Spectrum Analyzer	Keysight	N9030B	MY57140871	01-23-2024	01-22-2025
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-28-2024	04-27-2025
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-16-2024	04-15-2025
Horn Antenna	ETS-LINDGREN	3117	57407	07-03-2024	07-02-2025
Preamplifier	EMCI	EMC001330	980563	03-08-2024	03-07-2025
Preamplifier	Tonscend	TAP-011858	AP21B806112	07-25-2023	07-24-2024
Preamplifier	Tonscend	EMC051845SE	980380	12-14-2023	12-13-2024
Preamplifier	EMCI	EMC184055SE	980597	04-12-2024	04-11-2025
Communication test set	R&S	CMW500	102898	12-14-2023	12-13-2024
Temperature/Humidity Indicator	biaozhi	GM1360	EE1186631	04-07-2024	04-06-2025
RSE Automatic test software	JS Tonscend	JS36-RSE	V4.0.0.0	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	---	---
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	---	---
Cable line	Times	EMC104-NMNM-1000	SN160710	---	---

Cable line	Times	SFT205-NMSM- 3.00M	394813-0001	---	---
Cable line	Times	SFT205-NMNM- 1.50M	381964-0001	---	---
Cable line	Times	SFT205-NMSM- 7.00M	394815-0001	---	---
Cable line	Times	HF160-KMKM- 3.00M	393493-0001	---	---

5 Test results and Measurement Data

5.1 Antenna Requirement


Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	Please see Internal photos
The antenna is PCB antenna.	

5.2 Spurious Emissions

5.2.1 Duty Cycle


Test Requirement: 47 CFR Part 15C Section 15.35 (c)
Test Method: ANSI C63.10:2013

Test Setup:




Limit: N/A
Test Mode: Transmitting mode
Test Results: Pass
Test plot as follows:
Time slot:

The pulse train length is greater than 100 ms



T period



T on time (ms)	T period (ms)	Duty cycle %
100	100	100%

Note: Duty cycle=T on time / T period

5.2.2 Spurious Emissions

Test Requirement: 47 CFR Part 15C Section 15.231(b) and 15.209

Test Method: ANSI C63.10: 2013

Test Site: Measurement Distance: 3m (Semi-Anechoic Chamber)

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1GHz

Test Procedure:

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the only channel .
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.
- Repeat above procedures until all frequencies measured was complete.

**Limit:
(Spurious
Emissions)**

Frequency	Field strength (microvolt/meter)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

**Limit:
(Field strength of
the fundamental
signal)**

Fundamental Frequency	Limit (dBμV/m @3m)	Remark
868.35MHz	81.94	Average Value /quasi-peak Value
	101.94	Peak Value

**(Field strength of
spurious emission)**

Limit (dBμV/m @3m)	Remark
61.94	Average Value /quasi-peak Value
81.94	Peak Value

Test Mode:

Transmitting mode

Test Results:

Pass

Spurious Emissions


9KHz-30MHz

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30MHz-1GHz

Horizontal:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree	Comment
1		41.0095	0.47	14.50	14.97	40.00	-25.03	peak	199	79	
2		61.8539	0.88	12.92	13.80	40.00	-26.20	peak	199	131	
3		125.0065	8.30	10.43	18.73	43.50	-24.77	peak	100	248	
4		304.2363	4.63	17.34	21.97	46.00	-24.03	peak	100	166	
5		576.7454	1.77	23.45	25.22	46.00	-20.78	peak	199	7	
6		727.5701	2.52	25.20	27.72	46.00	-18.28	peak	100	166	
7	*	868.3686	44.09	27.77	71.86	81.94	-10.08	QP	100	104	

Vertical:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		48.9371	1.60	14.30	15.90	40.00	-24.10	peak	100	332
2		58.4279	1.87	13.68	15.55	40.00	-24.45	peak	100	281
3		125.0066	8.47	10.43	18.90	43.50	-24.60	peak	199	360
4		224.9921	3.90	14.65	18.55	46.00	-27.45	peak	100	188
5		378.1862	0.85	18.93	19.78	46.00	-26.22	peak	199	360
6		578.4671	1.52	23.50	25.02	46.00	-20.98	peak	100	250
7	*	868.5209	34.91	27.77	62.68	81.94	-19.26	QP	199	70

Above 1GHz

Average value:	
Calculate Formula:	Average value=Peak value + PDCF
	PDCF=20 log(Duty cycle)
	Duty cycle= T on time / T period
Test data:	T on time =100ms
	T period =100ms
	PDCF=0

Horizontal:

Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dB μV]	Level [dB μV/m]	Limit [dB μV/m]	Margin [dB]	Result	Polarity	Remark
1	1736.67	3.06	39.88	42.94	81.94	39.00	PASS	Horizontal	PK
		--	--	42.94	61.94	19.00	PASS	Horizontal	AV
2	2604.96	5.14	51.60	56.74	81.94	25.20	PASS	Horizontal	PK
		--	--	56.74	61.94	5.20	PASS	Horizontal	AV
3	4342.08	-17.15	54.15	37.00	81.94	44.94	PASS	Horizontal	PK
		--	--	37.00	61.94	24.94	PASS	Horizontal	AV

Vertical:

Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1738.87	3.08	37.08	40.16	81.94	41.78	PASS	Vertical	PK
		--	--	40.16	61.94	21.78	PASS	Vertical	AV
2	2604.96	5.14	45.70	50.84	81.94	31.10	PASS	Vertical	PK
		--	--	50.84	61.94	11.10	PASS	Vertical	AV
3	4342.08	-17.15	51.97	34.82	81.94	47.12	PASS	Vertical	PK
		--	--	34.82	61.94	27.12	PASS	Vertical	AV

Remark:


- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading - Correct Factor
Correct Factor = Preamplifier Factor- Antenna Factor-Cable Factor
- Scan from 9kHz to 5GHz, the disturbance below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- Average value=Peak value + PDCF

5.3 20dB Bandwidth

Test Requirement: tion 15.231 (c)

Test Method:

Test Setup:



Limit:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.


Test Mode: Transmitting mode

Test Results: Pass

Test data

20dB bandwidth (MHz)	Limit (MHz)	Results
0.1245	1.0848	PASS

Test plot as follows:



5.4 Dwell Time


Test Requirement:

47 CFR Part 15C Section 15.231 (a)

Test Method:

ANSI C63.10:2013

Test Setup:



Limit:

Not more than 5 seconds

Test Mode:

Transmitting mode

Test Results:

Pass

Requirements:

1. Regulation 15.231 (a) The provisions of this Section are restricted to periodic operation within the band 40.66~40.70 MHz and above 70 MHz. Except as shown in paragraph (e) of this Section, the intentional radiator is restricted to the transmission of a control signal such as those used with alarm systems, door openers, remote switches, etc. Radio control of toys is not permitted. Continuous transmissions, such as voice or video, and data transmissions are not permitted. The prohibition against data transmissions does not preclude the use of recognition codes. Those codes are used to identify the sensor that is activated or to identify the particular component as being part of the system.

Result:


The EUT is a remote switch without audio or video transmitted.
The EUT meets the requirements of this section.

2. Regulation 15.231 (a1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Result:

Test item	Limit (S)	Results (S)
Transmitting time	≤ 5	0.3043

Test plot as follows:



3. Regulation 15.231 (a2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

Result:

The EUT does not have automatic transmission.

4. Regulation 15.231 (a3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions to determine system integrity of transmitters used in security or safety applications are allowed if the periodic rate of transmission does not exceed one transmission of not more than one second duration per hour for each transmitter.

Result:

The EUT does not employ periodic transmission.

5. Regulation 15.231 (a4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.

Result:

This section is not applicable to the EUT.