

FCC RF Exposure

EUT Description: Open-Ear Headphones
 Model No.: G303S-Black, G303S-White
 FCC ID: 2BF86-G303S
 Equipment type: Portable devices

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance in mm})] \cdot [f(\text{GHz})] < 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

$$\text{EIRP} = \text{EMeas} + 20 \log(\text{dmeas}) - 104.7$$

EIRP is the equivalent isotropically radiated power,

EMeas in dBm is the field strength of the emission at the measurement distance, in dB u V/m

dmeas is the measurement distance, in m

EIRP(dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
2.433	1.7511	2402	5	0.5428	3.0
2.481	1.7705	2441	5	0.5532	3.0
2.328	1.7092	2480	5	0.5383	3.0

Field strength(dBuV/m)	EIRP(dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
89.61	-1.5476	0.7002	2402	5	0.2170	3.0
88.53	-1.6376	0.6859	2440	5	0.2143	3.0
90.66	-3.3376	0.4637	2480	5	0.1460	3.0

Conclusion: No SAR is required