



# MPE ESTIMATION

FCC ID: 2BFAW-D112

**1, Per FCC Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices, the limit for General Population/ Uncontrolled Exposures**

Frequency	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

## 2, Estimation Result

Mode	Frequency (MHz)	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )
2.4G WIFI	2437	14.57	14±1(15)	31.62	2.5	1.78	0.01120
$Pd = \frac{P_{out} * G}{4\pi r^2}$ ;							
Note:							
Note: The estimation distance is 20cm							
Note:							
PK Output power= conducted power.							
Conducted power see the test report <b>HK2402280859-E</b> , antenna gain=2.5dBi,							

When the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01120 mW/cm<sup>2</sup> which is < 1.0mW/cm<sup>2</sup>, RF Exposure testing is not required.

-----The End-----