# **RF Exposure Evaluation**

#### **LIMIT**

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0	614	1.63	*(100)	6			
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6			
30–300	61.4	0.163	1.0	6			
300–1500	-	-	f/300	6			
1500–100,000	-	-	5	6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30			
30–300	27.5	0.073	0.2	30			
300–1500	-	-	f/1500	30			
1500-100,000	-	-	1.0	30			

Note: f = frequency in MHz

## **EVALUATION METHOD**

Transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

Where

Pd = power density in mW/cm<sup>2</sup>, Pout = output power to antenna in mW, G = gain of antenna in linear scale;

Pi = 3.1416, R = distance between observation point and center of the radiator in cm

### **TEST RESULT**

|--|--|

Radio Type	Frequency range (MHz)	Conducted Average Power (dBm)	Maximum Tune-up (dBm)	Power Density (mW/cm2)	Limit (mW/cm2)	Result
Bluetooth-EDR	2402-2480	8.70	9.00	0.0049	1.0000	Pass
Bluetooth-BLE	2402-2480	7.98	8.00	0.0039	1.0000	Pass
2.4G WIFI	2412-2462	16.98	17.00	0.0307	1.0000	Pass
5G WIFI	5150-5250	15.02	15.50	0.0251	1.0000	Pass
5G WIFI	5725-5850	13.76	14.00	0.0178	1.0000	Pass

Consider the BT and wifi can transmitting simultaneously, the total transmitting MPE rate as below formula: MPE rate=Power density of Bluetooth-EDR /limit + Power density of 2.4G WIFI /limit <1

The worst case is Bluetooth-EDR and 2.4G WIFI transmitting simultaneously, the result as below:

Evaluation mode	Power density/limit	Sum of the MPE rate	limit
Bluetooth-EDR	0.0049	0.00=0	1.0000
2.4G WIFI	0.0307	0.0356	

#### Note:

- 1) The maximum antenna gain is 4.89dBi(2.4G) and 5.52dBi(5G)
- 2) The exposure evaluation safety distance is 20cm.