






e_{por}



No.: BCTC/RF-EMC-005 Page: 66 of 85 / / / Edition: B.1







No.: BCTC/RF-EMC-005

Page: 67 of 85' / / / / |

Edition: B.1



13. Number Of Hopping Frequency

13.1 Block Diagram Of Test Setup

EUT SPECTRUM ANALYZER

13.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

13.3 Test procedure


- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
- 3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
- 4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

13.4 Test Result


Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH1	79	15	Pass
NVNT	2-DH1	79	15	Pass
NVNT	3-DH1	79	15	Pass

No. : BCTC/RF-EMC-005 Page: 68 of 85' / / / | Edition : B.1'






BCTC






No.: BCTC/RF-EMC-005

Report No.: BCTC2403798054-1E







14. Dwell Time

14.1 Block Diagram Of Test Setup

EUT	SPECTRUM		
	ANALYZER		

14.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

14.3 Test procedure

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set spectrum analyzer span = 0. Centred on a hopping channel;
- 3. Set RBW = 1MHz and VBW = 3MHz.Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- 4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

14.4 Test Result

Mode	Frequency (MHz)	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
1-DH1	2441	0.381	120.396	316	31600	400	Pass
1-DH3	2441	1.638	257.166	157	31600	400	Pass
1-DH5	2441	2.887	352.214	122	31600	400	Pass
2-DH1	2441	0.391	123.556	316	31600	400	Pass
2-DH3	2441	1.643	264.523	161	31600	400	Pass
2-DH5	2441	2.892	274.74	95	31600	400	Pass
3-DH1	2441	0.391	123.947	317	31600	400	Pass
3-DH3	2441	1.643	259.594	158	31600	400	Pass
3-DH5	2441	2.894	292.294	101	31600	400	Pass


Note: Total Dwell Time (ms) = Pulse Time (ms)*Burst Count

No. : BCTC/RF-EMC-005 Page: 71 of 85 / / / / Edition : B.1

Span 0 Hz Sweep 31.60 s (10001 pts) e_{por}




Center 2.441000000 GHz Res BW 1.0 MHz



No.: BCTC/RF-EMC-005 Page: 72 of 85 / / / Edition: B.1


#VBW 3.0 MHz







No.: BCTC/RF-EMC-005 Page: 73 of 85 / / / / Edition 18.1









No.: BCTC/RF-EMC-005 Page: 74 of 85 / / Edițion: B.1






No.: BCTC/RF-EMC-005 Page: 75 of 85 / / / Edition: B.1








No.: BCTC/RF-EMC-005 Page: 76 of 85 / / Edition: B.1



Center 2.441000000 GHz Res BW 1.0 MHz Report No.: BCTC2403798054-1E

Span 0 Hz Sweep 31.60 s (10001 pts)



No.: BCTC/RF-EMC-005 Page: 77 of 85 Edition: B.1


#VBW 3.0 MHz

STATUS



Center 2.441000000 GHz Res BW 1.0 MHz Report No.: BCTC2403798054-1E

Span 0 Hz Sweep 31.60 s (10001 pts) epor



No.: BCTC/RF-EMC-005 Page: 78 of 85 / / Edition: B.1


#VBW 3.0 MHz

STATUS



Center 2.441000000 GHz Res BW 1.0 MHz Report No.: BCTC2403798054-1E

Span 0 Hz Sweep 31.60 s (10001 pts)





No. : BCTC/RF-EMC-005 Page: 79 of 85 / / / Edition : B.1

#VBW 3.0 MHz

STATUS







No.: BCTC/RF-EMC-005 Page: 80 of 85 / / Edition: B.1




15. Antenna Requirement

15.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.2 Test Result

The EUT antenna is Internal antenna, fulfill the requirement of this section.



No.: BCTC/RF-EMC-005



16. EUT Photographs

EUT Photo



NOTE: Appendix-Photographs Of EUT Constructional Details





17. EUT Test Setup Photographs

Conducted emissions



Radiated Measurement Photos




No. : BCTC/RF-EMC-005 Page: 83 of 85 / / / Edition : B.1


BC APPE











No.: BCTC/RF-EMC-005

Page: 84 of 85

Edition: B.1



STATEMENT

- 1. The equipment lists are traceable to the national reference standards.
- 2. The test report can not be partially copied unless prior written approval is issued from our lab.
- 3. The test report is invalid without the "special seal for inspection and testing".
- 4. The test report is invalid without the signature of the approver.
- 5. The test process and test result is only related to the Unit Under Test.
- 6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
- 7. The quality system of our laboratory is in accordance with ISO/IEC17025.
- 8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: http://www.chnbctc.com

E-Mail: bctc@bctc-lab.com.cn

**** END ****

No.: BCTC/RF-EMC-005 Page: 85 of 85 / / Edition : B.

