Label Location On EUT



Portable Power Station

- Model: EP1800
- Battery Capacity: 1536Wh(40Ah/38.4V)
- AC Charge:1500W Max 100V-120VAC 50/60Hz
- DC(XT60)Input:12V-90V-1200W Max
- USB-A(x2)Output: 5V-3A 9V-2A 12V-1.5A ,Total 36W
- Type-C PD 20W(x1)Output: 5V-3A, 9V-2.22A,

12V-1.67A, Total 20W

- Type-C PD 100W Output: (5V/9V/12V/15V)--3A
 20V--5A, Total 100W
- 12V Output:12V—10A
- LED:3W

156mm

151mm

- OperatingTemperature: -10~40°C
- Charging Temperature: 0~40°C
- AC Output: 100V-120VAC 50/60Hz

Off-grid Mode: Rated 1800W Bypass Input: 1650W Max

- Total DC Output: 276W
- Total AC and DC Output: 2076W
- FCC ID: 2BFF7EP1800

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

This device may not cause harmful interference, and This device must accept any interference received, including interference that may cause undesired operation.

A CAUTION

This device is not intended for use in a commercial repair facility.Risk of Electric Shock. Refer replacement to qualified service personnel. Do not remove cover. Risk of Injury To Persons. Do not use this product if the power cord or the battery cables are damaged in any way.

⚠ WARNING

Risk of Electric Shock and Risk of Fire. This device is not to be stored in a vehicle. Do not overcharge the internal battery. See Instruction Manual. Do not smoke, strike a match, or cause a spark in the vicinity of the power pack. Only charge the internal battery in a well ventilated area.

△ DANGER

This device is intended to be used indoors only. Do not use outdoors.











Made in China

81mm

86mm

贴纸尺寸:86*156mm,公差-0.1mm; **材质工艺:**75#合成纸,覆哑膜,防刮, 黑底白字;

注意:产品1800W放电时会达到60°C以上,在这个温度内不能脱胶。