

## Maximum Permissible Exposure Report

### Product Information

EUT : Motorcycle DVR Dash Camera  
 Model Number : HM502  
 Model Declaration : N/A  
 Test Model : HM502  
 Power Supply : DC 9-36V  
 Hardware version : HFK\_M35\_M17\_Main\_V0.2\_231020  
 Software version : M35-2024-01-30-V1.1  
 Sample ID : TZ240205390-2#&TZ240205390-4#

### WiFi

WLAN : Supported IEEE 802.11a/b/g/n/ac  
 IEEE 802.11b:2412-2462MHz  
 IEEE 802.11g:2412-2462MHz  
 IEEE 802.11n HT20:2412-2462MHz / 5180-5240MHz / 5745-5825MHz  
 WLAN FCC Operation : IEEE 802.11n HT40: 2422-2452MHz / 5190-5230MHz / 5755-5795MHz  
 Frequency : IEEE 802.11a: 5180-5240MHz / 5745-5825MHz  
 IEEE 802.11ac VHT20: 5180-5240MHz / 5745-5825MHz  
 IEEE 802.11ac VHT40: 5190-5230MHz / 5755-5795MHz  
 IEEE 802.11ac VHT80: 5210MHz / 5775MHz  
 WLAN Channel Number : 11 Channels for 2412-2462MHz(IEEE 802.11b/g/n HT20)  
 7 Channels for 2422-2452MHz(IEEE 802.11n HT40)  
 4 Channels for 5180-5240MHz (IEEE 802.11a/ac VHT20/n HT20)  
 2 Channels for 5190-5230MHz (IEEE 802.11ac VHT40/n HT40)  
 1 Channels for 5210MHz (IEEE 802.11ac VHT80)  
 5 Channels for 5745-5825MHz(IEEE 802.11a/ac VHT20/n HT20)  
 2 Channels for 5755-5795MHz(IEEE 802.11ac VHT40/n HT40)  
 1 Channels for 5775MHz(IEEE 802.11ac VHT80)  
 WLAN Modulation : IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)  
 Technology : IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)  
 : IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)  
 IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)  
 IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)  
 Antenna Type And Gain : Antenna 1:  
 1.01dBi (Max.), for TX/RX (WLAN 2.4G Band)  
 1.53dBi (Max.), for TX/RX (WLAN 5.2G Band)  
 1.4dBi (Max.), for TX/RX (WLAN 5.8G Band)  
 : Antenna 2:  
 0.4dBi (Max.), for TX/RX (WLAN 2.4G Band)  
 1.68dBi (Max.), for TX/RX (WLAN 5.2G Band)  
 1.42dBi (Max.), for TX/RX (WLAN 5.8G Band)

*Note 1: Antenna position refer to EUT Photos.*

*Note 2: the above information was supplied by the applicant.*

## 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

### 3. Limit

#### 3.1 Refer evaluation method

ANSI C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices

#### 3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

#### 4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

#### 5. Antenna Information

This Product can only use antennas certificated as follows provided by manufacturer;

Antenna Gain and type refer to Product information

## 6. Conducted Power

2.4G Band:

WiFi 2.4GHz Band

Test Mode	Antenna	Frequency[MHz]	Result [dBm]
11B	Ant1	2412	16.63
11B	Ant2	2412	12.22
11B	Ant1	2437	15.72
11B	Ant2	2437	11.68
11B	Ant1	2462	17.18
11B	Ant2	2462	11.58
11G	Ant1	2412	18.52
11G	Ant2	2412	16.71
11G	Ant1	2437	15.92
11G	Ant2	2437	17.78
11G	Ant1	2462	16.21
11G	Ant2	2462	17.62
11N20MIMO	Ant1	2412	16.43
11N20MIMO	Ant2	2412	13.46
11N20MIMO	total	2412	18.20
11N20MIMO	Ant1	2437	15.71
11N20MIMO	Ant2	2437	12.51
11N20MIMO	total	2437	17.41
11N20MIMO	Ant1	2462	16.31
11N20MIMO	Ant2	2462	12.52
11N20MIMO	total	2462	17.83
11N40MIMO	Ant1	2422	16.64
11N40MIMO	Ant2	2422	13.61
11N40MIMO	total	2422	18.39
11N40MIMO	Ant1	2437	16.35
11N40MIMO	Ant2	2437	13.03
11N40MIMO	total	2437	18.01
11N40MIMO	Ant1	2452	16.27
11N40MIMO	Ant2	2452	12.86
11N40MIMO	total	2452	17.90

5G Band  
UNII-1 Band

Test Mode	Antenna	Frequency[M Hz]	Result [dBm]
11A	Ant1	5180	14.16
11A	Ant2	5180	13.88
11A	Ant1	5200	13.83
11A	Ant2	5200	13.43
11A	Ant1	5240	15.08
11A	Ant2	5240	14.78
11N20MIMO	Ant1	5180	14.13
11N20MIMO	Ant2	5180	13.76
11N20MIMO	total	5180	16.96
11N20MIMO	total	5200	16.60
11N20MIMO	Ant1	5200	13.71
11N20MIMO	Ant2	5200	13.47
11N20MIMO	Ant1	5240	12.70
11N20MIMO	Ant2	5240	12.32
11N20MIMO	total	5240	15.52
11N40MIMO	Ant1	5190	11.57
11N40MIMO	Ant2	5190	11.18
11N40MIMO	total	5190	14.39
11N40MIMO	Ant1	5230	12.13
11N40MIMO	Ant2	5230	11.89
11N40MIMO	total	5230	15.02
11AC20MIMO	Ant1	5180	14.16
11AC20MIMO	Ant2	5180	13.70
11AC20MIMO	total	5180	16.95
11AC20MIMO	Ant1	5200	9.62
11AC20MIMO	Ant2	5200	9.75
11AC20MIMO	total	5200	12.70
11AC20MIMO	Ant1	5240	11.30
11AC20MIMO	Ant2	5240	11.26
11AC20MIMO	total	5240	14.29
11AC40MIMO	Ant1	5190	11.66
11AC40MIMO	Ant2	5190	11.40
11AC40MIMO	total	5190	14.54
11AC40MIMO	Ant1	5230	12.38
11AC40MIMO	Ant2	5230	11.67
11AC40MIMO	total	5230	15.05
11AC80MIMO	Ant1	5210	12.08
11AC80MIMO	Ant2	5210	11.56
11AC80MIMO	total	5210	14.84

## UNII-3 Band

Test Mode	Antenna	Frequency[MHz]	Result [dBm]
11A	Ant1	5745	17.60
11A	Ant2	5745	15.96
11A	Ant1	5785	15.79
11A	Ant2	5785	14.50
11A	Ant1	5825	14.35
11A	Ant2	5825	13.38
11N20MIMO	Ant1	5745	9.93
11N20MIMO	Ant2	5745	8.84
11N20MIMO	total	5745	12.43
11N20MIMO	Ant1	5785	11.25
11N20MIMO	Ant2	5785	9.81
11N20MIMO	total	5785	13.60
11N20MIMO	Ant1	5825	9.87
11N20MIMO	Ant2	5825	8.74
11N20MIMO	total	5825	12.35
11N40MIMO	Ant1	5755	11.97
11N40MIMO	Ant2	5755	10.78
11N40MIMO	total	5755	14.43
11N40MIMO	Ant1	5795	10.94
11N40MIMO	Ant2	5795	9.33
11N40MIMO	total	5795	13.22
11AC20MIMO	Ant1	5745	10.97
11AC20MIMO	Ant2	5745	9.65
11AC20MIMO	total	5745	13.37
11AC20MIMO	Ant1	5785	9.88
11AC20MIMO	Ant2	5785	8.71
11AC20MIMO	total	5785	12.34
11AC20MIMO	Ant1	5825	8.65
11AC20MIMO	Ant2	5825	7.49
11AC20MIMO	total	5825	11.12
11AC40MIMO	Ant1	5755	8.37
11AC40MIMO	Ant2	5755	7.18
11AC40MIMO	total	5755	10.83
11AC40MIMO	Ant1	5795	9.83
11AC40MIMO	Ant2	5795	9.14
11AC40MIMO	total	5795	12.51
11AC80MIMO	Ant1	5775	9.22
11AC80MIMO	Ant2	5775	10.34
11AC80MIMO	total	5775	12.83

## 7. Manufacturing Tolerance

### WiFi 2.4GHz Band – Antenna 1

IEEE 802.11b(Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	16.0	15.0	16.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	18.0	15.5	15.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	16.0	15.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	16.0	16.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

### WiFi 2.4GHz Band – Antenna 2

IEEE 802.11b(Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11.5	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	16.0	17.5	17.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	12.5	12.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0

## UNII-1 Band – Antenna 1

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.5	13.5	14.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.5	16.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.0	9.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	11.0	11.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	11.0	12.0	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 42	--	--
Target (dBm)	11.5	--	--
Tolerance $\pm$ (dB)	1.0	--	--

## UNII-1 Band – Antenna 2

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.5	13.0	14.5
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.5	13.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.0	9.5	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	10.5	11.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	--
Target (dBm)	11.0	11.0	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 42	--	--
Target (dBm)	11.0	--	--
Tolerance $\pm$ (dB)	1.0	--	--



## UNII-3 Band – Antenna 1

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	17.0	15.5	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	11.5	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.5	9.5	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	11.5	10.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	8.0	9.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 155	--	--
Target (dBm)	8.5	--	--
Tolerance $\pm$ (dB)	1.0	--	--

## UNII-3 Band – Antenna 2

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	15.5	14.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	8.5	9.5	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	9.0	8.0	7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	10.5	9.0	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	6.5	8.5	--
Tolerance $\pm$ (dB)	1.0	1.0	--
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 155	--	--
Target (dBm)	12.5	--	--
Tolerance $\pm$ (dB)	1.0	--	--

## 8. Measurement Results

### 8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

#### WiFi 2.4GHz Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11b	17.5	56.2341	1.01	1.2618	100%	0.0141	1.0000
IEEE 802.11g	19.0	79.4328	1.01	1.2618	100%	0.0200	1.0000
IEEE 802.11n HT20	17.0	50.1187	1.01	1.2618	100%	0.0126	1.0000
IEEE 802.11n HT40	17.0	50.1187	1.01	1.2618	100%	0.0126	1.0000

#### WiFi 2.4GHz Band – Ant 2

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11b	12.5	17.7828	0.4	1.0965	100%	0.0039	1.0000
IEEE 802.11g	18.5	70.7946	0.4	1.0965	100%	0.0155	1.0000
IEEE 802.11n HT20	14.0	25.1189	0.4	1.0965	100%	0.0055	1.0000
IEEE 802.11n HT40	14.0	25.1189	0.4	1.0965	100%	0.0055	1.0000

#### UNII-1 Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11a	15.5	35.4813	1.53	1.4223	100%	0.0100	1.0000
IEEE 802.11n HT20	17.0	50.1187	1.53	1.4223	100%	0.0142	1.0000
IEEE 802.11ac VHT20	14.5	28.1838	1.53	1.4223	100%	0.0080	1.0000
IEEE 802.11n HT40	12.5	17.7828	1.53	1.4223	100%	0.0050	1.0000
IEEE 802.11ac VHT40	13.0	19.9526	1.53	1.4223	100%	0.0056	1.0000
IEEE 802.11ac VHT80	12.5	17.7828	1.53	1.4223	100%	0.0050	1.0000

#### UNII-1 Band – Ant 2

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11a	15.5	35.4813	1.68	1.4723	100%	0.0104	1.0000

IEEE 802.11n HT20	14.5	28.1838	1.68	1.4723	100%	0.0083	1.0000
IEEE 802.11ac VHT20	14.0	25.1189	1.68	1.4723	100%	0.0074	1.0000
IEEE 802.11n HT40	12.5	17.7828	1.68	1.4723	100%	0.0052	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	1.68	1.4723	100%	0.0046	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	1.68	1.4723	100%	0.0046	1.0000

## UNII-3 Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11a	18.0	63.0957	1.4	1.3804	100%	0.0173	1.0000
IEEE 802.11n HT20	12.0	15.8489	1.4	1.3804	100%	0.0044	1.0000
IEEE 802.11ac VHT20	11.5	14.1254	1.4	1.3804	100%	0.0039	1.0000
IEEE 802.11n HT40	12.5	17.7828	1.4	1.3804	100%	0.0049	1.0000
IEEE 802.11ac VHT40	10.5	11.2202	1.4	1.3804	100%	0.0031	1.0000
IEEE 802.11ac VHT80	9.5	8.9125	1.4	1.3804	100%	0.0024	1.0000

## UNII-3 Band – Ant 2

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11a	16.5	44.6684	1.42	1.3868	100%	0.0123	1.0000
IEEE 802.11n HT20	10.5	11.2202	1.42	1.3868	100%	0.0031	1.0000
IEEE 802.11ac VHT20	10.0	10.0000	1.42	1.3868	100%	0.0028	1.0000
IEEE 802.11n HT40	11.5	14.1254	1.42	1.3868	100%	0.0039	1.0000
IEEE 802.11ac VHT40	9.5	8.9125	1.42	1.3868	100%	0.0025	1.0000
IEEE 802.11ac VHT80	13.5	22.3872	1.42	1.3868	100%	0.0062	1.0000

## Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

## 8.2 Simultaneous Transmission MPE

Bluetooth + Wi-Fi

Maximum MPE(mW/cm <sup>2</sup> ) WIFI Ant.1	Maximum MPE(mW/cm <sup>2</sup> ) WIFI Ant.2	∑MPE (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Results
0.0200	0.0155	0.0354	1.0000	PASS

## Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

## 9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----