

RF exposure Estimation

1. Introduction

Product: Bluetooth Headset

Model No.: ASTRUM MX PRO, HT320, HT430, HT250, HT100

FCC ID: 2BFJ5-ASTRUMMXPRO

The EUT is a Bluetooth Headset, which contain BT function inside.

Note: All models have the same technical construction including circuit diagram, PCB layout, components and component layout. Only the model's name and outlook/color are different. So RF exposure evaluation only applied on ASTRUM MX PRO, other models are deemed to fulfill the requirement.

2. Details about the Test Laboratory

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12 & 13, Zhiheng Wisdomland Business Park, Guankou Erlu,
Nantou, Nanshan District, Shenzhen 518052, P.R. China

Telephone: 86 755 8828 6998

Fax: 86 755 828 5299

FCC Registration No.: 514049

No.:

FCC Designation Number: CN5009

3. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r02, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right]$$

$$\sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz.

4. Calculation method

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$

Conducted Power + tune up tolerance = 0.41dBm= 1.099mW

Distance = 5 mm

f = 2.441 GHz

$[1.099/5] \cdot \text{SQRT}(2.441) = 0.343$

$0.343 \leq 3.0$

Therefore, excluded from SAR testing.

- TÜV SÜD China, Shenzhen Branch -

Reviewed by:

Prepared By:




John Zhi/Project Manager
Date: 2024-04-26



Sanvin Zheng/Project Engineer
Date: 2024-04-26