


TEST REPORT

Report No.	CISRR24051304202
Project No.	CISR240513042
FCC ID	2BFQI-V98PRO
Applicant	Jiangxi Jichi Technology Co., Ltd
Address	Plant No.3,Block B13-1-2, B14-1, Jinggangshan Economic and Development Zone,Ji 'an,Jiangxi,China
Manufacturer	Jiangxi Jichi Technology Co., Ltd
Address	Plant No.3,Block B13-1-2, B14-1, Jinggangshan Economic and Development Zone,Ji 'an,Jiangxi,China
Product Name	keyboard
Trade Mark	--
Model/Type reference	V98Pro
Listed Model(s)	--
Standard	Part 15 Subpart C Section 15.247
Test date	May 13, 2024 ~ July 16, 2024
Issue date	July 16, 2024
Test result	Complied



Prepared by: Rory Huang



Approved by: Genry Long

The test results relate only to the tested samples.

The test report should not be reproduced except in full without the written approval of Shenzhen Bangce Testing Technology Co., Ltd.

Contents

1. REPORT VERSION	3
2. SUMMARY OF TEST RESULT	4
3. SUMMARY	5
3.1. Product Description	5
3.2. Radio Specification Description	5
3.3. Modification of EUT	6
3.4. Testing Site	6
3.5. Field Strength Calculation	6
3.6. DISTURBANCE Calculation	6
4. TEST CONFIGURATION	7
4.1. Test frequency list	7
4.2. Test mode	7
4.3. Support unit used in test configuration and system	7
4.4. Test sample information	7
4.5. Testing environmental condition	8
4.6. Statement of the measurement uncertainty	8
4.7. Equipment Used during the Test	9
5. TEST CONDITIONS AND RESULTS	10
5.1. Antenna Requirement	10
5.2. AC Conducted Emission	11
5.3. 20 dB Bandwidth	14
5.4. Radiated Band edge Emission	16
5.5. Radiated Spurious Emission	18
6. TEST SETUP PHOTOS	23
7. EXTERNAL AND INTERNAL PHOTOS	23
7.1 External photos	23
7.2 Internal photos	23

1. REPORT VERSION

Version No.	Issue date	Description
00	July 16, 2024	Original

2. SUMMARY OF TEST RESULT

Report clause	Test Item	Standard Requirement	Result
5.1	Antenna Requirement	15.203/15.247 (c)	PASS
5.2	AC Conducted Emission	15.207	PASS
5.3	20 dB Bandwidth	15.215 (c)	PASS
5.4	Radiated Band Edge Emission	15.205/15.209	PASS
5.5	Radiated Spurious Emission	15.249(a)(c)/15.205/15.209	PASS

Note:

- The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Product Description

Main unit information:	
Product Name:	keyboard
Trade Mark:	--
Model No.:	V98Pro
Listed Model(s):	--
Power supply:	Input:DC 5V DC 3.7V from Battery
Hardware version:	2023-10-27
Software version:	V1.5

3.2. Radio Specification Description

Technology:	2.4G
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	16
Antenna type:	PCB Antenna
Antenna gain:	2.24dBi

Channel list:

1CH	2402 MHz	9CH	2414 MHz
2CH	2426 MHz	10CH	2436 MHz
3CH	2440MHz	11CH	2459 MHz
4CH	2463 MHz	12CH	2473 MHz
5CH	2407 MHz	13CH	2419 MHz
6CH	2422 MHz	14CH	2439 MHz
7CH	2445 MHz	15CH	2453 MHz
8CH	2466 MHz	16CH	2480 MHz

3.3. Modification of EUT

No modifications are made to the EUT during all test items.

3.4. Testing Site

Laboratory Name	Shenzhen Bangce Testing Technology Co., Ltd.
Laboratory Location	101, building 10, Yunli Intelligent Park, Shutianpu community, Matian Street, Guangming District, Shenzhen, Guangdong, China
FCC registration number	736346

3.5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS \text{ (dBuV/m)} = RA \text{ (dBuV)} + AF \text{ (dB/m)} + CL \text{ (dB)} - AG \text{ (dB)}$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

3.6. DISTURBANCE Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD \text{ (dBuV)} = RA \text{ (dBuV)} + PL \text{ (dB)} + CL \text{ (dB)}$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

4. TEST CONFIGURATION

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

4.1. Test frequency list

Channel	Frequency (MHz)
CH-L	2402
CH-M	2440
CH-H	2480

4.2. Test mode

For RF test items:

The engineering prototype is provided with key switching channel to realize EUT continuous transmission..Power setting Default.

Test Item	Test Mode	Modulation
Conducted test item	TX CH-L	GFSK
	TX CH-M	GFSK
	TX CH-H	GFSK
	Normal link	--
Radiated test item	TX CH-L	GFSK
	TX CH-M	GFSK
	TX CH-H	GFSK
	Normal link	--

Remark:

- The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.All patterns have predictions, and the report only shows the worst pattern data.

4.3. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Item	Equipment name	Trade Name	Model No.
1	Adapter	Huawei	HW-05002000C
2	Notebook	ASUS	4D8A76B96FC2

4.4. Test sample information

Type	sample no.
Engineer sample	CISR240513042--S01
Normal sample	CISR240513042--S01

4.5. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.6. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	1.63dB
2	Peak Output Power	1.34dB
3	Power Spectral Density	1.34dB
4	6dB Bandwidth	0.002%
5	99% Occupied Bandwidth	0.002%
6	Duty cycle	-
7	Conducted Band Edge and Spurious Emission	1.93dB
8	Radiated Band Edge Emission	3.76dB for 30MHz-1GHz 3.80dB for above 1GHz
9	Radiated Spurious Emission	3.76dB for 30MHz-1GHz 3.80dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.7. Equipment Used during the Test

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	SKET	9.3*6.3*6	N/A	2021.10.15	3Year
Spectrum analyzer	Agilent	N9020A	MY50530263	2024.01.08	1Year
Receiver	ROHDE&SCHWARZ	ESCI	100853	2024.01.08	1Year
Spectrum analyzer	R&S	FSV-40N	/	2024.01.08	1Year
Bilog Antenna	Schwarzbeck	VULB 9163	1463	2023.01.09	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	2487	2023.01.09	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	/	2023.01.09	2Year
RF Cable	Tonscend	Cable 1	/	2024.01.08	1Year
RF Cable	Tonscend	Cable 2	/	2024.01.08	1Year
RF Cable	SKET	Cable 3	/	2024.01.08	1Year
Pre-amplifier	Tonscend	TAP9K3G32	AP21G806153	2024.01.08	1Year
Pre-amplifier	Tonscend	TAP01018050	AP22E806229	2024.01.08	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8127	/	2024.01.08	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	2024.01.08	1Year
Horn Antenna	SCHWARZBECK	BBHA9170	1130	2023.01.09	2 Year
Preamplifier	Tonscend	TAP18040048	AP21C806126	2024.01.08	1Year
variable-frequency power source	Pinhong	PH1110	/	2024.01.08	1Year
6dB Attenuator	SKET	DC-6G	/	N/A	N/A
Artificial power network	Schwarzbeck	NSLK8127	8127-01096	2024.01.08	1Year
EMI Test Receiver	Rohde&schwarz	ESCI7	100853	2024.01.08	1Year
8-wire Impedance Stabilization Network	Schwarzbeck	NTFM 8158	8158-00337	2024.01.08	1Year
Artificial power network	Schwarzbeck	ENV216	/	2024.01.08	1Year
Antenna tower	SKET	Bk-4AT-BS	AT2021040101-V1	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Standard Applicable

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Description

The EUT antenna is PCB antenna (2.24dBi), the directional gain of the antenna less than 6dBi. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used. Antenna structure please refer to the EUT internal photographs antenna photo.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen Bangce Testing Technology Co., Ltd. does not assume any responsibility.

5.2. AC Conducted Emission

Limit:

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test configuration:



Test procedure:

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.


Test mode:

Refer to the clause 4.2

Result:


Passed

Have pre-scan all test channel, found CH01 which it was worst case, so only show the worst case's data on this report.



Test Line:

N



No.	Frequency	Limit dBuV	Level dBuV	Margin dB	Reading dBuV	Factor dB	Detector	Polar
1	150.000kHz	66.0	40.4	-25.6	40.4	0.0	QP	N
2	462.000kHz	56.7	43.4	-13.3	43.3	0.1	QP	N
3	950.000kHz	56.0	38.4	-17.6	38.3	0.1	QP	N
4	2.134MHz	56.0	33.3	-22.7	33.2	0.1	QP	N
5	5.706MHz	60.0	30.2	-29.8	30.0	0.2	QP	N
6	10.374MHz	60.0	36.7	-23.3	36.4	0.3	QP	N
7	182.000kHz	54.4	27.3	-27.1	27.3	0.0	CAV	N
8	462.000kHz	46.7	38.7	-8.0	38.6	0.1	CAV	N
9	886.000kHz	46.0	26.9	-19.1	26.8	0.1	CAV	N
10	1.594MHz	46.0	23.9	-22.1	23.8	0.1	CAV	N
11	2.458MHz	46.0	23.5	-22.5	23.4	0.1	CAV	N
12	10.546MHz	50.0	23.5	-26.5	23.2	0.3	CAV	N

Note:


- Factor = LISN Factor + Cable Factor
- Level= Reading + Factor
- Margin= Level – Limit

5.3. 20 dB Bandwidth

Limit:

--

Test configuration:



Test procedure:

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW $\geq 1\%$ to 5% of the 20 dB bandwidth, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

Test mode:

Refer to the clause 4.2


Result:

Passed


Test Result of 20dB Bandwidth Measurement

Test Frequency(MHz)	20dB Bandwidth(MHz)	Limit(MHz)
2402	1.306	Non-Specified
2440	1.305	Non-Specified
2480	1.301	Non-Specified


20dB Bandwidth



2402MHz



2440MHz



2480MHz


5.4. Radiated Band edge Emission

Limit:

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

Test configuration:



Test procedure:

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement
 - d) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=Average, Trace=RMS for Average measurement

Test mode:

Refer to the clause 4.2

Result:

Passed

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Margin = Limit - Level
- 3) Average measurement was not performed if peak level is lower than average limit
- 4) The other emission levels were very low against the limit.

Test channel:CH01										
Freq. (MHz)	Reading (dBuv)	Ant. Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)	Level (dBuv)	Limit (dBu V/m)	Margin (dB)	Remark	Polarity
2390.00	70.64	28.62	4.08	38.62	-5.92	64.72	74	9.28	Peak	Horizontal
2390.00	51.01	28.62	4.08	38.62	-5.92	45.09	54	8.91	Average	Horizontal
2390.00	68.98	28.62	4.08	38.62	-5.92	63.06	74	10.94	Peak	Vertical
2390.00	50.11	28.62	4.08	38.62	-5.92	44.19	54	9.81	Average	Vertical

Test channel:CH16										
Freq. (MHz)	Reading (dBuv)	Ant. Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)	Level (dBuv)	Limit (dBu V/m)	Margin (dB)	Remark	Polarity
2483.50	69.72	29.45	3.91	40.17	-6.81	62.91	74	11.09	Peak	Horizontal
2483.50	49.63	29.45	3.91	40.17	-6.81	42.82	54	11.18	Average	Horizontal
2483.50	67.78	29.45	3.91	40.17	-6.81	60.97	74	13.03	Peak	Vertical
2483.50	51.27	29.45	3.91	40.17	-6.81	44.46	54	9.54	Average	Vertical

5.5. Radiated Spurious Emission

Limit:

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)

Limit dBuV/m @3m = Limit dBuV/m @30m + 40*log(30/3)


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

Test configuration:


9kHz~30MHz



30 MHz ~ 1 GHz



Above 1 GHz



Test procedure:

1. The EUT was setup and tested according to ANSI C63.10.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement
 - d) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=Average, Trace=RMS for Average measurement

Test mode:

Refer to the clause 4.2

Result:**Passed**

Note:


- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Margin = Limit – Level
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.
- 4) The other emission levels were very low against the limit.
- 5) This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.

For 9 kHz ~ 30 MHz

The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.


For 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH1 which it was worst case, so only show the worst case's data on this report.



Polarization:

Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	51.922	19.06	15.23	40.00	20.94	Vertical	PASS
2	76.851	21.44	10.30	40.00	18.56	Vertical	PASS
3	111.189	18.24	13.43	43.50	25.26	Vertical	PASS
4	180.059	19.59	11.55	43.50	23.91	Vertical	PASS
5	422.171	24.40	18.21	46.00	21.60	Vertical	PASS
6	924.728	37.80	25.67	46.00	8.20	Vertical	PASS

For 1 GHz ~ 25 GHz

Test channel:2402MHz

Freq. (MHz)	Reading (dBuv)	Ant. Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correc tion Factor (dB/m)	Level (dBuv)	Limit (dBu V/m)	Margin (dB)	Remark	Polarity
2402.00	92.27	29.18	4.02	38.35	-5.15	87.12	114	26.88	Peak	Horizontal
2402.00	80.95	29.18	4.02	38.35	-5.15	75.80	94	18.20	Average	Horizontal
2402.00	81.26	29.18	4.02	38.35	-5.15	76.11	114	37.89	Peak	Vertical
2402.00	67.16	29.18	4.02	38.35	-5.15	62.01	94	31.99	Average	Vertical
4804.00	69.25	31.33	4.23	38.62	-3.06	66.19	74	7.81	Peak	Horizontal
4804.00	50.89	31.33	4.23	38.62	-3.06	47.83	54	6.17	Average	Horizontal
4804.00	65.92	31.33	4.23	38.62	-3.06	62.86	74	11.14	Peak	Vertical
4804.00	51.12	31.33	4.23	38.62	-3.06	48.06	54	5.94	Average	Vertical

Test channel:2440MHz

Freq. (MHz)	Reading (dBuv)	Ant. Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correc tion Factor (dB/m)	Level (dBuv)	Limit (dBu V/m)	Margin (dB)	Remark	Polarity
2440.00	92.87	29.23	4.02	38.2	-4.95	87.92	114	26.08	Peak	Horizontal
2440.00	80.69	29.23	4.02	38.2	-4.95	75.74	94	18.26	Average	Horizontal
2440.00	82.21	29.23	4.02	38.2	-4.95	77.26	114	36.74	Peak	Vertical
2440.00	69.06	29.23	4.02	38.2	-4.95	64.11	94	29.89	Average	Vertical
4880.00	70.20	30.26	4.09	38.29	-3.94	66.26	74	7.74	Peak	Horizontal
4880.00	51.74	30.26	4.09	38.29	-3.94	47.80	54	6.20	Average	Horizontal
4880.00	66.78	30.26	4.09	38.29	-3.94	62.84	74	11.16	Peak	Vertical
4880.00	52.39	30.26	4.09	38.29	-3.94	48.45	54	5.55	Average	Vertical

Test channel:2480MHz

Freq. (MHz)	Reading (dBuv)	Ant. Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correc tion Factor (dB/m)	Level (dBuv)	Limit (dBu V/m)	Margin (dB)	Remark	Polarity
2480.00	94.46	29.2	4.02	38.3	-5.08	89.38	114	24.62	Peak	Horizontal
2480.00	81.02	29.2	4.02	38.3	-5.08	75.94	94	18.06	Average	Horizontal
2480.00	82.83	29.2	4.02	38.3	-5.08	77.75	114	36.25	Peak	Vertical
2480.00	67.48	29.2	4.02	38.3	-5.08	62.40	94	31.60	Average	Vertical
4960.00	63.19	31.97	4.11	38.47	-2.39	60.80	74	13.20	Peak	Horizontal
4960.00	52.10	31.97	4.11	38.47	-2.39	49.71	54	4.29	Average	Horizontal
4960.00	66.08	31.97	4.11	38.47	-2.39	63.69	74	10.31	Peak	Vertical
4960.00	49.22	31.97	4.11	38.47	-2.39	46.83	54	7.17	Average	Vertical

6. TEST SETUP PHOTOS

Please refer to separated files for Test Setup Photos of the EUT.

7. EXTERNAL AND INTERNAL PHOTOS

7.1 External photos

Please refer to separated files for External Photos of the EUT.

7.2 Internal photos

Please refer to separated files for Internal Photos of the EUT.

-----End of the report-----