



Shenzhen CTL Testing Technology Co., Ltd.  
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

# TEST REPORT

## FCC PART 15 SUBPART E 15.407

Report Reference No.....: CTL2311242081-WF04

Compiled by:  
( position+printed name+signature)


Happy Guo  
(File administrators)

Tested by:  
( position+printed name+signature)

Yapeng Jin  
(Test Engineer)

Approved by:  
( position+printed name+signature)

Ivan Xie  
(Manager)



Product Name.....: Car multimedia infotainment system

Model/Type reference.....: Q1062LT22A

List Model(s).....: N/A

Trade Mark.....: RoadRover

FCC ID.....: 2BFQL-Q1062LT22A

Applicant's name.....: Dongguan RoadRover Intelligent Technology Co., Ltd.

Address of applicant.....: No.28, Luxi 1st Road, Xixi Village,Liaobu Town, Dongguan City,Guangdong Province,P.R.China

Test Firm.....: Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm.....: Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

Test specification.....:

Standard.....: 47 CFR FCC Part 15 Subpart E 15.407

TRF Originator.....: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF.....: Dated 2011-01

Date of receipt of test item.....: Dec. 04, 2023

Date of Test Date.....: Dec. 05, 2023 - Feb. 02, 2024

Date of Issue.....: Feb. 23, 2024

Result.....: Pass

**Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

# TEST REPORT

<b>Test Report No. :</b>	<b>CTL2311242081-WF04</b>	Feb. 23, 2024 Date of issue
--------------------------	---------------------------	--------------------------------

Equipment under Test : Car multimedia infotainment system

Sample No : CTL2311242081

Model /Type : Q1062LT22A

Listed Models : N/A

**Applicant** : **Dongguan RoadRover Intelligent Technology Co., Ltd.**

Address : No.28, Luxi 1st Road, Xixi Village, Liaobu Town, Dongguan City, Guangdong Province, P.R.China

**Manufacturer** : **Dongguan RoadRover Intelligent Technology Co., Ltd.**

Address : No.28, Luxi 1st Road, Xixi Village, Liaobu Town, Dongguan City, Guangdong Province, P.R.China

<b>Test result</b>	<b>Pass *</b>
--------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.



**Table of Contents**

**Page**

**1. SUMMARY .....5**

1.1. TEST STANDARDS ..... 5

1.2. TEST DESCRIPTION ..... 5

1.3. TEST FACILITY ..... 6

1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY ..... 6

**2. GENERAL INFORMATION ..... 8**

2.1. ENVIRONMENTAL CONDITIONS ..... 8

2.2. GENERAL DESCRIPTION OF EUT ..... 8

2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY ..... 9

2.4. EQUIPMENTS USED DURING THE TEST ..... 10

2.5. RELATED SUBMITTAL(S) / GRANT (S) ..... 11

2.6. MODIFICATIONS ..... 11

**3. TEST CONDITIONS AND RESULTS ..... 12**

3.1. CONDUCTED EMISSIONS TEST ..... 12

3.2. RADIATED EMISSIONS ..... 15

3.3. MAXIMUM CONDUCTED AVERAGE OUTPUT POWER ..... 43

3.4. POWER SPECTRAL DENSITY ..... 44

3.5. EMISSION BANDWIDTH (26DBM BANDWIDTH) ..... 46

3.6. MINIMUM EMISSION BANDWIDTH (6DBM BANDWIDTH) ..... 47

3.7. FREQUENCY STABILITY ..... 48

3.8. ANTENNA REQUIREMENT ..... 49

**4. TEST SETUP PHOTOS OF THE EUT ..... 49**

**5. PHOTOS OF THE EUT ..... 51**

# 1. SUMMARY

## 1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15 Subpart E](#)—Unlicensed National Information Infrastructure Devices

[ANSI C63.10: 2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB789033 D02](#): General UNII Test Procedures New Rules v02r01

## 1.2. Test Description

FCC Requirement		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.407(a)	Emission Bandwidth(26dBm Bandwidth)	PASS <sup>Note1</sup>
FCC Part 15.407(e)	Minimum Emission Bandwidth(6dBm Bandwidth)	PASS <sup>Note2</sup>
FCC Part 15.407(a)	Maximum Conducted Output Power	PASS
FCC Part 15.407(a)	Peak Power Spectral Density	PASS
FCC Part 15.407(g)	Frequency Stability	PASS
FCC Part 15.407(b)	Undesirable emission	PASS
FCC Part 15.407(b)/15.205/15.209	Radiated Emissions	PASS
FCC Part 15.203	Antenna Requirement	PASS
FCC Part 15.407(c)	Operation in the absence of information to the transmit	PASS

Note 1: Apply to U-NII 1 and U-NII 3 band.

Note 2: Apply to U-NII 3 band only.

## 1.3. Test Facility

### 1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No.3011, Shahehexi Road, Nanshan District, Shenzhen, China 518055

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

#### **CNAS-Lab Code: L7497**

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

#### **A2LA-Lab Cert. No. 4343.01**

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### **IC Registration No.: 9618B**

#### **CAB identifier: CN0041**

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B on Jan. 22, 2019.

#### **FCC-Registration No.: 399832**

#### **Designation No.: CN1216**

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

## 1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	$\pm 0.57$ dB	(1)
Transmitter power Radiated	$\pm 2.20$ dB	(1)
Conducted spurious emission 9KHz-40 GHz	$\pm 2.20$ dB	(1)
Occupied Bandwidth	$\pm 0.01$ ppm	(1)
Radiated Emission 9KHz~30MHz	$\pm 3.66$ dB	(1)
Radiated Emission 30~1000MHz	$\pm 4.10$ dB	(1)
Radiated Emission Above 1GHz	$\pm 4.32$ dB	(1)
Conducted Disturbance 0.15~30MHz	$\pm 3.20$ dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

## 2. GENERAL INFORMATION

### 2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

### 2.2. General Description of EUT

Product Name:	Car multimedia infotainment system			
Model/Type reference:	Q1062LT22A			
Power supply:	DC 12V			
<b>5G WIFI :</b>				
Supported type:	20MHz system	40MHz system	80MHz system	160MHz system
	802.11a 802.11n 802.11ac	802.11n 802.11ac	802.11ac	N/A
Operation frequency:	5180 - 5240MHz 5260 - 5320MHz 5500 - 5700MHz 5745 - 5825MHz	5190 - 5795MHz 5270 - 5310MHz 5510 - 5670MHz 5755MHz 5795MHz	5210MHz 5290MHz 5530MHz 5775MHz	N/A
Modulation:	OFDM	OFDM	OFDM	N/A
Channel number:	24	11	2	N/A
Channel separation:	20MHz	40MHz	80MHz	N/A
Antenna type:	Ceramic Antenna			
Antenna gain:	7.21 dBi			
MIMO:	Not Supported			

Note1: For more details, please refer to the user's manual of the EUT.

Note2: Antenna gain provided by the applicant.



## 2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing.

All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band:

Operating band	20MHz		40MHz		80MHz	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
U-NII 1 (5150MHz-5250MHz)	36	5180	38	5190	42	5210
	40	5200				
	44	5220	46	5230		
	48	5240				
U-NII 2A (5120MHz-5350MHz)	52	5260	54	5270	58	5290
	56	5280				
	60	5300	62	5310		
	64	5320				
U-NII 2C (5470MHz-5725MHz)	100	5500	102	5510	106	5530
	104	5520				
	108	5540	110	5550		
	112	5560				
	116	5580	118	5590	--	--
	132	5660	134	5670	--	--
	136	5680			--	--
	140	5700	--	--	--	--
U-NII 3 (5725MHz-5850MHz)	149	5745	151	5755	155	5775
	153	5765				
	157	5785	159	5795		
	161	5805				
	165	5825				

Note:

1. "--"Means no channel(s) available any more.
2. The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

### Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Conducted Output Power Power Spectral Density Emission Bandwidth(26dBm Bandwidth) Minimum Emission Bandwidth(6dBm Bandwidth) Undesirable emission Frequency Stability	11a/OFDM	6 Mbps
	11n(20MHz), 11ac(20MHz)/OFDM	7.2 Mbps
	11n(40MHz), 11ac(40MHz)/OFDM	15.0Mbps
	11ac(80MHz)/OFDM	65.0Mbps

## 2.4. Equipments Used during the Test

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	1166.5950.03	2023/05/04	2024/05/03
	LISN	ROHDE & SCHWARZ	ESH2-Z5	860014/010	2023/05/04	2024/05/03
	Limitator	ROHDE & SCHWARZ	ESH3-Z2	100408	2023/05/04	2024/05/03
Software:						
Name of Software:				Version:		
ES-K1				V1.71		

Radiated Emissions and Band Edge					
Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Active Loop Antenna	Da Ze	ZN30900A	0703	2021/05/13	2024/05/12
Double cone logarithmic antenna	Schwarzbeck	VULB 9168	824	2023/02/13	2026/02/12
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2021/12/23	2024/12/22
Horn Antenna	Ocean Microwave	OBH1004 00	26999002	2021/12/22	2024/12/21
Amplifier	MRT-AP01M 06	MRT	S-001	2023/05/04	2024/05/03
Amplifier	Agilent	8449B	3008A02306	2023/05/04	2024/05/03
Amplifier	Brief&Smart	LNA-4018	2104197	2023/05/05	2024/05/04
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	1166.5950.03	2023/05/04	2024/05/03
Spectrum Analyzer	RS	FSP	1164.4391.38	2023/05/05	2024/05/04
Test software					
Name of Software			Version		
EZ_EMG(Below 1GHz)			V1.1.4.2		
EZ_EMG(Above 1GHz)			V1.1.4.2		

Maximum Conducted Output Power & Power Spectral Density & 6dB Bandwidth & Out-of-band Emissions					
Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Spectrum Analyzer	Keysight	N9020A	MY53420874	2023/05/04	2024/05/03
Temperature/Humidity Meter	Ji Yu	MC501	/	2023/05/09	2024/05/08
Test Software					

Name of Software	Version
TST-PASS	V2.0

The calibration interval was one year

## 2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

## 2.6. Modifications

No modifications were implemented to meet testing criteria.

### 3. TEST CONDITIONS AND RESULTS

#### 3.1. Conducted Emissions Test


##### LIMIT

According to FCC CFR Title 47 Part 15 Subpart C Section 15.207, AC Power Line Conducted Emissions Limits for Licence-Exempt Radio Apparatus as below:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

##### TEST CONFIGURATION



##### TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a Car multimedia infotainment system op system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

**TEST RESULTS**

Remark: 802.11a / 802.11n (HT20) / 802.11ac (HT20) / 802.11n (HT40) / 802.11ac (HT40) / 802.11ac (HT80) mode all have been tested, only worse case is reported


<b>Test Mode</b>	<b>WIFI</b>	<b>Line:</b>	<b>L</b>
------------------	-------------	--------------	----------

*Shenzhen CTL Testing Technology Co., Ltd.*

**Voltage Mains Test FCC PART 15 C**

EUT: Q1062LT22A  
 Manufacturer: Shenzhen RoadRover Technology Co., Ltd  
 Operating Condition: WIFI5G BAND4 5745MHz  
 Test Site: /  
 Operator: JYP  
 Test Specification: DC 12V  
 Comment: /  
 Start of Test: 12/12/2023 / 8:26:55PM

**SCAN TABLE: "Voltage (9K-30M) FIN"**  
 Short Description: 150K-30M Voltage



\*\*\*MES CTL231212243\_fin

**MEASUREMENT RESULT: "CTL231212243\_fin"**

12/12/2023 8:29PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
17.605500	45.00	11.2	60	15.0	QP	L1	GND
17.907000	46.90	11.2	60	13.1	QP	L1	GND
18.501000	47.10	11.2	60	12.9	QP	L1	GND
18.802500	46.40	11.2	60	13.6	QP	L1	GND
21.187500	45.50	11.0	60	14.5	QP	L1	GND
22.087500	45.70	10.9	60	14.3	QP	L1	GND

**MEASUREMENT RESULT: "CTL231212243\_fin2"**

12/12/2023 8:29PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.172500	34.20	10.0	55	20.6	AV	L1	GND
16.134000	25.90	11.2	50	24.1	AV	L1	GND
16.228500	29.10	11.2	50	20.9	AV	L1	GND
17.610000	26.80	11.2	50	23.2	AV	L1	GND
18.501000	27.70	11.2	50	22.3	AV	L1	GND
18.793500	26.70	11.2	50	23.3	AV	L1	GND


Test Mode	WIFI	Line:	N
-----------	------	-------	---

Shenzhen CTL Testing Technology Co., Ltd.

**Voltage Mains Test FCC PART 15 C**

EUT: Q1062LT22A  
 Manufacturer: Shenzhen RoadRover Technology Co., Ltd  
 Operating Condition: WIFI5G BAND4 5745MHz  
 Test Site: /  
 Operator: JYP  
 Test Specification: DC 12V  
 Comment: /  
 Start of Test: 12/12/2023 / 8:24:11PM

**SCAN TABLE: "Voltage (9K-30M)FIN"**  
 Short Description: 150K-30M Voltage



**MEASUREMENT RESULT: "CTL231212242\_fin"**

12/12/2023 8:26PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
17.610000	45.00	11.2	60	15.0	QP	N	GND
17.907000	46.70	11.2	60	13.3	QP	N	GND
18.199500	44.00	11.2	60	16.0	QP	N	GND
18.501000	46.40	11.2	60	13.6	QP	N	GND
18.802500	45.90	11.2	60	14.1	QP	N	GND
19.401000	43.60	11.2	60	16.4	QP	N	GND

**MEASUREMENT RESULT: "CTL231212242\_fin2"**

12/12/2023 8:26PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.172500	33.90	10.0	55	20.9	AV	N	GND
15.981000	25.90	11.2	50	24.1	AV	N	GND
16.170000	27.70	11.2	50	22.3	AV	N	GND
16.228500	29.80	11.2	50	20.2	AV	N	GND
16.381500	26.70	11.2	50	23.3	AV	N	GND
17.871000	24.30	11.2	50	25.7	AV	N	GND

## 3.2. Radiated Emissions

### Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

#### Undesirable emission limits

Requirement	Limit(EIRP)	Limit (Field strength at 3m) <sup>Note1</sup>
15.407(b)(1)	PK:-27(dBm/MHz)	PK:68.2(dBμV/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)		

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$


- (5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
- (6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

#### Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

**TEST CONFIGURATION**


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz





## Test Procedure

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 40GHz.
- The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

- Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

## TEST RESULTS

Remark:


- This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
- All modes U-NII 1,U-NII 2A,U-NII 2C,U-NII 3 All modulations 802.11a / 802.11n (HT20) / 802.11ac (HT20) / 802.11n (HT40) / 802.11ac (HT40) / 802.11ac (HT80) have been tested for below 1GHz test, only the worst case 802.11n (HT20) low channel of U-NII 1 band was recorded.
- All modes U-NII 1,U-NII 2A,U-NII 2C,U-NII 3 All modulations 802.11a / 802.11n (HT20) / 802.11ac (HT20) / 802.11n (HT40) / 802.11ac (HT40) / 802.11ac (HT80) have been tested for above 1GHz test, only the worst case 802.11n (HT20) was recorded.
- Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194



Site LAB Chamber 2  
Limit: FCC Part15 RE-Class C\_30-1000MHz  
EUT: /  
M/N: Q1062LT22A  
Mode: WIFI5.1G 5180MHz  
Note: Shenzhen RoadRover Technology Co., Ltd

Polarization: **Horizontal**  
Power:  
Distance: 3m


Temperature: 25(C)  
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	198.5879	17.99	11.20	29.19	43.50	14.31	peak	100	90	P	
2	248.5519	16.88	12.96	29.84	46.00	16.16	peak	100	259	P	
3	348.0274	25.34	15.42	40.76	46.00	5.24	peak	100	98	P	
4	714.1733	8.04	22.44	30.48	46.00	15.52	peak	100	90	P	
5	842.1296	7.61	25.51	33.12	46.00	12.88	peak	100	250	P	
6	955.4381	6.76	26.36	33.12	46.00	12.88	peak	100	63	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194



Site LAB Chamber 2	Polarization: <b>Vertical</b>	Temperature: 25(C)
Limit: FCC Part15 RE-Class C_30-1000MHz	Power:	Humidity: 50 %
EUT: /	Distance: 3m	
M/N: Q1062LT22A		
Mode: WIFI5.1G 5180MHz		
Note: Shenzhen RoadRover Technology Co., Ltd		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	348.0274	16.64	15.42	32.06	46.00	13.94	peak	100	351	P	
2	649.6597	8.59	21.98	30.57	46.00	15.43	peak	100	324	P	
3	750.1083	8.90	23.80	32.70	46.00	13.30	peak	100	81	P	
4	818.8341	7.78	25.28	33.06	46.00	12.94	peak	100	10	P	
5	909.6667	7.46	25.89	33.35	46.00	12.65	peak	100	2	P	
6	942.1305	6.67	26.33	33.00	46.00	13.00	peak	100	90	P	





**U-NII 3 & 802.11n (HT20) Mode (above 1GHz)**


Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
149 (5745MHz)	5720.00	87.85	PK	H	110.80	22.95	76.34	37.64	9.28	35.41	11.51
	5725.00	94.94	PK	H	122.20	27.26	83.43	37.64	9.28	35.41	11.51
	11490.00	50.44	PK	H	68.20	17.76	32.18	39.69	12.90	34.33	18.26
	--	--	--	--	--	--	--	--	--	--	--
157 (5785MHz)	11570.00	48.74	PK	H	68.20	19.46	30.29	39.71	13.05	34.31	18.45
	--	--	--	--	--	--	--	--	--	--	--
165 (5825MHz)	5850.00	90.5	PK	H	122.50	32	78.96	37.64	9.28	35.38	11.54
	5855.00	87.12	PK	H	110.80	23.68	75.58	37.64	9.28	35.38	11.54
	11650.00	51.19	PK	H	68.20	17.01	32.57	39.73	13.19	34.30	18.62
	--	--	--	--	--	--	--	--	--	--	--

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
149 (5745MHz)	5720.00	89.04	PK	V	110.80	21.76	77.53	37.64	9.28	35.41	11.51
	5725.00	95.77	PK	V	122.20	26.43	84.26	37.64	9.28	35.41	11.51
	11490.00	49.93	PK	V	68.20	18.27	31.67	39.69	12.90	34.33	18.26
	--	--	--	--	--	--	--	--	--	--	--
157 (5785MHz)	11570.00	50.62	PK	V	68.20	17.58	32.17	39.71	13.05	34.31	18.45
	--	--	--	--	--	--	--	--	--	--	--
165 (5825MHz)	5850.00	92.09	PK	V	122.50	30.41	80.55	37.64	9.28	35.38	11.54
	5855.00	85.80	PK	V	110.80	25.00	74.26	37.64	9.28	35.38	11.54
	11650.00	49.49	PK	V	68.20	18.71	30.87	39.73	13.19	34.30	18.62
	--	--	--	--	--	--	--	--	--	--	--

**REMARKS:**

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the other emission levels were very low against the limit.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
6. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20 ,IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;

**Band Edge Test Plots**




5180MHz 802.11n ( HT20 )

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**



Site LAB Chamber 2      Polarization: **Vertical**      Temperature: 25(C)  
 Limit: 5180-5210BAND      Power:      Humidity: 50 %  
 EUT:      Distance: 3m  
 M/N: Q1062LT22A  
 Mode: WIFI5.1G 5180MHz TX  
 Note: Shenzhen RoadRover Technology Co., Ltd

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5150.002	36.84	18.24	55.08	125.20	70.12	peak	150	360	P	
2	5150.002	29.97	18.24	48.21	125.20	76.99	AVG	150	0	P	
3	5155.372	36.51	18.23	54.74	125.20	70.46	peak	150	360	P	
4	5155.372	29.51	18.23	47.74	125.20	77.46	AVG	150	0	P	



5190MHz 802.11n ( HT40 )

Horizontal



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194


**Radiated Emission Measurement**

File :RF-RSE 4

Data :#3005

Date: 2024/01/04

Time: 2:49:12



Site LAB Chamber 2

Polarization: **Horizontal**

Temperature: 25(C)

Limit: 5180-5210BAND

Power:

Humidity: 50 %

EUT:

Distance: 3m

M/N: Q1062LT22A

Mode: WIFI5.1G 5190MHz TX

Note: Shenzhen RoadRover Technology Co., Ltd

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5150.002	36.87	18.24	55.11	125.20	70.09	peak	150	360	P	
2	5150.002	30.08	18.24	48.32	125.20	76.88	AVG	150	0	P	
3	5155.372	36.69	18.23	54.92	125.20	70.28	peak	150	360	P	
4	5155.372	28.91	18.23	47.14	125.20	78.06	AVG	150	0	P	

5190MHz 802.11n ( HT40 )

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**


File :RF-RSE 4

Data #3004

Date: 2024/01/04

Time: 2:48:04

140.0 dBuV/m



Site LAB Chamber 2

Polarization: **Vertical**

Temperature: 25(C)

Limit: 5180-5210BAND

Power:

Humidity: 50 %

EUT:

Distance: 3m

M/N: Q1062LT22A

Mode: WIFI5.1G 5190MHz TX

Note: Shenzhen RoadRover Technology Co., Ltd

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5150.002	37.42	18.24	55.66	125.20	69.54	peak	150	360	P	
2	5150.002	29.99	18.24	48.23	125.20	76.97	AVG	150	0	P	
3	5155.372	36.33	18.23	54.56	125.20	70.64	peak	150	360	P	
4	5155.372	29.55	18.23	47.78	125.20	77.42	AVG	150	0	P	

5210MHz 802.11ac ( HT80 )


Horizontal



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**

File :RF-RSE 4      Data :#3009      Date: 2024/01/04      Time: 2:59:54



Site LAB Chamber 2      Polarization: **Horizontal**      Temperature: 25(C)  
 Limit: 5180-5210BAND      Power:      Humidity: 50 %  
 EUT:      Distance: 3m  
 M/N: Q1062LT22A  
 Mode: WIFI5.1G 5210MHz TX  
 Note: Shenzhen RoadRover Technology Co., Ltd


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5350.124	37.25	18.15	55.40	68.20	12.80	peak	150	360	P	
2	5350.124	30.48	18.15	48.63	68.20	19.57	AVG	150	0	P	
3	5355.494	37.23	18.14	55.37	68.20	12.83	peak	150	360	P	
4	5355.494	30.38	18.14	48.52	68.20	19.68	AVG	150	0	P	

5210MHz 802.11ac ( HT80 )

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194



Site LAB Chamber 2  
Limit: 5180-5210BAND  
EUT:

Polarization: **Vertical**  
Power:  
Distance: 3m

Temperature: 25(C)  
Humidity: 50 %

M/N: Q1062LT22A  
Mode: WIFI5.1G 5210MHz TX

Note: Shenzhen RoadRover Technology Co., Ltd

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5350.124	36.26	18.15	54.41	68.20	13.79	peak	150	360	P	
2	5350.124	29.48	18.15	47.63	68.20	20.57	AVG	150	0	P	
3	5355.494	38.15	18.14	56.29	68.20	11.91	peak	150	360	P	
4	5355.494	31.22	18.14	49.36	68.20	18.84	AVG	150	0	P	

5230MHz 802.11n ( HT40 )

Horizontal



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**


File :RF-RSE 4

Data :#3006

Date: 2024/01/04

Time: 2:51:11

140.0 dBuV/m



Site LAB Chamber 2  
Limit: 5180-5210BAND

Polarization: *Horizontal*

Temperature: 25(C)

EUT:

Power:

Humidity: 50 %

M/N: Q1062LT22A

Distance: 3m

Mode: WIFI5.1G 5230MHz TX

Note: Shenzhen RoadRover Technology Co., Ltd


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5350.124	36.55	18.15	54.70	68.20	13.50	peak	150	360	P	
2	5350.124	29.17	18.15	47.32	68.20	20.88	AVG	150	0	P	
3	5355.494	36.61	18.14	54.75	68.20	13.45	peak	150	360	P	
4	5355.494	29.75	18.14	47.89	68.20	20.31	AVG	150	0	P	

5230MHz 802.11n ( HT40 )

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194



Site LAB Chamber 2  
Limit: 5180-5210BAND  
EUT:

Polarization: **Vertical**  
Power:  
Distance: 3m

Temperature: 25(C)  
Humidity: 50 %

M/N: Q1062LT22A  
Mode: WIFI5.1G 5230MHz TX  
Note: Shenzhen RoadRover Technology Co., Ltd


No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5350.124	38.60	18.15	56.75	68.20	11.45	peak	150	360	P	
2	5350.124	30.97	18.15	49.12	68.20	19.08	AVG	150	0	P	
3	5355.494	36.27	18.14	54.41	68.20	13.79	peak	150	360	P	
4	5355.494	29.44	18.14	47.58	68.20	20.62	AVG	150	0	P	

5240MHz 802.11n ( HT20 )

Horizontal



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194



Site: LAB Chamber 2  
Limit: 5180-5210BAND  
EUT:

Polarization: **Horizontal**  
Power:  
Distance: 3m

Temperature: 25(C)  
Humidity: 50 %

M/N: Q1062LT22A  
Mode: WIFI5.1G 5240MHz TX

Note: Shenzhen RoadRover Technology Co., Ltd

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5350.124	36.00	18.15	54.15	68.20	14.05	peak	150	360	P	
2	5350.124	29.81	18.15	47.96	68.20	20.24	AVG	150	0	P	
3	5355.494	37.07	18.14	55.21	68.20	12.99	peak	150	360	P	
4	5355.494	30.40	18.14	48.54	68.20	19.66	AVG	150	0	P	

5240MHz 802.11n ( HT20 )

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**


File :RF-RSE 4

Data :#3003

Date: 2024/01/04

Time: 2:42:03

140.0 dBuV/m



Site LAB Chamber 2

Polarization: **Vertical**

Temperature: 25(C)

Limit: 5180-5210BAND

Power:

Humidity: 50 %

EUT:

Distance: 3m

M/N: Q1062LT22A

Mode: WIFI5.1G 5240MHz TX

Note: Shenzhen RoadRover Technology Co., Ltd

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5350.124	37.37	18.15	55.52	68.20	12.68	peak	150	360	P	
2	5350.124	30.41	18.15	48.56	68.20	19.64	AVG	150	0	P	
3	5355.494	36.70	18.14	54.84	68.20	13.36	peak	150	360	P	
4	5355.494	28.98	18.14	47.12	68.20	21.08	AVG	150	0	P	



5745MHz 802.11n ( HT20 )

Horizontal



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**


File :RF-RSE 4

Data :#3011

Date: 2024/01/04

Time: 3:05:28

150.0 dBuV/m



Site LAB Chamber 2

Polarization: **Horizontal**

Temperature: 25(C)

Limit: 5725-5850 BAND

Power:

Humidity: 50 %

EUT:

Distance: 3m

M/N: Q1062LT22A

Mode: WIFI5.8G 5745MHz TX

Note: Shenzhen RoadRover Technology Co., Ltd


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5720.323	39.06	18.83	57.89	111.54	53.65	peak	150	360	P	
2	5720.323	31.96	18.83	50.79	111.54	60.75	AVG	150	0	P	
3	5725.097	45.08	18.84	63.92	125.20	61.28	peak	150	360	P	
4	5725.097	38.03	18.84	56.87	125.20	68.33	AVG	150	0	P	

5745MHz 802.11n ( HT20 )

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194



Site LAB Chamber 2	Polarization: <b>Vertical</b>	Temperature: 25(C)
Limit: 5725-5850 BAND	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N: Q1062LT22A		
Mode: WIFI5.8G 5745MHz TX		
Note: Shenzhen RoadRover Technology Co., Ltd		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5720.323	36.28	18.83	55.11	111.54	56.43	peak	150	360	P	
2	5720.323	29.58	18.83	48.41	111.54	63.13	AVG	150	0	P	
3	5725.097	39.81	18.84	58.65	125.20	66.55	peak	150	360	P	
4	5725.097	32.95	18.84	51.79	125.20	73.41	AVG	150	0	P	


5755MHz 802.11n ( HT40 )

Horizontal



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**



Site LAB Chamber 2	Polarization: <b>Horizontal</b>	Temperature: 25(C)
Limit: 5725-5850 BAND	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N: Q1062LT22A		
Mode: WIFI5.8G 5755MHz TX		
Note: Shenzhen RoadRover Technology Co., Ltd		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5720.323	43.04	18.83	61.87	111.54	49.67	peak	150	360	P	
2	5720.323	36.13	18.83	54.96	111.54	56.58	AVG	150	0	P	
3	5725.097	45.48	18.84	64.32	125.20	60.88	peak	150	360	P	
4	5725.097	38.41	18.84	57.25	125.20	67.95	AVG	150	0	P	


5755MHz 802.11n ( HT40 )

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**



Site LAB Chamber 2  
Limit: 5725-5850 BAND  
EUT:

Polarization: **Vertical**  
Power:  
Distance: 3m

Temperature: 25(C)  
Humidity: 50 %

M/N: Q1062LT22A  
Mode: WIFI5.8G 5755MHz TX

Note: Shenzhen RoadRover Technology Co., Ltd

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5720.323	37.78	18.83	56.61	111.54	54.93	peak	150	360	P	
2	5720.323	30.95	18.83	49.78	111.54	61.76	AVG	150	0	P	
3	5725.097	39.86	18.84	58.70	125.20	66.50	peak	150	360	P	
4	5725.097	32.30	18.84	51.14	125.20	74.06	AVG	150	0	P	

5775MHz 802.11ac ( HT80 )


Horizontal



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**

File :RF-RSE 4      Data :#3019      Date: 2024/01/04      Time: 3:22:41



Site LAB Chamber 2      Polarization: **Horizontal**      Temperature: 25(C)  
 Limit: 5725-5850 BAND      Power:      Humidity: 50 %  
 EUT:      Distance: 3m  
 M/N: Q1062LT22A  
 Mode: WIFI5.8G 5775MHz TX  
 Note: Shenzhen RoadRover Technology Co., Ltd


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5850.244	46.05	19.04	65.09	121.64	56.55	peak	150	360	P	
2	5850.244	39.38	19.04	58.42	121.64	63.22	AVG	150	0	P	
3	5855.018	42.62	19.07	61.69	110.79	49.10	peak	150	360	P	
4	5855.018	35.72	19.07	54.79	110.79	56.00	AVG	150	0	P	

5775MHz 802.11ac ( HT80 )

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194



Site LAB Chamber 2  
Limit: 5725-5850 BAND  
EUT:

Polarization: **Vertical**  
Power:  
Distance: 3m

Temperature: 25(C)  
Humidity: 50 %

M/N: Q1062LT22A  
Mode: WIFI5.8G 5775MHz TX  
Note: Shenzhen RoadRover Technology Co., Ltd

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5850.244	40.07	19.04	59.11	121.64	62.53	peak	150	360	P	
2	5850.244	33.13	19.04	52.17	121.64	69.47	AVG	150	0	P	
3	5855.018	37.68	19.07	56.75	110.79	54.04	peak	150	360	P	
4	5855.018	30.20	19.07	49.27	110.79	61.52	AVG	150	0	P	

5795MHz 802.11n ( HT40 )


Horizontal



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**

File :RF-RSE 4      Data :#3017      Date: 2024/01/04      Time: 3:17:51



Site LAB Chamber 2      Polarization: **Horizontal**      Temperature: 25(C)  
 Limit: 5725-5850 BAND      Power:      Humidity: 50 %  
 EUT:      Distance: 3m  
 M/N: Q1062LT22A  
 Mode: WIFI5.8G 5795MHz TX  
 Note: Shenzhen RoadRover Technology Co., Ltd

No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5850.244	38.12	19.04	57.16	121.64	64.48	peak	150	360	P	
2	5850.244	31.69	19.04	50.73	121.64	70.91	AVG	150	0	P	
3	5855.018	38.10	19.07	57.17	110.79	53.62	peak	150	360	P	
4	5855.018	31.03	19.07	50.10	110.79	60.69	AVG	150	0	P	


5795MHz 802.11n ( HT40 )

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**



Site: LAB Chamber 2  
Limit: 5725-5850 BAND  
EUT:  
M/N: Q1062LT22A  
Mode: WIFI5.8G 5795MHz TX  
Note: Shenzhen RoadRover Technology Co., Ltd

Polarization: **Vertical**  
Power:  
Distance: 3m

Temperature: 25(C)  
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5850.244	37.32	19.04	56.36	121.64	65.28	peak	150	360	P	
2	5850.244	30.10	19.04	49.14	121.64	72.50	AVG	150	0	P	
3	5855.018	36.08	19.07	55.15	110.79	55.64	peak	150	360	P	
4	5855.018	29.67	19.07	48.74	110.79	62.05	AVG	150	0	P	



5825MHz 802.11n ( HT20 )


Horizontal



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

**Radiated Emission Measurement**

File :RF-RSE 4      Data :#3012      Date: 2024/01/04      Time: 3:08:16



Site LAB Chamber 2      Polarization: **Horizontal**      Temperature: 25(C)  
 Limit: 5725-5850 BAND      Power:      Humidity: 50 %  
 EUT:      Distance: 3m  
 M/N: Q1062LT22A  
 Mode: WIFI5.8G 5825MHz TX  
 Note: Shenzhen RoadRover Technology Co., Ltd


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5850.244	39.89	19.04	58.93	121.64	62.71	peak	150	360	P	
2	5850.244	32.85	19.04	51.89	121.64	69.75	AVG	150	0	P	
3	5855.018	40.73	19.07	59.80	110.79	50.99	peak	150	360	P	
4	5855.018	33.14	19.07	52.21	110.79	58.58	AVG	150	0	P	

5825MHz 802.11n ( HT20 )

Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194



Site LAB Chamber 2  
Limit: 5725-5850 BAND  
EUT:

Polarization: **Vertical**  
Power:  
Distance: 3m

Temperature: 25(C)  
Humidity: 50 %

M/N: Q1062LT22A  
Mode: WIFI5.8G 5825MHz TX  
Note: Shenzhen RoadRover Technology Co., Ltd

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5850.244	36.73	19.04	55.77	121.64	65.87	peak	150	360	P	
2	5850.244	29.10	19.04	48.14	121.64	73.50	AVG	150	0	P	
3	5855.018	36.23	19.07	55.30	110.79	55.49	peak	150	360	P	
4	5855.018	29.89	19.07	48.96	110.79	61.83	AVG	150	0	P	

### 3.3. Maximum Conducted Average Output Power

#### Limit

##### **FCC requirement:**

##### **For the band 5.15-5.25 GHz.**

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6dBi.

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi.


**For the 5.25-5.35 GHz and 5.47-5.725 GHz bands**, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or  $11\text{dBm} + 10\log B$ , where B is the 26 dB emission bandwidth in megahertz.

**For the band 5.725-5.85 GHz**, the maximum conducted output power over the frequency band of operation shall not exceed 1 W

#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum.

#### Test Configuration



#### Test Results

Raw data reference to Section 2 from CTL2311242081-WF04 Appendix.

### 3.4. Power Spectral Density

#### Limit

##### **FCC requirement:**

##### **For the band 5.15-5.25 GHz.**

(i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17dBm in any 1 MHz band.<sup>note1</sup>

(ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17dBm in any 1 MHz band.<sup>note1</sup>

(iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23dBi.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 MHz band.<sup>note1</sup>

##### **For the 5.25-5.35 GHz and 5.47-5.725 GHz bands**

The maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

##### **IC requirement:**

##### **For the band 5.15-5.25 GHz.**

The e.i.r.p. spectral density shall not exceed 10dBm in any 1.0 MHz band.

##### **Frequency band 5250-5350 MHz**

The power spectral density shall not exceed 11dBm in any 1.0 MHz band

##### **Frequency bands 5470-5600 MHz and 5650-5725 MHz**

The power spectral density shall not exceed 11dBm in any 1.0 MHz band.

##### **For the band 5.725 - 5.85 GHz**

The maximum power spectral density shall not exceed 30dBm in any 500 kHz band.<sup>note1, note2</sup>

Note1: If transmitting antennas of directional gain greater than 6dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

**Test Procedure**

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 1MHz for U-NII 1, U-NII 2A, U-NII C band and 510KHz for U-NII 3 band.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Set the span to encompass the entire EBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.

**Test Configuration****Test Results**

Raw data reference to Section 3 from CTL2311242081-WF04 Appendix.

### 3.5. Emission Bandwidth (26dBm Bandwidth)

#### Limit

N/A

#### Test Procedure

1. Set resolution bandwidth (RBW) = approximately 1 % of the EBW.
2. Set the video bandwidth (VBW) > RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW / EBW ratio is approximately 1 %.

#### Test Configuration



#### Test Results

Raw data reference to Section 1 from CTL2311242081-WF04 Appendix.

### 3.6. Minimum Emission Bandwidth (6dBm Bandwidth)

#### Limit

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 kHz for the band 5.725-5.85 GHz

#### Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth 3 x RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### Test Configuration



#### Test Results


Raw data reference to Section 1 from CTL2311242081-WF04 Appendix.

### 3.7. Frequency Stability

#### LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

#### TEST CONFIGURATION



#### TEST PROCEDURE

##### **Frequency Stability under Temperature Variations:**

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

##### **Frequency Stability under Voltage Variations:**

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ( $\pm 15\%$ ) and endpoint, record the maximum frequency change.

#### TEST RESULTS

Raw data reference to Section 4 from Appendix.



### 3.8. Antenna Requirement

#### Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited


And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

#### **Refer to statement below for compliance**

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.



#### Antenna Connected Construction

The maximum gain of antenna was 7.21dBi  
PSD Limit= $10-(7.21-6)=9.79$



5G WIFI Antenna

### 4. Test Setup Photos of the EUT



## 5. Photos of the EUT

Reference to the test report No. CTL2311242081-WF01

\*\*\*\*\* End of Report \*\*\*\*\*