

# TEST REPORT

Applicant Name: Nimba Wellness Technology Limited  
Address: RM 908 Two Grand Tower 625 Nathan Rd Kln Hong Kong  
Report Number: 2401S28724E-RF-00  
FCC ID: 2BFTS-OFLO

## Test Standard (s)

FCC PART 15.247

## Sample Description

Product Type: NIMBA OFLO Sound Machine  
Model No.: OFLO  
Multiple Model(s) No.: N/A  
Trade Mark: NIMBA  
Date Received: 2024/04/26  
Issue Date: 2024/06/19

Test Result:	Pass <sup>▲</sup>
--------------	-------------------

▲ In the configuration tested, the EUT complied with the standards above.

## Prepared and Checked By:

*wills.yu*

Wills Yu  
RF Engineer

## Approved By:

*Nancy Wang*

Nancy Wang  
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

## Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

**TABLE OF CONTENTS**

**DOCUMENT REVISION HISTORY .....4**

**GENERAL INFORMATION.....5**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....5

    OBJECTIVE .....5

    TEST METHODOLOGY .....5

    MEASUREMENT UNCERTAINTY .....6

    TEST FACILITY .....6

**SYSTEM TEST CONFIGURATION .....7**

    DESCRIPTION OF TEST CONFIGURATION .....7

    EQUIPMENT MODIFICATIONS .....7

    EUT EXERCISE SOFTWARE .....7

    DUTY CYCLE .....8

    SUPPORT EQUIPMENT LIST AND DETAILS .....9

    EXTERNAL I/O CABLE.....9

    BLOCK DIAGRAM OF TEST SETUP .....10

**SUMMARY OF TEST RESULTS .....11**

**TEST EQUIPMENT LIST .....12**

**§1.1307(B)(3)(I)(A)&§2.1091 –RF EXPOSURE.....13**

    APPLICABLE STANDARD .....13

    RESULT .....13

**FCC §15.203 - ANTENNA REQUIREMENT.....14**

    APPLICABLE STANDARD .....14

    ANTENNA CONNECTOR CONSTRUCTION .....14

**FCC §15.207 (A) - AC LINE CONDUCTED EMISSIONS .....15**

    APPLICABLE STANDARD .....15

    EUT SETUP .....15

    EMI TEST RECEIVER SETUP.....15

    TEST PROCEDURE .....15

    FACTOR & OVER LIMIT CALCULATION.....16

    TEST DATA .....16

**FCC §15.209, §15.205 & §15.247(D) – UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS19**

    APPLICABLE STANDARD .....19

    EUT SETUP .....19

    EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....20

    TEST PROCEDURE .....21

    FACTOR & OVER LIMIT/MARGIN CALCULATION .....21

    TEST DATA .....21

**FCC §15.247(A) (2) - 6 DB EMISSION BANDWIDTH .....36**

    STANDARD APPLICABLE .....36

    TEST PROCEDURE .....36

    TEST DATA .....36

**FCC §15.247(B) (3) - PEAK OUTPUT POWER MEASUREMENT .....39**  
    APPLICABLE STANDARD .....39  
    TEST PROCEDURE .....39  
    TEST DATA .....39

**FCC §15.247(E) - POWER SPECTRAL DENSITY.....43**  
    APPLICABLE STANDARD .....43  
    TEST PROCEDURE .....43  
    TEST DATA .....43

**FCC §15.247(D) - 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....47**  
    APPLICABLE STANDARD .....47  
    TEST PROCEDURE .....47  
    TEST DATA .....48

**EUT PHOTOGRAPHS.....50**

**TEST SETUP PHOTOGRAPHS .....51**

**DOCUMENT REVISION HISTORY**

Revision Number	Report Number	Description of Revision	Date of Revision
0	2401S28724E-RF-00	Original Report	2024/06/19

**GENERAL INFORMATION**

**Product Description for Equipment under Test (EUT)**

Product	NIMBA OFLO Sound Machine
Tested Model	OFLO
Multiple Model(s)	N/A
Frequency Range	BLE 1M/2M: 2402-2480MHz
Maximum Conducted Peak Output Power	BLE: -5.96 dBm
Modulation Technique	BLE: GFSK
Antenna Specification <sup>#</sup>	-5.09dBi (provided by the applicant)
Voltage Range	DC 5V from adapter or DC 3.7V from battery
Sample serial number	2KL-1 for Conducted and Radiated Emissions Test 2KL-2 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	Model: XH075-0500-1000LU Input: AC 100-240V~50/60Hz 0.2A MAX Output: DC 5.0V, 1.0A

**Objective**

This report is in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209, 15.247 rules.

**Test Methodology**

All tests and measurements indicated in this document were performed in accordance ANSI C63.10-2013.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

## Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF output power, conducted		0.72 dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.94dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.84dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	4.55dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	4.85dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.05dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.16dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

### Equipment Modifications

No modification was made to the EUT tested.


### EUT Exercise Software

“BT Tool v1.1.2”<sup>#</sup> exercise software was used and the power level is 3<sup>#</sup>. The software and power level was provided by the applicant.

Duty cycle

Test Modes	T <sub>on</sub> (ms)	T <sub>on+off</sub> (ms)	Duty Cycle (%)	1/T <sub>on</sub> (Hz)	VBW Setting (KHz)
BLE 1Mbps	0.400	0.628	63.69	2500	3
BLE 2Mbps	0.215	0.619	34.73	4651	5


BLE 1M



ProjectNo.:2401S28724E-RF Tester:Allen Bai  
 Date: 14.MAY.2024 20:50:53



**BLE 2M**



ProjectNo.:2401S28724E-RF Tester:Allen Bai  
 Date: 14.MAY.2024 21:07:38

**Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
Bull	Receptacle	Unknown	Unknown

**External I/O Cable**


Cable Description	Length (m)	From Port	To
Un-shielding Detachable Cable	1.2	EUT	Adapter
Un-shielding Un-detachable Cable	0.8	Receptacle	LISN/AC Mains

### Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions:



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307(b)(3)(i)(A)& §2.1091	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Conducted Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/01/16	2025/01/15
Rohde & Schwarz	LISN	ENV216	101613	2024/01/16	2025/01/15
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2023/08/03	2024/08/02
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
<b>Radiated Emission Test</b>					
R&S	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
Sonoma instrument	Pre-amplifier	310 N	186238	2023/06/08	2024/06/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
BACL	Active Loop Antenna	1313-1A	4031911	2024/03/21	2025/03/20
Unknown	Cable	Chamber Cable 1	F-03-EM236	2023/08/03	2024/08/02
Unknown	Cable	Chamber Cable 4	EC-007	2023/08/03	2024/08/02
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
COM-POWER	Pre-amplifier	PA-122	181919	2023/06/29	2024/06/28
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2023/10/08	2024/10/07
Unknown	RF Cable	UFA147	219661	2023/10/08	2024/10/07
Unknown	RF Cable	XH750A-N	J-10M	2023/10/08	2024/10/07
SNSD	2.4G Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2023/08/03	2024/08/02
A.H.System	Pre-amplifier	PAM-1840VH	190	2023/08/02	2024/08/01
Electro-Mechanics Co	Horn Antenna	3116	2026	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
<b>RF Conducted Test</b>					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200982	2023/12/18	2024/12/17
Unknown	10dB Attenuator	Unknown	F-03-EM190	2023/07/04	2024/07/03
Unknown	RF Cable	65475	01670515	2023/07/04	2024/07/03

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**§1.1307(b)(3)(i)(A)&§2.1091 –RF EXPOSURE**

**Applicable Standard**

According to FCC §2.1091 and §1.1307(b) (3), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance

1-mW Test Exemption:

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

**Result**

**For worst case:**

Mode	Frequency (MHz)	Tune up conducted power <sup>#</sup> (dBm)	Antenna Gain <sup>#</sup>	Maximum Tune up conducted power		Exemption Limit (mW)	Test Exemption
				dBm	mW		
BLE	2402-2480	-5.50	-5.09	-5.50	0.28	1	Yes

**Result: Compliant**

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

### **Antenna Connector Construction**

The EUT has an internal antenna arrangement which was permanently attached and the maximum antenna gain<sup>#</sup> is -5.09 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


**Result: Compliant**

**FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS**

**Applicable Standard**

FCC§15.207

**EUT Setup**



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

**EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

**Test Procedure**

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

## Test Data

### Environmental Conditions


<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	62 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Macy Shi on 2024-05-22.*

*EUT operation mode: Transmitting (Maximum output power mode, BLE 1M, Middle Channel)*




AC 120V/60 Hz, Line



Condition: Line  
 Project : 2401S28724E-RF  
 test Mode: Macy.shi  
 : BLE

	Read Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	2.18	15.50	36.01	10.31	10.20	46.00	-9.99	Average
2	2.18	18.40	38.91	10.31	10.20	56.00	-17.09	QP
3	2.92	16.30	36.91	10.35	10.26	46.00	-9.09	Average
4	2.92	19.10	39.71	10.35	10.26	56.00	-16.29	QP
5	3.64	21.10	41.75	10.39	10.26	46.00	-4.25	Average
6	3.64	23.90	44.55	10.39	10.26	56.00	-11.45	QP
7	4.75	2.50	23.19	10.46	10.23	46.00	-22.81	Average
8	4.75	17.20	37.89	10.46	10.23	56.00	-18.11	QP
9	5.11	2.30	23.01	10.49	10.22	50.00	-26.99	Average
10	5.11	15.10	35.81	10.49	10.22	60.00	-24.19	QP
11	21.37	4.00	24.83	10.68	10.15	50.00	-25.17	Average
12	21.37	16.80	37.63	10.68	10.15	60.00	-22.37	QP

AC 120V/60 Hz, Neutral



Condition: Neutral  
 Project : 2401S28724E-RF  
 tester : Macy.shi  
 Note : BLE

	Read Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	2.18	11.89	32.23	10.14	10.20	46.00	-13.77	Average
2	2.18	14.69	35.03	10.14	10.20	56.00	-20.97	QP
3	2.92	13.20	33.72	10.26	10.26	46.00	-12.28	Average
4	2.92	22.40	42.92	10.26	10.26	56.00	-13.08	QP
5	3.64	17.20	37.82	10.36	10.26	46.00	-8.18	Average
6	3.64	19.40	40.02	10.36	10.26	56.00	-15.98	QP
7	4.36	13.40	34.05	10.40	10.25	46.00	-11.95	Average
8	4.36	17.00	37.65	10.40	10.25	56.00	-18.35	QP
9	5.84	1.90	22.52	10.40	10.22	50.00	-27.48	Average
10	5.84	13.20	33.82	10.40	10.22	60.00	-26.18	QP
11	6.56	4.00	24.62	10.40	10.22	50.00	-25.38	Average
12	6.56	10.80	31.42	10.40	10.22	60.00	-28.58	QP


## FCC §15.209, §15.205 & §15.247(D) – UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### EUT Setup


9 kHz-30MHz:



30MHz-1GHz:



**Above 1GHz:**



The radiated emission tests were performed in the 3meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.205, FCC 15.209, FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1-25 GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T_{on}$

Note:  $T_{on}$  is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

**Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

**Factor & Over Limit/Margin Calculation**

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	22~25.3 °C
<b>Relative Humidity:</b>	50~54 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Anson Su on 2024-05-09 for below 1GHz and Tyler Wu from 2024-05-11 to 2024-06-19 for above 1GHz.*

*EUT operation mode: Transmitting*


*Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.*

**9 kHz-30MHz(Maximum output power, BLE 1M, Middle Channel) :**

*The amplitude of spurious emissions attenuated more than 20 dB below the limit was not recorded.*

**30MHz-1GHz (Maximum output power, BLE 1M, Middle Channel):**


**Horizontal**



Site : Chamber A  
 Condition : 3m Horizontal  
 Project Number: 2401S28724E-RF  
 Note : BLE  
 Tester : Anson Su

	Freq Factor		Read Level		Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	41.04	-12.19	25.53	13.34	40.00	-26.66	QP
2	79.28	-18.19	37.50	19.31	40.00	-20.69	QP
3	164.26	-14.10	46.30	32.20	43.50	-11.30	QP
4	206.31	-13.61	45.01	31.40	43.50	-12.10	QP
5	282.24	-13.40	40.74	27.34	46.00	-18.66	QP
6	762.04	-5.48	26.92	21.44	46.00	-24.56	QP

**Vertical**



Site : Chamber A  
 Condition : 3m Vertical  
 Project Number: 2401S28724E-RF  
 Note : BLE  
 Tester : Anson Su

	Freq Factor		Read Level		Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	48.61	-17.88	35.55	17.67	40.00	-22.33	QP
2	79.28	-18.73	46.11	27.38	40.00	-12.62	QP
3	160.98	-14.21	41.32	27.11	43.50	-16.39	QP
4	205.31	-14.70	41.10	26.40	43.50	-17.10	QP
5	581.47	-8.24	28.38	20.14	46.00	-25.86	QP
6	818.12	-5.30	26.93	21.63	46.00	-24.37	QP




**1-25 GHz:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/AV					
<b>BLE 1M</b>							
Low Channel 2402MHz							
2372.34	55.06	PK	H	-2.93	52.13	74	-21.87
2372.34	41.32	AV	H	-2.93	38.39	54	-15.61
2373.27	55.47	PK	V	-2.93	52.54	74	-21.46
2373.27	41.78	AV	V	-2.93	38.85	54	-15.15
4804.00	51.25	PK	H	2.42	53.67	74	-20.33
4804.00	45.32	AV	H	2.42	47.74	54	-6.26
4804.00	51.08	PK	V	2.42	53.50	74	-20.50
4804.00	44.37	AV	V	2.42	46.79	54	-7.21
Middle Channel 2440MHz							
4880.00	52.98	PK	H	2.56	55.54	74	-18.46
4880.00	47.69	AV	H	2.56	50.25	54	-3.75
4880.00	51.74	PK	V	2.56	54.30	74	-19.70
4880.00	46.32	AV	V	2.56	48.88	54	-5.12
High Channel 2480MHz							
4960.00	51.86	PK	H	2.68	54.54	74	-19.46
4960.00	46.89	AV	H	2.68	49.57	54	-4.43
4960.00	51.24	PK	V	2.68	53.92	74	-20.08
4960.00	45.57	AV	V	2.68	48.25	54	-5.75
<b>BLE 2M</b>							
Low Channel 2402MHz							
2334.83	55.13	PK	H	-3.03	52.10	74	-21.90
2334.83	42.08	AV	H	-3.03	39.05	54	-14.95
2383.69	55.56	PK	V	-2.93	52.63	74	-21.37
2383.69	42.57	AV	V	-2.93	39.64	54	-14.36
4804.00	50.93	PK	H	2.42	53.35	74	-20.65
4804.00	42.07	AV	H	2.42	44.49	54	-9.51
4804.00	50.26	PK	V	2.42	52.68	74	-21.32
4804.00	41.49	AV	V	2.42	43.91	54	-10.09
Middle Channel 2440MHz							
4880.00	54.08	PK	H	2.56	56.64	74	-17.36
4880.00	45.34	AV	H	2.56	47.90	54	-6.10
4880.00	53.75	PK	V	2.56	56.31	74	-17.69
4880.00	44.72	AV	V	2.56	47.28	54	-6.72
High Channel 2480MHz							
4960.00	53.87	PK	H	2.68	56.55	74	-17.45
4960.00	45.64	AV	H	2.68	48.32	54	-5.68
4960.00	52.75	PK	V	2.68	55.43	74	-18.57
4960.00	44.92	AV	V	2.68	47.60	54	-6.40


**Note:**

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor  
 Corrected Amplitude/Level = Corrected Factor + Reading  
 Margin = Corrected Amplitude/Level - Limit  
 The other spurious emission which is in the noise floor level was not recorded.

**Test plots for Band Edge Measurements (Radiated):**




BLE 1M			
Test Channel:	2480MHz	Ant. Polar. :	Vertical



Condition : Vertical  
 Project No.: 2401S28724E-RF  
 Tester : Tyler Wu  
 Note : BLE1M\_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.637	-3.17	37.96	34.79	54.00	-19.21	Average
2	2483.637	-3.17	54.81	51.64	74.00	-22.36	peak


BLE 2M			
Test Channel:	2480MHz	Ant. Polar. :	Horizontal



Condition : Horizontal  
 Project No.: 2401S28724E-RF  
 Tester : Tyler Wu  
 Note : BLE2M\_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2485.297	-3.17	42.34	39.17	54.00	-14.83	Average
2	2485.297	-3.17	53.94	50.77	74.00	-23.23	peak


BLE 2M			
Test Channel:	2480MHz	Ant. Polar. :	Vertical




Condition : Vertical  
 Project No.: 2401S28724E-RF  
 Tester : Tyler Wu  
 Note : BLE2M\_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2493.315	-3.19	42.51	39.32	54.00	-14.68	Average
2	2493.315	-3.19	54.70	51.51	74.00	-22.49	peak

Listed with the worst harmonic margin test plot:



Vertical




1-4GHz

Condition : Vertical  
 Project No.: 2401S28724E-RF  
 Tester : Tyler Wu  
 Note : BLE1M\_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3952.260	-0.16	35.99	35.83	54.00	-18.17	Average
2	3952.260	-0.16	48.33	48.17	74.00	-25.83	Peak

Horizontal




4-18GHz

Condition : Horizontal  
 Project No.: 2401S28724E-RF  
 Tester : Tyler Wu  
 Note : BLE1M\_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4960.000	2.68	46.89	49.57	54.00	-4.43	Average
2	4960.000	2.68	51.86	54.54	74.00	-19.46	Peak
3	17998.370	24.61	22.85	47.46	54.00	-6.54	Average
4	17998.370	24.61	37.64	62.25	74.00	-11.75	Peak



Vertical




4-18GHz

Condition : Vertical  
 Project No.: 2401S28724E-RF  
 Tester : Tyler Wu  
 Note : BLE1M\_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4960.000	2.68	45.57	48.25	54.00	-5.75	Average
2	4960.000	2.68	51.24	53.92	74.00	-20.08	Peak
3	17972.280	24.42	23.04	47.46	54.00	-6.54	Average
4	17972.280	24.42	37.92	62.34	74.00	-11.66	Peak

**Horizontal**


18-25GHz



Condition : Horizontal  
 Project No.: 2401S28724E-RF  
 Tester : Tyler Wu  
 Note : BLE1M\_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	24574.930	18.90	28.97	47.87	54.00	-6.13	Average
2	24574.930	18.90	42.55	61.45	74.00	-12.55	Peak

**Vertical**



18-25GHz

Condition : Vertical  
 Project No.: 2401S28724E-RF  
 Tester : Tyler Wu  
 Note : BLE1M\_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	24408.710	18.79	28.95	47.74	54.00	-6.26	Average
2	24408.710	18.79	42.88	61.67	74.00	-12.33	Peak

## FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH

### Standard Applicable


According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



### Test Data

#### Environmental Conditions

<b>Temperature:</b>	24 °C
<b>Relative Humidity:</b>	46 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Allen Bai on 2024-05-14*


*EUT operation mode: Transmitting*

**Test Result: Compliant.**

Test Modes	Test Channel	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
BLE 1M	Lowest	2402	0.669	≥0.5
	Middle	2440	0.669	≥0.5
	Highest	2480	0.669	≥0.5
BLE 2M	Lowest	2402	1.164	≥0.5
	Middle	2440	1.152	≥0.5
	Highest	2480	1.158	≥0.5

6 dB Bandwidth





## **FCC §15.247(b) (3) - PEAK OUTPUT POWER MEASUREMENT**


### **Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### **Test Procedure**

Test Method: ANSI C63.10-2013 Clause 11.9.1.1

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	24 °C
<b>Relative Humidity:</b>	46 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Allen Bai on 2024-05-14*


*EUT operation mode: Transmitting*

***Test Result: Compliant.***

Test Modes	Test Frequency (MHz)	Peak Conducted Output Power (dBm)	Limits (dBm)
BLE 1M	2402	-6.54	$\leq 30$
	2440	-5.96	$\leq 30$
	2480	-6.20	$\leq 30$
BLE 2M	2402	-6.64	$\leq 30$
	2440	-6.00	$\leq 30$
	2480	-6.26	$\leq 30$







## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard


According to FCC §15.247(e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



### Test Data

#### Environmental Conditions


<b>Temperature:</b>	24 °C
<b>Relative Humidity:</b>	46 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Allen Bai on 2024-05-14.*

*Test Mode: Transmitting*

***Test Result: Compliant.***

Test Modes	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BLE 1M	2402	-23.59	≤8.00
	2440	-22.96	≤8.00
	2480	-23.26	≤8.00
BLE 2M	2402	-26.49	≤8.00
	2440	-25.76	≤8.00
	2480	-26.12	≤8.00






## **FCC §15.247(d) - 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

### **Test Procedure**



Test Method: ANSI C63.10-2013 Clause 11.11

1. Set the RBW =100 kHz.
2. Set the VBW  $\geq 3 \times$  RBW.
3. Detector = peak
4. Sweep time = auto couple.
5. Trace mode=max hold
6. All trace to fully stabilize
7. Use the peak marker function to determine the maximum amplitude level.  
Ensure that amplitude of all unwanted emissions outside of the authorized frequency band(excluding restricted frequency bands) is attenuated by at least the minimum requirement specified in 11.11.  
Report the three highest emissions relative to the limit.

**Test Data**


**Environmental Conditions**

<b>Temperature:</b>	24 °C
<b>Relative Humidity:</b>	46 %
<b>ATM Pressure:</b>	101.0 kPa


The testing was performed by Allen Bai on 2024-05-14.

EUT operation mode: Transmitting

**Test Result: Compliant.**







---

## **EUT PHOTOGRAPHS**

---

Please refer to the attachment 2401S28724E-RF External photo and 2401S28724E-RF Internal photo.

## **TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment 2401S28724E-RF Test Setup photo.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***