

SPECIFICATIONS FOR APPROVAL

Customer Name: Shenzhen Yolanda Technology Co., Ltd.

Product Name: BT Antenna

Product Model: C21001G11

Address: Room 201, jinfulai Building, No.49-1, Dabao Road, Dalang Area, Xinan Street, Baoan, Shenzhen, China

Write By : _____

Issued Date: 2022-9-15


CUSTOMER

ENGINEER R&D DEPT	BUSSINESS DEPT	APPROVED BY

SOUTHSTAR

R & D D E P T	ENGINEER R&D DEPT	APPROVAL

The basic parameters:


A. Electrical Characteristics	
Frequency	2400 MHz ~2500 MHz
VSWR	< 2
Efficiency	>40%
Impedance	50 Ohm
Polarization	Linear
Gain	>0.5dbi
B. Material & Mechanical Characteristics	
Material of Radiator	PCB black PIFA
Cable Type	
Connector Type	
Dimension	
C. Environmental	
Operation Temperature	-10 °C ~ + 50 °C
Storage Temperature	- 30 °C ~ + 85 °C

Test Equipment & Conditions


1. Network Analyzers :

Agilent 8753D 5071B


2. 3D Chamber Test System



(Testing by 3D anechoic chamber)





Phi axis test




Theta axis test


3. Antenna Impedance: S11 (parameter)




4. Total Efficiency-2.4G:




5. GAIN-2.4G:




6. 01 directional diagram (xy plane, Z=0)




6.02 directional diagram (xy plane, Y=0)



6.03 directional diagram(YZ plane, X=0)



6.03 Apple Chart



7. Installation method

