


Antenna Specification

Specifications Summary


ITEM	SPEC.
Model Name	PCB Antenna
Frequency	2400-2500 MHz
MAX. GAIN	-0.58 dBi
Polarization	Horizontal
Azimuth Beam Pattern	Omni-directional
Impedance	50 Ω



Manufacturer	Shenzhen CHYUHSIN Intelligent Technology Co., Ltd.
Address	202, Building A1, Fuqiao 6th Industrial Park, Xintian Community, Fuhai Street, Bao'an District, Shenzhen City, China.
Test company	ADVANCED CERAMIC X CORP.
Test Address	16 Tzu Chiang Road, Hsinchu Industrial District Hsinchu Hsien 303, Taiwan
Test Date	2023-08-10
Test Instrument	vector network analyzer - R&S ZVB20

1. Main antenna : 2400MHz

1.1 Horizontal



Frequency(MHZ): **2441**


Antenna Polarity: **Horizontal**

Maximum Value(dBi): **-0.58**

Average Gain(dBi) : **-3.32**

Minimum Gain(dBi): **-53.04**

1.2 Vertical



Frequency(MHZ): **2441**

Antenna Polarity: **Vertical**


Maximum Value(dBi): **-4.91**

Average Gain(dBi) : **-6.64**

Minimum Gain(dBi): **-48.4**

2. Main antenna : 2450MHz

2.1 Horizontal



Frequency(MHZ): **2441**


Antenna Polarity: **Horizontal**

Maximum Value(dBi): **-1.29**

Average Gain(dBi) : **-4.46**

Minimum Gain(dBi): **-55.84**

2.2 Vertical



Frequency(MHZ): **2441**

Antenna Polarity: **Vertical**


Maximum Value(dBi): **-4.94**

Average Gain(dBi) : **-7.64**

Minimum Gain(dBi): **-46.8**

3. Main antenna : 2500MHz

3.1 Horizontal



Frequency(MHZ): **2441**


Antenna Polarity: **Horizontal**

Maximum Value(dBi): **-1.26**

Average Gain(dBi) : **-3.44**

Minimum Gain(dBi): **-54.71**

3.2 Vertical



Frequency(MHZ): **2441**

Antenna Polarity: **Vertical**

Maximum Value(dBi): **-4.98**

Average Gain(dBi) : **-6.85**

Minimum Gain(dBi): **-45.82**