

FCC ID: 2BG88SU602

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
BLE(1M)	2.402	-0.56	1.48	1.5±1	2.5	1.78	<5	0.55121	3.00	YES
	2.440	0.67	1.43	1.5±1	2.5	1.78	<5	0.55555	3.00	YES
	2.480	1.36	1.48	1.5±1	2.5	1.78	<5	0.56009	3.00	YES
BLE(2M)	2.402	-0.45	1.55	1.5±1	2.5	1.78	<5	0.55121	3.00	YES
	2.440	0.75	1.49	1.5±1	2.5	1.78	<5	0.55555	3.00	YES
	2.480	1.52	1.52	1.5±1	2.5	1.78	<5	0.56009	3.00	YES

Conclusion:

For the max result : $0.55555 \leq 3.0$ for 1g SAR, SAR is not required.

Signature:



Date: 2024-07-11

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.