


# FCC TEST REPORT

**Report No.** ..... : NTC-ER2404054

**Applicant's name** ..... : IQ Group (WuNing) Ltd.

**Address** ..... : Tong Tuo Industrial Park, Wu Ning Industrial Region,  
Wu Ning County, Jiu Jiang City, Jiang Xi, China



## DONGGUAN NEW TESTING CENTRE CO., LTD

•Address: 1F & 3F, No. 1 the 1st North Industry Road Songshan Lake Science & Technology Park Dongguan, People's Republic of China 523808  
•Tel: +86-769-22212079      •Web: <http://www.ntc-cert.com>      •E-mail: [dave@ntc-cert.com](mailto:dave@ntc-cert.com)

## TEST REPORT DECLARE

|                             |   |
|-----------------------------|---|
| <b>FCC ID</b>               | : 2BGCM-IQ30  |
| <b>Applicant</b>            | : IQ Group (WuNing) Ltd.  |
| <b>Address</b>              | : Tong Tuo Industrial Park, Wu Ning Industrial Region, Wu Ning County, Jiu Jiang City, Jiang Xi, China                          |
| <b>Equipment under Test</b> | : IQ Wireless Door Chimes   |
| <b>Model/Type reference</b> | : IQ30  |
| <b>List Model(s)</b>        | : IQ33, WD-1010, IQ101, WD-2010, IQ201, WD-2010-F, IQ201F, WD-3010, IQ301, IQ401W, IQ302, IQ401B                                |
| <b>Trade Mark</b>           | : IQ America, Lumiqs, IQ-group  |
| <b>Manufacturer</b>         | : IQ Group (WuNing) Ltd.  |
| <b>Address</b>              | : Tong Tuo Industrial Park, Wu Ning Industrial Region, Wu Ning County, Jiu Jiang City, Jiang Xi, China                          |
| <b>Test Laboratory</b>      | : Dongguan New Testing Centre Co., Ltd  |
| <b>Address</b>              | : 1F & 3F, No. 1 the 1st North Industry Road Songsan Lake Science & Technology Park Dongguan, People's Republic of China 523808 |

### Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C 15.231, ANSI C63.10:2020.

### We Declare:

The equipment described above is tested by Dongguan New Testing Centre Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan New Testing Centre Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.


**After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.**

|                      |                                |
|----------------------|--------------------------------|
| <b>Report No.:</b>   | NTC-ER2404054                  |
| <b>Date of Test:</b> | Apr. 24, 2024 to May. 13, 2024 |

**Prepared By:**



Jack Liu/Engineer



Dave Gao/LAB Manager

## \*\* Modified History \*\*

**Table of Contents**

|   | <b>Page</b> |
|---|-------------|
| <b>1. SUMMARY.....</b>                                  | <b>4</b>    |
| 1.1. TEST STANDARDS.....                                | 4           |
| 1.2. TEST DESCRIPTION.....                              | 4           |
| 1.3. TEST FACILITY .....                                | 5           |
| <b>2. GENERAL INFORMATION.....</b>                      | <b>6</b>    |
| 2.1. ENVIRONMENTAL CONDITIONS .....                     | 6           |
| 2.2. GENERAL DESCRIPTION OF EUT .....                   | 6           |
| 2.3. RELATED SUBMITTAL(s) / GRANT (s) .....             | 6           |
| 2.4. MODIFICATIONS.....                                 | 6           |
| <b>3. TEST CONDITIONS AND RESULTS .....</b>             | <b>7</b>    |
| 3.1. CONDUCTED EMISSION (AC MAIN) .....                 | 7           |
| 3.2. RADIATED EMISSION .....                            | 9           |
| 3.3. 20DB BANDWIDTH.....                                | 15          |
| 3.4. DEACTIVATION TIME .....                            | 17          |
| 3.5. ANTENNA REQUIREMENT.....                           | 18          |
| <b>4. TEST SETUP PHOTOS OF THE EUT .....</b>            | <b>19</b>   |
| <b>5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</b> | <b>20</b>   |

## 1. SUMMARY

### 1.1. Test Standards

The tests were performed according to following standards:

[\*\*FCC Rules Part 15.231:\*\*](#) Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.

[\*\*ANSI C63.10:2020 :\*\*](#) American National Standard for Testing Unlicensed Wireless Devices

### 1.2. Test Description

| <b>FCC and IC Requirements</b>     |   |      |
|------------------------------------|---|------|
| FCC Part 15.207                    | Conducted Emission                              | N/A  |
| FCC Part 15.231(a)(1)              | Automatically Deactivate                        | PASS |
| FCC Part 15.231(b)                 | Electric Field Strength of Fundamental Emission | PASS |
| FCC Part 15.205 &15.209& 15.231(b) | Electric Field Strength of Spurious Emission    | PASS |
| FCC Part 15.231(c)                 | -20dB bandwidth                                 | PASS |

Remark: The measurement uncertainty is not included in the test result.

## 1.3. Test Facility

### 1.3.1 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

| Test Item   | Uncertainty           |
|---|-----------------------|
| Uncertainty for Conduction emission test                  | 2.44dB                |
| Uncertainty for Radiation Emission test<br>(30MHz – 1GHz) | 3.14 dB (Polarize: V) |
|   | 3.16 dB (Polarize: H) |
| Uncertainty for Radiation Emission test<br>(1GHz – 18GHz) | 4.27 dB (Polarize: V) |
|   | 4.51 dB (Polarize: H) |
| Uncertainty for conducted RF Power                        | 0.63dB                |
| Stop Transmitting Time Test                               | ±0.5%                 |
| Uncertainty for frequency error                           | 5.8 x 10-8            |

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2. GENERAL INFORMATION

### 2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

|                     |         |
|---------------------|---------|
| Normal Temperature: | 25°C    |
| Relative Humidity:  | 55 %    |
| Air Pressure:       | 101 kPa |

### 2.2. General Description of EUT

|                       |                         |
|-----------------------|-------------------------|
| Product Name:         | IQ Wireless Door Chimes |
| Model/Type reference: | IQ30                    |
| Power supply:         | DC 3V                   |
| Modulation:           | ASK                     |
| Operation frequency:  | 433.90MHz               |
| Channel number:       | 1                       |
| Antenna type:         | Internal antenna        |
| Antenna gain:         | 0dBi                    |

Note: For more details, please refer to the user's manual of the EUT.

### 2.3. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.231 of the FCC Part 15, Subpart C Rules.

### 2.4. Modifications

No modifications were implemented to meet testing criteria.

### 3. TEST CONDITIONS AND RESULTS

#### 3.1. Conducted Emission (AC Main)

##### Test equipment

| Item | Equipment            | Manufacturer | Model No.           | Serial No.   | Last Cal.  | Cal. Interval |
|------|----------------------|--------------|---------------------|--------------|------------|---------------|
| 1    | Test Receiver        | R&S          | ESCI                | 101699       | 2023-07-27 | 1 Year        |
| 2    | LISN                 | R&S          | ENV216              | 3650.6550.06 | 2023-05-19 | 1 Year        |
| 3    | LISN                 | KHC          | KH3765              | 37650053     | 2023-05-19 | 1 Year        |
| 4    | 8-WIRE ISN for CAT6  | R&S          | ENY81-CA6           | 101862       | 2023-05-19 | 1 Year        |
| 5    | RF Cable             | HUBER        | SUCOFLEX100         | 30722/4E     | 2023-05-19 | 2 Year        |
| 6    | MEASUREMENT SOFTWARE | FARAD        | EZ-EMC(VER:1.1.4.2) | N/A          | N/A        | N/A           |

##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

##### TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a flood stand system; a wooden table with a height of 0.1 meters is used and is placed on the ground plane as per ANSI C63.10-2020.
2. Support equipment, if needed, was placed as per ANSI C63.10-2020
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.

7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

**TEST RESULTS**

Not applicable for device which is battery supply.

### 3.2. Radiated Emission

#### Test equipment

| Item | Equipment                  | Manufacturer | Model No.           | Serial No.                     | Last Cal.  | Cal. Interval |
|------|----------------------------|--------------|---------------------|--------------------------------|------------|---------------|
| 1    | Test Receiver              | R&S          | ESR                 | 101380                         | 2023-05-19 | 1 Year        |
| 2    | Trilog Broadband Antenna   | Schwarzbeck  | VULB9168            | 00969                          | 2023-05-19 | 2 Year        |
| 3    | Horn antenna               | Schwarzbeck  | BBHA9120D           | 453                            | 2023-05-19 | 2 Year        |
| 4    | Pre-amplifier              | Agilent      | 8449B               | 3008A04721                     | 2023-05-19 | 1 Year        |
| 5    | Double Ridged Horn Antenna | A.H. System  | SAS-574             | 584                            | 2023-05-19 | 1 Year        |
| 6    | Active Loop antenna        | Schwarzbeck  | FMZB-1519           | 1519-038                       | 2023-05-19 | 1 Year        |
| 7    | Pre-amplifier              | R&S          | 8447F               | 3113A04553                     | 2023-05-19 | 1 Year        |
| 8    | RF Cable                   | GORE         | OSQ01Q010<br>78.7   | SN1545847<br>3                 | 2023-05-19 | 2 Year        |
| 9    | RF Cable                   | ESCO         | ETS-LINGR<br>EN     | RFC-SMS-1<br>00-SMS-340<br>-IN | 2023-05-19 | 2 Year        |
| 10   | Measurement software       | Farad        | EZ-EMC(VER:1.1.4.2) | N/A                            | N/A        | N/A           |

#### Limit

For intentional device, according to 15.209(a) the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table.

| Frequency (MHz) | Distance (Meters) | Radiated (dB $\mu$ V/m)          | Radiated ( $\mu$ V/m) |
|-----------------|-------------------|----------------------------------|-----------------------|
| 0.009-0.49      | 3                 | 20log(2400/F(KHz))+40log(300/3)  | 2400/F(KHz)           |
| 0.49-1.705      | 3                 | 20log(24000/F(KHz))+ 40log(30/3) | 24000/F(KHz)          |
| 1.705-30        | 3                 | 20log(30)+ 40log(30/3)           | 30                    |
| 30-88           | 3                 | 40.0                             | 100                   |
| 88-216          | 3                 | 43.5                             | 150                   |
| 216-960         | 3                 | 46.0                             | 200                   |
| Above 960       | 3                 | 54.0                             | 500                   |

In addition to the provisions of 15.231(b) and RSS 210-A1.1.2, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:


| Fundamental frequency (MHz) | Field strength of fundamental (microvolts/meter) | Field strength of spurious emissions (microvolts/meter) |
|-----------------------------|--|---|
| 40.66-40.70                 | 2,250  | 225   |
| 70-130                      | 1,250  | 125   |
| 130-174                     | <sup>1</sup> 1,250 to 3,750                      | <sup>1</sup> 125 to 375                                 |
| 174-260                     | 3,750  | 375   |
| 260-470                     | <sup>1</sup> 3,750 to 12,500                     | <sup>1</sup> 375 to 1,250                               |
| Above 470                   | 12,500   | 1,250   |

<sup>1</sup> Linear interpolations.


[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 260-470 MHz,  $\mu\text{V/m}$  at 3 meters =  $41.6667(F) - 7083.3333$ . The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

## TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



### **Test Procedure**

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 5GHz.

## TEST RESULTS

The emissions from 30MHz to 5GHz are measured peak and average level, below 1 GHz measured QP level, detailed test data please see below. Besides, we tested 3 directions and recorded the worst data.


| Emission Styles | Frequency (MHz) | Reading Level(dBuV) | Correct Factor(dB) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Direction (H/V) |
|-----------------|-----------------|---------------------|--------------------|----------------|----------------|-------------|----------|-----------------|
| Fundamental     | 433.90          | 82.35               | -9.34              | 73.01          | 100.82         | -27.81      | PK       | H               |
| Fundamental     | 433.90          | --                  | --                 | 64.70          | 80.82          | -16.12      | AV       | H               |
| Harmonics       | 867.80          | 54.75               | -2.81              | 51.94          | 80.82          | -28.88      | PK       | H               |
| Harmonics       | 867.80          | --                  | --                 | 43.63          | 60.82          | -17.19      | AV       | H               |
| Harmonics       | 1735.60         | 50.90               | -11.62             | 39.28          | 80.82          | -41.54      | PK       | H               |
| Harmonics       | 1735.60         | --                  | --                 | 30.97          | 60.82          | -29.85      | AV       | H               |
| --              | --              | --                  | --                 | --             | --             | --          | --       | --              |
| Fundamental     | 433.90          | 84.84               | -9.34              | 75.50          | 100.82         | -25.32      | PK       | V               |
| Fundamental     | 433.90          | --                  | --                 | 67.19          | 80.82          | -13.63      | AV       | V               |
| Harmonics       | 867.80          | 55.27               | -2.81              | 52.46          | 80.82          | -28.36      | PK       | V               |
| Harmonics       | 867.80          | --                  | --                 | 44.15          | 60.82          | -16.67      | AV       | V               |
| Harmonics       | 1735.60         | 53.26               | -11.62             | 41.64          | 80.82          | -39.18      | PK       | V               |
| Harmonics       | 1735.60         | --                  | --                 | 33.33          | 60.82          | -27.49      | AV       | V               |
| --              | --              | --                  | --                 | --             | --             | --          | --       | --              |

Note:


1. All Readings are Peak Value
2. Correct Factor= Antenna Factor +Cable Loss- Amplifier Gain
3. Emission Level= Reading Level+Probe Factor +Cable Loss
4. AV Level (dBuV/m)= PK Level (dBuV/m)+ AV Factor(dB)
5. Margin = TrueValue – limit(if margin is minus means under limit)
6. In a transmit cycle 33.40 ms period found 0.445 ms burst 14 pcs, 0.940 ms burst 7 pcs, the Duty Cycle can calculate as below:  

$$\text{Duty Cycle} = (0.445 * 14 + 0.940 * 7) / 33.40 = 0.384$$


$$\text{AV Factor} = 20 * \log(\text{Duty Cycle}) = 20 * \log(0.384) = -8.31$$
7. (The plot of Duty Cycle See the follow page)
8. All the x/y/z orientation has been investigated, and only worst case is presented in this report,
9. New battery is used during all test.



(Transmit cycle 33.40ms)



(Total Bursts in a transmit cycle 21pcs)



(0.445ms burst 14pcs)



(0.940ms burst 7pcs)

### 3.3. 20dB Bandwidth


#### Test equipment

| Item | Equipment         | Manufacturer | Model No. | Serial No. | Last Cal.  | Cal. Interval |
|------|-------------------|--------------|-----------|------------|------------|---------------|
| 1    | Spectrum Analyzer | Keysight     | N9020A    | MY50141563 | 2024-05-14 | 1Year         |

#### Limit

According to 47 CFR 15.231(c) The bandwidth of the emission shall be no wider than 0.25% of the centre frequency for devices operating above 70MHz and below 900MHz. Bandwidth is determined at the points 20dB down from the modulated carrier.

#### Test Configuration



#### Test Procedure

The 20dB bandwidth and 99% bandwidth is measured with a spectrum analyzer connected via a receive antenna placed near the EUT while the EUT is operating in transmission mode.


The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

The occupied bandwidth (OBW), that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

### Test Results

| Modulation | Channel Frequency (MHz) | 99% OBW (KHz) | 20dB bandwidth (KHz) | Limit (KHz)           | Result |
|------------|-------------------------|---------------|----------------------|-----------------------|--------|
| ASK        | 433.90                  | 33.817        | 15.71                | 0.25%*433.90=1084.475 | Pass   |

Test plot as follows:



### 3.4. Deactivation Time


## Test equipment

| Item | Equipment         | Manufacturer | Model No. | Serial No. | Last Cal.  | Cal. Interval |
|------|-------------------|--------------|-----------|------------|------------|---------------|
| 1    | Spectrum Analyzer | Keysight     | N9020A    | MY50141563 | 2024-05-14 | 1 Year        |

## Limit

According to FCC §15.231(a)(1), A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

## Test Configuration




## Test Procedure

1. The EUT was placed on a wooded table which is 0.8m height and close to receiver antenna of spectrum analyzer.
2. The spectrum analyzer resolution bandwidth was set to 1 MHz and video bandwidth was set to 1 MHz to encompass all significant spectral components during the test. The spectrum analyzer was operated in linear scale and zero span mode after tuning to the transmitter carrier frequency.

## **TEST RESULTS**

Note: The transmitter was automatically activated, and the carrier frequency 433.90MHz:

| Frequency (MHz) | One transmission time (S) | Limit(S) | Result |
|-----------------|---------------------------|----------|--------|
| 433.90          | 1.660                     | 5        | Pass   |



### 3.5. Antenna Requirement

#### Standard Applicable

According to FCC Part 15C 15.203


- a) An intentional radiator shall be de-signed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.
- b) The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### **Refer to statement below for compliance.**


The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

#### Antenna Connected Construction

The antenna used in this product is an internal Antenna, The directional gains of antenna used for transmitting is 0 dBi.





#### 4. Test Setup Photos of the EUT





## 5. External and Internal Photos of the EUT


### External Photos of EUT





**Internal Photos of EUT**





\*\*\*\*\* End of Report \*\*\*\*\*