



# EMI - TEST REPORT

- FCC Part 15.209, RSS-GEN -

**Type / Model Name** : G7116B

**Product Description** : Multicolumn Thermostat

**Applicant** : Agilent Technologies Deutschland GmbH

**Address** : Hewlett-Packard-Strasse 8

76337 Waldbronn, Baden-Württemberg

GERMANY

**Manufacturer** : Agilent Technologies Singapore (International) Pte. Ltd.

**Address** : No. 1 Yishun Ave 7

SINGAPORE 768923

SINGAPORE

<b>Test Result</b> according to the standards listed in clause 1 test standards:	<b>POSITIVE</b>
--	-----------------

<b>Test Report No. :</b> <b>80192406-00 Rev_1</b>	15. October 2024 <small>Date of issue</small>
---	--



Deutsche  
Akkreditierungsstelle  
D-PL-12030-01-00

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

# Contents

<b>1</b>	<b><u>TEST STANDARDS</u></b>	<b>3</b>
<b>2</b>	<b><u>EQUIPMENT UNDER TEST</u></b>	<b>4</b>
2.1	Information provided by the Client	4
2.2	Sampling	4
2.3	Photo documentation of the EUT	4
2.4	Short description of the equipment under test (EUT)	4
2.5	Variants of the EUT	5
2.6	EUT operation mode	5
2.7	Antenna	5
2.8	EUT configuration	5
2.9	Power supply system utilised	5
<b>3</b>	<b><u>TEST RESULT SUMMARY</u></b>	<b>6</b>
3.1	Revision history of test report	6
3.2	FINAL ASSESSMENT	6
<b>4</b>	<b><u>TEST ENVIRONMENT</u></b>	<b>7</b>
4.1	Address of the test laboratory	7
4.2	Environmental conditions	7
4.3	Statement of the measurement uncertainty	7
4.4	Conformity Decision Rule	8
4.5	Measurement protocol for FCC and ISED	8
<b>5</b>	<b><u>TEST CONDITIONS AND RESULTS</u></b>	<b>10</b>
5.1	Conducted emissions	10
5.2	Field strength of the fundamental wave	13
5.3	Spurious emissions	15
5.4	Bandwidth	22
<b>6</b>	<b><u>USED TEST EQUIPMENT AND ACCESSORIES</u></b>	<b>24</b>

ATTACHMENT A to ATTACHMENT C as separate supplement

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

# **1 TEST STANDARDS**

The tests were performed according to following standards:

## **FCC Rules and Regulations Part 15, Subpart A - General (January 2024)**

### **FCC Rules and Regulations Part 15, Subpart C - Intentional Radiators (January 2024)**

Part 15, Subpart C, Section 15.207 Conducted limits

Part 15, Subpart C, Section 15.209 Radiated emission limits, general requirements

## **RSS Rules and Regulations**

RSS-Gen, Issue 5, March 2018  
Amendment 1 (March 2019)  
Amendment 2 (February 2021) General Requirements and Information for the Certification of Radiocommunication Equipment

RSS-210, Issue 11, June 2024 Licence-Exempt Radio Apparatus: Category I Equipment

ANSI C63.10: 2013 Testing Unlicensed Wireless Devices

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

## **2 EQUIPMENT UNDER TEST**

### **2.1 Information provided by the Client**

Please note, we do not take any responsibility for information provided by the client or his representative which may have an influence on the validity of the test results.

### **2.2 Sampling**

The customer is responsible for the choice of sample. Sample configuration, start-up and operation is carried out by the customer or according his/her instructions.

### **2.3 Photo documentation of the EUT**

Detailed photos see ATTACHMENT A and ATTACHMENT C

ATTACHMENT A: External views

ATTACHMENT B: Internal views

ATTACHMENT C: Test setup



### **2.4 Short description of the equipment under test (EUT)**

The EUT is a UHPLC column oven that provides precise temperature control over a broad temperature range with cooling to 20 degrees below ambient and heating up to 110 °C.

Nine internal 125 kHz antennas are located in the device. The TAG reader reads sequentially each antenna.

Number of tested samples: 1  
 Serial number: DEBA412667

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

## 2.5 Variants of the EUT

According to the customer, there are other variants of this device.  
It is expressly pointed out here, that no measurements have been carried out on these devices!

G7116A MultiColumn Thermostat temperature up to 85°C

## 2.6 EUT operation mode


The equipment under test was operated during the measurement under the following conditions:

- Cont. TAG reading at 125 kHz (all antennas are read sequentially)
- 

## 2.7 Antenna

Antenna: 125KHz

Agilent PN 9140-5210: PCB Mountable Part • IND-FXD 900uH 5% 10mA 3.6X11.8mm SMT  
Manufacturer: Premo, SDTR1103-0090J



## 2.8 EUT configuration

The following peripheral devices and interface cables were connected during the measurements:

- 5 Port Gigabit Switch Model : Netgear – GS105 v4
- Measurement Laptop Model : HP – EliteBook 840 (CSA No.:01-01/01-15-019)
- \_\_\_\_\_ Model : \_\_\_\_\_

## 2.9 Power supply system utilised

Power supply voltage : 100 – 240 V AC, 50 or 60 Hz

All tests were carried out with a supply voltage of 120 V, 60 Hz unless otherwise stated. Exceptions are described in the detailed test conditions.

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

### 3 TEST RESULT SUMMARY

FCC Rule Part	RSS Rule Part	Description	Result
15.207	RSS-Gen, 8.8 RSS-210, 7	AC power line conducted emissions	passed
15.209	RSS-Gen, 8.9 RSS-210, 7	Field strength of fundamental	passed
15.209	RSS-Gen, 8.9 RSS-210, 7	Spurious emissions	passed
15.215	RSS-Gen, 6.7 RSS-210, 7	Occupied bandwidth	passed

#### 3.1 Revision history of test report

Test report No	Rev.	Issue Date	Changes
80192406-00	0	25 September 2024	Initial test report
80192406-00	1	15 October 2024	Changes in point 2.5 (Variants of the EUT)

The test report with the highest revision number replaces the previous test reports.

#### 3.2 FINAL ASSESSMENT

The equipment under test fulfills the EMI requirements cited in clause 1 test standards.

Date of receipt of test sample : acc. to storage records

Testing commenced on : 10 January 2024

Testing concluded on : 06 February 2024

Checked by:

Tested by:

\_\_\_\_\_  
Klaus Gegenfurtner  
Teamleader Radio

\_\_\_\_\_  
Josef Knab  
Radio Team

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

## 4 TEST ENVIRONMENT

### 4.1 Address of the test laboratory

**CSA Group Bayern GmbH**  
**Ohmstrasse 1-4**  
**94342 STRASSKIRCHEN**  
**GERMANY**

### 4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15 - 35 ° C

Humidity: 30 - 60 %

Atmospheric pressure: 86 - 106 kPa

### 4.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. It is noted that the expanded measurement uncertainty corresponds to the measurement results from the standard measurement uncertainty multiplied by the coverage factor  $k = 2$ . The true value is located in the corresponding interval with a probability of 95 %. The measurement uncertainty was calculated for all measurements listed in this test report on basis of the ETSI Technical Report TR 100 028 Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1 and Part 2. The results are documented in the quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	$\pm 3.29$ dB
20 dB Bandwidth	Center frequency of EuT	95%	$\pm 2.5 \cdot 10^{-7}$
99% Occupied Bandwidth	Center frequency of EuT	95%	$\pm 2.5 \cdot 10^{-7}$
Radiated Spurious Emissions	9 kHz to 30 MHz	95%	$\pm 3.53$ dB
Radiated Spurious Emissions	30 MHz to 1000 MHz	95%	$\pm 3.71$ dB
Radiated Spurious Emissions	1000 MHz to 10000 MHz	95%	$\pm 2.34$ dB
Peak conducted output power	902 MHz to 928 MHz	95%	$\pm 0.35$ dB
Conducted Spurious Emissions	9 kHz to 10000 MHz	95%	$\pm 2.15$ dB

**FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X**

#### 4.4 Conformity Decision Rule

The applied conformity decision rule is based on ILAC G8:09/2019 clause 4.2.1 Binary Statement for Simple Acceptance Rule ( $w = 0$ ).  
 Details can be found in the procedure CSA\_B\_V50\_29.

#### 4.5 Measurement protocol for FCC and ISED

##### 4.5.1 GENERAL INFORMATION

CSA Group Bayern GmbH is recognized as wireless testing laboratory under the CAB identifier:

**FCC: DE 0011  
 ISED: DE0009**

##### 4.5.2 General Standard information

The test methods used comply with ANSI C63.10 - "Testing Unlicensed Wireless Devices".


##### 4.5.2.1 Justification

The equipment under test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions.

##### 4.5.3 Details of test procedures

##### 4.5.3.1 Conducted emission

Test setup according ANSI C63.10



The final level, expressed in  $\text{dB}\mu\text{V}$ , is arrived at by taking the reading directly from the Spectrum analyser. This level is compared to the limit.

To convert between  $\text{dB}\mu\text{V}$  and  $\mu\text{V}$ , the following conversions apply:

$$\text{dB}\mu\text{V} = 20(\log \mu\text{V})$$

$$\mu\text{V} = \text{Inverse log}(\text{dB}\mu\text{V}/20)$$

Conducted emissions on the 50 Hz and/or 60 Hz power interface of the EUT are measured in the frequency range of 150 kHz to 30 MHz. The measurements are performed using a receiver, which has CISPR characteristic bandwidth and quasi-peak detection and a Line Impedance Stabilization Network (LISN) with  $50 \Omega / 50 \mu\text{H}$  (CISPR 16) characteristics. The receiver is protected by means of an impedance matched pulse limiter connected directly to the RF input. Table top equipment is placed on a non-conducting table 80 centimetres above the floor and is positioned 40 centimetres from the vertical ground plane (wall) of the screen room. If the minimum limit margin appears to be less than 20 dB with a peak mode measurement, the emission is re-measured using a tuned receiver with quasi-peak and average detection and recorded on the data sheets.




**FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X**

**4.5.3.2 Radiated emission**

**4.5.3.2.1 OATS1 test site (9 kHz - 30 MHz):**


Test setup according ANSI C63.10



Emissions from the EUT are measured in the frequency range of 9 MHz to 30 MHz using a tuned receiver and a calibrated loop antenna. Table top equipment is placed on a 1.0 X 1.5 m non-conducting table 80 centimetres above the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screened room located outside the test area. The antenna is positioned 3, 10 or 30 metres horizontally from the EUT and is repeated vertically. To locate maximum emissions from the test sample the antenna is varied along the site axis and the EUT is rotated 360 degrees.

**4.5.3.2.2 OATS1 test site (30 MHz - 1 GHz):**

Test setup according ANSI C63.10.



Spurious emissions from the EUT are measured in the frequency range of 30 MHz to 1000 MHz using a tuned receiver and appropriate broadband linearly polarised antennas. Measurements between 30 MHz and 1000 MHz are made with 120 kHz/6 dB bandwidth and quasi-peak detection. Table top equipment is placed on a 1.0 X 1.5 m non-conducting table 80 centimetres above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screened room located outside the test area. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 metres and the EUT is rotated 360 degrees. The final level in dBµV/m is calculated by taking the reading from the EMI receiver (Level dBµV) and adding the correction factors and cable loss factor (dB). The FCC limit is subtracted from this result in order to provide the limit margin listed in the measurement protocol.

The resolution bandwidth setting:

30 MHz – 1000 MHz: RBW: 120 kHz

Example:

Frequency (MHz)	Level (dBµV)	+	Factor (dB)	=	Level (dBµV/m)	-	Limit (dBµV/m)	=	Delta (dB)
719.0	75.0	+	32.6	=	107.6	-	110.0	=	-2.4

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

## 5 TEST CONDITIONS AND RESULTS

### 5.1 Conducted emissions

For test instruments and accessories used, see section 6 Part A 4.

#### 5.1.1 Description of the test location

Test location: Shielded Room S2

#### 5.1.2 Photo documentation of the test set-up

See ATTACHMENT C to this test report.

#### 5.1.3 Applicable standard

FCC Part 15, Section 15.207 / RSS-GEN, Section 8.8

#### 5.1.4 Description of Measurement

The radiated power of the spurious emission from the EUT is measured in a test setup following the procedures set out in ANSI C63.10.

#### 5.1.5 Test result

Frequency range: 0.15 MHz - 30 MHz

Min. limit margin >15 dB

Limit according to FCC Part 15, Section 15.207:

Limit according to RSS-GEN, Section 8.8:

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency

The requirements are **FULFILLED**.

**Remarks:** For detailed results, please see the following page(s).

---




---

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

5.1.6 Test protocol


<b>File No.:</b>	80192406-00 Rev_1	<b>Result:</b>	<b>PASS</b>
<b>Operation mode:</b>	Cont. TAG reading at 125 kHz		
<b>Tested by:</b>	KJ	<b>Nexio Version:</b>	2022.0.32.0
<b>Location:</b>	S2	<b>Date:</b>	12.01.2024 09:55:41
<b>Remarks:</b>	Test point L1		



Frequency (Hz)	QuasiPeak (dBµV)	QP Margin	QP Limit (dBµV)	Average (dBµV)	AV Margin	AV Limit (dBµV)	Line	Correction (dB)
150 k	35.721	30.279	66	27.267	28.733	56	Phase 1	10.074
204 k	32.703	30.743	63.446	27.453	25.993	53.446	Phase 1	10.086
305.25 k	29.242	30.856	60.099	25.556	24.543	50.099	Phase 1	10.111
507.75 k	16.347	39.653	56	13.42	32.58	46	Phase 1	10.16
811.5 k	11.583	44.417	56	6.528	39.472	46	Phase 1	10.188
813.75 k	11.715	44.285	56	6.569	39.431	46	Phase 1	10.188
2.02875 M	7.978	48.022	56	2.953	43.047	46	Phase 1	10.27
2.031 M	8.92	47.08	56	3.997	42.003	46	Phase 1	10.27
3.129 M	5.437	50.563	56	0.237	45.763	46	Phase 1	10.332
3.5835 M	7.802	48.198	56	2.759	43.241	46	Phase 1	10.34
6.05625 M	11.767	48.233	60	6.345	43.655	50	Phase 1	10.529
6.11925 M	12.24	47.76	60	7.694	42.306	50	Phase 1	10.537
8.62575 M	15.38	44.62	60	10.47	39.53	50	Phase 1	10.638
10.176 M	15.745	44.255	60	10.098	39.902	50	Phase 1	10.665
17.49975 M	34.396	25.604	60	30.787	19.213	50	Phase 1	11.142
20.751 M	35.479	24.521	60	33.174	16.826	50	Phase 1	11.285
23.5005 M	35.37	24.63	60	34.162	15.838	50	Phase 1	11.437

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

<b>File No.:</b>	80192406-00 Rev_1	<b>Result:</b>	<b>PASS</b>
<b>Operation mode:</b>	Cont. TAG reading at 125 kHz		
<b>Tested by:</b>	KJ	<b>Nexio Version:</b>	2022.0.32.0
<b>Location:</b>	S2	<b>Date:</b>	12.01.2024 09:55:41
<b>Remarks:</b>	Test point N		



Frequency (Hz)	QuasiPeak (dBµV)	QP Margin	QP Limit (dBµV)	Average (dBµV)	AV Margin	AV Limit (dBµV)	Line	Correction (dB)
150 k	37.609	28.391	66	31.757	24.243	56	Neutral	10.104
305.25 k	24.062	36.037	60.099	19.232	30.867	50.099	Neutral	10.15
307.5 k	24.306	35.731	60.038	18.962	31.076	50.038	Neutral	10.151
507.75 k	14.507	41.493	56	11.563	34.437	46	Neutral	10.18
811.5 k	9.247	46.753	56	4.736	41.264	46	Neutral	10.211
1.68 M	4.426	51.574	56	-1.005	47.005	46	Neutral	10.296
2.031 M	6.096	49.904	56	0.626	45.374	46	Neutral	10.3
2.74875 M	7.616	48.384	56	2.601	43.399	46	Neutral	10.367
3.4035 M	6.686	49.314	56	1.531	44.469	46	Neutral	10.376
5.7345 M	11.055	48.945	60	6.494	43.506	50	Neutral	10.5
6.1215 M	12.529	47.471	60	7.939	42.061	50	Neutral	10.531
8.628 M	15.218	44.782	60	10.227	39.773	50	Neutral	10.629
10.059 M	15.173	44.827	60	9.413	40.587	50	Neutral	10.653
17.49975 M	34.521	25.479	60	30.738	19.262	50	Neutral	10.992
20.751 M	35.312	24.688	60	32.904	17.096	50	Neutral	11.143
23.5005 M	34.897	25.103	60	33.837	16.163	50	Neutral	11.122

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

**FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X**

**5.2 Field strength of the fundamental wave**

For test instruments and accessories used see section 6 Part CPR 1.

**5.2.1 Description of the test location**

Test location: OATS 1  
 Test distance: 3 m

**5.2.2 Photo documentation of the test set-up**

See ATTACHMENT C to this test report.

**5.2.3 Applicable standard**

FCC Part 15, Section 15.209(a) / RSS-GEN, Section 8.9

**5.2.4 Description of Measurement**

The radiated power of the spurious emission from the EUT is measured in a test setup following the procedures set out in ANSI C63.10.

**5.2.5 Test result accd. to FCC**

- a) Result at a measurement distance of 3 m

Frequency (kHz)	Level (dB $\mu$ V)	Ant. factor (dB 1/m)	Field strength dB( $\mu$ V/m)
125.00	47.5	18.0	65.5

- b) Result extrapolated to a distance of 300 m

Frequency (kHz)	Field strength dB( $\mu$ V/m) @3m	Extrapolation factor (dB)	Field strength dB( $\mu$ V/m) @300m	Limit dB( $\mu$ V/m)	Delta (dB)
125.00	65.5	-80.0	-14.5	25.7	-40.2

Limit according to FCC Part 15, Section 15.209(a):

Frequency (kHz)	Field strength of fundamental wave ( $\mu$ V/m)	dB( $\mu$ V/m)	Measurement distance (metres)
125	19.2	25.7	300

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

**FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X**

**5.2.6 Test result accd. to RSS**

a) Result at a measurement distance of 3 m

Frequency (kHz)	Level (dB $\mu$ A)	Ant. factor (dB 1/m)	Field strength dB( $\mu$ A/m)
125.00	-4.0	18.0	14.0

b) Result extrapolated to a distance of 300 m

Frequency (kHz)	Field strength dB( $\mu$ A/m) @3m	Extrapolation factor (dB)	Field strength dB( $\mu$ A/m) @300m	Limit dB( $\mu$ A/m)	Delta (dB)
125.00	14.0	-80.0	-66.0	-25.9	-40.1

Limit according to RSS-GEN, Section 8.9:

Frequency (kHz)	Field strength of fundamental wave ( $\mu$ A/m)	dB( $\mu$ A/m)	Measurement distance (metres)
125	0.05096	-25.9	300

The requirements are **FULFILLED**.

**Remarks:** The measurements were carried out with a PK detector because the EuT operate over several antennas at different times.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

### 5.3 Spurious emissions

For test instruments and accessories used see section 6 Part SER 1, SER 2.

#### 5.3.1 Description of the test location

Test location: OATS 1  
Test distance: 3 metres

#### 5.3.2 Photo documentation of the test set-up

See ATTACHMENT C to this test report.

#### 5.3.3 Applicable standard

FCC Part 15, Section 15.209 / RSS-GEN, Section 8.9

#### 5.3.4 Description of Measurement

The radiated power of the spurious emission from the EUT is measured in a test setup following the procedures set out in ANSI C63.10.

The resolution bandwidth during the measurement is as follows:

9 kHz – 150 kHz: RBW: 200 Hz

150 kHz – 30 MHz: RBW: 9 kHz


30 MHz – 1000 MHz: RBW: 120 kHz

Detector: QP (In frequency range 9-90 kHz and 110-490 kHz a linear average detector is used)

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

5.3.5 Test result < 30MHz accd. to FCC

Frequency (kHz)	Level @3m (dBµV)	Ant. factor (dB 1/m)	Field strength @3m dB(µV/m)	Extrapolation factor @300m (dB)	Field strength level @300m dB(µV/m)	Limit dB(µV/m)	Delta (dB)
375.00	22.2	16.9	39.1	-80.0	-40.9	16.1	-57.0




The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.



FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

Frequency (kHz)	Level @3m (dBµV)	Ant. factor (dB 1/m)	Field strength @3m dB(µV/m)	Extrapolation factor @30m (dB)	Field strength level @30m dB(µV/m)	Limit dB(µV/m)	Delta (dB)
625.70	18.6	18.5	37.1	-40.0	-2.9	31.7	-34.6
1000*	21.2	18.2	39.4	-40.0	-0.6	27.6	-28.2
12000*	6.6	17.6	24.2	-40.0	-15.8	29.5	-45.3
24000*	4.3	18.0	22.3	-40.0	-17.7	29.5	-47.2

Note: \*) Ambient noise, no other spurious emissions could be detected




The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

5.3.6 Test result < 30MHz accd. to RSS

Frequency (kHz)	Level @3m (dBμA)	Ant. factor (dB 1/m)	Field strength @3m dB(μA/m)	Extrapolation factor @300m (dB)	Field strength level @300m dB(μA/m)	Limit dB(μA/m)	Delta (dB)
375.00	-29.3	16.9	-12.4	-80.0	-92.4	-35.4	-57.0




The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

Frequency (kHz)	Level @3m (dBμA)	Ant. factor (dB 1/m)	Field strength @3m dB(μA/m)	Extrapolation factor @30m (dB)	Field strength level @30m dB(μA/m)	Limit dB(μA/m)	Delta (dB)
625.70	-32.9	18.5	-14.4	-40.0	-54.4	-19.8	-34.6
1000*	-30.3	18.2	-12.1	-40.0	-52.1	-23.9	-28.2
12000*	-44.9	17.6	-27.3	-40.0	-67.3	-21.9	-45.4
24000*	-47.2	18.0	-29.2	-40.0	-69.2	-21.9	-47.3

Note: \*) Ambient noise, no other spurious emissions could be detected.




The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

5.3.7 Test result 30 MHz < f < 1 GHz

Frequency (MHz)	Reading Vert. (dBµV)	Reading Hor. (dBµV)	Correct. Vert. (dB)	Correct. Hor. (dB)	Level Vert. (dBµV/m)	Level Hor. (dBµV/m)	Limit (dBµV/m)	Dlimit (dB)
50*	-0.3	-1.7	17.6	18.8	17.3	17.1	40.0	-22.7
200*	2.7	2.5	17.0	16.5	19.7	19.0	43.5	-23.8
400*	-0.9	-2.2	23.3	23.6	22.4	21.4	46.0	-23.6
600*	-1.0	-2.3	28.3	28.6	27.3	26.3	46.0	-18.7
800*	-2.4	-2.4	31.6	31.9	29.2	29.5	46.0	-16.5
1000*	0.3	-3.6	34.0	34.4	34.3	30.8	54.0	-19.7

Note: The correction factor includes cable loss and antenna factor.  
 Note: \*) Ambient noise, no other spurious emissions could be detected.



The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

**FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X**

Limit according to FCC Part 15, Section 15.209(a)

Frequency (MHz)	Field strength of spurious emissions		Measurement distance (metres)
	( $\mu$ V/m)	dB( $\mu$ V/m)	
0.009 - 0.490	2400/F(kHz)	--	300
0.490 - 1.705	24000/F (kHz)	--	30
1.705 - 30.0	30	29.5	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

Limit according to RSS-Gen, Section 8.9

Frequency (MHz)	Field strength of spurious emissions		Measurement distance (metres)
	( $\mu$ A/m)	dB( $\mu$ A/m)	
0.009 - 0.490	6.37/F(kHz)	--	300 (Note 1)
0.490 - 1.705	63.7/F (kHz)	--	30
1.705 - 30.0	0.08	-22	30
Frequency (MHz)	Field strength of spurious emissions		Measurement distance (metres)
	( $\mu$ V/m)	dB( $\mu$ V/m)	
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

The requirements are **FULFILLED**.

**Remarks:** Measurement has been performed up to 1000 MHz.  
The measurements were carried out with a PK detector because the EuT operate over several  
antennas at different times.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

**FCC ID: 2BGE529G7116X    IC ID: 32551-29G7116X**

## 5.4 Bandwidth

For test instruments and accessories used see section 6 Part MB.

### 5.4.1 Description of the test location

Test location:                AREA4

### 5.4.2 Photo documentation of the test set-up

See ATTACHMENT C to this test report.

### 5.4.3 Applicable standard

According to FCC Part 15, Section 15.215(c) / RSS-GEN, Section 6.7

### 5.4.4 Test result

Measured Bandwidth	result (kHz)	Limit (kHz)
20dB	11.181	--
99%	25.605	--

The requirements are **FULFILLED**.

**Remarks:**     For detailed test result please refer to following test protocol.

---




---

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.


FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

5.4.5 Test protocol

20 dB bandwidth



99% Bandwidth



FCC ID: 2BGE529G7116X IC ID: 32551-29G7116X

## 6 USED TEST EQUIPMENT AND ACCESSORIES

All test instruments used are calibrated and verified regularly. The calibration history is available on request.  
All listed measuring devices were calibrated at the time of use.

Test ID	Model Type	Equipment No.	Next Calib.	Last Calib.	Next Verif.	Last Verif.
A 4	BAT-EMC 2023.0.8.0	01-02/68-13-001				
	ESR 7	02-02/03-17-001	01/08/2024	01/08/2023		
	ESH 2 - Z 5	02-02/20-05-004	13/10/2025	13/10/2022	17/04/2024	17/04/2023
	N-4000-BNC	02-02/50-05-138				
	ESH 3 - Z 2	02-02/50-05-155	09/11/2025	09/11/2022	25/07/2024	25/07/2023
	6430	02-02/50-13-014				
CPR 1	ESW26	02-02/03-17-002	08/03/2024	08/03/2023		
	HFH 2 - Z 2	02-02/24-05-020	01/06/2025	01/06/2022	05/09/2024	05/09/2023
	KK-EF393-21N-16	02-02/50-05-033				
	NW-2000-NB	02-02/50-05-113				
	KK-EF393/U-16N-21N20 m	02-02/50-12-018				
	KK-SD_7/8-2X21N-33,0M	02-02/50-15-028				
MB	METRAHIT WORLD	02-02/32-15-001	22/11/2024	22/11/2023		
	WK-340/40	02-02/45-05-001	27/07/2024	27/07/2023		
	Type 5315.5	02-02/50-05-197				
	7405	02-02/50-05-235				
	ESW44	09-16/03-24-001	21/11/2024	21/11/2023		
SER 1	ESW26	02-02/03-17-002	08/03/2024	08/03/2023		
	HFH 2 - Z 2	02-02/24-05-020	01/06/2025	01/06/2022	05/09/2024	05/09/2023
	KK-EF393-21N-16	02-02/50-05-033				
	NW-2000-NB	02-02/50-05-113				
	KK-EF393/U-16N-21N20 m	02-02/50-12-018				
	KK-SD_7/8-2X21N-33,0M	02-02/50-15-028				
SER 2	ESVS 30	02-02/03-05-006	27/07/2024	27/07/2023		
	ESW26	02-02/03-17-002	08/03/2024	08/03/2023		
	VULB 9168	02-02/24-05-005	20/04/2024	20/04/2023	03/05/2024	03/05/2023
	NW-2000-NB	02-02/50-05-113				
	KK-EF393/U-16N-21N20 m	02-02/50-12-018				
	KK-SD_7/8-2X21N-33,0M	02-02/50-15-028				
	50F-003 N 3 dB	02-02/50-21-010				

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.