

Appendix B

Highest Test Plots

Table of Contents

1. BT Body-worn 0mm SAR..... 3

1. BT Body-worn 0mm SAR

Date: 15.05.2024

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q24040749-2E

DUT: Portable Bluetooth Speaker; Model Number: Vega Mini; Serial: S24040749-005

Communication System: UID 0, Bluetooth (0); Communication System Band: Bluetooth; Frequency: 2402 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): $f = 2402$ MHz; $\sigma = 1.786$ S/m; $\epsilon_r = 39.286$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ConvF(7.95, 7.95, 7.95); Calibrated: 29.04.2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 29.04.2024
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1197
- DASYS2 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Front side 3DH5 2402/Area Scan (10x21x1): Measurement grid: dx=10mm, dy=10mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.117 W/kg

Configuration/Front side 3DH5 2402/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.378 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.182 W/kg

SAR(1 g) = 0.083 W/kg; SAR(10 g) = 0.037 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.143 W/kg

