

FCC TEST REPORT

FCC ID:2BGG9-MODE13

Report No. : SSP24040297-1E

Applicant : Wuxi Lursk Innovation Supply Chain Co.,LTD

Product Name : Tesla model3 shift knob docking station / model3

Model Name : Tesla model3 shift knob docking station Ver1.0

Test Standard : FCC Part 15.247

Date of Issue : 2024-05-17




Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	Wuxi Lursk Innovation Supply Chain Co.,LTD	
Address of Applicant.....:	91-99 Qingyang Road, Liangxi District, Wuxi City number-4010, China	
Manufacturer:	Jiangsu Dingkong Electronic Technology Co.LTD	
Address of Manufacturer.....:	Jiangsu Dingkong, No. 1, Menlou, Changjing Town, Jiangyin, Wuxi, Jiangsu	
Product Name:	Tesla model3 shift knob docking station / model3	
Brand Name:	LURSK	
Main Model:	Tesla model3 shift knob docking station Ver1.0	
Series Models:	-	
Test Standard:	FCC Part 15 Subpart C KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.4-2014 ANSI C63.10-2013	
Date of Test	2024-05-07 to 2024-05-17	
Test Result:	PASS	
Tested By	<u>Coke Huang</u> (Coke Huang)	
Reviewed By:	<u>Lieber Ouyang</u> (Lieber Ouyang)	
Authorized Signatory:	<u>Lahm Peng</u> (Lahm Peng)	
<p>Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.</p>		

CONTENTS

1. General Information.....	5
1.1 Product Information	5
1.2 Test Setup Information.....	6
1.3 Compliance Standards.....	7
1.4 Test Facilities.....	7
1.5 List of Measurement Instruments	8
1.6 Measurement Uncertainty	8
2. Summary of Test Results	9
3. Antenna Requirement.....	10
3.1 Standard and Limit.....	10
3.2 Test Result.....	10
4. Conducted Emissions	11
4.1 Standard and Limit.....	11
4.2 Test Procedure.....	11
4.3 Test Data and Results	12
5. Radiated Emissions	13
5.1 Standard and Limit.....	13
5.2 Test Procedure.....	13
5.3 Test Data and Results	15
6. Band-edge Emissions(Radiated).....	19
6.1 Standard and Limit.....	19
6.2 Test Procedure.....	19
6.3 Test Data and Results	19
7. Maximum Peak Conducted Output Power	21
7.1 Standard and Limit.....	21
7.2 Test Procedure.....	21
7.3 Test Data and Results	21
8. Occupied Bandwidth(-6dB).....	23
8.1 Standard and Limit.....	23
8.2 Test Procedure.....	23
8.3 Test Data and Results	23
9. Maximum Power Spectral Density	25
9.1 Standard and Limit.....	25
9.2 Test Procedure.....	25
9.3 Test Data and Results	25
10. Band-edge Emission(Conducted).....	27
10.1 Standard and Limit.....	27
10.2 Test Procedure.....	27
10.3 Test Data and Results	27
11. Conducted RF Spurious Emissions.....	29
11.1 Standard and Limit.....	29
11.2 Test Procedure.....	29
11.3 Test Data and Results	29

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2024-05-17	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	Tesla model3 shift knob docking station / model3
Trade Name:	LURSK
Main Model:	Tesla model3 shift knob docking station Ver1.0
Series Models:	-
Rated Voltage:	DC 12V by accumulator
Battery:	-
Power Adaptor:	-
Hardware Version:	V1.2
Software Version:	V1.2.3
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	

Wireless Specification	
Wireless Standard:	Bluetooth BLE
Operating Frequency:	2402MHz ~ 2480MHz
RF Output Power:	2.85dBm
Number of Channel:	40
Channel Separation:	2MHz
Modulation:	GFSK
Antenna Gain:	1.2dBi
Type of Antenna:	PCB antenna
Type of Device:	<input type="checkbox"/> Portable Device <input checked="" type="checkbox"/> Mobile Device <input type="checkbox"/> Modular Device

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	BLE_1Mbps	2402/2440/2480MHz	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
-	-	-	-
-	-	-	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2402	11	2422	21	2442	31	2462
02	2404	12	2424	22	2444	32	2464
03	2406	13	2426	23	2446	33	2466
04	2408	14	2428	24	2448	34	2468
05	2410	15	2430	25	2450	35	2470
06	2412	16	2432	26	2452	36	2472
07	2414	17	2434	27	2454	37	2474
08	2416	18	2436	28	2456	38	2476
09	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
KDB 558074 D01 15.247 Meas Guidance v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREA SPECTRUMSYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No.:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2023-10-21	2024-10-20
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2023-07-31	2024-07-30
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2023-07-31	2024-07-30
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2023-07-31	2024-07-30
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2023-07-31	2024-07-30
Amplifier	SCHWARZBECK	BBV 9743B	00251	2023-07-31	2024-07-30
Amplifier	HUABO	YXL0518-2.5-45	--	2023-07-31	2024-07-30
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2023-07-31	2024-07-30
Loop Antenna	DAZE	ZN30900C	21104	2023-08-07	2024-08-06
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2023-08-07	2024-08-06
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2023-08-07	2024-08-06
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2023-08-07	2024-08-06
Conducted RF Testing					
RF Test System	MWRFTest	MW100-RFCB	220418SQS-37	2023-07-31	2024-07-30
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2023-07-31	2024-07-30

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Conducted Output Power	9kHz ~ 26GHz	±0.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %
Conducted Spurious Emission	9kHz ~ 26GHz	±1.32 dB
Power Spectrum Density	9kHz ~ 26GHz	±0.62 dB

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.247(i)	RF Exposure(see the RF exposure report)	Passed
FCC Part 15.207	Conducted Emissions	N/A
FCC Part 15.209, 15.247(d)	Radiated Emissions	Passed
FCC Part 15.247(d)	Band-edge Emissions(Radiated)	Passed
FCC Part 15.247(b)(3)	Maximum Peak Conducted Output Power	Passed
FCC Part 15.247(a)(2)	Occupied Bandwidth(-6dB)	Passed
FCC Part 15.247(e)	Maximum Power Spectral Density	Passed
FCC Part 15.247(d)	Band-edge Emissions(Conducted)	Passed
FCC Part 15.247(d)	Conducted RF Spurious Emissions	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an PCB antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit


According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
 Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

- Attenuation: 10dB
- Start Frequency: 0.15MHz
- Stop Frequency: 30MHz
- IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

- d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f) LISN is at least 80 cm from nearest part of EUT chassis.
- g) For the actual test configuration, please refer to the related Item - photographs of the test setup.

4.3 Test Data and Results

Because the product power is supply through DC 12V by lithium battery, so not applicable.

5. Radiated Emissions

5.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:

Frequency of Emission (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Note: The more stringent limit applies at transition frequencies.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure


Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, 10kHz for $f < 30\text{MHz}$
VBW \geq RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.


5.3 Test Data and Results

All of the BLE_1M modes have been tested, the EUT complied with the FCC Part 15.247 standard limit for a wireless device, and with the worst case BLE_1M_2402MHz as below:

Remark: Level = Reading + Factor, Margin = Level - Limit


Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode:	TM1
Test Antenna Polarization:	Horizontal
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	61.7781	35.61	-10.04	25.57	40.00	-14.43	QP	200	12	P	
2 *	70.0903	39.59	-10.95	28.64	40.00	-11.36	QP	200	62	P	
3	113.3163	34.55	-11.42	23.13	43.50	-20.37	QP	200	348	P	
4	230.0985	38.05	-10.57	27.48	46.00	-18.52	QP	200	348	P	
5	399.0302	31.77	-5.88	25.89	46.00	-20.11	QP	100	348	P	
6	869.1302	30.48	2.55	33.03	46.00	-12.97	QP	200	277	P	

Radiated Emission Test Data (30MHz to 1GHz)	
Tested Mode:	TM1
Test Antenna Polarization:	Vertical
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	62.4314	33.47	-10.11	23.36	40.00	-16.64	QP	100	103	P	
2 *	70.0903	37.67	-10.95	26.72	40.00	-13.28	QP	100	124	P	
3	209.3129	32.85	-11.65	21.20	43.50	-22.30	QP	100	42	P	
4	414.7223	31.93	-5.70	26.23	46.00	-19.77	QP	200	348	P	
5	689.5644	29.23	0.39	29.62	46.00	-16.38	QP	100	12	P	
6	869.1302	29.46	2.55	32.01	46.00	-13.99	QP	200	348	P	

Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
BLE_1M_Lowest Channel (2402MHz)							
4804	77.63	-14.72	62.91	74	-11.09	H	PK
4804	61.07	-14.72	46.35	54	-7.65	H	AV
7206	62.6	-8.41	54.19	74	-19.81	H	PK
7206	48.16	-8.41	39.75	54	-14.25	H	AV
4804	75.92	-14.72	61.2	74	-12.8	V	PK
4804	58.43	-14.72	43.71	54	-10.29	V	AV
7206	62.06	-8.41	53.65	74	-20.35	V	PK
7206	50.22	-8.41	41.81	54	-12.19	V	AV
BLE_1M_Middle Channel (2440MHz)							
4880	78.87	-14.64	64.23	74	-9.77	H	PK
4880	62.69	-14.64	48.05	54	-5.95	H	AV
7320	62.39	-8.28	54.11	74	-19.89	H	PK
7320	45.78	-8.28	37.5	54	-16.5	H	AV
4880	76.03	-14.64	61.39	74	-12.61	V	PK
4880	57.78	-14.64	43.14	54	-10.86	V	AV
7320	64.51	-8.28	56.23	74	-17.77	V	PK
7320	49.48	-8.28	41.2	54	-12.8	V	AV
BLE_1M_Highest Channel (2480MHz)							
4960	78.97	-14.53	64.44	74	-9.56	H	PK
4960	60.67	-14.53	46.14	54	-7.86	H	AV
7440	63.63	-8.13	55.5	74	-18.5	H	PK
7440	49.79	-8.13	41.66	54	-12.34	H	AV
4960	78.65	-14.53	64.12	74	-9.88	V	PK
4960	57.13	-14.53	42.6	54	-11.4	V	AV
7440	64.25	-8.13	56.12	74	-17.88	V	PK
7440	46.91	-8.13	38.78	54	-15.22	V	AV

Note 1: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded in report.18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.


6. Band-edge Emissions(Radiated)

6.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

6.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6 and section 6.10.



Test Setup Block Diagram

As the radiated emissions testing, set the Lowest and Highest Transmitting Channel, observed the outside band of 2310MHz to 2400MHz and 2483.5MHz to 2500MHz, than mark the higher-level emission for comparing with the FCC rules.

6.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.247 standard limit, and with the worst case as below:

Test Mode	Frequency	Limit	Result
	MHz	dBuV/dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

Radiated Emission Test Data (Band edge emissions)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
BLE_2M_Lowest Channel GFSK (2402MHz)							
2310	69.94	-21.34	48.6	74	-25.4	H	PK
2310	49.93	-21.34	28.59	54	-25.41	H	AV
2390	65.06	-20.96	44.1	74	-29.9	H	PK
2390	51.04	-20.96	30.08	54	-23.92	H	AV
2400	67.62	-20.91	46.71	74	-27.29	H	PK
2400	54.1	-20.91	33.19	54	-20.81	H	AV
2310	64.85	-21.34	43.51	74	-30.49	V	PK
2310	50.73	-21.34	29.39	54	-24.61	V	AV
2390	64.97	-20.96	44.01	74	-29.99	V	PK
2390	52.28	-20.96	31.32	54	-22.68	V	AV
2400	69.56	-20.91	48.65	74	-25.35	V	PK
2400	52.18	-20.91	31.27	54	-22.73	V	AV
BLE_2M_Highest Channel GFSK (2480MHz)							
2483.50	70.31	-20.51	49.8	74	-24.2	H	PK
2483.50	56.17	-20.51	35.66	54	-18.34	H	AV
2500	68.37	-20.43	47.94	74	-26.06	H	PK
2500	51.32	-20.43	30.89	54	-23.11	H	AV
2483.50	67.02	-20.51	46.51	74	-27.49	V	PK
2483.50	54.62	-20.51	34.11	54	-19.89	V	AV
2500	65.99	-20.43	45.56	74	-28.44	V	PK
2500	51.92	-20.43	31.49	54	-22.51	V	AV

Remark: Level = Reading + Factor, Margin = Level - Limit


7. Maximum Peak Conducted Output Power

7.1 Standard and Limit

According to 15.247(b)(3). For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

7.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 2MHz, VBW = 6MHz, Sweep = Auto, Detector = RMS.
- 4) Measure the highest amplitude appearing on spectral display and mark the value.
- 5) Repeat the above procedures until all frequencies measured were complete.




Test Setup Block Diagram

7.3 Test Data and Results


Test Mode	Test Channel MHz	Conducted Output Power (dBm)	Limit (dBm)	Test Result
BLE_1Mbps	2402	1.41	30	Pass
	2440	2.46	30	Pass
	2480	2.85	30	Pass

BLE_1Mbps


2402MHz



2440MHz



2480MHz



8. Occupied Bandwidth(-6dB)

8.1 Standard and Limit

According to 15.247(a)(2), Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto.
- 4) Set a reference level on the measuring instrument equal to the highest peak value.
- 5) Measure the frequency difference of two frequencies that were attenuated 6dB from the reference level.

Record the frequency difference as the emission bandwidth.

- 6) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

8.3 Test Data and Results

Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit 6 dB Bandwidth (MHz)	Test Result
BLE_1Mbps	2402	0.654	1.038	0.5	Pass
	2440	0.664	1.043	0.5	Pass
	2480	0.644	1.04	0.5	Pass

BLE_1Mbps

6dB bandwidth

2402MHz



99% bandwidth

2402MHz



2440MHz



2440MHz



2480MHz



2480MHz



9. Maximum Power Spectral Density

9.1 Standard and Limit

According to FCC 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

9.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 3kHz, VBW = 10kHz, Sweep = Auto, Detector = RMS.
- 4) Measure the highest amplitude appearing on spectral display and mark the value.
- 5) Repeat above procedures until all frequencies measured were complete.




Test Setup Block Diagram

9.3 Test Data and Results


Test Mode	Test Channel MHz	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Test Result
BLE_1Mbps	2402	-14.92	8	Pass
	2440	-13.77	8	Pass
	2480	-13.31	8	Pass

BLE_1Mbps


2402MHz



2440MHz



2480MHz



10. Band-edge Emission(Conducted)


10.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

10.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.10.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = RMS.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Set a convenient frequency span including 100 kHz bandwidth from band edge.
- 6) Measure the emission and marking the edge frequency.
- 7) Repeat above procedures until all frequencies measured were complete.




Test Setup Block Diagram

10.3 Test Data and Results


Test Mode	Band-edge	Test Channel (MHz)	Max. Value (dBc)	Limit (dBc)	Test Result
BLE_1Mbps	Lowest	2402	-35.93	-20	Pass
	Highest	2480	-43.5	-20	Pass

BLE_1Mbps Lowest

Reference Power




Band-edge Emission




BLE_1Mbps Highest

Reference Power



Band-edge Emission



11. Conducted RF Spurious Emissions


11.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

11.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.7.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = RMS.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Measure the spurious emissions with frequency range from 9kHz to 26.5GHz.
- 6) Repeat above procedures until all measured frequencies were complete.



Test Setup Block Diagram

11.3 Test Data and Results


Note: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions measurement data.

BLE_1Mbps Lowest

Reference Power



Spurious Emissions




BLE_1Mbps Middle

Reference Power



Spurious Emissions




BLE_1Mbps Highest

Reference Power



Spurious Emissions



***** END OF REPORT *****