



12. Radio Frequency Exposure

12.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)

12.2 EUT Specification

Frequency band (Operating)	☐ WLAN: 2412MHz ~ 2462MHz ☐ WLAN: 5150MHz ~ 5250MHz ☐ WLAN: 5250MHz ~ 5350MHz ☐ WLAN: 5470MHz ~ 5725MHz ☐ WLAN: 5725MHz ~ 5850MHz ☒ Bluetooth: 2402MHz ~ 2480MHz
Device category	☒ Portable (<20cm separation) ☐ Mobile (>20cm separation)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☐ Blanket 1 mW Blanket Exemption ☐ MPE-based Exemption ☒ SAR-based Exemption
Remark: The maximum conducted output power is 2.78dBm (2.13mW) at 2480MHz (with 0.57Bi antenna gain.)	

12.3 Test Result

Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Max. Tune up power (mW)	ANT Gain (dBi)	Max. Tune up e.i.r.p. Power (dBm)	Max. Tune up e.r.p. Power (dBm)	Max. Tune up e.r.p. Power (mW)	Distance (mm)	SAR test exclusion thresholds (mW)
2402-2480	2.78	3.28	2.13	0.70	3.98	1.83	1.52	5	2.72

No non-compliance noted.

-----THE END OF REPORT-----