

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout * G) / (4 * pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

Band	Frequency	Max output power (dBm)	Output power (mW)	Antenna gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Verdict
BT EDR	2441MHz	7.79	6.01	1.86	0.0018	1.0	PASS
BLE	2480MHz	6.47	4.44	1.86	0.0014	1.0	
2.4G WIFI	2437MHz ANT 1	18.32	67.92	2.31	0.0230	1.0	
	2412MHz MIMO	18.04	63.68	2.31	0.0215	1.0	
5.2G WIFI	5200MHz ANT 2	17.48	55.98	2.52	0.0199	1.0	
	5240MHz MIMO	16.85	48.42	2.52	0.0172	1.0	
5.3G WIFI	5290MHz ANT 2	16.83	48.19	3.51	0.0215	1.0	
	5320MHz MIMO	16.41	43.75	3.51	0.0195	1.0	
5.6G WIFI	5770MHz ANT 2	17.27	53.33	5.57	0.0383	1.0	
	5700MHz MIMO	16.62	45.92	5.57	0.0330	1.0	
5.8G WIFI	5755MHz ANT 2	18.20	66.07	4.61	0.0380	1.0	
	5775MHz MIMO	16.88	48.75	4.61	0.0280	1.0	

BT and WIFI Simultaneous Transmission:

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k}$$

BT + 2.4G WIFI =(0.0018/1)+(0.0230/1) =0.0018+0.0230=0.0248<1

BT + 5G WIFI=(0.0018/1) +(0.0380/1)=0.0018+0.0380=0.0398<1

The max power density is less than MPE exempt limit, so it is compliance.