

正反四色印刷 128g 铜版纸
尺寸: 90*100mm

90mm


100mm

Wireless HDMI Extender Transmitter & Receiver

USER
MANUAL

Connection Diagram

Please refer to the instructions to connect



Connection Steps


Connection of receiver and transmitter. The product has been paired out of the factory, plug and play.



1. Connect the HDMI port of the signal Receiver (RX) to the HDMI port of your monitor or TV. Then connect USB-C with your power Port and plug power cable into the power adapter. Connect the signal cable to the TV. The display enters the HDMI connection status screen.
2. Plug power cable into the power adapter and connect the signal transmitter (TX) to the computer or other device with HDMI audio output function. Current and voltage (power) are set.
3. Transmitter (TX) the indicator light changes from flashing to steady (about 3 seconds) to connection is complete.



Enjoying
the convenience of wireless HDMI



If you need any help, have any questions or complaints about the product, please do not hesitate to contact us (yourself, contact us immediately)

***Notes**
Please refer to user manual for connection and other details.
Please ensure that the transmitter (TX) of sound delay and receiver (Receiver) are always powered on and connected to power source or power cable. The connection will be interrupted if the device is disconnected by the power source lock (PLS) of the device to connect.

Pairing Settings
During use, the connection may be interrupted or other connection, the connection fails, or the connection is unstable.
Control center: The device needs to be restarted to connect.

***Notes 1** The max can pair with 1 TV.

Common problem

Q: What HDMI version of this product support? What is the Max resolution support?
A: This product support HDMI 2.0 Version. Max resolution is 4096x2160@60Hz.

Q: What are the functions of the product's function buttons?
A: Press the transmitter function button to disconnect or reconnect.

Q: Why the connection failed, or the connection was interrupted?
A: Please check the receiver and transmitter are plugged into working HD port when using.
A: Please check the power cord is plugged in. The current must not be less than 1A.
A: Please make sure there are not too many other wireless products around the product to avoid interference and also interference that may cause the product to be disconnected.
If the receiver is not working, please unplug the product together with power cable, connect the corresponding device, and repeat the connection steps.

Q: How does transmission distance and delay affect?
A: The product max transmission distance is 300m (984 feet), latency is less than 100ms. The actual speed of signal transmission is 100% to ensure the consistency of signal transmission.

Q: Why is the product not compatible with my phone?
A: The product supports computers, tablets, TV, mobile phones and other devices with HDMI interfaces. For smartphones, it only supports some models.

Q: Why do images appear blurred or stuck?
A: If it appears after successful connection and the words "Thinking" will be covered due to signal performance" appear at the bottom of the screen, this indicates the product has an automatic signal optimization function. The screen will return to the normal signal if the signal has too much interference and is not enough to maintain normal picture transmission and all products will connect to the previous signal and will not require a delay. Please refer to the user manual for more details. At this time, the user needs to adjust the position of the transmitter and receiver, change the use environment, shorten the distance between the transmitter and receiver, or change the power source. The above solutions are all to solve the problem, please contact the after-sales team.

If the above answers do not solve the problem, please contact the after-sales team. 24 hours dedicated service to you.

FCC Statement

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

Specific Absorption Rate (SAR) information:

This HDMI Wireless extender meets the government's requirements for exposure to radio waves. The guidelines are based on standards that were developed by independent scientific organizations through periodic and thorough evaluation of scientific studies. The standards include a substantial safety margin designed to assure the safety of all persons regardless of age or health. FCC RF Exposure Information and Statement the SAR limit of USA (FCC) is 1.6 W/kg averaged over one gram of tissue. Device types: HDMI Wireless extender has also been tested against this SAR limit. This device was tested for typical body-worn operations with the back of the HDMI Wireless extender kept 5mm from the body. To maintain compliance with FCC RF exposure requirements, use accessories that maintain an 5mm separation distance between the user's body and the back of the HDMI Wireless extender. The use of belt clips, holsters and similar accessories should not contain metallic components in its assembly. The use of accessories that do not satisfy these requirements may not comply with FCC RF exposure requirements, and should be avoided.