
357mm
63.3mm
11.7±0.5mm
2.5±0.3mm
4.6±0.3mm
3.8±0.3mm
tp-link | tapo
Smart Wi-Fi Power Strip
Model: Tapo P316M
Rating: 125V~ 60Hz 15A 1875W MAX
VPR: 1200V(L-N)
Type 3 SPD
USB: 5V ⎓ 2.4A Each & Total
CONFORMS TO UL STD.
1363&1449&62368- 1&60730-1
FCC ID: 2BH7FP316M
IC: 32876-P316M
Intertek
5013298
CAUTION:
To Reduce the Risk of Electric Shock – Use Only Indoors.
Risk of Electric Shock. Do not plug into another relocatable power tap or an extension cord.
USE ONLY IN DRY LOCATIONS.
WARNING:
Timer could turn-on unexpectedly without the user being present.
To Reduce the Hazardous Condition – Unplug the appliance from the receptacle before servicing.
This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: 1) This device may not cause harmful interference. 2) This device must accept any interference received, including interference that may cause undesired operation.
matter
1234-567-8901
MAC:XX-XX-XX-XX-XX-XX
S/N:XXXXXXXXXXXXX US/1.6
MADE IN VIETNAM


tp-link | tapo
Smart Wi-Fi Power Strip
Model: Tapo P316M
Rating: 125V~ 60Hz 15A 1875W MAX
VPR: 1200V(L-N)
Type 3 SPD
USB: 5V ⎓ 2.4A Each & Total
CONFORMS TO UL STD.
1363&1449&62368- 1&60730-1
FCC ID: 2BH7FP316M
IC: 32876-P316M
Intertek
5013298
CAUTION:
To Reduce the Risk of Electric Shock – Use Only Indoors.
Risk of Electric Shock. Do not plug into another relocatable power tap or an extension cord.
USE ONLY IN DRY LOCATIONS.
WARNING:
Timer could turn-on unexpectedly without the user being present.
To Reduce the Hazardous Condition – Unplug the appliance from the receptacle before servicing.
This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: 1) This device may not cause harmful interference. 2) This device must accept any interference received, including interference that may cause undesired operation.
matter
1234-567-8901
MAC:XX-XX-XX-XX-XX-XX
S/N:XXXXXXXXXXXXX US/1.6
MADE IN VIETNAM


Label Location