

# TEST REPORT

**Product Name** : Dosing pump  
**Model Number** : MP001  
**FCC ID** : 2BH8P-MP0XY

**Prepared for** : Bluewater Sweden AB  
**Address** : Danderydsgatan 11 11426 Stockholm Sweden

**Prepared by** : EMTEK (DONGGUAN) CO., LTD.  
**Address** : -1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology Research and Development Base, No.9, Xincheng Avenue, Songshanhu High-technology Industrial Development Zone, Dongguan, Guangdong, China

TEL: +86-0769-22807078  
FAX: +86-0769-22807079

**Report Number** : EDG2407290154E02202R  
**Date(s) of Tests** : July 29, 2024 to September 06, 2024  
**Date of issue** : September 06, 2024

## Table of Contents

1. TEST RESULT CERTIFICATION .....	3
2. EUT SPECIFICATION .....	5
3. TEST REQUIREMENT: .....	6
RF EXPOSURE EVALUATION .....	6



# 1. TEST RESULT CERTIFICATION

Applicant : Bluewater Sweden AB  
 Address : Danderydsgatan 11 11426 Stockholm Sweden  
 Manufacturer : Dongguan Filba Water Purification Technology Co., Ltd  
 Address : No. 5, Lian Xin Rd, Shang Jiao District, Chang' an Town, Dongguan City, Guangdong Province, China  
 EUT : Dosing pump  
 Model Name : MP001  
 Trademark : Bluewater

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093, 1.1307(b)(1)	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093, 1.1307(b)(1). The test results of this report relate only to the tested sample identified in this report

Date of Test : July 29, 2024 to September 06, 2024

Prepared by : Warren Deng  
 Warren Deng /Editor

Reviewer : Galen Xiao  
 Galen Xiao /Supervisor

Approve & Authorized Signer :  EMTEK (DONGGUAN) CO., LTD. TESTING  
 Sam Lv /Manager

## Modified History

Version	Report No.	Revision Date	Summary
	EDG2407290154E02202R	/	Original Report



## 2. EUT Specification

Characteristics	Description
<b>Product:</b>	Dosing pump
<b>Model Number:</b>	MP001
<b>Sample:</b>	2#
<b>Device Type:</b>	SRD
<b>Modulation:</b>	GFSK for SRD
<b>Operating Frequency Range(s) :</b>	2440 MHz
<b>Number of Channels:</b>	1 channel for SRD
<b>Transmit Power Max:</b>	93.15dBuV@3m for SRD
<b>Antenna Gain:</b>	4.04 dBi
<b>Power supply:</b>	DC12V from Adapter
<b>Evaluation applied:</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

### 3. Test Requirement:

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

- a) For 100 MHz to 6 GHz and *test separation distances* ≤ 50 mm, the 1-g and 10-g *SAR test exclusion thresholds* are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f_{(\text{GHz})}} \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR,}^{30} \text{ where}$$

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>31</sup>
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds* in step b) below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

- b) For 100 MHz to 6 GHz and *test separation distances* > 50 mm, the 1-g and 10-g *SAR test exclusion thresholds* are determined by the following (also illustrated in Appendix B):<sup>32</sup>

- 1) {[Power allowed at *numeric threshold* for 50 mm in step a)] + [(test separation distance – 50 mm) · (f<sub>(MHz)</sub>/150)]} mW, for 100 MHz to 1500 MHz
- 2) {[Power allowed at *numeric threshold* for 50 mm in step a)] + [(test separation distance – 50 mm) · 10]} mW, for > 1500 MHz and ≤ 6 GHz

- c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):<sup>33</sup>

- 1) For *test separation distances* > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by [1 + log(100/f<sub>(MHz)</sub>)]
- 2) For *test separation distances* ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by ½
- 3) SAR measurement procedures are not established below 100 MHz.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

According to ANSI C63.10-2013

9.5 Equations to calculate EIRP

Calculate the EIRP from the radiated field strength in the far field using Equation (22):

$$EIRP = E + 20\log(d) - 104.7 \quad (22)$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E is the field strength of the emission at the measurement distance, in dBμV/m

d is the measurement distance, in m

## 2.4G SRD

Channel Freq. (MHz)	Max Field Strength (dBuV/m)	peak output power (dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	Limit (mW/cm2)
2440	93.15	-1.01	-2±1	-1	0.00019894	1

According to KDB 447498 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines

\*\*\* End of Report \*\*\*