

1. RF Exposure Requirements

1.1 General Information

Client Information

Applicant: SHENZHEN VIEWPT-INNOVATIONS TECHNOLOGY CO., LTD
A1, 4th Floor, Block A, Building 13, Lehui Science and Technology
Address of applicant: Innovation Center, No. 489 Jihua Road, Bantian Street, Longgang
District, Shenzhen, Guangdong, China

Manufacturer: SHENZHEN VIEWPT-INNOVATIONS TECHNOLOGY CO., LTD
A1, 4th Floor, Block A, Building 13, Lehui Science and Technology
Address of manufacturer: Innovation Center, No. 489 Jihua Road, Bantian Street, Longgang
District, Shenzhen, Guangdong, China

General Description of EUT:

Product Name: Realia
Trade Name: /
Model No.: VR2
Adding Model(s): /
Rated Voltage: Battery DC7.4V
Battery Capacity: 1900mAh
Power Adapter: Power PD 30W
Input:AC100-240V 50/60Hz 1A
Output:DC5V5A;9V2A;12V2.5A 30W
FCC ID: 2BHEF-VR2
Equipment Type: Fixed device

Technical Characteristics of EUT:

Wi-Fi (2.4G)

Support Standards: 802.11b, 802.11g, 802.11n, 802.11ax
Frequency Range: 2412-2462MHz for 802.11b/g/n/ax(HT/HE20)
RF Output Power: Antenna 1: 15.21dBm (Conducted)
Antenna 2: 15.10dBm (Conducted)
Type of Modulation: CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM, 256QAM,1024QAM
Quantity of Channels: 11 for 802.11b/g/n/ax(HT/HE20)
Channel Separation: 5MHz
Type of Antenna: FPC antenna
Antenna Gain: Antenna 1: 2.13dBi; Antenna 2: 1.35dBi

Wi-Fi (5G)

Support Standards: 802.11a, 802.11n(HT20) , 802.11n-HT40,
802.11ac-VHT20/40/80, 802.11ax-HE20/40/80
Frequency Range: 5180-5240MHz, 5745-5825MHz
Max. RF Output Power: Antenna 1: 15.96dBm (Conducted)

Type of Modulation:	Antenna 2: 15.77dBm (Conducted) QPSK, 16QAM, 64QAM;256QAM; 1024QAM
Type of Antenna:	FPC antenna 5180-5240MHz
Antenna Gain:	Antenna 1: 2.18dBi; Antenna 2: 3.53dBi 5745-5825MHz Antenna 1: 3.16dBi; Antenna 2: 4.21dBi

1.2 RF Exposure Exemption

According to §1.1307(b)(3) and KDB 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Option A: FCC Rule Part 1.1307 (b)(3)(i)(A):The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

Option B: FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C: FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R ²
1.34-30	3,450 R ² /f ²
30-300	3.83 R ²
300-1,500	0.0128 R ² f
1,500-100,000	19.2R ²

For Multiple RF sources: FCC Rule Part 1.1307(b)(3)(ii):

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

1.3 Calculated Result

Radio Access Technology	Prediction Frequency (MHz)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	Tune-Up Time-Averaged Power (dBm)	ERP (dBm)
Wi-Fi (2.4G) Antenna 1	2412	15.21	2.13	100	16.00	15.98
Wi-Fi (2.4G) Antenna 2	2412	15.10	1.35	100	16.00	15.20
Wi-Fi (5G) Antenna 1	5180	15.44	2.18	100	16.00	16.03
Wi-Fi (5G) Antenna 2	5180	15.77	3.53	100	16.00	17.38
Wi-Fi (5G) Antenna 1	5745	15.96	3.16	100	16.00	17.01
Wi-Fi (5G) Antenna 2	5745	15.35	4.21	100	16.00	18.06

Frequency (MHz)	Option	Min. Distance	Max. Power		Exposure Limit	Ratio	Result
		(cm)	(dBm)	(mW)	(mW)		Pass/Fail
2412	C	20.00	15.98	39.63	768.00	0.05	Pass

2412	C	20.00	15.20	33.11	768.00	0.04	Pass
5180	C	20.00	16.03	40.09	768.00	0.05	Pass
5180	C	20.00	17.38	54.70	768.00	0.07	Pass
5745	C	20.00	17.01	50.23	768.00	0.07	Pass
5745	C	20.00	18.06	63.97	768.00	0.08	Pass

Note: 1. Time-Averaged Power=Output Power * Duty Cycle; ERP= Time-Averaged Power+ Antenna gain-2.15dB

2. Option A, B and C refers as clause 1.2.

3. For option B, Max (time-averaged power, effective radiated power (ERP)) converts to Max. Power. For option C, ERP converts to Max. Power;

4. For option B, P_{th} (mW) converts to Exposure Limit (mW); For option C, ERP (W) converts to Exposure Limit (mW).

5. Ratio= Tune-Up ERP (mW)/ Exposure Limit (mW)

Mode for Simultaneous Multi-band Transmission:

Radio Access Technology	Ratio 1	Ratio 2	Simultaneous Ratio	Limit	Result
					Pass/Fail
Antenna 1 + Antenna 2	0.07	0.08	0.15	1	Pass

Result: Pass