



EMC TEST REPORT

Report No.: 20240817G15837X-W1

Product Name: Discovery Series Night Vision

FCC ID: 2BHFB-DR200

Model No. : Discovery DR200

Trade Name: Nocpix Recreation

Applicant: Inlumen Technologies Co., Ltd.

Address: Building B3, NO.800 Wangjiang West Road, National High-tech Industry Development District, Hefei, Anhui, China.

Received Date: 2024.08.16

Dates of Testing: 2024.08.16-2024.09.24

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No.43, Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

Tel: 86-755-26627338 **E-Mail:** manager@ccic-set.com

This test report consists of **19** pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product Name..... Discovery Series Night Vision

Model No. Discovery DR200

Applicant..... Inlumen Technologies Co., Ltd.

Applicant Address..... Building B3, NO.800 Wangjiang West Road, National High-tech Industry Development District, Hefei, Anhui, China.

Manufacturer..... Inlumen Technologies Co., Ltd.

Manufacturer Address..... Building B3, NO.800 Wangjiang West Road, National High-tech Industry Development District, Hefei, Anhui, China.

Test Standards..... 47 CFR Part 15 Subpart B

Test Result..... PASS

Tested by Sun Jiaohui
Sun Jiaohui, Test Engineer 2024.10.18

Reviewed by..... Chris You
Chris You, Senior Engineer 2024.10.18

Approved by..... Wang Shijie
Wang Shijie, Manager 2024.10.18



TABLE OF CONTENTS

1.	GENERAL INFORMATION	4
1.1	EUT Description	4
1.2	Test Standards and Results	5
1.3	Facilities and Accreditations	6
1.3.1	Facilities	6
1.3.2	Test Environment Conditions	6
1.3.3	Measurement Uncertainty	6
2.	TEST CONDITIONS SETTING	7
2.1	Test Peripherals	7
2.2	Test Mode	7
2.3	Test Setup and Equipments List	8
2.3.1	Conducted Emission	8
2.3.2	Radiated Emission	9
3.	47 CFR PART 15B REQUIREMENTS	11
3.1	Conducted Emission	11
3.1.1	Requirement	11
3.1.2	Test Description	11
3.1.3	Test Result	11
3.2	Radiated Emission	14
3.2.1	Requirement	14
3.2.2	Test Description	15
3.2.3	Test Result	15

Change History		
Issue	Date	Reason for change
1.0	2024.10.18	First edition

1. GENERAL INFORMATION

1.1 EUT Description

EUT Name	Discovery Series Night Vision
Power supply	Battery Model No: INR18650-32E Rated Capacity: 3200mAh Rated Voltage: 3.7V Manufacturer: Dongguan Rishengzhi New Energy Technology Co., Ltd.

Note 1: The EUT is a Discovery Series Night Vision; It could support the following operating mode and frequency band: 2.4G WIFI

Note 2: The EUT have the following typical setups during the test:

Setup1: 2.4G WIFI + EUT working + Adapter + Charger;

Setup2: 2.4G WIFI + EUT working + Battery;

Setup3: EUT + Notebook PC + DATA;

Note 3: All the patterns have been tested and only the worst results are recorded in the report.

Note 4: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE:

- (1) The EUT has been tested according to 47 CFR Part 15 Subpart B, CLASS B. The test procedure is according to ANSI C63.4:2014.



1.3 Facilities and Accreditations

1.3.1 Facilities

FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until Jun.30, 2025.

ISED Registration: 11185A-1

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until Jun.30, 2025.

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15°C - 35°C
Relative Humidity (%):	25% -75%
Atmospheric Pressure (kPa):	86kPa-106kPa

1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	Uc = 3.2 dB (k=2)
Uncertainty of Radiated Emission: (30MHz~1GHz)	Uc = 5.8 dB (k=2)
Uncertainty of Radiated Emission: (1~6GHz)	Uc = 5.1 dB (k=2)
Uncertainty of Radiated Emission: (6~18GHz)	Uc = 5.5 dB (k=2)



2. TEST CONDITIONS SETTING

2.1 Test Peripherals

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Support Equipment:

Description	Brand name	Model	Serial No.	FCCID
Adapter	/	VC56JBCH	/	/
Notebook	Lenovo	ThinkPad E14	/	/

Support Cable:

Description	Shield Type	Ferrite Core	Length
/	/	/	/

2.2 Test Mode

The EUT have the following typical setups during the test:

Setup1: 2.4G WIFI + EUT working + Adapter + Charger;


Setup2: 2.4G WIFI + EUT working + Battery;

Setup3: EUT + Notebook PC + DATA;

2.3 Test Setup and Equipments List

2.3.1 Conducted Emission

A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu\text{H}$ of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.


B. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
Test Receiver	KEYSIGHT	N9038A	A141202036	2024.06.05	2025.06.04
LISN	ROHDE&SCHWARZ	ENV216	A140701847	2024.05.23	2025.05.22
Cable	MATCHING PAD	W7	/	2024.08.02	2025.08.01


2.3.2 Radiated Emission

A. Test Setup:

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz



**B. Test Procedure**

The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

- 1) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

C. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
EMI Test Receiver	ROHDE&SCHWARZ	ESIB7	A0501375	2024.02.28	2025.02.27
Broadband Ant.	ETC	MCTD2786	A150402239	2024.01.19	2025.01.18
3M Anechoic Chamber	Albatross	SAC-3MAC 9*6*6m	A0412375	2024.02.27	2027.02.27
EMI Test Receiver	ROHDE&SCHWARZ	ESW26	A180502935	2024.05.24	2025.05.23
5M Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4m	A0304210	2022.03.25	2025.06.07
EMI Horn Ant.	ROHDE&SCHWARZ	HF906	A0304225	2022.04.12	2025.04.11

3. 47 CFR PART 15B REQUIREMENTS

3.1 Conducted Emission

3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2 Test Description

See section 2.3.1 of this report.

3.1.3 Test Result


The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

Note:

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a Nominal 230V AC, 50/60Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Test voltage and frequency (230V AC, 60Hz)


A. Mains terminal disturbance voltage, L phase, Setup 1



(Plot A: L Phase)

Frequency (MHz)	QuasiPea k	CAverage (dB μ V)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dB μ V)
0.150000	43.25	26.32	0.1	10.1	22.75	66.0	29.68	56.0
0.258000	35.69	25.58	0.1	10.1	25.80	61.5	25.92	51.5
0.307500	34.59	26.52	0.1	10.1	25.45	60.0	23.51	50.0
0.528000	33.69	25.31	0.1	10.1	22.31	56.0	20.69	46.0
4.461000	31.45	16.99	0.5	10.5	24.55	56.0	29.01	46.0
17.151000	35.16	27.68	0.5	10.5	24.84	60.0	22.32	50.0

B. Mains terminal disturbance voltage, N phase, Setup 1



(Plot B: N Phase)

Frequency (MHz)	QuasiPea k	CAverage (dB μ V)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dB μ V)
0.150000	40.23	25.86	0.1	10.1	25.77	66.0	30.14	56.0
0.186000	37.55	24.57	0.1	10.1	26.66	64.2	29.64	54.2
0.528000	31.65	23.65	0.1	10.1	24.35	56.0	22.35	46.0
1.072500	29.80	18.97	0.2	10.2	26.20	56.0	27.03	46.0
1.135500	28.14	18.21	0.2	10.2	27.86	56.0	27.79	46.0
16.674000	32.67	25.05	0.5	10.5	27.33	60.0	24.95	50.0

3.2 Radiated Emission

3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength		Field Strength Limitation at 3m Measurement Dist	
	$\mu\text{V/m}$	Dist	($\mu\text{V/m}$)	(dBuV/m)
30.0 - 88.0	100	3m	100	$20\log 100$
88.0 - 216.0	150	3m	150	$20\log 150$
216.0 - 960.0	200	3m	200	$20\log 200$
Above 960.0	500	3m	500	$20\log 500$

- For frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.
- Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.
- For below 1G: QP detector RBW 120 kHz, VBW 300 kHz.

For Above 1G: PK detector RBW 1MHz, VBW 3MHz for PK value; AV detector RBW 1MHz, VBW 10Hz for AV value.

Note:

- The tighter limit shall apply at the boundary between two frequency range.
- Limitation expressed in dBuV/m is calculated by $20\log \text{Emission Level}(\mu\text{V/m})$.
- If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of $Ld1 = Ld2 * (d2/d1)^2$.

Example:

F.S Limit at 30m distance is $30\mu\text{V/m}$, then F.S Limitation at 3m distance is adjusted as

$$Ld1 = L1 = 30\mu\text{V/m} * (10)^2 = 100 * 30\mu\text{V/m}.$$

3.2.2 Test Description

See section 2.3.2 of this report.


3.2.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.


A. Radiation disturbances, antenna polarization: Vertical, Setup1



(Plot C: Test Antenna Vertical 30M - 1G)

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB μ V/m)	Margin (dB)	Antenna	Cable Loss(dB)	ANT. Factor(dB)	Verdict
43.60	27.21	120.000	103	40.0	12.79	Vertical	0.5	11.2	Pass
51.40	20.42	120.000	108	40.0	19.58	Vertical	0.6	7.8	Pass
92.20	14.99	120.000	102	43.5	28.51	Vertical	0.8	9.3	Pass
133.04	15.83	120.000	106	43.5	27.67	Vertical	1.0	11.6	Pass
350.76	36.75	120.000	107	46.0	9.25	Vertical	1.4	15.6	Pass
514.04	25.69	120.000	103	46.0	20.31	Vertical	1.5	18.2	Pass


B. Radiation disturbances, antenna polarization: Horizontal, Setup1



(Plot D: Test Antenna Horizontal 30M - 1G)

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB μ V/m)	Margin (dB)	Antenna	Cable Loss(dB)	ANT. Factor(dB)	Verdict
30.00	14.26	120.000	104	40.0	25.74	Horizontal	0.5	18.8	Pass
43.60	10.94	120.000	103	40.0	29.06	Horizontal	0.5	11.4	Pass
92.20	16.99	120.000	107	43.5	26.51	Horizontal	0.8	9.3	Pass
101.92	12.92	120.000	106	43.5	30.58	Horizontal	0.9	10.2	Pass
350.74	40.18	120.000	104	46.0	5.82	Horizontal	1.4	15.6	Pass
471.26	25.95	120.000	102	46.0	20.05	Horizontal	1.5	17.6	Pass


A. Radiation disturbances, antenna polarization: Vertical, Setup1



(Plot M: Test Antenna Vertical 1G – 18G)

NO	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin[dB μV/m]	Trace	Height [cm]	Angle [°]	Polarity
1	1686.87	34.52	-13.30	74.00	39.48	PK	106	83	Vertical
2	1710.67	27.63	-13.20	54.00	26.37	AV	103	231	Vertical
3	3023.20	31.88	-8.53	54.00	22.12	AV	107	18	Vertical
4	3075.91	39.60	-8.37	74.00	34.40	PK	101	76	Vertical
5	4667.27	45.98	-1.23	74.00	28.02	PK	106	94	Vertical
6	4702.97	38.08	-1.08	54.00	15.92	AV	105	163	Vertical
7	6802.68	48.87	2.98	74.00	25.13	PK	102	56	Vertical
8	7197.12	41.91	3.48	54.00	12.09	AV	107	32	Vertical
9	10860.99	51.38	6.54	74.00	22.62	PK	106	348	Vertical
10	10888.19	43.68	6.57	54.00	10.32	AV	104	360	Vertical
11	17848.68	54.53	14.07	74.00	19.47	PK	102	303	Vertical
12	17969.40	46.34	14.80	54.00	7.66	AV	108	354	Vertical

B. Radiation disturbances, antenna polarization: Horizontal, Setup1



(Plot N: Test Antenna Horizontal 1G – 18G)

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin[dB μV/m]	Trace	Height [cm]	Angle [°]	Polarity
1	1686.87	27.79	-13.30	54.00	26.21	AV	107	351	Horizontal
2	1722.57	35.03	-13.14	74.00	38.97	PK	103	266	Horizontal
3	2406.04	30.91	-10.64	54.00	23.09	AV	106	284	Horizontal
4	2525.05	37.98	-10.17	74.00	36.02	PK	108	73	Horizontal
5	4585.66	37.70	-1.63	54.00	16.30	AV	103	258	Horizontal
6	4665.57	44.98	-1.24	74.00	29.02	PK	104	275	Horizontal
7	6442.24	41.83	2.23	54.00	12.17	AV	101	126	Horizontal
8	6765.28	48.81	2.86	74.00	25.19	PK	104	87	Horizontal
9	10543.05	50.96	6.26	74.00	23.04	PK	107	333	Horizontal
10	10762.38	42.96	6.41	54.00	11.04	AV	106	214	Horizontal
11	14244.32	44.18	9.64	54.00	9.82	AV	103	268	Horizontal
12	14300.43	51.83	9.89	74.00	22.17	PK	105	46	Horizontal

-----End of Report-----