



RF TEST REPORT

Report No.: 20240817G15734X-W3

Product Name: LUMI Thermal Imaging Monocular

Main Model No. : LUMI L19

Series Model No. : LUMI L35, LUMI H35, LUMI P13

FCC ID: 2BHFB-LUMI-00

Applicant: Inlumen Technologies Co., Ltd.

Address: Building B3, NO.800 Wangjiang West Road, National High-tech Industry Development District, Hefei, Anhui, China.

Dates of Testing: 08/14/2024 - 09/03/2024

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No.43, Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

Tel: 86-755-26627338 **E-Mail:** manager@ccic-set.com

This test report consists of 54 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product.....: LUMI Thermal Imaging Monocular

Trade Name: Nocpix

Applicant.....: Inlumen Technologies Co., Ltd.


Applicant Address.....: Building B3, NO.800 Wangjiang West Road, National High-tech Industry Development District, Hefei, Anhui, China.

Manufacturer.....: Inlumen Technologies Co., Ltd.


Manufacturer Address.....: Building B3, NO.800 Wangjiang West Road, National High-tech Industry Development District, Hefei, Anhui, China.

Test Standards.....: 47 CFR Part 15 Subpart C 15.247
ANSI C63.10-2020

Test Result.....: Pass

Tested by:  2024.09.03

Chuiwang Zhang, Test Engineer

Reviewed by.....:  2024.09.03

Sun Jiaohui, Senior Engineer

Approved by.....:  2024.09.03

Chris You, Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. EUT Description	5
1.2. Test Standards and Results	6
1.3. Channel List	6
1.4. Test environment and mode	7
1.5. Table for Supporting Units	7
1.6. EUT Operation Test Setup	7
1.7. Laboratory Facilities	8
2. TEST REQUIREMENTS	9
2.1. Antenna requirement	9
2.2. Maximum Conducted Output Power	10
2.3. 6dB and 99% Bandwidth	12
2.4. Power spectral density (PSD)	14
2.5. Conducted Band Edges and Spurious Emissions	16
2.6. Radiated Band Edge and Spurious Emission	18
2.7. AC Power Line Conducted Emission	30
3. LIST OF MEASURING EQUIPMENT	34
4. UNCERTAINTY OF EVALUATION	35
APPENDIX A	36



Change History		
Issue	Date	Reason for change
1.0	2024.09.03	First edition

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	LUMI Thermal Imaging Monocular
EUT supports Radios application	WLAN2.4GHz 802.11b/g/n(20MHz)
Frequency Range	802.11b/g/n(20MHz): 2.412GHz - 2.462GHz
Channel Number	802.11b/g/n-20MHz: 11
Transfer Rate	802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n: up to 72.2 Mbps
Modulation Type	DSSS (802.11b), OFDM (802.11g/n)
Antenna Type	Internal Antenna
Antenna Gain	2.2dBi
Power supply	Model No: JQ033-203L Rated Capacity:3850mAh Typical Capacity: 4000mAh Rated Voltage: 3.6 V Manufacturer: Jinqu New Energy (Zhejiang) Co., Ltd.

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Note 2: The information of antenna gain and cable loss is provided by the manufacturer and our lab is not responsible for the accuracy of the antenna gain and cable loss information.

Note 3: That the IRIS IL35 have the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction, with IRIS IL19. The difference lies only in lens focal length of the different models.

Note 4: LUMI L35 has the same technical construction as LUMI L19, including circuit diagrams, PCB layouts, components and their layouts, all electrical constructions, and mechanical constructions, with the only difference being the lens focal length of the different models. LUMI H35 also has the same technical construction as LUMI L19, including circuit diagrams, PCB layouts, components and their layouts, all electrical constructions, and mechanical constructions, with the differences lying only in the lens focal length and the thermal imaging module of the different models. LUMI P13 shares the same technical construction with LUMI L19, including circuit diagrams, PCB layouts, components and their layouts, all electrical constructions, and mechanical constructions, with the differences being only in the lens focal length and the thermal imaging module of the different models.

1.2. Test Standards and Results

The purpose of the report is to conduct testing according to the following FCC certification standards:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart C	Radio Frequency Devices
2	KDB 558074 D01 15.247 Meas Guidance v05r02	Cuidance for Compliance Measurement on Digital Transmission Systems, Frequency Hopping Spread Spectrum Systems, and Hybrid System Devices Operating under Section 15.247 of the FCC Rules
4	ANSI C63.10-2020	American National Standard for Testing Unlicensed Wireless Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	Description	Result
1	15.203 15.247(c)	Antenna Requirement	PASS
2	15.247(b)(3)	Maximum Conducted Output Power	PASS
3	15.247(a)(2)	6dB and 99% Bandwidth	PASS
4	15.247(d)	Conducted Band Edges and Spurious Emission	PASS
5	15.247(e)	Power spectral density (PSD)	PASS
6	15.207	AC Power Line Conducted Emission	PASS
7	15.205 15.209 15.247(d)	Radiated Band Edges and Spurious Emission	PASS

Note 1: The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10-2020.

Note 2: These RF tests were performed according to the method of measurements prescribed in KDB 558074 D01 15.247 Meas Guidance v05r02.

1.3. Channel List

Channel No.	Frequency	Channel No.	Frequency	Channel No.	Frequency
1	2412MHz	5	2432MHz	9	2452MHz
2	2417MHz	6	2437MHz	10	2457MHz
3	2422MHz	7	2442MHz	11	2462MHz
4	2427MHz	8	2447MHz	/	/

Note: Channel 1, 6 & 11 selected for 802.11b/g/n-20MHz as Lowest, Middle and Highest channel.

1.4. Test environment and mode

During the measurement, the environmental conditions were within the listed ranges:

Operating Environment	
Temperature	15°C - 35°C
Humidity	30% -60%
Atmospheric Pressure	86kPa-106kPa
Test mode:	
Continuously transmitting mode	Keep the EUT in continuous transmitting with modulation

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Conducted Output Power Power Spectral Density 6dB and 99% Bandwidth Conducted Spurious Emission Radiated Spurious Emission	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n-HT20/OFDM	MCS 0	1/11
	11n-HT40/OFDM	MCS 0	3/9
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n-HT20/OFDM	MCS 0	1/11
	11n-HT40/OFDM	MCS 0	3/9

1.5. Table for Supporting Units

No.	Equipment	Brand Name	Model Name	Manufacturer	Serial No.	Note
1	Laptop	HP	TPN-Q221	HP	5CD14347QB	FCC DOC

1.6. EUT Operation Test Setup

For RF test items, an engineering test program was provided and enable to make EUT transmitting.



1.7. Laboratory Facilities

FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until Jun. 30th, 2025.

ISED Registration: 11185A

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A on Aug. 04, 2016, valid time is until Jun. 30th, 2025.

CAB number: CN0064

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

2. Test Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

And according to FCC 47 CFR Section 15.247(c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

2.1.2. Antenna Information

Antenna Category: Internal Antenna

A internal Antenna was soldered to the antenna port of EUT via an adaptor cable, can't be removed.

Antenna General Information:

No.	EUT	Operating frequency range	Ant. Type	Ant. Gain
1	LUMI Thermal Imaging Monocular	2412-2462MHz	Internal Antenna	2.2dBi

1.1.1. Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Maximum Conducted Output Power


2.2.1. Limit of Maximum Conducted Output Power

For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W.

2.2.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.2.3. Test Setup



2.2.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 Section 11.9.2.2.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings:
Set instrument center frequency to DTS channel center frequency / Set span to at least 1.5 times the OBW / $RBW = 1\% \text{ to } 5\% \text{ of the OBW, not to exceed } 1 \text{ MHz.}$ / Set $VBW \geq [3 \times RBW]$. /
Detector: RMS / Sweep time: Auto / Trace mode: Average / Trace average at least 100 traces in power averaging (rms) mode.
5. Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges.
6. Add $[10 \log (1 / D)]$, where D is the duty cycle), to the measured PSD to compute the average PSD during the actual transmission time.
7. Record the measurement results in the test report.



2.2.5. Test Result of Maximum Conducted Output Power

Please refer to Appendix A for detail.

2.3. 6dB and 99% Bandwidth


2.3.1. Limit of 6dB Bandwidth

The minimum 6 dB Occupied bandwidth shall be at least 500 kHz.

2.3.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.3.3. Test Setup



2.3.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 Section 11.8.1 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the spectrum analyzer “Channel Bandwidth” function to easurement the 6dB EBW and 99% OBW.
5. For 6dB EBW Use the following spectrum analyzer settings:
RBW: 100kHz / VBW: 300kHz / Detector: Peak / Trace mode: Max hold / Sweep time: Auto couple / Allow trace to fully stabilize.
6. For 99% OBW Use the following spectrum analyzer settings:
Set Span = 1.5 times to 5.0 times the OBW/ $RBW = \text{Within } 1\% \text{ to } 5\% \text{ of OBW/VBW} \geq 3 \times RBW$
Set Detector = Peak/Trace mode = max hold/ Sweep time = auto couple.
7. Record the measurement results in the test report.



2.3.5. Test Results of 6dB and 99% Bandwidth

Please refer to Appendix A for detail.

2.4. Power spectral density (PSD)


2.4.1. Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

2.4.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.4.3. Test Setup



2.4.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 Section 11.10.5.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings:
Set instrument center frequency to DTS channel center frequency / Set the span to 1.5 times the DTS bandwidth / RBW: 3kHz / VBW: 10kHz / Detector: RMS / Sweep time: Auto couple / Trace mode: Average / Employ trace averaging (rms) mode over a minimum of 100 traces / Use the peak marker function to determine the maximum power level.
5. Add $[10 \log (1 / D)]$, where D is the duty cycle), to the measured PSD to compute the average PSD during the actual transmission time.
6. Record the measurement results in the test report.



2.4.5. Test Results of Power Spectral Density

Please refer to Appendix A for detail.

2.5. Conducted Band Edges and Spurious Emissions


2.5.1. Limit of Conducted Band Edges and Spurious Emissions

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

2.5.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.5.3. Test Setup



2.5.4. Test Procedure

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 Section 11.11 and 11.12.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings:

Reference level measurement: Set spectrum analyzer center frequency to DTS channel center frequency / Set the span to ≥ 1.5 times the DTS bandwidth / RBW: 100kHz / VBW: 300kHz /

Detector: Peak / Sweep time: Auto couple / Trace mode: Max hold / Allow trace to fully stabilize /

Use the peak marker function to determine the maximum PSD level and attenuate it by 30dB.

Emission level measurement: Set the center frequency and span to encompass frequency range to be measured / RBW: 100kHz / VBW: 300kHz / Detector: Peak / Sweep time: Auto couple / Trace mode: Max hold / Allow trace to fully stabilize / Use the peak marker function to determine the maximum amplitude level.

5. Record the measurement results in the test report.



2.5.5. Test Results of Conducted Band Edges and Spurious Emissions

Please refer to Appendix A for detail.

2.6. Radiated Band Edge and Spurious Emission

2.6.1. Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level. If the transmitter uses an RMS average conducted power limit, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

§15.209(a) Radiated emission limits:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Restricted bands of operation refer to §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41	/	/	/

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.


²Above 38.6.

2.6.2. Measuring Instruments


The measuring equipment is listed in the section 3 of this test report.

2.6.3. Test Setup


For radiated emissions from 9 kHz to 30 MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



2.6.4. Test Procedures

1. The EUT was placed on the top of a rotating table 0.8m for below 1GHz and 1.5m for above 1GHz above the ground at a 3 meters semi-anechoic chamber.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then

reported in a data sheet.

7. For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $> 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

2.6.5. Test Results of Radiated Band Edge and Spurious Emission


For 9 kHz to 30MHz, The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

For 30MHz to 1GHz, All of the EUT Configure mode were tested and found 802.11b_2462MHz channel is the worst mode, the worst case is recorded in this report.

For 1GHz to 25GHz, Only worst-case data is reported.

For 30MHz to 1000MHz

Test site:	3M anechoic chamber	Environment:	Temp: 23℃; Humi:48%;101kPa
Operator:	Huang Chaoming	Test Date:	2024.08.23
Test Mode:	WIFI - TX	Test Result:	Pass




Frequency (MHz)	QuasiPeak (dBμV/m)	Bandwidth (kHz)	Height (cm)	Polarity	Corr. (dB/m)	Margin - QPK	Limit - QPK
30.000000	14.62	120.000	100.0	H	19.2	25.38	40.0
33.887776	13.10	120.000	100.0	H	17.4	26.90	40.0
150.521042	19.51	120.000	100.0	H	12.1	23.99	43.5
164.128257	28.62	120.000	100.0	H	12.0	14.88	43.5
385.731463	29.84	120.000	100.0	H	16.6	16.16	46.0
644.268537	31.06	120.000	100.0	H	21.2	14.94	46.0

Remark:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB).
- Margin value = Limit value - Emission Level.
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Only the antenna height (from 1m to 4m) at maximum reading are recorded.

Test site:	3M anechoic chamber	Environment:	Temp: 23°C; Humi:48%;101kPa
Operator:	Huang Chaoming	Test Date:	2024.08.23
Test Mode:	WIFI - TX	Test Result:	Pass



Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Height (cm)	Polarity	Corr. (dB/m)	Margin - QPK	Limit - QPK
43.607214	24.80	120.000	100.0	V	12.6	15.20	40.0
82.484970	27.43	120.000	100.0	V	8.2	12.57	40.0
136.913828	25.03	120.000	100.0	V	11.7	18.47	43.5
164.128257	39.55	120.000	100.0	V	12.0	3.95	43.5
385.731463	29.67	120.000	100.0	V	16.6	16.33	46.0
644.268537	32.00	120.000	100.0	V	21.2	14.00	46.0

Remark:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB).
- Margin value = Limit value - Emission Level.
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Only the antenna height (from 1m to 4m) at maximum reading are recorded.

For 1GHz to 25GHz

2.4G Wi-Fi 802.11b_2412MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
2390.00	52.48	74.00	-21.52	1.50	200	55.57	-3.09	Horizontal	Peak
2390.00	42.81	54.00	-11.19	1.50	200	45.90	-3.09	Horizontal	Average
4824.00	47.35	74.00	-26.65	1.50	200	46.18	1.17	Horizontal	Peak
4824.00	41.38	54.00	-12.62	1.50	200	40.21	1.17	Horizontal	Average
7236.00	51.36	74.00	-22.64	1.50	200	45.41	5.95	Horizontal	Peak
7236.00	41.33	54.00	-12.67	1.50	200	35.38	5.95	Horizontal	Average
2390.00	54.14	74.00	-19.86	1.50	180	57.23	-3.09	Vertical	Peak
2390.00	43.03	54.00	-10.97	1.50	180	46.12	-3.09	Vertical	Average
4824.00	48.91	74.00	-25.09	1.50	180	47.74	1.17	Vertical	Peak
4824.00	41.08	54.00	-12.92	1.50	180	39.91	1.17	Vertical	Average
7236.00	51.35	74.00	-22.65	1.50	180	45.40	5.95	Vertical	Peak
7236.00	41.32	54.00	-12.68	1.50	180	35.37	5.95	Vertical	Average
2.4G Wi-Fi 802.11b_2437MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
4874.00	47.03	74.00	-26.97	1.50	200	46.07	0.96	Horizontal	Peak
4874.00	41.80	54.00	-12.20	1.50	200	40.84	0.96	Horizontal	Average
7311.00	51.46	74.00	-22.54	1.50	200	45.92	5.54	Horizontal	Peak
7311.00	40.88	54.00	-13.12	1.50	200	35.34	5.54	Horizontal	Average
4874.00	49.35	74.00	-24.65	1.50	180	48.39	0.96	Vertical	Peak
4874.00	41.11	54.00	-12.89	1.50	180	40.15	0.96	Vertical	Average
7311.00	51.74	74.00	-22.26	1.50	180	46.20	5.54	Vertical	Peak
7311.00	40.97	54.00	-13.03	1.50	180	35.43	5.54	Vertical	Average
Remark: - Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m) - Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB) - Margin value = Emission Level – Limit value - The emission levels of other frequencies are very lower than the limit and not show in test report. - Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.									

2.4G Wi-Fi 802.11b_2462MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
2483.50	53.95	74.00	-20.05	1.50	200	58.70	-4.75	Horizontal	Peak
2483.50	43.84	54.00	-10.16	1.50	200	48.59	-4.75	Horizontal	Average
4924.00	47.25	74.00	-26.75	1.50	200	46.65	0.60	Horizontal	Peak
4924.00	40.04	54.00	-13.96	1.50	200	39.44	0.60	Horizontal	Average
7386.00	50.80	74.00	-23.20	1.50	200	44.87	5.93	Horizontal	Peak
7386.00	40.95	54.00	-13.05	1.50	200	35.02	5.93	Horizontal	Average
2483.50	53.78	74.00	-20.22	1.50	180	58.53	-4.75	Vertical	Peak
2483.50	44.01	54.00	-9.99	1.50	180	48.76	-4.75	Vertical	Average
4924.00	46.72	74.00	-27.28	1.50	180	46.12	0.60	Vertical	Peak
4924.00	36.77	54.00	-17.23	1.50	180	36.17	0.60	Vertical	Average
7386.00	51.40	74.00	-22.60	1.50	180	45.47	5.93	Vertical	Peak
7386.00	40.95	54.00	-13.05	1.50	180	35.02	5.93	Vertical	Average
Remark: 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m) 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB) 3. Margin value = Emission Level – Limit value 4. The emission levels of other frequencies are very lower than the limit and not show in test report. 5. Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.									

2.4G Wi-Fi 802.11g_2412MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
2390.00	52.06	74.00	-21.94	1.50	200	55.15	-3.09	Horizontal	Peak
2390.00	42.89	54.00	-11.11	1.50	200	45.98	-3.09	Horizontal	Average
4824.00	47.04	74.00	-26.96	1.50	200	45.87	1.17	Horizontal	Peak
4824.00	41.29	54.00	-12.71	1.50	200	40.12	1.17	Horizontal	Average
7236.00	51.15	74.00	-22.85	1.50	200	45.20	5.95	Horizontal	Peak
7236.00	40.84	54.00	-13.16	1.50	200	34.89	5.95	Horizontal	Average
2390.00	53.98	74.00	-20.02	1.50	180	57.07	-3.09	Vertical	Peak
2390.00	43.14	54.00	-10.86	1.50	180	46.23	-3.09	Vertical	Average
4824.00	48.51	74.00	-25.49	1.50	180	47.34	1.17	Vertical	Peak
4824.00	41.24	54.00	-12.76	1.50	180	40.07	1.17	Vertical	Average
7236.00	51.08	74.00	-22.92	1.50	180	45.13	5.95	Vertical	Peak
7236.00	41.04	54.00	-12.96	1.50	180	35.09	5.95	Vertical	Average
2.4G Wi-Fi 802.11g_2437MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
4874.00	47.18	74.00	-26.82	1.50	200	46.22	0.96	Horizontal	Peak
4874.00	41.51	54.00	-12.49	1.50	200	40.55	0.96	Horizontal	Average
7311.00	51.00	74.00	-23.00	1.50	200	45.46	5.54	Horizontal	Peak
7311.00	41.21	54.00	-12.79	1.50	200	35.67	5.54	Horizontal	Average
4874.00	49.02	74.00	-24.98	1.50	180	48.06	0.96	Vertical	Peak
4874.00	41.43	54.00	-12.57	1.50	180	40.47	0.96	Vertical	Average
7311.00	52.10	74.00	-21.90	1.50	180	46.56	5.54	Vertical	Peak
7311.00	41.41	54.00	-12.59	1.50	180	35.87	5.54	Vertical	Average
Remark: 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m) 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB) 3. Margin value = Emission Level – Limit value 4. The emission levels of other frequencies are very lower than the limit and not show in test report. 5. Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.									

**2.4G Wi-Fi 802.11g_2462MHz**

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
2483.50	54.27	74.00	-19.73	1.50	200	59.02	-4.75	Horizontal	Peak
2483.50	43.68	54.00	-10.32	1.50	200	48.43	-4.75	Horizontal	Average
4924.00	47.34	74.00	-26.66	1.50	200	46.74	0.60	Horizontal	Peak
4924.00	40.08	54.00	-13.92	1.50	200	39.48	0.60	Horizontal	Average
7386.00	51.12	74.00	-22.88	1.50	200	45.19	5.93	Horizontal	Peak
7386.00	40.95	54.00	-13.05	1.50	200	35.02	5.93	Horizontal	Average
2483.50	53.53	74.00	-20.47	1.50	180	58.28	-4.75	Vertical	Peak
2483.50	44.32	54.00	-9.68	1.50	180	49.07	-4.75	Vertical	Average
4924.00	46.98	74.00	-27.02	1.50	180	46.38	0.60	Vertical	Peak
4924.00	36.38	54.00	-17.62	1.50	180	35.78	0.60	Vertical	Average
7386.00	51.69	74.00	-22.31	1.50	180	45.76	5.93	Vertical	Peak
7386.00	40.91	54.00	-13.09	1.50	180	34.98	5.93	Vertical	Average

Remark:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.

2.4G Wi-Fi 802.11n-HT20_2412MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
2390.00	51.70	74.00	-22.30	1.50	200	54.79	-3.09	Horizontal	Peak
2390.00	42.77	54.00	-11.23	1.50	200	45.86	-3.09	Horizontal	Average
4824.00	46.74	74.00	-27.26	1.50	200	45.57	1.17	Horizontal	Peak
4824.00	41.35	54.00	-12.65	1.50	200	40.18	1.17	Horizontal	Average
7236.00	51.11	74.00	-22.89	1.50	200	45.16	5.95	Horizontal	Peak
7236.00	40.94	54.00	-13.06	1.50	200	34.99	5.95	Horizontal	Average
2390.00	54.38	74.00	-19.62	1.50	180	57.47	-3.09	Vertical	Peak
2390.00	43.29	54.00	-10.71	1.50	180	46.38	-3.09	Vertical	Average
4824.00	48.97	74.00	-25.03	1.50	180	47.80	1.17	Vertical	Peak
4824.00	41.29	54.00	-12.71	1.50	180	40.12	1.17	Vertical	Average
7236.00	51.10	74.00	-22.90	1.50	180	45.15	5.95	Vertical	Peak
7236.00	41.27	54.00	-12.73	1.50	180	35.32	5.95	Vertical	Average
2.4G Wi-Fi 802.11n-HT20_2437MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
4874.00	46.70	74.00	-27.30	1.50	200	45.74	0.96	Horizontal	Peak
4874.00	41.42	54.00	-12.58	1.50	200	40.46	0.96	Horizontal	Average
7311.00	51.45	74.00	-22.55	1.50	200	45.91	5.54	Horizontal	Peak
7311.00	41.57	54.00	-12.43	1.50	200	36.03	5.54	Horizontal	Average
4874.00	48.70	74.00	-25.30	1.50	180	47.74	0.96	Vertical	Peak
4874.00	41.15	54.00	-12.85	1.50	180	40.19	0.96	Vertical	Average
7311.00	52.58	74.00	-21.42	1.50	180	47.04	5.54	Vertical	Peak
7311.00	41.34	54.00	-12.66	1.50	180	35.80	5.54	Vertical	Average
Remark: 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m) 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) - Pre-Amplifier Factor(dB) 3. Margin value = Emission Level – Limit value 4. The emission levels of other frequencies are very lower than the limit and not show in test report. 5. Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.									



2.4G Wi-Fi 802.11n-HT20_2462MHz									
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)	Polarity	Detector
2483.50	54.18	74.00	-19.82	1.50	200	58.93	-4.75	Horizontal	Peak
2483.50	43.59	54.00	-10.41	1.50	200	48.34	-4.75	Horizontal	Average
4924.00	47.71	74.00	-26.29	1.50	200	47.11	0.60	Horizontal	Peak
4924.00	40.05	54.00	-13.95	1.50	200	39.45	0.60	Horizontal	Average
7386.00	50.72	74.00	-23.28	1.50	200	44.79	5.93	Horizontal	Peak
7386.00	40.72	54.00	-13.28	1.50	200	34.79	5.93	Horizontal	Average
2483.50	53.05	74.00	-20.95	1.50	180	57.80	-4.75	Vertical	Peak
2483.50	44.29	54.00	-9.71	1.50	180	49.04	-4.75	Vertical	Average
4924.00	46.65	74.00	-27.35	1.50	180	46.05	0.60	Vertical	Peak
4924.00	36.41	54.00	-17.59	1.50	180	35.81	0.60	Vertical	Average
7386.00	52.13	74.00	-21.87	1.50	180	46.20	5.93	Vertical	Peak
7386.00	40.86	54.00	-13.14	1.50	180	34.93	5.93	Vertical	Average
Remark: 1. $Emission\ Level(dBuV/m) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$ 2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB)$ 3. $Margin\ value = Emission\ Level - Limit\ value$ 4. The emission levels of other frequencies are very lower than the limit and not show in test report. 5. Only the antenna height (from 1m to 4m) and turntable angle (from 0 degrees to 360 degrees) at maximum reading are recorded.									

2.7. AC Power Line Conducted Emission

2.7.1. Limit of AC Power Line Conducted Emission


For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

2.7.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.7.3. Test Setup



2.7.4. Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 micrometry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

2.7.5. Test Results of Conducted Emission


The EUT configuration of the emission tests is 2.4G WLAN Link + USB Cable (Charging from Adapter).

All of the EUT Configure mode were tested and found 802.11b_2462MHz channel is the worst mode, the worst case is recorded in this report.



Project Information

Test site:	Shield ROOM 1	Environment:	Temp: 23℃ ; Humi:53%;101kPa
Operator:	LIAOHONGTING	Test Date:	2024.08.21
Test Mode:	2.4G WIFI - TX	Test Part:	L




Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Corr.Factor (dB)	Margin - QPK	Limit - QPK (dBμV)	Margin - AV (dB)	Limit - AV (dBμV)
0.190500	34.10	23.12	20.4	29.92	64.0	30.89	54.0
0.541500	29.59	22.00	20.4	26.41	56.0	24.00	46.0
1.077000	32.00	20.18	20.4	24.00	56.0	25.82	46.0
1.203000	31.70	20.13	20.4	24.30	56.0	25.87	46.0
4.672500	26.36	13.57	20.2	29.64	56.0	32.43	46.0
16.795500	30.04	23.21	19.9	29.96	60.0	26.79	50.0

Test Result : Pass

Note: Final Level = Receiver Read level + Correction factor.

Project Information

Test site:	Shield ROOM 1	Environment:	Temp: 23°C; Humi:53%;101kPa
Operator:	LIAOHONGTING	Test Date:	2024.08.21
Test Mode:	2.4G WIFI - TX	Test Part:	N



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Corr.Factor (dB)	Margin - QPK	Limit - QPK (dBμV)	Margin - AV (dB)	Limit - AV (dBμV)
0.307500	32.20	25.16	20.2	27.84	60.0	24.88	50.0
0.550500	26.93	20.16	20.1	29.07	56.0	25.84	46.0
0.942000	28.91	18.97	20.2	27.09	56.0	27.03	46.0
1.068000	32.56	19.16	20.2	23.44	56.0	26.84	46.0
1.203000	31.18	20.22	20.2	24.82	56.0	25.78	46.0
17.133000	27.69	20.80	19.5	32.31	60.0	29.20	50.0

Test Result : Pass

Note: Final Level = Receiver Read level + Correction factor.

3. List of measuring equipment

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	5M Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4m	A0304210	2023.08.01	2026.07.31
2	EMI Test Receiver	ROHDE&SCHWARZ	ESW26	A180502935	2024.05.23	2025.05.22
3	Loop Antenna	Schwarz beck	HFH2-Z2	A0304220	2022.05.02	2025.05.01
4	Broadband antenna (30MHz~1GHz)	R&S	HL562	A0304224	2023.06.08	2026.06.07
5	EMI Horn Ant. (1-18G)	ETC	MCTD-1209	A150402241	2023.05.16	2026.05.15
6	Horn antenna (18GHz~26.5GHz)	AR	AT4510	A0804450	2023.06.01	2026.05.31
7	Amplifier 30M~1GHz	MILMEGA	80RF1000-10004	A140101634	2023.10.20	2024.10.19
8	Amplifier 1G~18GHz	MILMEGA	AS0104R-800/400	A160302517	2023.10.20	2024.10.19
9	Spectrum Analyzer	KEYSIGHT	N9030A	A160702554	2024.01.18	2025.01.17
10	Test Receiver	R&S	ESIB7	A0501375	2024.02.28	2025.02.27
11	Broadband Ant.	ETC	MCTD 2786	A150402240	2023.05.22	2026.05.21
12	3M Anechoic Chamber	Albatross	SAC-3MAC 9*6*6m	A0412375	2024.02.27	2027.02.26
13	Temperature chamber	ESPEC	SU-642	A150802409	2024.02.22	2025.02.21
14	Test Receiver	KEYSIGHT	N9038A	A141202036	2024.06.05	2025.06.04
15	LISN	ROHDE&SCHWARZ	ENV216	A140701847	2024.05.23	2025.05.22

4. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2020. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence . The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of AC Power Line Conducted Emission Measurement (150kHz~30MHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	2.8dB
--	-------

Uncertainty of Radiated Emission Measurement (9kHz~30MHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	3.5dB
--	-------

Uncertainty of Radiated Emission Measurement (30MHz~1GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	3.91dB
--	--------

Uncertainty of Radiated Emission Measurement (1GHz~18GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	4.5dB
--	-------

Uncertainty of Radiated Emission Measurement (18GHz~40GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	4.9dB
--	-------

Uncertainty of RF Conducted Measurement (9kHz~40GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	1.2dB
--	-------



Appendix A

Duty Cycle

Test Result and Data

TestMode	Antenna	Frequency[MHz]	ON Time[ms]	Period[ms]	Duty Cycle[%]	DC Factor
11B	Ant1	2412	8.42	8.52	98.83	0.05
11G	Ant1	2412	1.39	1.50	92.67	0.33
11N20SISO	Ant1	2412	1.30	1.41	92.20	0.35



Maximum Conducted Output Power

Test Result and Data

TestMode	Antenna	Frequency[MHz]	Average Power[dBm]	DC Factor [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	13.27	0.05	13.32	≤30.00	PASS
11B	Ant1	2437	13.38	0.05	13.43	≤30.00	PASS
11B	Ant1	2462	13.56	0.05	13.61	≤30.00	PASS
11G	Ant1	2412	12.46	0.33	12.79	≤30.00	PASS
11G	Ant1	2437	12.70	0.33	13.03	≤30.00	PASS
11G	Ant1	2462	12.62	0.33	12.95	≤30.00	PASS
11N20SISO	Ant1	2412	12.44	0.35	12.79	≤30.00	PASS
11N20SISO	Ant1	2437	12.56	0.35	12.91	≤30.00	PASS
11N20SISO	Ant1	2462	12.71	0.35	13.06	≤30.00	PASS

Note: Duty cycle factor added to the result.

Test Graphs

11B-Ant1-2412-PASS



11B-Ant1-2437-PASS



11B-Ant1-2462-PASS



11G-Ant1-2412-PASS




11G-Ant1-2437-PASS




11G-Ant1-2462-PASS



11N20SISO-Ant1-2412-PASS



11N20SISO-Ant1-2437-PASS



11N20SISO-Ant1-2462-PASS



**6dB Bandwidth****Test Result and Data**

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.040	0.5	PASS
11B	Ant1	2437	7.560	0.5	PASS
11B	Ant1	2462	8.560	0.5	PASS
11G	Ant1	2412	16.280	0.5	PASS
11G	Ant1	2437	15.320	0.5	PASS
11G	Ant1	2462	15.760	0.5	PASS
11N20SISO	Ant1	2412	15.800	0.5	PASS
11N20SISO	Ant1	2437	17.520	0.5	PASS
11N20SISO	Ant1	2462	17.560	0.5	PASS

Test Graphs

11B-Ant1-2412-PASS



11B-Ant1-2437-PASS




11B-Ant1-2462-PASS




11G-Ant1-2412-PASS



11G-Ant1-2437-PASS




11G-Ant1-2462-PASS



11N20SISO-Ant1-2412-PASS



11N20SISO-Ant1-2437-PASS



11N20SISO-Ant1-2462-PASS



**99% Occupied Bandwidth****Test Result and Data**

TestMode	Antenna	Frequency[MHz]	99% OBW[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	14.008	---	---
11B	Ant1	2437	14.087	---	---
11B	Ant1	2462	14.096	---	---
11G	Ant1	2412	16.865	---	---
11G	Ant1	2437	16.858	---	---
11G	Ant1	2462	16.945	---	---
11N20SISO	Ant1	2412	18.051	---	---
11N20SISO	Ant1	2437	18.020	---	---
11N20SISO	Ant1	2462	18.020	---	---

Test Graphs

11B-Ant1-2412



11B-Ant1-2437



11B-Ant1-2462



11G-Ant1-2412




11G-Ant1-2437



11G-Ant1-2462



11N20SISO-Ant1-2412



11N20SISO-Ant1-2437



11N20SISO-Ant1-2462





Power Spectral Density

Test Result and Data

TestMode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-17.79	≤8.00	PASS
11B	Ant1	2437	-17.27	≤8.00	PASS
11B	Ant1	2462	-17.38	≤8.00	PASS
11G	Ant1	2412	-20.64	≤8.00	PASS
11G	Ant1	2437	-20.28	≤8.00	PASS
11G	Ant1	2462	-20.45	≤8.00	PASS
11N20SISO	Ant1	2412	-20.44	≤8.00	PASS
11N20SISO	Ant1	2437	-20.33	≤8.00	PASS
11N20SISO	Ant1	2462	-20.71	≤8.00	PASS

Note: Duty cycle factor added to the result.

Test Graphs

11B-Ant1-2412-PASS



11B-Ant1-2437-PASS




11B-Ant1-2462-PASS




11G-Ant1-2412-PASS




11G-Ant1-2437-PASS




11G-Ant1-2462-PASS




11N20SISO-Ant1-2412-PASS



11N20SISO-Ant1-2437-PASS



11N20SISO-Ant1-2462-PASS




**Conducted Band Edges****Test Result and Data**


Test Mode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	5.20	-36.16	≤ -24.8	PASS
11B	Ant1	High	2462	4.11	-48.47	≤ -25.89	PASS
11G	Ant1	Low	2412	2.25	-31.96	≤ -27.75	PASS
11G	Ant1	High	2462	1.44	-42.88	≤ -28.57	PASS
11N20SISO	Ant1	Low	2412	1.11	-31.5	≤ -28.89	PASS
11N20SISO	Ant1	High	2462	1.46	-38.07	≤ -28.54	PASS

Test Graphs


11B-Ant1-2412-PASS




11B-Ant1-2462-PASS




11G-Ant1-2412-PASS




11G-Ant1-2462-PASS



11N20SISO-Ant1-2412-PASS



11N20SISO-Ant1-2462-PASS



Conducted Spurious Emissions

Test Result and Data


Test Mode	Antenna	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	0~Reference	4.00	4.00	---	PASS
11B	Ant1	2412	30~25000	4.00	-48.95	≤-26	PASS
11B	Ant1	2437	0~Reference	3.75	3.75	---	PASS
11B	Ant1	2437	30~25000	3.75	-48.46	≤-26.25	PASS
11B	Ant1	2462	0~Reference	2.00	2.00	---	PASS
11B	Ant1	2462	30~25000	2.00	-48.26	≤-28	PASS
11G	Ant1	2412	0~Reference	-2.08	-2.08	---	PASS
11G	Ant1	2412	30~25000	-2.08	-52.05	≤-32.08	PASS
11G	Ant1	2437	0~Reference	-1.44	-1.44	---	PASS
11G	Ant1	2437	30~25000	-1.44	-52.75	≤-31.44	PASS
11G	Ant1	2462	0~Reference	0.79	0.79	---	PASS
11G	Ant1	2462	30~25000	0.79	-52.86	≤-29.21	PASS
11N20SISO	Ant1	2412	0~Reference	1.06	1.06	---	PASS
11N20SISO	Ant1	2412	30~25000	1.06	-52.44	≤-28.94	PASS
11N20SISO	Ant1	2437	0~Reference	0.32	0.32	---	PASS
11N20SISO	Ant1	2437	30~25000	0.32	-52.39	≤-29.68	PASS
11N20SISO	Ant1	2462	0~Reference	0.45	0.45	---	PASS
11N20SISO	Ant1	2462	30~25000	0.45	-41.67	≤-29.55	PASS

Test Graphs

11B-Ant1-2412-0~Reference-PASS




11B-Ant1-2412-30~25000-PASS



11B-Ant1-2437-0~Reference-PASS




11B-Ant1-2437-30~25000-PASS



11B-Ant1-2462-0~Reference-PASS




11B-Ant1-2462-30~25000-PASS



11G-Ant1-2412-0~Reference-PASS




11G-Ant1-2412-30~25000-PASS



11G-Ant1-2437-0~Reference-PASS




11G-Ant1-2437-30~25000-PASS




11G-Ant1-2462-0~Reference-PASS




11G-Ant1-2462-30~25000-PASS



11N20SISO-Ant1-2412-0~Reference-PASS




11N20SISO-Ant1-2412-30~25000-PASS



11N20SISO-Ant1-2437-0~Reference-PASS




11N20SISO-Ant1-2437-30~25000-PASS



11N20SISO-Ant1-2462-0~Reference-PASS



11N20SISO-Ant1-2462-30~25000-PASS



END OF REPORT