

**FCC ID: 2BHFO-YJ9901**

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHZ})} \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
ASK	0.27025	-42.61	0.00	-42±1	-41.00	0.00	<5	0.00001	3.00	YES

Note:  $\text{dbm} = \text{dbuv/m} - 95.2 - 2.15 = 57.74 - 95.2 - 2.15 = -39.61 \text{ dBm(ERP)}$ , so the conduct peak power =  $-39.61 - 3 = -42.61 \text{ dBm}$

**Conclusion:**

For the max result :  $0.00001 \leq \text{FCC Limit } 3.0$  for 1g SAR.