

RF EXPOSURE

FCC ID : 2BHL8-QWI046
IC : 32779-QWI046

1. FCC Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1	30

f=frequency in MHz, * = plane-wave equivalent power density

2. ISED Regulation

According to RSS-102 Issue 6 §5.3.2 The electric and magnetic field strength reference levels, power density reference levels, and associated reference period for devices employed by the general public (uncontrolled environment) and controlled-use devices (controlled environment) are specified in table 7 and table 8. Note that the power density limits specified in these tables apply to whole body exposure conditions.

Table 7: RF field strength and power density limits for devices used by the general public (uncontrolled environment)

Frequency Range	Electric Field Strength [V/m rms]	Magnetic Field Strength [A/m rms]	Power Density [W/m ²]	Reference Period [minutes]
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/f ^{1.2}

Note: f is frequency in MHz.



MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

3. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

MPE Calculations : FSK

- Frequency Range : 921.1 MHz ~ 921.1 MHz
- Measured RF Maximum Output Power : -5.51 dBm
- Target Power & Tolerance -5.00 dBm & \pm 1.00 dB

(Maximum : -4.00 dBm & Minimum : -6.00 dBm)
- Maximum Peak Antenna Gain : 1.38 dBi
- Maximum Output Power for the Calculation : -4.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The MPE Calculations for this exposure is shown below.

$ \begin{aligned} - \text{EIRP} &= P + G \\ &= \underline{-4.00} \text{ dBm} + \underline{1.38} \text{ dBi} \\ &= \underline{-2.62} \text{ dBm} \\ &= \underline{0.55} \text{ mW} \end{aligned} $	<p>- NOTE</p> <p>P : Max tuneup Power (dBm)</p> <p>G : Maximum Peak Antenna Gain (dBi)</p>
--	--

Power Density at the specific separation

$ \begin{aligned} - S &= \text{EIRP} / (4 \times R^2 \pi) \\ &= 0.55 / (4 \times 20^2 \times \pi) \\ &= \underline{0.000\ 109} \text{ mW/cm}^2 \text{ (Limit : 0.61) } \\ &= \underline{0.001\ 088} \text{ W/m}^2 \text{ (Limit : 2.78) } \end{aligned} $	<p>- NOTE</p> <p>S : Maximum Power Density (mW/cm²)</p> <p>EIRP : Equivalent Isotropic Radiated Power (mW)</p> <p>R : Distance to the center of the radiation of the antenna (<u>20</u> cm)</p>
--	--