

## TEST REPORT

**Application No.:** SHCR2407001328AT  
**FCC ID:** 2BHTA-B282E  
**Applicant:** SYNLAN TECHNOLOGY PTE. LTD.  
**Address of Applicant:** 7 TEMASEK BOULEVARD #29-01D SUNTEC TOWER ONE SINGAPORE (038987)  
**Manufacturer:** SYNLAN TECHNOLOGY PTE. LTD.  
**Address of Manufacturer:** 7 TEMASEK BOULEVARD #29-01D SUNTEC TOWER ONE SINGAPORE (038987)  
**Factory:** Jixian Branch of Xi'an BYD Electronics Co., Ltd.  
**Address of Factory:** No. 5, Jixian Avenue, Jixian Industrial Park, High-tech Zone, Xi'an  
**Equipment Under Test (EUT):**  
**EUT Name:** iFLYTEK AINOTE Air 2  
**Model No.:** XF-DX-B282E  
**Trade Mark:** iFLYTEK  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2024-07-08  
**Date of Test:** 2024-07-10 to 2024-08-24  
**Date of Issue:** 2024-08-27

**Test Result:**

**Pass\***

\* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR240700132801

Page: 2 of 108

| Revision Record |             |            |        |
|-----------------|-------------|------------|--------|
| Version         | Description | Date       | Remark |
| 00              | Original    | 2024-08-27 | /      |
|                 |             |            |        |
|                 |             |            |        |

|                          |  |                          |  |  |
|--------------------------|--|--------------------------|--|--|
| Authorized for issue by: |  |                          |  |  |
| Tested By                |  | Bill Wu                  |  |  |
|                          |  | Bill Wu/Project Engineer |  |  |
| Approved By              |  | Parlam Zhan              |  |  |
|                          |  | Parlam Zhan / Reviewer   |  |  |

## 2 Test Summary

| Radio Spectrum Technical Requirement   |                                  |        |   |        |
|--|----------------------------------|--------|---|--------|
| Item   | Standard                         | Method | Requirement                                     | Result |
| Antenna Requirement  | 47 CFR Part 15, Subpart C 15.247 | N/A    | 47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4) | Pass   |
| Other requirements<br>Frequency Hopping<br>Spread Spectrum<br>System Hopping<br>Sequence |                                  | N/A    | 47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)  | Pass   |

| Radio Spectrum Matter Part                            |                                  |                                    |   |        |
|---|----------------------------------|------------------------------------|---|--------|
| Item  | Standard                         | Method                             | Requirement                               | Result |
| Conducted Emissions at AC Power Line (150kHz-30MHz)   | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 6.2     | 47 CFR Part 15, Subpart C 15.207          | Pass   |
| Radiated Emissions which fall in the restricted bands |                                  | ANSI C63.10 (2013) Section 6.10.5  | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Radiated Spurious Emissions Below 1GHz                |                                  | ANSI C63.10 (2013) Section 6.4,6.5 | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Radiated Spurious Emissions Above 1GHz                |                                  | ANSI C63.10 (2013) Section 6.6     | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Conducted Peak Output Power                           |                                  | ANSI C63.10 (2013) Section 7.8.5   | 47 CFR Part 15, Subpart C 15.247(b)(1)    | Pass   |
| 20dB Bandwidth  |                                  | ANSI C63.10 (2013) Section 7.8.7   | 47 CFR Part 15, Subpart C 15.247(a)(1)    | Pass   |
| Carrier Frequencies Separation                        |                                  | ANSI C63.10 (2013) Section 7.8.2   | 47 CFR Part 15, Subpart C 15.247a(1)      | Pass   |
| Hopping Channel Number                                |                                  | ANSI C63.10 (2013) Section 7.8.3   | 47 CFR Part 15, Subpart C 15.247a(1)(iii) | Pass   |
| Dwell Time  |                                  | ANSI C63.10 (2013) Section 7.8.4   | 47 CFR Part 15, Subpart C 15.247a(1)(iii) | Pass   |
| Conducted Band Edges Measurement                      |                                  | ANSI C63.10 (2013) Section 7.8.6   | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |
| Conducted Spurious Emissions                          |                                  | ANSI C63.10 (2013) Section 7.8.8   | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |

### 3 Contents

|  | Page      |
|--|-----------|
| <b>1 COVER PAGE .....</b>  | <b>1</b>  |
| <b>2 Test Summary .....</b>  | <b>3</b>  |
| <b>3 Contents .....</b>  | <b>4</b>  |
| <b>4 General Information.....</b>  | <b>7</b>  |
| 4.1 Details of E.U.T. ....   | 7         |
| 4.2 Description of Support Units .....   | 7         |
| 4.3 Power level setting using in test.....   | 7         |
| 4.4 Measurement Uncertainty .....  | 7         |
| 4.5 Test Location.....   | 8         |
| 4.6 Test Facility .....  | 8         |
| 4.7 Deviation from Standards.....  | 8         |
| 4.8 Abnormalities from Standard Conditions .....                                       | 8         |
| <b>5 Equipment List .....</b>  | <b>9</b>  |
| <b>6 Radio Spectrum Technical Requirement .....</b>                                    | <b>11</b> |
| 6.1 Antenna Requirement .....  | 11        |
| 6.1.1 Test Requirement: .....  | 11        |
| 6.1.2 Conclusion .....   | 11        |
| 6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence ..... | 12        |
| 6.2.1 Test Requirement: .....  | 12        |
| 6.2.2 Conclusion .....   | 12        |
| <b>7 Radio Spectrum Matter Test Results .....</b>                                      | <b>13</b> |
| 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz).....                           | 13        |
| 7.1.1 E.U.T. Operation .....   | 13        |
| 7.1.2 Test Mode Description.....   | 13        |
| 7.1.3 Test Setup Diagram.....  | 13        |
| 7.1.4 Measurement Procedure and Data.....  | 14        |
| 7.2 Radiated Emissions which fall in the restricted bands .....                        | 17        |
| 7.2.1 E.U.T. Operation .....   | 17        |
| 7.2.2 Test Mode Description.....   | 17        |
| 7.2.3 Test Setup Diagram.....  | 17        |
| 7.2.4 Measurement Procedure and Data.....  | 18        |
| 7.3 Radiated Spurious Emissions Below 1GHz .....                                       | 31        |
| 7.3.1 E.U.T. Operation .....   | 31        |
| 7.3.2 Test Mode Description.....   | 31        |
| 7.3.3 Test Setup Diagram.....  | 31        |
| 7.3.4 Measurement Procedure and Data.....  | 32        |
| 7.4 Radiated Spurious Emissions Above 1GHz.....  | 35        |
| 7.4.1 E.U.T. Operation .....   | 35        |
| 7.4.2 Test Mode Description.....   | 35        |
| 7.4.3 Test Setup Diagram.....  | 35        |
| 7.4.4 Measurement Procedure and Data.....  | 36        |
| 7.5 Conducted Peak Output Power.....   | 55        |
| 7.5.1 E.U.T. Operation .....   | 55        |
| 7.5.2 Test Mode Description.....   | 55        |
| 7.5.3 Test Setup Diagram.....  | 55        |
| 7.5.4 Measurement Procedure and Data.....  | 55        |

|        |  |    |
|--------|--|----|
| 7.6    | 20dB Bandwidth .....                             | 56 |
| 7.6.1  | E.U.T. Operation .....                           | 56 |
| 7.6.2  | Test Mode Description .....                      | 56 |
| 7.6.3  | Test Setup Diagram .....                         | 56 |
| 7.6.4  | Measurement Procedure and Data .....             | 56 |
| 7.7    | Carrier Frequencies Separation .....             | 57 |
| 7.7.1  | E.U.T. Operation .....                           | 57 |
| 7.7.2  | Test Mode Description .....                      | 57 |
| 7.7.3  | Test Setup Diagram .....                         | 57 |
| 7.7.4  | Measurement Procedure and Data .....             | 57 |
| 7.8    | Hopping Channel Number .....                     | 58 |
| 7.8.1  | E.U.T. Operation .....                           | 58 |
| 7.8.2  | Test Mode Description .....                      | 58 |
| 7.8.3  | Test Setup Diagram .....                         | 58 |
| 7.8.4  | Measurement Procedure and Data .....             | 58 |
| 7.9    | Dwell Time .....                                 | 59 |
| 7.9.1  | E.U.T. Operation .....                           | 59 |
| 7.9.2  | Test Mode Description .....                      | 59 |
| 7.9.3  | Test Setup Diagram .....                         | 59 |
| 7.9.4  | Measurement Procedure and Data .....             | 59 |
| 7.10   | Conducted Band Edges Measurement .....           | 60 |
| 7.10.1 | E.U.T. Operation .....                           | 60 |
| 7.10.2 | Test Mode Description .....                      | 60 |
| 7.10.3 | Test Setup Diagram .....                         | 60 |
| 7.10.4 | Measurement Procedure and Data .....             | 60 |
| 7.11   | Conducted Spurious Emissions .....               | 61 |
| 7.11.1 | E.U.T. Operation .....                           | 61 |
| 7.11.2 | Test Mode Description .....                      | 61 |
| 7.11.3 | Test Setup Diagram .....                         | 61 |
| 7.11.4 | Measurement Procedure and Data .....             | 61 |
| 8      | Test Setup Photo .....                           | 62 |
| 9      | EUT Constructional Details (EUT Photos) .....    | 62 |
| 10     | Appendix .....                                   | 62 |
| 10.1   | Appendix A: 20dB Emission Bandwidth .....        | 62 |
| 10.1.1 | Test Result .....                                | 62 |
| 10.1.2 | Test Graphs .....                                | 63 |
| 10.2   | Appendix B: Occupied Channel Bandwidth .....     | 67 |
| 10.2.1 | Test Result .....                                | 67 |
| 10.2.2 | Test Graphs .....                                | 68 |
| 10.3   | Appendix C: Maximum conducted output power ..... | 72 |
| 10.3.1 | Test Result .....                                | 72 |
| 10.3.2 | Test Graphs .....                                | 73 |
| 10.4   | Appendix D: Carrier frequency separation .....   | 77 |
| 10.4.1 | Test Result .....                                | 77 |
| 10.4.2 | Test Graphs .....                                | 78 |
| 10.5   | Appendix E: Time of occupancy .....              | 80 |
| 10.5.1 | Test Result .....                                | 80 |
| 10.5.2 | Test Graphs .....                                | 81 |
| 10.6   | Appendix F: Number of hopping channels .....     | 88 |
| 10.6.1 | Test Result .....                                | 88 |
| 10.6.2 | Test Graphs .....                                | 89 |
| 10.7   | Appendix G: Band edge measurements .....         | 91 |
| 10.7.1 | Test Result .....                                | 91 |
| 10.7.2 | Test Graphs .....                                | 92 |



**SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.**

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR240700132801

Page: 6 of 108

|        |   |    |
|--------|---|----|
| 10.8   | Appendix H: Conducted Spurious Emission ..... | 97 |
| 10.8.1 | Test Result .....                             | 97 |
| 10.8.2 | Test Graphs.....                              | 98 |

## 4 General Information

### 4.1 Details of E.U.T.

|                      |                                      |
|----------------------|--------------------------------------|
| Power supply:        | DC 3.8V 2600mAh Rechargeable battery |
| Test Voltage:        | AC 120V 60Hz                         |
| Operation Frequency: | 2402MHz to 2480MHz                   |
| Modulation Type:     | GFSK, Pi/4DQPSK, 8DPSK               |
| Channel Spacing:     | 1MHz                                 |
| Number of Channels:  | 79                                   |
| Antenna Type:        | PIFA Antenna                         |
| Antenna Gain:        | -0.33 dBi (Provided by manufacturer) |
| Power Class:         | <10mW                                |
| Receiver Category:   | 2                                    |

### 4.2 Description of Support Units

| Description | Manufacturer | Model No. | Serial No. |
|-------------|--------------|-----------|------------|
| Laptop      | LENOVO       | L460      | -          |

### 4.3 Power level setting using in test

| Channel | Power setting |      |      |
|---------|---------------|------|------|
|         | DH5           | 2DH5 | 3DH5 |
| Low     | 5             | 5    | 5    |
| Middle  | 5             | 5    | 5    |
| High    | 5             | 5    | 5    |

### 4.4 Measurement Uncertainty

| No. | Item                            | Measurement Uncertainty |
|-----|---------------------------------|-------------------------|
| 1   | Radio Frequency                 | $8.4 \times 10^{-8}$    |
| 2   | Timeout                         | 2s                      |
| 3   | Duty cycle                      | 0.4%                    |
| 4   | Occupied Bandwidth              | 3%                      |
| 5   | RF conducted power              | 0.6dB                   |
| 6   | RF power density                | 2.9dB                   |
| 7   | Conducted Spurious emissions    | 0.75dB                  |
| 8   | RF Radiated power               | 5.2dB (Below 1GHz)      |
|     |                                 | 5.9dB (Above 1GHz)      |
| 9   | Radiated Spurious emission test | 4.2dB (Below 30MHz)     |
|     |                                 | 4.5dB (30MHz-1GHz)      |
|     |                                 | 5.1dB (1GHz-6GHz)       |
|     |                                 | 5.4dB (6GHz-18GHz)      |
| 10  | Temperature test                | 1°C                     |
| 11  | Humidity test                   | 3%                      |
| 12  | Supply voltages                 | 1.5%                    |
| 13  | Time                            | 3%                      |

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

#### 4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab  
588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc ) is provided by the applicant. (if applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).
3. Sample source: sent by customer.

#### 4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6332.01)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the American Association for Laboratory Accreditation(A2LA).

- **FCC (Designation Number: CN1301)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0020)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.  
Company Number: 8617A

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

#### 4.7 Deviation from Standards

None

#### 4.8 Abnormalities from Standard Conditions

None



## 5 Equipment List

| Equipment                 | Manufacturer | Model No                      | Inventory No          | Cal Date   | Cal Due Date |
|---------------------------|--------------|-------------------------------|-----------------------|------------|--------------|
| <b>RF Conducted Test</b>  |              |                               |                       |            |              |
| Spectrum Analyzer         | R&S          | FSP-30                        | SHEM002-1             | 2023-12-19 | 2024-12-18   |
| Spectrum Analyzer         | Keysight     | N9020B                        | SHEM241-1             | 2023-12-19 | 2024-12-18   |
| Spectrum Analyzer         | Agilent      | N9020A                        | SHEM181-1             | 2023-08-01 | 2024-07-31   |
| Spectrum Analyzer         | Agilent      | N9020A                        | SHEM181-1             | 2024-07-31 | 2025-07-30   |
| Signal Generator          | R&S          | SMR20                         | SHEM006-1             | 2023-08-01 | 2024-07-31   |
| Signal Generator          | R&S          | SMR20                         | SHEM006-1             | 2024-07-31 | 2025-07-30   |
| Signal Generator          | Agilent      | N5182A                        | SHEM182-1             | 2023-08-01 | 2024-07-31   |
| Signal Generator          | Agilent      | N5182A                        | SHEM182-1             | 2024-07-31 | 2025-07-30   |
| Communication Tester      | R&S          | CMW270                        | SHEM183-1             | 2024-05-23 | 2025-05-22   |
| Communication Tester      | R&S          | CMW500                        | SHEM268-1             | 2024-05-23 | 2025-05-22   |
| Power Sensor              | Keysight     | U2021XA * 4                   | SHEM184-1             | 2023-08-01 | 2024-07-31   |
| Power Sensor              | Keysight     | U2021XA * 4                   | SHEM293-1             | 2024-07-31 | 2025-07-30   |
| Splitter                  | Anritsu      | MA1612A                       | SHEM185-1             | /          | /            |
| Coupler                   | e-meca       | 803-S-1                       | SHEM186-1             | /          | /            |
| High-low Temp Cabinet     | Suzhou Zhihe | TL-40                         | SHEM087-1             | 2022-11-08 | 2024-11-07   |
| AC Power Stabilizer       | APC          | KDF-31020T-V0-F0              | SHEM216-1             | 2023-12-19 | 2024-12-18   |
| DC Power Supply           | HP           | 6010A                         | SHEM222-1             | 2023-12-19 | 2024-12-18   |
| Conducted test Cable      | /            | RF01~RF04                     | /                     | 2023-12-19 | 2024-12-18   |
| Switcher                  | Tonscend     | JS0806                        | SHEM184-1             | 2023-08-01 | 2024-07-31   |
| Switcher                  | Tonscend     | JS0806                        | SHEM293-1             | 2024-07-31 | 2025-07-30   |
| Test software             | Tonscend     | JS Tonscend<br>BT/WIFI System | Version: 2.6          | /          | /            |
| Switcher+Power Sensor     | TST          | TSPS2023R                     | SHEM263-1             | 2023-08-01 | 2024-07-31   |
| Switcher+Power Sensor     | TST          | TSPS2023R                     | SHEM263-1             | 2024-07-31 | 2025-07-30   |
| Test software             | TST          | TST PASS                      | Version: 2.0          | /          | /            |
| <b>RF Radiated Test</b>   |              |                               |                       |            |              |
| EMI test Receiver         | R&S          | ESU40                         | SHEM051-1             | 2023-12-19 | 2024-12-18   |
| Spectrum Analyzer         | R&S          | FSP-30                        | SHEM002-1             | 2023-12-19 | 2024-12-18   |
| Communication Tester      | R&S          | CMW500                        | SHEM268-1             | 2024-05-23 | 2025-05-22   |
| Loop Antenna (9kHz-30MHz) | Schwarzbeck  | FMZB1519                      | SHEM135-1             | 2023-12-19 | 2024-12-18   |
| Antenna (25MHz-2GHz)      | Schwarzbeck  | VULB9168                      | SHEM048-1             | 2023-09-03 | 2025-09-02   |
| Antenna (25MHz-2GHz)      | Schwarzbeck  | VULB9168                      | SHEM202-1             | 2023-04-17 | 2025-04-16   |
| Horn Antenna (1-18GHz)    | Schwarzbeck  | HF906                         | SHEM009-1             | 2024-08-05 | 2026-08-04   |
| Horn Antenna (1-18GHz)    | Schwarzbeck  | BBHA9120D                     | SHEM050-1             | 2023-09-03 | 2025-09-02   |
| Horn Antenna (14-40GHz)   | Schwarzbeck  | BBHA 9170                     | SHEM049-1             | 2023-09-03 | 2025-09-02   |
| Pre-Amplifier             | HP           | 8447D                         | SHEM236-1             | 2023-12-19 | 2024-12-18   |
| High-amplifier (14-40GHz) | Schwarzbeck  | 10001                         | SHEM049-2             | 2023-12-19 | 2024-12-18   |
| Band Filter               | LORCH        | 9BRX-875/X150                 | SHEM156-1             | /          | /            |
| Band Filter               | LORCH        | 13BRX-1950/X500               | SHEM083-2             | /          | /            |
| Band Filter               | LORCH        | 5BRX-2400/X200                | SHEM155-1             | /          | /            |
| Band Filter               | LORCH        | 5BRX-5500/X1000               | SHEM157-2             | /          | /            |
| High pass Filter          | Wainwright   | WHK3.0/18G                    | SHEM157-1             | /          | /            |
| High pass Filter          | Wainwright   | WHKS1700                      | SHEM157-3             | /          | /            |
| Semi/Fully Anechoic       | ST           | 11*6*6M                       | SHEM078-2             | 2023-05-06 | 2026-05-05   |
| RE test Cable             | /            | PT18-NMNM-10M                 | SHEM217-2             | 2023-12-19 | 2024-12-18   |
| Test software             | ESE          | E3                            | Version:<br>6.111221a | /          | /            |



**SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.**

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR240700132801

Page: 10 of 108

| Conducted Emissions at Mains Power Port (150kHz-30MHz) |                 |           |                      |            |              |
|--|-----------------|-----------|----------------------|------------|--------------|
| Equipment  | Manufacturer    | Model No. | Inventory No.        | Cal Date   | Cal Due Date |
| EMI test receiver                                      | Rohde & Schwarz | ESR7      | SHEM162-1            | 2023/12/19 | 2024/12/18   |
| Line impedance stabilization network                   | SCHWARZBECK     | NSLK8127  | SHEM061-1            | 2023/12/19 | 2024/12/18   |
| Line impedance stabilization network                   | EMCO            | 3816_2    | SHEM019-1            | 2023/12/19 | 2024/12/18   |
| Pulse limiter  | Rohde & Schwarz | ESH3-Z2   | SHEM029-1            | 2023/12/19 | 2024/12/18   |
| Shielding Room   | ZHONGYU         | 8*4*3M    | SHEM079-2            | 2023/12/19 | 2024/12/18   |
| CE test Cable  | /               | /         | SHEM172-1            | 2023/12/19 | 2024/12/18   |
| Test Software  | ESE             | e3        | Version:<br>6.191211 | N/A        | N/A          |

## **6 Radio Spectrum Technical Requirement**

### **6.1 Antenna Requirement**

#### **6.1.1 Test Requirement:**

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### **6.1.2 Conclusion**

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is PIFA antenna and no consideration of replacement. The best case gain of the antenna is -0.33 dBi.

Antenna location: Refer to internal photo.

## **6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence**

### **6.2.1 Test Requirement:**

47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)

### **6.2.2 Conclusion**

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

> Number of shift register stages: 9

> Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits

> Longest sequence of zeros: 8 (non-inverted signal)

Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

The system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

| Frequency of emission(MHz) | Conducted limit(dBμV) |           |
|----------------------------|-----------------------|-----------|
|                            | Quasi-peak            | Average   |
| 0.15-0.5                   | 66 to 56*             | 56 to 46* |
| 0.5-5                      | 56                    | 46        |
| 5-30                       | 60                    | 50        |

\*Decreases with the logarithm of the frequency.

Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C


Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

#### 7.1.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 00        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |

#### 7.1.3 Test Setup Diagram




**7.1.4 Measurement Procedure and Data**

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor

Test Mode: 00; Line: Live line




LISM : LINE  
EUT/Project No : 1328AT  
Test Mode : 00

|    | Freq<br>(MHz) | Read<br>level<br>(dBuV) | LISM<br>Factor<br>(dB) | Cable<br>Loss<br>(dB) | Emission<br>Level<br>(dBuV) | Limit<br>(dBuV) | Over<br>Limit<br>(dB) | Remark  |
|----|---------------|-------------------------|------------------------|-----------------------|-----------------------------|-----------------|-----------------------|---------|
| 1  | 0.17          | 22.43                   | 0.50                   | 9.90                  | 32.83                       | 55.16           | -22.33                | Average |
| 2  | 0.17          | 42.23                   | 0.50                   | 9.90                  | 52.63                       | 65.16           | -12.53                | QP      |
| 3  | 0.19          | 27.83                   | 0.50                   | 9.90                  | 38.23                       | 54.20           | -15.97                | Average |
| 4  | 0.19          | 42.16                   | 0.50                   | 9.90                  | 52.56                       | 64.20           | -11.64                | QP      |
| 5  | 0.21          | 23.33                   | 0.48                   | 9.90                  | 33.71                       | 53.23           | -19.52                | Average |
| 6  | 0.21          | 39.16                   | 0.48                   | 9.90                  | 49.54                       | 63.23           | -13.69                | QP      |
| 7  | 0.24          | 26.73                   | 0.45                   | 9.90                  | 37.08                       | 52.26           | -15.18                | Average |
| 8  | 0.24          | 38.45                   | 0.45                   | 9.90                  | 48.80                       | 62.26           | -13.46                | QP      |
| 9  | 0.27          | 22.27                   | 0.40                   | 9.90                  | 32.57                       | 51.16           | -18.59                | Average |
| 10 | 0.27          | 34.16                   | 0.40                   | 9.90                  | 44.46                       | 61.16           | -16.70                | QP      |
| 11 | 23.76         | 17.51                   | 0.68                   | 10.70                 | 28.89                       | 50.00           | -21.11                | Average |
| 12 | 23.76         | 26.80                   | 0.68                   | 10.70                 | 38.18                       | 60.00           | -21.82                | QP      |

Notes: Emission Level = Read Level + LISM Factor + Cable loss

Test Mode: 00; Line: Neutral Line



LISN : NEUTRAL  
EUT/Project No : 1328AT  
Test Mode : 00

|    | Freq<br>(MHz) | Read<br>level<br>(dBuV) | LISN<br>Factor<br>(dB) | Cable<br>Loss<br>(dB) | Emission<br>Level<br>(dBuV) | Limit<br>(dBuV) | Over<br>Limit<br>(dB) | Remark  |
|----|---------------|-------------------------|------------------------|-----------------------|-----------------------------|-----------------|-----------------------|---------|
| 1  | 0.17          | 21.31                   | 0.32                   | 9.90                  | 31.53                       | 54.86           | -23.33                | Average |
| 2  | 0.17          | 40.41                   | 0.32                   | 9.90                  | 50.63                       | 64.86           | -14.23                | QP      |
| 3  | 0.19          | 27.06                   | 0.30                   | 9.90                  | 37.26                       | 53.84           | -16.58                | Average |
| 4  | 0.19          | 42.38                   | 0.30                   | 9.90                  | 52.58                       | 63.84           | -11.26                | QP      |
| 5  | 0.22          | 24.89                   | 0.30                   | 9.90                  | 35.09                       | 52.66           | -17.57                | Average |
| 6  | 0.22          | 39.97                   | 0.30                   | 9.90                  | 50.17                       | 62.66           | -12.49                | QP      |
| 7  | 0.27          | 21.97                   | 0.30                   | 9.90                  | 32.17                       | 51.16           | -18.99                | Average |
| 8  | 0.27          | 34.98                   | 0.30                   | 9.90                  | 45.18                       | 61.16           | -15.98                | QP      |
| 9  | 0.31          | 18.01                   | 0.30                   | 9.90                  | 28.21                       | 49.88           | -21.67                | Average |
| 10 | 0.31          | 30.12                   | 0.30                   | 9.90                  | 40.32                       | 59.88           | -19.56                | QP      |
| 11 | 23.76         | 18.07                   | 1.20                   | 10.70                 | 29.97                       | 50.00           | -20.03                | Average |
| 12 | 23.76         | 27.01                   | 1.20                   | 10.70                 | 38.91                       | 60.00           | -21.09                | QP      |

Notes: Emission Level = Read Level + LISN Factor + Cable loss



### 7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| Above 960      | 500                              | 3                            |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

#### 7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 24.9 °C Humidity: 55.0 % RH Atmospheric Pressure: 1010 mbar

#### 7.2.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 00        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |

#### 7.2.3 Test Setup Diagram




**7.2.4 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1:  $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Antenna Polarity :HORIZONTAL  
EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB                  | dBuv/m         | dBuv/m     | dB         |        |
| 2386.12 | 45.21      | 28.80          | 3.34       | 35.18               | 42.17          | 74.00      | -31.83     | Peak   |
| 2390.00 | 43.72      | 28.80          | 3.34       | 35.18               | 40.68          | 74.00      | -33.32     | Peak   |
| 2402.15 | 101.00     | 28.85          | 3.34       | 35.19               | 98.00          | 74.00      | 24.00      | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |        |
| 2363.17 | 46.91      | 28.68          | 3.31       | 35.16               | 43.74          | 74.00      | -30.26     | Peak   |
| 2390.00 | 42.75      | 28.80          | 3.34       | 35.18               | 39.71          | 74.00      | -34.29     | Peak   |
| 2402.25 | 93.26      | 28.85          | 3.34       | 35.19               | 90.26          | 74.00      | 16.26      | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB                  | dBuv/m         | dBuv/m     | dB         |        |
| 2479.88 | 99.33      | 29.08          | 3.40       | 35.25               | 96.56          | 74.00      | 22.56      | Peak   |
| 2483.50 | 43.82      | 29.09          | 3.36       | 35.26               | 41.01          | 74.00      | -32.99     | Peak   |
| 2496.74 | 44.94      | 29.12          | 3.36       | 35.27               | 42.15          | 74.00      | -31.85     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High




Antenna Polarity :VERTICAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB                  | dBuv/m         | dBuv/m     | dB         |        |
| 2479.88 | 91.83      | 29.08          | 3.40       | 35.25               | 89.06          | 74.00      | 15.06      | Peak   |
| 2483.50 | 42.74      | 29.09          | 3.36       | 35.26               | 39.93          | 74.00      | -34.07     | Peak   |
| 2495.85 | 45.04      | 29.10          | 3.33       | 35.26               | 42.21          | 74.00      | -31.79     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Horizontal; Modulation:  $\pi/4$  DQPSK; Channel: Low




Antenna Polarity :HORIZONTAL  
EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB                  | dBuv/m         | dBuv/m     | dB         |        |
| 2386.83 | 44.19      | 28.80          | 3.34       | 35.18               | 41.15          | 74.00      | -32.85     | Peak   |
| 2390.00 | 42.21      | 28.80          | 3.34       | 35.18               | 39.17          | 74.00      | -34.83     | Peak   |
| 2401.95 | 97.84      | 28.85          | 3.34       | 35.19               | 94.84          | 74.00      | 20.84      | Peak   |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamplifier Factor

Test Mode: 00; Polarity: Vertical; Modulation:  $\pi/4$  DQPSK; Channel: Low



Antenna Polarity : VERTICAL


EUT/Project : 1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB                  | dBuv/m         | dBuv/m     | dB         |        |
| 2382.68 | 44.32      | 28.76          | 3.33       | 35.17               | 41.24          | 74.00      | -32.76     | Peak   |
| 2390.00 | 42.67      | 28.80          | 3.34       | 35.18               | 39.63          | 74.00      | -34.37     | Peak   |
| 2402.15 | 95.44      | 28.85          | 3.34       | 35.19               | 92.44          | 74.00      | 18.44      | Peak   |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamplifier Factor



Test Mode: 00; Polarity: Horizontal; Modulation:  $\pi/4$  DQPSK; Channel: High




Antenna Polarity :HORIZONTAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB                  | dBuv/m         | dBuv/m     | dB         |        |
| 2479.96 | 97.13      | 29.08          | 3.40       | 35.25               | 94.36          | 74.00      | 20.36      | Peak   |
| 2483.50 | 43.69      | 29.09          | 3.36       | 35.26               | 40.88          | 74.00      | -33.12     | Peak   |
| 2484.70 | 44.87      | 29.09          | 3.36       | 35.26               | 42.06          | 74.00      | -31.94     | Peak   |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamplifier Factor

Test Mode: 00; Polarity: Vertical; Modulation:  $\pi/4$  DQPSK; Channel: High




Antenna Polarity : VERTICAL

EUT/Project : 1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB                  | dBuv/m         | dBuv/m     | dB         |        |
| 2479.88 | 96.40      | 29.08          | 3.40       | 35.25               | 93.63          | 74.00      | 19.63      | Peak   |
| 2483.50 | 42.69      | 29.09          | 3.36       | 35.26               | 39.88          | 74.00      | -34.12     | Peak   |
| 2495.03 | 45.46      | 29.10          | 3.33       | 35.26               | 42.63          | 74.00      | -31.37     | Peak   |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamplifier Factor

Test Mode: 00; Polarity: Horizontal; Modulation:8DPSK; Channel:Low




Antenna Polarity :HORIZONTAL  
EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 2385.51 | 45.22      | 28.80          | 3.34       | 35.18         | 42.18          | 74.00      | -31.82     | Peak   |
| 2390.00 | 41.92      | 28.80          | 3.34       | 35.18         | 38.88          | 74.00      | -35.12     | Peak   |
| 2402.15 | 98.97      | 28.85          | 3.34       | 35.19         | 95.97          | 74.00      | 21.97      | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:8DPSK; Channel:Low




Antenna Polarity :VERTICAL  
EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 2383.19 | 43.80      | 28.76          | 3.33       | 35.17         | 40.72          | 74.00      | -33.28     | Peak   |
| 2390.00 | 41.65      | 28.80          | 3.34       | 35.18         | 38.61          | 74.00      | -35.39     | Peak   |
| 2402.15 | 95.94      | 28.85          | 3.34       | 35.19         | 92.94          | 74.00      | 18.94      | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Horizontal; Modulation: 8DPSK; Channel: High




Antenna Polarity : HORIZONTAL  
EUT/Project : 1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |        |
| 2480.10 | 97.32      | 29.08          | 3.40       | 35.25               | 94.55          | 74.00      | 20.55      | Peak   |
| 2483.50 | 50.89      | 29.09          | 3.36       | 35.26               | 48.08          | 74.00      | -25.92     | Peak   |
| 2496.00 | 45.36      | 29.10          | 3.33       | 35.26               | 42.53          | 74.00      | -31.47     | Peak   |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamplifier Factor

Test Mode: 00; Polarity: Vertical; Modulation:8DPSK; Channel:High



Antenna Polarity :VERTICAL  
EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |        |
| 2480.03 | 95.58      | 29.08          | 3.40       | 35.25               | 92.81          | 74.00      | 18.81      | Peak   |
| 2483.50 | 52.34      | 29.09          | 3.36       | 35.26               | 49.53          | 74.00      | -24.47     | Peak   |
| 2485.22 | 47.57      | 29.09          | 3.36       | 35.26               | 44.76          | 74.00      | -29.24     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

### 7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| 960-1000       | 500                              | 3                            |

#### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C


Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

#### 7.3.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 00        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |

#### 7.3.3 Test Setup Diagram



#### **7.3.4 Measurement Procedure and Data**


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Test Mode: 00; Polarity: Horizontal



Antenna Polarity :HORIZONTAL


EUT/Project :1328AT

Test mode :00

|   | Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
|   | MHz     | dBuV       | dB/m           | dB         | dB            | dBuV/m         | dBuV/m     | dB         |        |
| 1 | 59.232  | 43.01      | 13.08          | 1.55       | 33.20         | 24.44          | 40.00      | -15.56     | QP     |
| 2 | 122.404 | 50.47      | 11.25          | 2.44       | 33.10         | 31.06          | 43.50      | -12.44     | QP     |
| 3 | 199.986 | 55.51      | 10.00          | 3.04       | 33.00         | 35.55          | 43.50      | -7.95      | QP     |
| 4 | 263.819 | 51.74      | 12.11          | 3.45       | 32.80         | 34.50          | 46.00      | -11.50     | QP     |
| 5 | 497.677 | 39.86      | 17.96          | 4.91       | 32.70         | 30.03          | 46.00      | -15.97     | QP     |
| 6 | 595.133 | 42.66      | 19.85          | 5.44       | 32.70         | 35.25          | 46.00      | -10.75     | QP     |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical



Antenna Polarity :VERTICAL  
 EUT/Project :1328AT  
 Test mode :00

|   | Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
|   | MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |        |
| 1 | 39.994  | 43.71      | 13.40          | 1.34       | 33.20               | 25.25          | 40.00      | -14.75     | QP     |
| 2 | 58.819  | 39.21      | 13.14          | 1.54       | 33.20               | 20.69          | 40.00      | -19.31     | QP     |
| 3 | 119.856 | 37.69      | 11.10          | 2.30       | 33.11               | 17.98          | 43.50      | -25.52     | QP     |
| 4 | 199.986 | 47.00      | 10.00          | 3.04       | 33.00               | 27.04          | 43.50      | -16.46     | QP     |
| 5 | 263.819 | 43.24      | 12.11          | 3.45       | 32.80               | 26.00          | 46.00      | -20.00     | QP     |
| 6 | 595.133 | 40.39      | 19.85          | 5.44       | 32.70               | 32.98          | 46.00      | -13.02     | QP     |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

### 7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| Above 1000     | 500                              | 3                            |

#### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 24.9 °C


Humidity: 54.9 % RH

Atmospheric Pressure: 1010 mbar

#### 7.4.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 00        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |

#### 7.4.3 Test Setup Diagram




#### **7.4.4 Measurement Procedure and Data**

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

**Remark:**

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4804.11 | 39.43      | 33.57          | 5.22       | 36.79         | 41.43          | 74.00      | -32.57     | Peak   |
| 7206.31 | 37.81      | 36.24          | 7.13       | 35.53         | 45.65          | 74.00      | -28.35     | Peak   |
| 9608.43 | 34.94      | 37.75          | 8.66       | 33.58         | 47.77          | 74.00      | -26.23     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuV       | dB/m           | dB         | dB            | dBuV/m         | dBuV/m     | dB         |        |
| 4804.11 | 39.09      | 33.57          | 5.22       | 36.79         | 41.09          | 74.00      | -32.91     | Peak   |
| 7206.31 | 37.58      | 36.24          | 7.13       | 35.53         | 45.42          | 74.00      | -28.58     | Peak   |
| 9608.43 | 34.29      | 37.75          | 8.66       | 33.58         | 47.12          | 74.00      | -26.88     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuV       | dB/m           | dB         | dB            | dBuV/m         | dBuV/m     | dB         |        |
| 4882.15 | 39.55      | 33.66          | 5.36       | 36.81         | 41.76          | 74.00      | -32.24     | Peak   |
| 7323.27 | 36.10      | 36.33          | 7.33       | 35.42         | 44.34          | 74.00      | -29.66     | Peak   |
| 9764.37 | 34.43      | 37.54          | 8.84       | 33.50         | 47.31          | 74.00      | -26.69     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:middle



Antenna Polarity :VERTICAL


EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4882.15 | 39.97      | 33.66          | 5.36       | 36.81         | 42.18          | 74.00      | -31.82     | Peak   |
| 7323.27 | 37.31      | 36.33          | 7.33       | 35.42         | 45.55          | 74.00      | -28.45     | Peak   |
| 9764.37 | 33.69      | 37.54          | 8.84       | 33.50         | 46.57          | 74.00      | -27.43     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor



Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4960.31 | 39.79      | 33.65          | 5.46       | 36.83         | 42.07          | 74.00      | -31.93     | Peak   |
| 7440.91 | 36.76      | 36.31          | 7.43       | 35.34         | 45.16          | 74.00      | -28.84     | Peak   |
| 9920.99 | 32.37      | 37.62          | 8.69       | 33.41         | 45.27          | 74.00      | -28.73     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High




Antenna Polarity :VERTICAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4960.31 | 40.30      | 33.65          | 5.46       | 36.83         | 42.58          | 74.00      | -31.42     | Peak   |
| 7440.91 | 38.20      | 36.31          | 7.43       | 35.34         | 46.60          | 74.00      | -27.40     | Peak   |
| 9920.99 | 32.65      | 37.62          | 8.69       | 33.41         | 45.55          | 74.00      | -28.45     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Horizontal; Modulation:  $\pi/4$  DQPSK; Channel: Low




Antenna Polarity : HORIZONTAL

EUT/Project : 1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4804.11 | 38.82      | 33.57          | 5.22       | 36.79         | 40.82          | 74.00      | -33.18     | Peak   |
| 7206.31 | 36.77      | 36.24          | 7.13       | 35.53         | 44.61          | 74.00      | -29.39     | Peak   |
| 9608.43 | 33.25      | 37.75          | 8.66       | 33.58         | 46.08          | 74.00      | -27.92     | Peak   |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:  $\pi/4$  DQPSK; Channel: Low




Antenna Polarity : VERTICAL

EUT/Project : 1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4804.11 | 39.11      | 33.57          | 5.22       | 36.79         | 41.11          | 74.00      | -32.89     | Peak   |
| 7206.31 | 37.55      | 36.24          | 7.13       | 35.53         | 45.39          | 74.00      | -28.61     | Peak   |
| 9608.43 | 33.93      | 37.75          | 8.66       | 33.58         | 46.76          | 74.00      | -27.24     | Peak   |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Test Mode: 00; Polarity: Horizontal; Modulation:  $\pi/4$  DQPSK; Channel: middle




Antenna Polarity :HORIZONTAL  
EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4882.15 | 41.65      | 33.66          | 5.36       | 36.81         | 43.86          | 74.00      | -30.14     | Peak   |
| 7323.27 | 36.51      | 36.33          | 7.33       | 35.42         | 44.75          | 74.00      | -29.25     | Peak   |
| 9764.37 | 33.66      | 37.54          | 8.84       | 33.50         | 46.54          | 74.00      | -27.46     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:  $\pi/4$  DQPSK; Channel: middle




Antenna Polarity :VERTICAL  
EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4882.15 | 39.31      | 33.66          | 5.36       | 36.81         | 41.52          | 74.00      | -32.48     | Peak   |
| 7323.27 | 37.03      | 36.33          | 7.33       | 35.42         | 45.27          | 74.00      | -28.73     | Peak   |
| 9764.37 | 32.31      | 37.54          | 8.84       | 33.50         | 45.19          | 74.00      | -28.81     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Horizontal; Modulation:  $\pi/4$  DQPSK; Channel: High




Antenna Polarity :HORIZONTAL  
EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4960.31 | 40.52      | 33.65          | 5.46       | 36.83         | 42.80          | 74.00      | -31.20     | Peak   |
| 7440.91 | 38.16      | 36.31          | 7.43       | 35.34         | 46.56          | 74.00      | -27.44     | Peak   |
| 9920.99 | 32.55      | 37.62          | 8.69       | 33.41         | 45.45          | 74.00      | -28.55     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:  $\pi/4$  DQPSK; Channel: High



Antenna Polarity : VERTICAL


EUT/Project : 1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuV       | dB/m           | dB         | dB            | dBuV/m         | dBuV/m     | dB         |        |
| 4960.31 | 40.41      | 33.65          | 5.46       | 36.83         | 42.69          | 74.00      | -31.31     | Peak   |
| 7440.91 | 37.74      | 36.31          | 7.43       | 35.34         | 46.14          | 74.00      | -27.86     | Peak   |
| 9920.99 | 32.66      | 37.62          | 8.69       | 33.41         | 45.56          | 74.00      | -28.44     | Peak   |

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor



Test Mode: 00; Polarity: Horizontal; Modulation:8DPSK; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4804.11 | 39.23      | 33.57          | 5.22       | 36.79         | 41.23          | 74.00      | -32.77     | Peak   |
| 7206.31 | 37.49      | 36.24          | 7.13       | 35.53         | 45.33          | 74.00      | -28.67     | Peak   |
| 9608.43 | 34.23      | 37.75          | 8.66       | 33.58         | 47.06          | 74.00      | -26.94     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:8DPSK; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB                  | dBuv/m         | dBuv/m     | dB         |        |
| 4804.11 | 39.45      | 33.57          | 5.22       | 36.79               | 41.45          | 74.00      | -32.55     | Peak   |
| 7206.31 | 36.25      | 36.24          | 7.13       | 35.53               | 44.09          | 74.00      | -29.91     | Peak   |
| 9608.43 | 33.23      | 37.75          | 8.66       | 33.58               | 46.06          | 74.00      | -27.94     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Horizontal; Modulation:8DPSK; Channel:middle




Antenna Polarity :HORIZONTAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuV       | dB/m           | dB         | dB            | dBuV/m         | dBuV/m     | dB         |        |
| 4882.15 | 39.75      | 33.66          | 5.36       | 36.81         | 41.96          | 74.00      | -32.04     | Peak   |
| 7323.27 | 34.74      | 36.33          | 7.33       | 35.42         | 42.98          | 74.00      | -31.02     | Peak   |
| 9764.37 | 32.66      | 37.54          | 8.84       | 33.50         | 45.54          | 74.00      | -28.46     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:8DPSK; Channel:middle




Antenna Polarity :VERTICAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuV       | dB/m           | dB         | dB            | dBuV/m         | dBuV/m     | dB         |        |
| 4882.15 | 40.53      | 33.66          | 5.36       | 36.81         | 42.74          | 74.00      | -31.26     | Peak   |
| 7323.27 | 36.45      | 36.33          | 7.33       | 35.42         | 44.69          | 74.00      | -29.31     | Peak   |
| 9764.37 | 34.60      | 37.54          | 8.84       | 33.50         | 47.48          | 74.00      | -26.52     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Horizontal; Modulation:8DPSK; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4960.31 | 40.16      | 33.65          | 5.46       | 36.83         | 42.44          | 74.00      | -31.56     | Peak   |
| 7440.91 | 36.34      | 36.31          | 7.43       | 35.34         | 44.74          | 74.00      | -29.26     | Peak   |
| 9920.99 | 31.87      | 37.62          | 8.69       | 33.41         | 44.77          | 74.00      | -29.23     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:8DPSK; Channel:High



Antenna Polarity :VERTICAL

EUT/Project :1328AT

| Freq    | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Emission Level | Limit Line | Over Limit | Remark |
|---------|------------|----------------|------------|---------------|----------------|------------|------------|--------|
| MHz     | dBuv       | dB/m           | dB         | dB            | dBuv/m         | dBuv/m     | dB         |        |
| 4960.31 | 40.18      | 33.65          | 5.46       | 36.83         | 42.46          | 74.00      | -31.54     | Peak   |
| 7440.91 | 39.31      | 36.31          | 7.43       | 35.34         | 47.71          | 74.00      | -26.29     | Peak   |
| 9920.99 | 33.03      | 37.62          | 8.69       | 33.41         | 45.93          | 74.00      | -28.07     | Peak   |

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

### 7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.5

Limit:

| Frequency range(MHz) | Output power of the intentional radiator(watt)         |
|----------------------|--|
| 902-928              | 1 for $\geq 50$ hopping channels                       |
|                      | 0.25 for $25 \leq$ hopping channels $< 50$             |
|                      | 1 for digital modulation                               |
| 2400-2483.5          | 1 for $\geq 75$ non-overlapping hopping channels       |
|                      | 0.125 for all other frequency hopping systems          |
|                      | 1 for digital modulation                               |
| 5725-5850            | 1 for frequency hopping systems and digital modulation |

#### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 24.9 °C


Humidity: 54.9 % RH

Atmospheric Pressure: 1010 mbar

#### 7.5.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 00        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |

#### 7.5.3 Test Setup Diagram



#### 7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

### 7.6 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247(a)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.7

#### 7.6.1 E.U.T. Operation


Operating Environment:

Temperature: 24.9 °C Humidity: 54.9 % RH Atmospheric Pressure: 1010 mbar

#### 7.6.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 00        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |

#### 7.6.3 Test Setup Diagram



#### 7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



### 7.7 Carrier Frequencies Separation

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)

Test Method: ANSI C63.10 (2013) Section 7.8.2

Limit:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

#### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.8 °C


Humidity: 54.9 % RH

Atmospheric Pressure: 1010 mbar

#### 7.7.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 01        | TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |

#### 7.7.3 Test Setup Diagram



#### 7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

### 7.8 Hopping Channel Number

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.3

Limit:

| Frequency range(MHz) | Number of hopping channels (minimum) |
|----------------------|--------------------------------------|
| 902-928              | 50 for 20dB bandwidth <250kHz        |
|                      | 25 for 20dB bandwidth ≥250kHz        |
| 2400-2483.5          | 15                                   |
| 5725-5850            | 75                                   |

#### 7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 24.8 °C


Humidity: 54.8 % RH

Atmospheric Pressure: 1010 mbar

#### 7.8.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 01        | TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |

#### 7.8.3 Test Setup Diagram



#### 7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

### 7.9 Dwell Time

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.4

Limit:

| Frequency(MHz) | Limit   |
|----------------|---|
| 902-928        | 0.4S within a 20S period(20dB bandwidth<250kHz)                           |
|                | 0.4S within a 10S period(20dB bandwidth≥250kHz)                           |
| 2400-2483.5    | 0.4S within a period of 0.4S multiplied by the number of hopping channels |
| 5725-5850      | 0.4S within a 30S period  |

#### 7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 24.9 °C


Humidity: 54.8 % RH

Atmospheric Pressure: 1010 mbar

#### 7.9.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 01        | TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |

#### 7.9.3 Test Setup Diagram



#### 7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

### 7.10 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 7.8.6

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### 7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 24.8 °C


Humidity: 54.8 % RH

Atmospheric Pressure: 1010 mbar

#### 7.10.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 00        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |
| Final test            | 01        | TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.                                   |

#### 7.10.3 Test Setup Diagram



#### 7.10.4 Measurement Procedure and Data

Please Refer to Appendix for Details

### 7.11 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 7.8.8

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### 7.11.1 E.U.T. Operation

Operating Environment:

Temperature: 24.9 °C


Humidity: 54.9 % RH

Atmospheric Pressure: 1010 mbar

#### 7.11.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description  |
|-----------------------|-----------|--|
| Final test            | 00        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation, Pi/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report. |

#### 7.11.3 Test Setup Diagram



#### 7.11.4 Measurement Procedure and Data

Please Refer to Appendix for Details

## 8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SHCR2407001328AT

## 9 EUT Constructional Details (EUT Photos)

Refer to Appendix - Photographs of EUT Constructional Details for SHCR2407001328AT

## 10 Appendix


### 10.1 Appendix A: 20dB Emission Bandwidth

#### 10.1.1 Test Result

| Test Mode | Antenna | Channel | 20dB EBW[MHz] | FL[MHz]  | FH[MHz]  | Limit[MHz] | Verdict |
|-----------|---------|---------|---------------|----------|----------|------------|---------|
| DH5       | Ant1    | 2402    | 0.969         | 2401.511 | 2402.480 | ---        | ---     |
|           |         | 2441    | 0.954         | 2440.514 | 2441.468 | ---        | ---     |
|           |         | 2480    | 0.981         | 2479.499 | 2480.480 | ---        | ---     |
| 2DH5      | Ant1    | 2402    | 1.326         | 2401.313 | 2402.639 | ---        | ---     |
|           |         | 2441    | 1.296         | 2440.340 | 2441.636 | ---        | ---     |
|           |         | 2480    | 1.284         | 2479.343 | 2480.627 | ---        | ---     |
| 3DH5      | Ant1    | 2402    | 1.293         | 2401.337 | 2402.630 | ---        | ---     |
|           |         | 2441    | 1.275         | 2440.337 | 2441.612 | ---        | ---     |
|           |         | 2480    | 1.308         | 2479.328 | 2480.636 | ---        | ---     |

### 10.1.2 Test Graphs


DH5\_Ant1\_2402




DH5\_Ant1\_2441




DH5\_Ant1\_2480



2DH5\_Ant1\_2402



2DH5\_Ant1\_2441





**SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.**

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR240700132801

Page: 65 of 108


2DH5\_Ant1\_2480



3DH5\_Ant1\_2402



3DH5\_Ant1\_2441





## 10.2 Appendix B: Occupied Channel Bandwidth

### 10.2.1 Test Result


| Test Mode | Antenna | Channel | OCB [MHz] | FL[MHz]   | FH[MHz]   | Limit[MHz] | Verdict |
|-----------|---------|---------|-----------|-----------|-----------|------------|---------|
| DH5       | Ant1    | 2402    | 0.84199   | 2401.5562 | 2402.3982 | ---        | ---     |
|           |         | 2441    | 0.85091   | 2440.5457 | 2441.3966 | ---        | ---     |
|           |         | 2480    | 0.85047   | 2479.5482 | 2480.3986 | ---        | ---     |
| 2DH5      | Ant1    | 2402    | 1.1818    | 2401.3882 | 2402.5700 | ---        | ---     |
|           |         | 2441    | 1.1801    | 2440.3877 | 2441.5678 | ---        | ---     |
|           |         | 2480    | 1.1865    | 2479.3850 | 2480.5715 | ---        | ---     |
| 3DH5      | Ant1    | 2402    | 1.1743    | 2401.3868 | 2402.5611 | ---        | ---     |
|           |         | 2441    | 1.1767    | 2440.3839 | 2441.5606 | ---        | ---     |
|           |         | 2480    | 1.1707    | 2479.3886 | 2480.5593 | ---        | ---     |

### 10.2.2 Test Graphs






2DH5\_Ant1\_2402




2DH5\_Ant1\_2441



### 2DH5\_Ant1\_2480



### 3DH5\_Ant1\_2402



### 3DH5\_Ant1\_2441





### 10.3 Appendix C: Maximum conducted output power

#### 10.3.1 Test Result


| Test Mode | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| DH5       | Ant1    | 2402    | 5.92        | ≤20.97     | PASS    |
|           |         | 2441    | 6.97        | ≤20.97     | PASS    |
|           |         | 2480    | 5.85        | ≤20.97     | PASS    |
| 2DH5      | Ant1    | 2402    | 7.82        | ≤20.97     | PASS    |
|           |         | 2441    | 8.76        | ≤20.97     | PASS    |
|           |         | 2480    | 7.07        | ≤20.97     | PASS    |
| 3DH5      | Ant1    | 2402    | 8.06        | ≤20.97     | PASS    |
|           |         | 2441    | 8.87        | ≤20.97     | PASS    |
|           |         | 2480    | 7.59        | ≤20.97     | PASS    |









2DH5\_Ant1\_2402




2DH5\_Ant1\_2441




2DH5\_Ant1\_2480



3DH5\_Ant1\_2402



3DH5\_Ant1\_2441





**SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.**

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR240700132801

Page: 77 of 108


**10.4 Appendix D: Carrier frequency separation**

**10.4.1 Test Result**

| Test Mode | Antenna | Channel | Result[MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| DH5       | Ant1    | Hop     | 1.226       | ≥0.981     | PASS    |
| 2DH5      | Ant1    | Hop     | 1.008       | ≥0.884     | PASS    |
| 3DH5      | Ant1    | Hop     | 1.324       | ≥1.308     | PASS    |

### 10.4.2 Test Graphs






**10.5 Appendix E: Time of occupancy**


**10.5.1 Test Result**


| Test Mode | Antenna | Channel | BurstWidth<br>[ms] | TotalHops<br>[Num] | Result[s] | Limit[s] | Verdict |
|-----------|---------|---------|--------------------|--------------------|-----------|----------|---------|
| DH1       | Ant1    | Hop     | 0.377              | 280                | 0.106     | ≤0.4     | PASS    |
| DH3       | Ant1    | Hop     | 1.633              | 40                 | 0.065     | ≤0.4     | PASS    |
| DH5       | Ant1    | Hop     | 2.882              | 60                 | 0.173     | ≤0.4     | PASS    |
| 2DH1      | Ant1    | Hop     | 0.385              | 270                | 0.104     | ≤0.4     | PASS    |
| 2DH3      | Ant1    | Hop     | 1.638              | 90                 | 0.147     | ≤0.4     | PASS    |
| 2DH5      | Ant1    | Hop     | 2.885              | 50                 | 0.144     | ≤0.4     | PASS    |
| 3DH1      | Ant1    | Hop     | 0.384              | 300                | 0.115     | ≤0.4     | PASS    |
| 3DH3      | Ant1    | Hop     | 1.635              | 90                 | 0.147     | ≤0.4     | PASS    |
| 3DH5      | Ant1    | Hop     | 2.885              | 90                 | 0.26      | ≤0.4     | PASS    |





### 10.5.2 Test Graphs







2DH1\_Ant1\_Hop



2DH3\_Ant1\_Hop