

# RF Exposure evaluation

FCC ID	2BK9F-V200
Product Name	Intelligent Microprojector
Model/Type reference	V200
Listed Model(s)	C2-P, C2-S, M200
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

## 1. Reference

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radio frequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radio frequency radiation exposure evaluation: mobile devices

## 2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 - 3.0	614	1.63	(100) *	6
3.0 - 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 - 300	61.4	0.163	1.0	6
300 - 1500	/	/	f/300	6
1500 - 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 - 3.0	614	1.63	(100) *	30
3.0 - 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	/	/	f/1500	30
1500 - 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 4. Antenna Information

Smart camera can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
BT ANT	FPC antenna	3.09dBi	2402-2480MHz
WIFI ANT	FPC antenna	3.01dBi	2412-5825MHz

### 5. Conducted Peak Output Power

BT

Modulation	Packet Type	Channel	Peak Output Power (dBm)	Peak Output Power (mW)
GFSK	DH5	0	0.86	1.22
		39	0.34	1.08
		78	0.94	1.24
$\pi/4$ DQPSK	2-DH5	0	1.30	1.35
		39	1.18	1.31
		78	1.84	1.53
8DPSK	3-DH5	0	1.59	1.44
		39	1.12	1.29
		78	2.13	1.63

## BLE

Modulation	Packet Type	Peak Output Power (dBm)	Peak Output Power (mW)	Mode
GFSK	BLE 1M	0	-0.64	0.86
		19	0.43	1.1
		39	-0.15	0.97

## 2.4GWIFI

Mode	Channel	Peak Output Power (dBm)	Peak Output Power (mW)
11b	1	8.05	6.38
	6	7.46	5.57
	11	7.26	5.32
11g	1	8.82	7.62
	6	8.63	7.29
	11	8.46	7.01
11n(HT20)	1	8.91	7.78
	6	8.86	7.69
	11	8.31	6.78
11n(HT40)	3	8.71	7.43
	6	8.77	7.53
	19	8.45	7.00

## 5.8GWIFI

Mode	Channel	Peak Output Power (dBm)	Peak Output Power (mW)
a	149	8.78	7.55
	157	7.79	6.01
	165	8.05	6.38
11n(HT20)	149	8.31	6.78
	157	8.44	6.98
	165	8.76	7.52
11n(HT40)	151	8.49	7.06
	159	8.51	7.10

ac(HT20)	149	8.47	7.03
	157	8.61	7.26
	165	8.07	6.41
ac(HT40)	151	8.36	6.85
	159	8.54	7.14
ac(HT80)	155	7.57	5.71

## 6. Manufacturing Tolerance

DH5			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
2DH5			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1	1	1
Tolerance $\pm$ (dB)	1.0	1.0	1.0
3DH5			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1	1	2
Tolerance $\pm$ (dB)	1.0	1.0	1.0

BLE			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

2.4GWIFI

Mode	11b		
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	8.0	7.0	7.0
Tolerance ± (dB)	1.0	1.0	1.0
Mode	11g		
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	8.0	8.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
Mode	11n(HT20)		
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	8.0	8.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
Mode	11n(HT40)		
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	8.0	8.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0

5.8GWIFI

Mode	11a		
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	8.0	7.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
Mode	11n(HT20)		
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	8.0	8.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
Mode	11n(HT40)		
Channel	Channel 151	--	Channel 159
Target (dBm)	8.0	--	8.0
Tolerance ± (dB)	1.0	--	1.0
Mode	11ac(HT20)		
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	8.0	8.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
Mode	11ac(HT40)		
Channel	Channel 151	--	Channel 159
Target (dBm)	8.0	--	8.0
Tolerance ± (dB)	1.0	--	1.0
Mode	11ac(HT80)		

Channel	Channel 155	--	--
Target (dBm)	7.0	--	--
Tolerance ± (dB)	1.0	--	--

## 7. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r=20\text{cm}$ , as well as the gain of the used antenna is 3.1dBi, the RF power density can be obtained.

Mode	Output power		Antenna Gain (dBi)	Antenna Gain(linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
EDR	3	2.00	3.09	2.04	0.0008	1.0000
BLE	1	1.26	3.09	2.04	0.0005	1.0000
2.4GWIFI	9	7.94	2.98	1.99	0.00314	1.0000
5.8GWIFI	9	7.94	3.01	2.00	0.00316	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

## 8. Simultaneous Transmission MPE Evaluation

The EUT equipped with one BT/BLE antenna and one 2.4GWIFI/5.8GWIFI antenna. So, need consider simultaneous transmission;

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\sum$  of MPE ratios  $\leq 1.0$

BT MPE ratios	BLE MPE ratios	2.4GWIFI MAX MPE ratios	5.8GWIFI MAX MPE ratios	$\sum$ MPE ratios	Limit	Results
0.0008	/	0.00314	/	0.00394	1.0	Pass
0.0008	/	/	0.00316	0.00396	1.0	Pass
/	0.0005	0.00314	/	0.00364	1.0	Pass
/	0.0005	/	0.00316	0.00366	1.0	Pass

## 9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----End of the report-----