



FCC TEST REPORT

FOR

Dongguan MeiYin keji Co., LTD.

karaoke microphone


Test Model: G50

Prepared for : Dongguan MeiYin keji Co., LTD.
Address : Room 1004, No.3, Lane 6, Minchang Road, Nanzha, Humen Town, Dongguan City, Guangdong Province, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : October 09, 2024
Number of tested samples : 2
Sample No. : A240929124 -1, A240929124 -2
Serial number : Prototype
Date of Test : October 09, 2024 ~ October 16, 2024
Date of Report : October 17, 2024





FCC TEST REPORT
FCC CFR 47 PART 15.239

Report Reference No. : LCSA09304071EB

Date of Issue: October 17, 2024

Testing Laboratory Name: Shenzhen LCS Compliance Testing Laboratory Ltd.

Address: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Testing Location/ Procedure: Full application of Harmonised standards, Partial application of Harmonised standards, Other standard testing method

Applicant's Name: Dongguan MeiYin keji Co., LTD.

Address: Room 1004, No.3, Lane 6, Minchang Road, Nanzha, Humen Town, Dongguan City, Guangdong Province, China

Test Specification

Standard: FCC CFR 47 PART 15.239 / ANSI C63.10: 2013

Test Report Form No: TRF-4-E-182 A/0

TRF Originator: Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF: Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material.

Test Item Description: karaoke microphone

Trade Mark: BONAOK

Test Model: G50

Ratings: Input: DC 5V, 1000mA; DC 3.7V by Rechargeable Li-ion Battery, 2600mAh

Result: Positive

Compiled by:

Ling Zhu (signature)

Ling Zhu/Administrator

Supervised by:

Cary Luo (signature)

Cary Luo/ Technique principal

Approved by:

Gavin Liang (signature)

Gavin Liang/ Manager





FCC -- TEST REPORT

Test Report No. : LCSA09304071EB	October 17, 2024 Date of issue
---	-----------------------------------

Test Model.....	: G50
EUT.....	: karaoke microphone
Applicant.....	: Dongguan MeiYin keji Co., LTD.
Address.....	: Room 1004, No.3, Lane 6, Minchang Road, Nanzha, Humen Town, Dongguan City, Guangdong Province, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Dongguan MeiYin keji Co., LTD.
Address.....	: Room 1004, No.3, Lane 6, Minchang Road, Nanzha, Humen Town, Dongguan City, Guangdong Province, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Guizhou Asicer Technology Industrial Co., Ltd.
Address.....	: Building 19, Dashui Industrial Park, Jinsha County, Bijie City, Guizhou Province
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	October 17, 2024	Initial Issue	---







TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	6
1.1 Description of Device (EUT)	6
1.2 Support equipment List	7
1.3 External I/O Cable	7
1.4 Description of Test Facility	7
1.5 Statement of the Measurement Uncertainty	7
1.6 Measurement Uncertainty	7
1.7 Description of Test Modes	8
2. TEST METHODOLOGY	9
2.1 EUT Configuration	9
2.2 EUT Exercise	9
2.3 General Test Procedures	9
2.4. Test Sample	9
3. SYSTEM TEST CONFIGURATION	10
3.1 Justification	10
3.2 EUT Exercise Software	10
3.3 Special Accessories	10
3.4 Block Diagram/Schematics	10
3.5 Equipment Modifications	10
3.6 Test Setup	10
4. SUMMARY OF TEST RESULTS	11
5. 99% BANDWIDTH	12
5.1 Limit	12
5.2 Block Diagram of Test Setup	12
5.3 Test Procedure	12
5.4 Test Results	12
6. RADIATED MEASUREMENT	14
6.1 Block Diagram of Test Setup	14
6.2 Radiated Fundamental Frequency Limit	15
6.3 Instruments Setting	15
6. POWER LINE CONDUCTED EMISSIONS	32
6.1 Standard Applicable	32
6.2 Block Diagram of Test Setup	32
7. ANTENNA REQUIREMENT	35
8. LIST OF TEST EQUIPMENT	36
9. TEST SETUP PHOTOGRAPHS OF EUT	37
10. EXTERIOR PHOTOGRAPHS OF THE EUT	37
11. INTERIOR PHOTOGRAPHS OF THE EUT	37






1. GENERAL INFORMATION

1.1 Description of Device (EUT)

EUT	: karaoke microphone
Test Model	: G50
Power Supply	: Input: DC 5V, 1000mA DC 3.7V by Rechargeable Li-ion Battery, 2600mAh
Hardware Version	: V14
Software Version	: /
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.3 (DSS)
Channel Spacing	: 1MHz for Bluetooth V5.3 (DSS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.3 (DSS)
Bluetooth Version	: V5.3
Antenna Description	: PCB Antenna, -0.58dBi(Max.)
FM	:
Frequency Range	: 88.5MHz, 89.5MHz, 90.5MHz
Channel Number	: 3
Modulation Type	: FM
Antenna Type	: Internal Antenna
Antenna Gain	: 0dBi(Max.)





1.2 Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN TIANYIN ELECTRONICS CO., LTD	Power Adapter	TPA-46050200UU	---	IC

Note: Auxiliary equipment is provided by the laboratory

1.3 External I/O Cable

I/O Port Description	Quantity	Cable
Type-C Port	1	N/A
Headphone Port	1	N/A

1.4 Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

ISED Designation Number is 9642A.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5 Statement of the Measurement Uncertainty


The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	3.10dB	(1)
	30MHz~200MHz	2.96dB	(1)
	200MHz~1000MHz	3.10dB	(1)
	1GHz~26.5GHz	3.80dB	(1)
	26.5GHz~40GHz	3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	1.63dB	(1)
Power disturbance	30MHz~300MHz	1.60dB	(1)
Occupied Channel Bandwidth	1GHz-40GHz	±5%	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.






1.7 Description of Test Modes

The karaoke microphone is powered by DC 3.7V In the audio port and MIC port give a 2.5 kHz tone at a level 16 dB higher than that required to produce a frequency deviation of 75 KHz and make it works in TX mode (88.5 MHz, 89.5 MHz and 90.5 MHz).

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be TX.

Radiated emission performed at both DC power supply and AC power adapter, recorded worst case;





2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR PART 15C 15.207, 15.209 and 15.239.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209, 15.239 under the FCC Rules Part 15 Subpart C.

2.3 General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table 0.8 meter above ground for below 1GHz and 1.5m for above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.

2.4. Test Sample

The application provides 2 samples to meet requirement;

Sample Number	Description
Sample 1(A240929124-1)	Engineer sample – continuous transmit
Sample 2(A240929124-2)	Normal sample – Intermittent transmit





3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a continuous transmit condition.

3.2 EUT Exercise Software

N/A.

3.3 Special Accessories

N/A.

3.4 Block Diagram/Schematics

Please refer to the related document.

3.5 Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6 Test Setup

Please refer to the test setup photo.





4. SUMMARY OF TEST RESULTS

Applied Standard: FCC CFR 47 PART 15.239		
FCC Rules	Description of Test	Result
15.239 (a)	Occupied Bandwidth	Compliant
15.239 (b)	Field Strength of Fundamental frequency	Compliant
15.205 (a) 15.209 (a)	Radiated Spurious Emissions	Compliant
15.207 (a)	AC Conducted Emissions	Compliant
15.203	Antenna Requirements	Compliant






5. 99% BANDWIDTH

5.1 Limit

According to §15.239 (a) Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88.5-90.5MHz.

5.2 Block Diagram of Test Setup



5.3 Test Procedure

- 1) The transmitter shall be operated at its maximum carrier power measured under normal test conditions
- 2) The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
- 4) Detector function = peak.
- 5) Trace = max hold.

5.4 Test Results

Frequency (MHz)	20dB Bandwidth (KHz)	99% Bandwidth (KHz)	Limit (KHz)	Conclusion
88.5	64.70	60.005	200.00	PASS
89.5	61.33	55.574	200.00	PASS
90.5	65.91	59.589	200.00	PASS

Remark:



- 1. Test results including cable loss;
- 2. Please refer to the following page.

Temperature	21.1°C	Humidity	52.2%
Test Engineer	Paddi Chen	Configurations	FM






99% and 20dB Bandwidth




Low Channel / 88.5 MHz



Middle Channel / 89.5 MHz




High Channel / 90.5 MHz






6. RADIATED MEASUREMENT

6.1 Block Diagram of Test Setup





6.2 Radiated Fundamental Frequency Limit

According to §15.239 (b): The field strength of any emissions within the permitted 200 kHz band shall not exceed 250 microvolts/meter at 3 meters. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Remark: (1) Emission level dB μ V = 20 log Emission level μ V/m;

(2) The smaller limit shall apply at the cross point between two frequency bands;

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.


5.3 Instruments Setting

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	30 MHz
Stop Frequency	1000 MHz
RB / VB (Emission in restricted band)	120KHz / 1MHz for Peak, 120 KHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	120KHz / 1MHz for Peak, 120 KHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP





5.4 Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.


Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.





2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.


Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.





3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.





4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

Premeasurement:

- The antenna is moved spherical over the EUT in different polarizations of the antenna.

Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

5.5 Results for Radiated Emissions


PASS.

Only record the worst test result in this report.

The test data please refer to following page:

Temperature	23.8°C	Humidity	52.1%
Test Engineer	Paddi Chen	Configurations	FM






Below 1GHz



TX-88.5MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	88.3421	73.31	-19.65	53.66	68.00	-14.34	peak
2	112.5242	47.47	-17.81	29.66	43.50	-13.84	peak
3	176.8877	55.09	-20.21	34.88	43.50	-8.62	peak
4	265.6757	54.38	-16.60	37.78	46.00	-8.22	peak
5	354.1831	51.38	-13.77	37.61	46.00	-8.39	peak
6	443.2941	50.83	-13.07	37.76	46.00	-8.24	peak






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	76.2442	45.22	-19.64	25.58	40.00	-14.42	AVG
2	88.3421	58.77	-19.65	39.12	48.00	-8.88	AVG
3	176.2685	52.74	-20.19	32.55	43.50	-10.95	AVG
4	265.6757	49.22	-16.60	32.62	46.00	-13.38	AVG
5	354.1831	32.91	-13.77	19.14	46.00	-26.86	AVG
6	620.7096	17.56	-10.30	7.26	46.00	-38.74	AVG







Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	88.3421	72.21	-19.05	53.16	68.00	-14.84	peak
2	112.5241	48.45	-19.29	29.16	43.50	-14.34	peak
3	176.8876	53.83	-18.95	34.88	43.50	-8.62	peak
4	265.6757	50.73	-15.45	35.28	46.00	-10.72	peak
5	354.1831	51.88	-14.84	37.04	46.00	-8.96	peak
6	443.2941	52.63	-14.44	38.19	46.00	-7.81	peak






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	76.2442	50.02	-19.73	30.29	40.00	-9.71	AVG
2	88.3421	57.90	-19.05	38.85	48.00	-9.15	AVG
3	100.2283	47.14	-18.20	28.94	48.00	-19.06	AVG
4	176.2684	52.88	-19.00	33.88	43.50	-9.62	AVG
5	265.6757	52.99	-15.45	37.54	46.00	-8.46	AVG
6	354.1831	43.14	-14.84	28.30	46.00	-17.70	AVG






TX-89.5MHz

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	65.3431	49.71	-17.85	31.86	40.00	-8.14	peak
2	89.5899	68.77	-19.60	49.17	68.00	-18.83	peak
3	178.7583	55.82	-20.25	35.57	43.50	-7.93	peak
4	268.4852	53.81	-16.53	37.28	46.00	-8.72	peak
5	357.9286	50.66	-13.79	36.87	46.00	-9.13	peak
6	447.9821	45.73	-13.01	32.72	46.00	-13.28	peak






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	77.3210	48.07	-19.74	28.33	40.00	-11.67	AVG
2	89.5899	57.27	-19.60	37.67	48.00	-10.33	AVG
3	178.7582	51.02	-20.25	30.77	43.50	-12.73	AVG
4	268.4852	40.05	-16.53	23.52	46.00	-22.48	AVG
5	357.9286	30.72	-13.79	16.93	46.00	-29.07	AVG
6	793.3958	17.41	-9.15	8.26	46.00	-37.74	AVG







Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	89.5899	67.20	-18.92	48.28	68.00	-19.72	peak
2	119.0178	45.57	-19.85	25.72	43.50	-17.78	peak
3	178.7583	53.63	-18.79	34.84	43.50	-8.66	peak
4	268.4852	51.20	-15.42	35.78	46.00	-10.22	peak
5	357.9286	51.67	-14.83	36.84	46.00	-9.16	peak
6	447.9821	49.85	-14.45	35.40	46.00	-10.60	peak






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	77.3210	48.93	-19.77	29.16	40.00	-10.84	AVG
2	89.2762	59.21	-18.95	40.26	48.00	-7.74	AVG
3	178.7583	49.61	-18.79	30.82	43.50	-12.68	AVG
4	268.4852	51.35	-15.42	35.93	46.00	-10.07	AVG
5	357.9286	41.64	-14.83	26.81	46.00	-19.19	AVG
6	447.9821	30.30	-14.45	15.85	46.00	-30.15	AVG







TX-90.5MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	90.5374	75.61	-19.47	56.14	68.00	-11.86	peak
2	181.2834	54.10	-20.22	33.88	43.50	-9.62	peak
3	271.3245	53.46	-16.46	37.00	46.00	-9.00	peak
4	361.7137	50.80	-13.80	37.00	46.00	-9.00	peak
5	452.7196	50.41	-12.98	37.43	46.00	-8.57	peak
6	543.2741	46.89	-12.29	34.60	46.00	-11.40	peak






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	90.2203	60.53	-19.53	41.00	48.00	-7.00	AVG
2	102.0013	49.49	-17.45	32.04	48.00	-15.96	AVG
3	180.6487	56.23	-20.25	35.98	43.50	-7.52	AVG
4	271.3245	49.66	-16.46	33.20	46.00	-12.80	AVG
5	361.7137	37.92	-13.80	24.12	46.00	-21.88	AVG
6	452.7196	29.92	-12.98	16.94	46.00	-29.06	AVG







Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	87.4175	49.80	-19.14	30.66	40.00	-9.34	peak
2	90.5374	74.20	-18.84	55.36	68.00	-12.64	peak
3	181.2834	54.49	-18.64	35.85	43.50	-7.65	peak
4	271.3245	51.71	-15.40	36.31	46.00	-9.69	peak
5	361.7137	49.36	-14.81	34.55	46.00	-11.45	peak
6	543.2741	48.41	-12.04	36.37	46.00	-9.63	peak





No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	78.4133	50.05	-19.81	30.24	40.00	-9.76	AVG
2	90.2203	58.42	-18.86	39.56	48.00	-8.44	AVG
3	180.6487	49.54	-18.66	30.88	43.50	-12.62	AVG
4	271.3245	50.77	-15.40	35.37	46.00	-10.63	AVG
5	361.7137	47.21	-14.81	32.40	46.00	-13.60	AVG
6	452.7196	42.51	-14.46	28.05	46.00	-17.95	AVG

Note: The result below 30MHz and above 1GHz is too low so there is no record. The test setup show in the test setup photograph is the worst case.



6. POWER LINE CONDUCTED EMISSIONS


6.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

* Decreasing linearly with the logarithm of the frequency

6.2 Block Diagram of Test Setup



6.3 Disturbance Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD \text{ (dB}\mu\text{V)} = RA \text{ (dB}\mu\text{V)} + PL \text{ (dB)} + CL \text{ (dB)}$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor


6.4 Test Results

Temperature	22.5°C	Humidity	53.7%
Test Engineer	Paddi Chen	Configurations	FM


PASS.

The test data please refer to following page.






Line




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.312	23.55	19.83	43.38	49.92	-6.54	AVG	
2		0.317	31.12	19.85	50.97	59.79	-8.82	QP	
3		0.433	21.60	19.99	41.59	47.19	-5.60	AVG	
4		0.942	30.93	19.11	50.04	56.00	-5.96	QP	
5	*	0.942	22.55	19.11	41.66	46.00	-4.34	AVG	
6		1.572	30.54	19.03	49.57	56.00	-6.43	QP	
7		1.572	19.67	19.03	38.70	46.00	-7.30	AVG	
8		2.828	29.11	19.19	48.30	56.00	-7.70	QP	
9		4.083	27.32	19.14	46.46	56.00	-9.54	QP	
10		7.543	18.53	19.55	38.08	50.00	-11.92	AVG	
11		13.511	17.41	19.80	37.21	50.00	-12.79	AVG	
12		21.048	33.42	18.99	52.41	60.00	-7.59	QP	





Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.159	38.67	19.62	58.29	65.52	-7.23	QP	
2		0.317	24.00	19.80	43.80	49.79	-5.99	AVG	
3		0.942	30.00	18.87	48.87	56.00	-7.13	QP	
4	*	0.942	23.34	18.87	42.21	46.00	-3.79	AVG	
5		1.567	30.42	19.00	49.42	56.00	-6.58	QP	
6		1.567	22.40	19.00	41.40	46.00	-4.60	AVG	
7		2.828	28.80	19.02	47.82	56.00	-8.18	QP	
8		2.828	20.26	19.02	39.28	46.00	-6.72	AVG	
9		4.398	25.73	18.92	44.65	56.00	-11.35	QP	
10		6.909	18.84	19.54	38.38	50.00	-11.62	AVG	
11		20.391	18.84	19.07	37.91	50.00	-12.09	AVG	
12		26.988	35.59	19.08	54.67	60.00	-5.33	QP	

***Note: Pre-scan all modes and recorded the worst case results in this report.

Measurement = Reading + Correct Factor, Margin = Measurement - Limit,

Correct Factor=Lisn Factor+Cable Factor+Insertion loss of Pulse Limiter.





7. ANTENNA REQUIREMENT

7.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

7.2 Antenna Connected Construction

7.2.1. Standard Applicable


According to § 15.203 & RSS-Gen Issue 4, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 0dBi, and the antenna is an Internal Antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

7.2.3. Results: Compliance.





8. LIST OF TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	MXA Signal Analyzer	Agilent	N9020A	MY49100060	2023-10-18	2024-10-17
2	DC Power Supply	Agilent	E3642A	N/A	2023-10-18	2024-10-17
3	Temperature & Humidity Chamber	GUANGZHOU GOGNWEN	GDS-100	70932	2023-10-05 2024-10-04	2024-10-04 2025-10-03
4	EMI Test Software	AUDIX	E3	/	N/A	N/A
5	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2024-06-06	2025-06-05
6	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
7	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2024-07-13	2027-07-12
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2024-08-03	2027-08-02
9	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2024-07-13	2027-07-12
10	EMI Test Receiver	R&S	ESR 7	101181	2024-06-06	2025-06-05
11	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2024-06-06	2025-06-05
12	Low-frequency amplifier	SchwarzZBECK	BBV9745	00253	2023-10-18	2024-10-17
13	High-frequency amplifier	JS Denki Pte	PA0118-43	JSPA21009	2023-10-18	2024-10-17
14	EMI Test Receiver	R&S	ESPI	101940	2024-06-06	2025-06-05
15	Artificial Mains	R&S	ENV216	101288	2024-06-06	2025-06-05
16	10dB Attenuator	SCHWARZBECK	MTS-IMP-13 6	261115-001-0032	2024-06-06	2025-06-05
17	EMI Test Software	Farad	EZ	/	N/A	N/A
18	Antenna Mast	Max-Full	MFA-515BSN	1308572	N/A	N/A
19	Pulse Limiter	R&S	ESH3-Z2	102750-NB	2024-06-06	2025-06-05
20	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2024-07-13	2027-07-12
21	Broadband Preamplifier	SCHWARZBECK	BBV9719	9719-025	2024-07-30	2025-07-29





9. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

10. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

11. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----

