

MPE TEST REPORT

Applicant Roadeazy
FCC ID 2BKST-RZ1VH2401
Product AI Vehicle Gateway
Model RZ1
Report No. R2408A1127-M1
Issue Date October 29, 2024

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Wei Fangying

Approved by: Fan Guangchang

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory	3
1.1	Notes of the Test Report.....	3
1.2	Test Facility.....	3
1.3	Testing Location.....	3
1.4	Laboratory Environment	3
2	Description of Equipment Under Test	4
3	Maximum Tune up and Antenna Gain	5
4	MPE Limit.....	6
5	RF Exposure Evaluation Result.....	8
	ANNEX A: The EUT Appearance	9

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
 Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
 City: Shanghai
 Post code: 201201
 Country: P. R. China
 Contact: Fan Guangchang
 Telephone: +86-021-50791141/2/3
 Fax: +86-021-50791141/2/3-8000
 Website: <https://www.eurofins.com/electrical-and-electronics>
 E-mail: Jack.Fan@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Roadeazy
Applicant address	1386 Enderby Way, Sunnyvale, CA USA
Manufacturer	Asiateco Technologies Co.
Manufacturer address	#68 HuaTuo Road, Building-8, Zhangjiang Hi-Tech Park, Pudong, Shanghai 201204, China

General Technologies

EUT Description			
Model	RZ1		
Lab internal SN	R2408A1127/S01		
Hardware Version	P2		
Software Version	V2		
Frequency	Band	TX (MHz)	RX (MHz)
	WCDMA Band II	1850 ~ 1910	1930 ~ 1990
	WCDMA Band IV	1710 ~ 1755	2110 ~ 2155
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 12	699 ~ 716	729 ~ 746
	LTE Band 13	777 ~ 787	746 ~ 756
	LTE Band 14	788 ~ 798	758 ~ 768
	LTE Band 25	1850 ~ 1915	1930 ~ 1995
	LTE Band 26	814 ~ 849	859 ~ 894
	LTE Band 66	1710 ~ 1780	2110 ~ 2180
	LTE Band 71	663 ~ 698	617 ~ 652
Bluetooth LE	2400 ~ 2483.5	2400 ~ 2483.5	
Date of Sample Received	August 22, 2024		
<p>Note:</p> <ol style="list-style-type: none"> 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant. 2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. 			

3 Maximum Tune up and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

Numeric gain (G)=10^(antenna gain/10)

Band	Maximum Tune up Power		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
WCDMA Band II	25.00	316.228	3.40	2.188
WCDMA Band IV	25.00	316.228	3.80	2.399
WCDMA Band V	25.00	316.228	1.30	1.349
LTE Band 2	25.00	316.228	3.40	2.188
LTE Band 4	25.00	316.228	3.80	2.399
LTE Band 5	25.00	316.228	1.30	1.349
LTE Band 12	25.00	316.228	2.70	1.862
LTE Band 13	25.00	316.228	1.70	1.479
LTE Band 14	25.00	316.228	1.40	1.380
LTE Band 25	25.00	316.228	3.40	2.188
LTE Band 26	25.00	316.228	2.20	1.660
LTE Band 66	25.00	316.228	3.80	2.399
LTE Band 71	25.00	316.228	4.60	2.884
Bluetooth (Low Energy)	4.00	2.512	3.20	2.089

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	f/300	6
1500-100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is $f/1500$, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
WCDMA Band II	1.000
WCDMA Band IV	1.000
WCDMA Band V	0.549
LTE Band 2	1.000
LTE Band 4	1.000
LTE Band 5	0.549
LTE Band 12	0.466
LTE Band 13	0.518
LTE Band 14	0.525
LTE Band 25	1.000
LTE Band 26	0.543
LTE Band 66	1.000
LTE Band 71	0.442
Bluetooth (Low Energy)	1.000

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE Ratio
WCDMA Band II	25.00	3.40	28.400	691.831	0.138	1.000	0.138
WCDMA Band IV	25.00	3.80	28.800	758.578	0.151	1.000	0.151
WCDMA Band V	25.00	1.30	26.300	426.580	0.085	0.549	0.155
LTE Band 2	25.00	3.40	28.400	691.831	0.138	1.000	0.138
LTE Band 4	25.00	3.80	28.800	758.578	0.151	1.000	0.151
LTE Band 5	25.00	1.30	26.300	426.580	0.085	0.549	0.155
LTE Band 12	25.00	2.70	27.700	588.844	0.117	0.466	0.251
LTE Band 13	25.00	1.70	26.700	467.735	0.093	0.518	0.180
LTE Band 14	25.00	1.40	26.400	436.516	0.087	0.525	0.165
LTE Band 25	25.00	3.40	28.400	691.831	0.138	1.000	0.138
LTE Band 26	25.00	2.20	27.200	524.807	0.104	0.543	0.192
LTE Band 66	25.00	3.80	28.800	758.578	0.151	1.000	0.151
LTE Band 71	25.00	4.60	29.600	912.011	0.181	0.442	0.410
Bluetooth (Low Energy)	4.00	3.20	7.200	5.248	0.001	1.000	0.001
Note: R = 20cm $\pi = 3.1416$ The MPE Ratio = Mac Result ÷ Limit Value							

So the simultaneous transmitting antenna pairs as below:

$$TER = \text{Bluetooth LE Antenna MPE ratio} + \text{WWAN Antenna MPE ratio} = 0.410 + 0.001 = 0.411 < 1$$

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*******END OF REPORT *******