





RF EXPOSURE REPORT

Applicant	ZhongShan Jingtu Innovation Technology Co., Ltd
Address	Room 5, 4th floor No.49 Xiangxing Road Shengfeng Community Xiaolan Town Zhongshan City Guangdong Province 528403 China

Manufacturer or Supplier	ZhongShan Jingtu Innovation Technology Co., Ltd		
Address	Room 5, 4th floor No.49 Xiangxing Road Shengfeng Community Xiaolan Town Zhongshan City Guangdong Province 528403 China		
Product	AIR PURIFIER		
Brand Name	N/A		
Model	AP500A		
Additional Model & Model Difference	AP500B, AP500C, AP450A, AP450B, AP450C, Sterra Paws, Sterra Breeze Pro, AP300A, AP300B, AP300C, AP300D, AP300E, AP300F; see items 1		
Date of tests	Aug. 30, 2024 ~ Sep. 11, 2024		

- **KDB 447498 D01 V06**
- **⊠** IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Eric Fang	Approved by Glyn He
Project Engineer / EMC Department	Assistant Manager / EMC Department

Date: Sep. 18, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China. Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@bureauveritas.com



TABLE OF CONTENTS

RELE	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE LIMIT	5
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@bureauveritas.com



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2408WDG0275	Original release	Sep. 18, 2024

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

 $\pmb{Email: \underline{customerservice.dg@bureauveritas.com}}\\$



1. CERTIFICATION

FCC ID:	2BKU3-JT		
PRODUCT:	AIR PURIFIER		
BRAND NAME:	N/A		
MODEL NO.:	AP500A		
ADDITIONAL NO.:	AP500B, AP500C, AP450A, AP450B, AP450C, Sterra Paws, Sterra Breeze Pro, AP300A, AP300B, AP300C AP300D, AP300E, AP300F		
TEST SAMPLE:	Engineering Sample		
APPLICANT:	T: ZhongShan Jingtu Innovation Technology Co., Ltd		
STANDARDS: FCC Part 2 (Section 2.1091)			
	KDB 447498 D01 V06		
	IEEE C95.1		

Note:

Additional models (See above table) are identical with test model except the appearance and model no. for trading purpose.



1. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)			
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500 F/1500 30						
1500-100,000			1.0	30		

F = Frequency in MHz

2. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

Fax: +86 769 8593 1080 Email: customerservice.dg@bureauveritas.com

Tel: +86 769 8998 2098

Page 5 of 7

Report Version 1



4. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type	
Chain 0	2.54(BT)	PCB Antenna	
Chain 0	2.45(WIFI)	PCB Antenna	

5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
802.11b	2412-2462	15	+-2	13	17
802.11g	2412-2462	12	+-2	10	14
802.11n(HT20)	2412-2462	12	+-2	10	14
BT-LE	2402-2480	5	+-2	3	8

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
802.11b	2462	15.46
802.11g	2462	12.14
802.11n(HT20)	2462	12.08
BT-LE	2440	5.56

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

 $\pmb{\text{Email:}} \ \underline{\text{customerservice.dg@bureauveritas.com}}$



FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2412-2462(WIFI)	17	2.45	20	0.017528	1.0
2402-2480(BT-LE)	8	2.54	20	0.002253	1.0

CONCLUSION:

The WIFI 2.4GHz and BT can not transmit simultaneously.

--- END ---