

RF Exposure Evaluation Report

Product : Bluetooth infrared remote control
Trade mark :  VALERION
Model/Type reference : VGTV-RC02
Serial Number : N/A
Report Number : EED32Q81358702
FCC ID : 2BKWN-VGTVRC02
Date of Issue : Nov. 27, 2024
Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
47 CFR Part 2.1091
47 CFR Part 2.1093
KDB 447498 D04 Interim General RF
Exposure Guidance v01
Test result : PASS

Prepared for:

VALERION TECHNOLOGY USA CO., LTD
1312 17th Street, Unit Num 2955, Denver, CO 80202, United States.

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Zhenxia Wen

Reviewed by:

Frazer Li

Approved by:

Zhenxia Wen

Aaron Ma

Date:

Nov. 27, 2024

Aaron Ma

Check No.: 9149300824



1 Version

Version No.	Date	Description
00	Nov. 27, 2024	Original

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
3.4 TEST LOCATION	5
3.5 DEVIATION FROM STANDARDS	5
3.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
4 SAR EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 Limits	6
4.1.2 Test Procedure	6
4.1.3 EUT RF Exposure Evaluation	7

3 General Information

3.1 Client Information

Applicant:	VALERION TECHNOLOGY USA CO., LTD
Address of Applicant:	1312 17th Street, Unit Num 2955, Denver, CO 80202, United States.
Manufacturer:	VALERION TECHNOLOGY USA CO., LTD
Address of Manufacturer:	1312 17th Street, Unit Num 2955, Denver, CO 80202, United States.
Factory:	Shenzhen WeProTalk Techology Co.,Ltd
Address of Factory:	2505, 2501, Yihua Financial Technology Building, No. 3939, Baishi Road, Binhai Community, Yuehai Street, Nanshan District, Shenzhen

3.2 General Description of EUT

Product Name:	Bluetooth infrared remote control
Model No.:	VGTV-RC02
Trade mark:	 VALERION

3.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz	
Modulation Type:	GFSK	
Test Power Grade:	Default	
Test Software of EUT:	Airoha.Tool.Kit	
Antenna Type:	PCB Antenna	
Antenna Gain:	-1.95dBi	
Power Supply:	Battery:	DC 1.5V*2
Test Voltage:	DC 3.0V	
Sample Received Date:	Oct. 30, 2024	
Sample tested Date:	Oct. 30, 2024 to Nov. 13, 2024	
Remark:	Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.	

3.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation

For Stand alone:

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	Result
2402	0.5	-1.91	-1.95	-4.06	0.3926	2.7877	Pass

Note:

- ① EIRP=conducted power+antenna gain;
- ② ERP=EIRP-2.15;
- ③ $EIRP(dBm) = \text{Field strength of the fundamental signal}(dBuV/m@3m) - 95.23$;
- ④ $ERP(mW) = 10^{(ERP(dBm)/10)}$;
- ⑤ The estimation distance is 0.5cm;
- ⑥ The test data please refer to the report of EED32Q81358701 and only the worst case data was recorded in the report.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***