



EUT Description: Tire pressure monitoring system sensor
Test type.: PBN-1515
Series model: PBN-1516, PBN-1517, PBN-1518, PBN-1519
PBN-1520, PBN-1521, PBN-1522, PBN-1523, PBN-1524
PBN-1525, PBN-1526
Equipment type: Mobile equipment
FCC ID: 2BL54-PBN

Test procedures according to the technical standards: KDB 447498 D01 V06 and FCC 2.1091.

RF Exposure Evaluation

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(6)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(0) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(d) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

F = frequency in MHz

Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where :

P_d = power density in mW/cm²,

P_{out} = output power to antenna in mW;

G = gain of antenna in linear scale,

π = 3.14;

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



Measurement Result:

TX frequency range: 315MHz

Operation Frequency: 315MHz

Type: external Antenna

R=20cm

$EIRP = E - 104.7 + 20 \log D = 76.65 - 104.7 + 20 \log 3 = -18.51 \text{ dBm}$

Maximum Conducted Output Power: -18.51dBm

Frequency(MHz)	EIRP Power (dBm)	EIRP Power (mW)	Turn-up (dBm)	Max Turn-up (dBm)	Evaluation result (mW/cm ²)	Power denslty Limits (mW/cm ²)
315	-18.51	0.014092	-18± 1	-17	0.0000004	0.28928

Conclusion: the max result : $0.0000004 \leq 0.28928$ compliance with FCC's RF Exposure.

So a SAR test is not required