# **RF Exposure Report**

#### FCC ID: 2BL75-RT003

The EUT is a Galaxy projector in the 2402-2480MHz frequency band.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

### (A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6

## (B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

#### MPE calculation method

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2}$$

S: power density mW/ cm<sup>2</sup>;

P: power input to the antenna in mW;

g: numeric gain of antenna;

r: distance to centre of radiation in cm

#### Unit dbuv/m@3m to mW calculation method

E=EIRP-20log(d)+104.8

E: is the electric field strength in dBuv/m;

EIRP: is the equivalent is otropically radiated power in dBm;

d: is the specified measurement distance in m

#### **Calculated result**

Mode	Max. Peak output power (dBm)	Max. Peak output power (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm²)	Limit of Power Density (S) (mW/ cm²)
BT	-8.91	0.128	0.874	0.000022	1

### For BT mode

-- The max. field strength of fundamental frequency is 85.71 dBuv/m.

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 85.71 - 95.2 = -9.49dBm,$ 

conducted power = EIRP - ANT gain = -9.49 - (-0.58) = -8.91dBm(0.128mW).

Note1: the antenna gain is -0.58dBi for BT.

Note2: Calculated distance is 20cm, which is declared by the manufacture.